

Agent API Documentation

Authentication, Permissions, Agent Endpoints, Player Endpoints

Last updated: 2026-01-22

This document describes the Agent API endpoints and required client behavior for authentication and token refresh. All request/response examples are taken from the provided endpoint files.

Key rules

- **Only one accessToken + refreshToken pair is valid per agent.**
- If an agent performs a duplicate signIn via the API, the **previous tokens become invalid** (access and refresh).
- **Access token TTL:** 1 hour.
- **Refresh token TTL:** 7 days.
- **Refresh token rotation:** after a successful refreshToken call, the old refresh token becomes invalid and a new token pair is issued.

Contents

- Authentication (signIn, refreshToken, invalid access token handling)
- Permissions and authorization (HTTP 403)
- Common response envelope and HTTP status codes
- Agent endpoints: getAgentAllWallets, depositToAgent, withdrawFromAgent, getChildren
- Player endpoints: registerPlayer, getPlayersForCurrentAgent, depositToPlayer, withdrawFromPlayer, getPlayerBalanceById

Authentication

All protected endpoints require the Authorization header: **Bearer <accessToken>**.

Invalid access token response (result = "ex")

If any protected endpoint returns the following response, the current access token is invalid or expired:

```
{
  "status": true,
  "html": "",
  "result": "ex",
  "notification": []
}
```

Client flow: If you have a refresh token, call **refreshToken** to obtain a new token pair. If the refresh token is missing or invalid, call **signIn**.

POST global/api/UserApi/signIn

Property	Value
Method	POST
Endpoint	global/api/UserApi/signIn
Headers	Content-Type: application/json

Request body example

```
{
  "username": "username",
  "password": "rightPassword"
}
```

Success response example (HTTP 200)

```
{
  "status": true,
  "html": "",
  "result": {
    "accessToken": "eyJ0eXAiOiJKV1QiLC...pDdyQxfKUY",
    "refreshToken": "02a84041753d851a...93db50e2debb"
  },
  "notification": []
}
```

Error response example (HTTP 401)

```
{
  "status": true,
  "html": "",
  "result": false,
  "notification": [
    {
      "code": 1,
      "content": "Invalid username or password.",
      "title": "signIn",
      "autoHideAfter": 5000,
      "list": [],
      "status": "error"
    }
  ]
}
```

POST global/api/UserApi/refreshToken

Property	Value
Method	POST
Endpoint	global/api/UserApi/refreshToken
Headers	Content-Type: application/json

Request body example

```
{
  "refreshToken": "421a1b6b1ac6bbb1...9d10fa241263"
}
```

Success response example (HTTP 200)

```
{
  "status": true,
  "html": "",
  "result": {
    "accessToken": "eyJ0eXAiOiJKV1QiLC...6oqJLoYdi0",
    "refreshToken": "cbfce885b2dca6e2...ab246394f67e"
  },
  "notification": []
}
```

Error response example (HTTP 401)

```
{
  "status": true,
  "html": "",
  "result": [],
  "notification": [
    {
      "code": 1,
      "content": "Invalid or expired refresh token",
      "title": "",
      "autoHideAfter": 5000,
      "list": [],
      "status": "error"
    }
  ]
}
```

Permissions and authorization

Agent access is controlled by partner configuration (assigned by Partner Admin).

If an agent does not have permission for a function, the API returns: **HTTP 403** with message **"You Don't have permission for this action."**

Permission functions

The following function names are used by the permission system:

Agent endpoints

- **getAgentAllWallets**
- **depositToAgent**
- **withdrawFromAgent**
- **getChildren**

Player endpoints

- **registerPlayer**
- **getPlayersForCurrentAgent**
- **depositToPlayer**
- **withdrawFromPlayer**
- **getPlayerBalanceById**

Common response format and HTTP status codes

Most endpoints return a consistent envelope: **status**, **html**, **result**, and **notification**.

Common HTTP status codes used in this API:

- **200 OK** - request processed successfully (note: some application-level errors may still return 200 with result set to false).
- **401 Unauthorized** - invalid credentials or invalid/expired refresh token.
- **403 Forbidden** - agent lacks permission for the requested function.
- **422 Unprocessable Entity** - validation or business rule error (examples: Wrong arguments, Not Supported Currency).

Agent endpoints

POST global/api/UserApi/getAgentAllWallets

Property	Value
Method	POST
Endpoint	global/api/UserApi/getAgentAllWallets
Headers	Authorization: Bearer <accessToken>

Request body example

```
{}
```

Success response example (HTTP 200)

```
{
  "status": true,
  "html": "",
  "result": [
    {
      "currencyName": "United Arab Emirates Dirham",
      "currencyCode": "AED",
      "availableWallet": "95763.82",
      "mainCurrency": "EUR",
      "creditLine": "1219249.2",
      "credit": "1219246.2",
      "availability": "717567.1",
      "balance": "-501679.1",
      "bonus": "6",
      "frozenBalance": "0",
      "withAmount": "0.00\0.00"
    },
    {
      "currencyName": "Lek",
      "currencyCode": "ALL",
      "availableWallet": "95763.82",
      "mainCurrency": "EUR",
      "creditLine": "323538.15",
      "credit": "313635.15",
      "availability": "209811",
      "balance": "-103824.15",
      "bonus": "0",
      "frozenBalance": "0",
      "withAmount": "0.00\0.00"
    }
  ],
  "notification": []
}
```

POST global/api/UserApi/depositToAgent

Property	Value
Method	POST
Endpoint	global/api/UserApi/depositToAgent

Headers	Authorization: Bearer <accessToken>
---------	-------------------------------------

Request body example

```
{
  "amount": 1, float
  "comment": "Your comment", // not required string
  "affiliateId": "2627036", // int
  "moneyStatus": 3, // 2-> credit , 3-> real // Enum (2,3)
  "currencyCode": "AMD" // string
}
```

Success response example (HTTP 200)

```
{
  "status": true,
  "html": "",
  "result": {
    "balance": "-1035.99",
    "creditLine": "1352923.00",
    "credit": "1227.99",
    "availability": "192.00",
    "bonus": "0.00",
    "currencyCode": "AMD"
  },
  "notification": [
    {
      "code": 1,
      "content": "Successful transaction",
      "title": "",
      "autoHideAfter": 5000,
      "list": [],
      "status": "success"
    }
  ]
}
```

Error response example (HTTP 422)

```
{
  "status": true,
  "html": "",
  "result": false,
  "notification": [
    {
      "code": 1,
      "content": "You don't have AMD wallet",
      "title": "",
      "autoHideAfter": 5000,
      "list": [],
      "status": "error"
    }
  ]
}
```

Error response example (HTTP 422)

```
{
  "status": true,
  "html": "",
  "result": false,
  "notification": [
    {
      "code": 1,
      "content": "Wrong arguments",
      "title": "",
      "autoHideAfter": 5000,
      "list": [],
      "status": "error"
    }
  ]
}
```

POST global/api/UserApi/withdrawFromAgent

Property	Value
Method	POST
Endpoint	global/api/UserApi/withdrawFromAgent
Headers	Authorization: Bearer <accessToken>

Request body example

```
{
  "amount": -1,
  "comment": "Your comment",
  "affiliateId": "2627036",
  "moneyStatus": 3, // 2-> credit , 3-> real // Enum (2,3)
  "currencyCode": "USD"
}
```

Success response example (HTTP 200)

```
{
  "status": true,
  "html": "",
  "result": {
    "balance": "-1034.99",
    "creditLine": "1352923.00",
    "credit": "1227.99",
    "availability": "193.00",
    "bonus": "0.00",
    "currencyCode": "AMD"
  },
  "notification": []
}
```

Error response example (HTTP 422)

```
{
  "status": true,
  "html": "",
  "result": false,
  "notification": [
    {
      "code": 1,
      "content": "Wrong arguments",
      "title": "",
      "autoHideAfter": 5000,
      "list": [],
      "status": "error"
    }
  ]
}
```

POST global/api/UserApi/getChildren

Property	Value
Method	POST
Endpoint	global/api/UserApi/getChildren
Headers	Authorization: Bearer <accessToken>

Request body example

```
{
  "start": 0,
  "limit": 20,
  "filter": {
    "self": {
      "action": "=",
      "value": false,
      "valueLabel": false
    },
    "status": {
      "action": "in",
      "value": [
        2,
        1
      ]
    },
    "affiliateId": {
      "action": "=",
      "value": "2594189",
      "valueLabel": "2594189"
    }
  },
  "isNextPage": true,
  "searchBy": {
    "agentChildrenList": ""
  }
}
```

Success response example (HTTP 200)

```
{
  "status": true,
  "html": "",
  "result": {
    "records": [
      {
        "affiliateId": "2594189",
        "username": "username15552",
        "mainCurrency": "AMD",
        "email": "testing1551@gmail.com",
        "parentAffiliateId": "56465"
      }
    ],
    "totalRecordsCount": "1",
    "titles": null,
    "total": null
  },
  "notification": []
}
```

Player endpoints

POST global/api/UserApi/registerPlayer

Property	Value
Method	POST
Endpoint	global/api/UserApi/registerPlayer
Headers	Authorization: Bearer <accessToken>

Request body example

```
{
  "player": {
    "email": "username511551@gmail.com",
    "password": "Y43d4RY43d4R++",
    "parentId": "2616430",
    "login": "username511551"
  }
}
```

Success response example (HTTP 200)

```
{"status":true,"html":"","result":1,"notification":[]}
```

Error response example (HTTP 422)

```
{
  "status": true,
  "html": "",
  "result": false,
  "notification": [
    {
      "code": 1,
      "content": "Not Supported Currency",
      "title": "",
      "autoHideAfter": 5000,
      "list": [],
      "status": "error"
    }
  ]
}
```

POST global/api/UserApi/getPlayersForCurrentAgent

Property	Value
Method	POST
Endpoint	global/api/UserApi/getPlayersForCurrentAgent
Headers	Authorization: Bearer <accessToken>

Request body examples

Example A - Search by playerId

```
{
  "start": 0,
  "limit": 20,
  "filter": {
    "withoutTotalCount": {
      "action": "=",
      "value": true
    },
    "playerId": {
      "action": "=",
      "value": "96525333",
      "valueLabel": "96525333"
    }
  },
  "isNextPage": false
}
```

Example B - Search by userName (like)

```
{
  "start": 0,
  "limit": 20,
  "filter": {
    "withoutTotalCount": {
      "action": "=",
      "value": true
    },
    "userName": {
      "action": "like",
      "value": "Ftes",
      "valueLabel": "Ftes"
    }
  },
  "isNextPage": false
}
```

Success response example (HTTP 200)

```

{
  "status": true,
  "html": "",
  "result": {
    "records": [
      {
        "affiliateId": "728333",
        "playerId": "357952521",
        "username": "dfvfjsq@refgwr.efgw",
        "registerDate": "2025-12-09 16:44:34",
        "firstname": null,
        "lastname": null,
        "currency": "EUR",
        "phoneNumber": null
      },
      {
        "affiliateId": "728333",
        "playerId": "357970652",
        "username": "dfvuj@rewgytg.rth",
        "registerDate": "2025-12-09 17:42:18",
        "firstname": null,
        "lastname": null,
        "currency": "EUR",
        "phoneNumber": null
      },
      {
        "affiliateId": "728333",
        "playerId": "357971471",
        "username": "ghrfcgyjfg@fdf.tgfh",
        "registerDate": "2025-12-09 17:44:48",
        "firstname": null,
        "lastname": null,
        "currency": "EUR",
        "phoneNumber": null
      },
      {
        "affiliateId": "728333",
        "playerId": "357977121",
        "username": "username2632",
        "registerDate": "2025-12-09 18:02:16",
        "firstname": null,
        "lastname": null,
        "currency": "EUR",
        "phoneNumber": null
      }
    ],
    "totalRecordsCount": "4",
    "titles": null,
    "total": null
  },
  "notification": []
}

```

POST global/api/UserApi/depositToPlayer

Property	Value
Method	POST
Endpoint	global/api/UserApi/depositToPlayer
Headers	Authorization: Bearer <accessToken>

Request body example

```
{
  "amount": 1,
  "comment": "test",
  "playerId": "15113649",
  "currencyCode": "AED",
  "currency": "EUR",
  "moneyStatus": 5
}
```

Success response example (HTTP 200)

```
{
  "status": true,
  "html": "",
  "result": {
    "balance": 4900.00,
    "creditLine": 1000.00,
    "credit": 500.00,
    "availability": 5400.00,
    "bonus": 100.00,
    "currencyCode": "AED"
  },
  "notification": []
}
```

Error response example (HTTP 422)

```
{
  "status": true,
  "html": "",
  "result": false,
  "notification": [
    {
      "code": 1,
      "content": "Not Supported Currency",
      "title": "",
      "autoHideAfter": 5000,
      "list": [],
      "status": "error"
    }
  ]
}
```

POST global/api/UserApi/withdrawFromPlayer

Property	Value
Method	POST
Endpoint	global/api/UserApi/withdrawFromPlayer
Headers	Authorization: Bearer <accessToken>

Request body example

```
{
  "amount": -11,
  "comment": "test",
  "playerId": "75105819",
  "currencyCode": "EUR",
  "currency": "EUR",
  "moneyStatus": 5
}
```

Success response example (HTTP 200)

```
{
  "status": true,
  "html": "",
  "result": {
    "balance": 4900.00,
    "creditLine": 1000.00,
    "credit": 500.00,
    "availability": 5400.00,
    "bonus": 100.00,
    "currencyCode": "AED"
  },
  "notification": []
}
```

Error response example (HTTP 422)

```
{
  "status": true,
  "html": "",
  "result": false,
  "notification": [
    {
      "code": 1,
      "content": "Withdrawal is restricted",
      "title": "",
      "autoHideAfter": 5000,
      "list": [],
      "status": "error"
    }
  ]
}
```

POST global/api/UserApi/getPlayerBalanceById

Property	Value
Method	POST
Endpoint	global/api/UserApi/getPlayerBalanceById
Headers	Authorization: Bearer <accessToken>

Request body example

```
{
  "playerId": "15107888"
}
```

Success response example (HTTP 200)

```
{
  "status": true,
  "html": "",
  "result": [
    {
      "balance": 0,
      "currencyCode": "EUR",
      "main": true
    }
  ],
  "notification": []
}
```

If player not found (HTTP 200)

```
{
  "status": true,
  "html": "",
  "result": [],
  "notification": []
}
```