



index.jsx

```
const [optimisticState, addOptimistic] = useOptimistic(initialState, updateFn);
```



CodeImage



index.jsx

```
"use client";
import { useOptimistic, useState, startTransition } from "react";

export default function SimpleOptimisticExample() {
  // ✅ Start with one message
  const [messages, setMessages] = useState([
    { text: "Hello there!", sending: false }
  ]);

  const [optimisticMessages, addOptimisticMessage] = useOptimistic(
    messages,
    (state, newMessage) => [
      { text: newMessage, sending: true },
      ...state
    ]
  );

  async function handleSend(e) {
    e.preventDefault();
    const form = e.target;
    const message = form.message.value;
    form.reset();

    // Add optimistic message immediately
    addOptimisticMessage(message);

    // Simulate a slow server response
    await new Promise(res => setTimeout(res, 1500));

    // When "server" responds, update real messages
    startTransition(() => {
      setMessages(prev => [{ text: message, sending: false }, ...prev]);
    });
  }

  return (
    <div>
      <form onSubmit={handleSend}>
        <input name="message" placeholder="Type a message..." />
        <button type="submit">Send</button>
      </form>

      {optimisticMessages.map((msg, i) => (
        <div key={i}>
          {msg.text}
          {msg.sending && <small> (Sending...) </small>}
        </div>
      ))}
    </div>
  );
}
```

Hello!

Send

HEY (Sending...)

Hello there!