

# Process-Supervised Reward Models for Verifying Clinical Note Generation: A Scalable Approach Guided by Domain Expertise

Hanyin Wang et al.

Mayo Clinic Health System & UIUC

EMNLP 2025

Presented by Liwen Sun

## Core Question

*"How do we verify LLM outputs when there is no ground-truth answer — especially in medicine?"*

### This Paper's Answer:

- **Process-Supervised Reward Models (PRMs)** for clinical note generation
- **Domain-informed scalable supervision** without expensive human annotation
- **Step-by-step verification** that enables explainability and quality control

### Preview:

- ① Why clinical note verification is uniquely challenging
- ② How to build PRMs without ground-truth answers
- ③ Domain-expert step decomposition + LLM-generated synthetic errors
- ④ State-of-the-art results: 98.8% verification, 56.2% preference accuracy

# Section 1: Motivation - Clinical Note Verification Challenges

## Why Clinical Note Verification Is Hard

### 1. Clinical notes are open-ended

- No single "correct" answer
- Multiple acceptable phrasings and styles
- Subjective physician preferences

### 2. Errors are subtle but high-stakes

- **Factual inaccuracies:** Wrong dosages, laterality errors (left vs right)
- **Hallucinations:** Fabricated symptoms or history never discussed
- **Omissions:** Missing critical follow-up instructions
- **Unhelpfulness:** Vague phrasing ("follow up soon" vs "in 2 weeks")

### 3. Current evaluation doesn't scale

- Expensive physician reader studies required
- Manual review is time-consuming
- Cannot keep pace with rapid AI deployment

# Section 1: Motivation - Clinical Context

## Ambient Scribing Adoption Is Accelerating

- **Current state:** AI systems generate clinical notes from patient-doctor dialogues
- **Projection:** 30% of healthcare market by 2025
- **Impact:** Substantial reduction in physician documentation burden
- **Challenge:** How to ensure quality at scale?

## Contrast with Math/Code PRMs

Aspect	Math/Code	Clinical Notes
Ground truth	Exact correctness	No single answer
Verification	Deterministic	Subjective judgment
Error detection	Clear (wrong output)	Subtle nuances
Stakes	Low	Patient safety

**Key insight:** Need verification method that handles subjectivity while maintaining rigor

# Section 1: Motivation - Reward Model Limitations

## Outcome-Supervised Reward Models (ORMs)

- Assign single scalar score to entire generation
- **Pros:** Simple to train, well-established
- **Cons:**
  - No explainability - cannot identify where errors occur
  - Coarse-grained feedback
  - Limited guidance for improvement

## Process-Supervised Reward Models (PRMs)

- Provide step-level verification
- **Advantages:**
  - **Explainability:** Pinpoint exact error locations
  - **Best-of-N filtering:** Better candidate selection
  - **Inference-time scaling:** Enable MCTS, beam search
  - **Step-level RL:** More granular training signals
- **Success stories:** Math reasoning (Lightman et al. 2023), code generation

# Section 1: Motivation - The Gap

## PRMs: Success in Math/Code, Gap in Open-Ended Domains

### Why PRMs worked for Math/Code:

- Clear solution steps (one equation per step)
- Deterministic correctness verification
- Easy to collect step-level annotations

### Why PRMs haven't worked for Clinical Notes:

- ① **Verification of correctness:** No objective ground-truth
  - How do you know a clinical reasoning step is "correct"?
  - Multiple valid approaches to same clinical situation
- ② **Process-supervised data collection:** Prohibitively expensive
  - Need physician annotations for **every step**
  - Cannot scale to thousands of samples
  - Domain expertise required at annotation time

**This paper's contribution:** Overcome both challenges with novel framework

## Section 3: Task Definition

### Ambient Scribing Task

**Input:** Patient–doctor dialogue (transcribed conversation) *Doctor: "Hello, what brings you in today?"*

*Patient: "I've been having chest pain and shortness of breath."*

*Doctor: "When did this start? How severe is the pain?"*

*Patient: "About 3 days ago. It's worse when I exercise."*

**Output:** Clinical note (focus on **Assessment & Plan**) *Assessment and Plan:*

*1. Chest pain, likely angina*

*Assessment: 55-year-old male with 3-day history of exertional chest pain...*

*Plan: Order stress test, start aspirin 81mg daily, cardiology referral...*

**Goal:** Train PRM to:

- 1 Verify notes step-by-step
- 2 Identify errors at precise locations
- 3 Select best note among multiple candidates (Best-of-N)

## Section 3: Why Assessment & Plan Only?

### Clinical Note Structure (SOAP Format):

- **Subjective:** Patient's reported symptoms
- **Objective:** Physical exam, vital signs, test results
- **Assessment:** Diagnosis and clinical reasoning
- **Plan:** Treatment plan and follow-up

### Why Focus on A&P?

- ① **Core clinical reasoning:** Contains key diagnostic thinking and decisions
- ② **Most error-prone:** Requires synthesis and medical judgment
- ③ **Time-consuming:** Most labor-intensive for physicians to write
- ④ **Highest value:** Directly impacts patient care and treatment
- ⑤ **Current gap:** After domain adaptation, LLMs generate high-quality Subjective/Objective sections, but notable gaps remain in A&P

**Other sections:** Subjective (nearly indistinguishable from human), Objective (imported from EHR)



# Section 3: Base Datasets

## Training Data Sources

### 1. **Dialogue-G** (1,205 cases)

- Synthetic patient-doctor conversations
- Generated by Gemini Pro 1.0
- Gold-reference notes following "Best Practice" format

### 2. **ACI-BENCH** (67 cases from training subset)

- Ambient Clinical Intelligence benchmark
- Multiple conversation types: virtual assistant, scribe, natural dialogue
- Notes regenerated with Gemini Pro 1.0 for consistency

### "Best Practice" Format:

- Developed by panel of internal medicine physicians
- Problem-oriented charting approach
- Clear structure: Problem → Assessment → Plan
- Standardized level of detail and completeness

**Key Point:** Gold-reference notes are high-quality baselines, not perfect ground truth

## Section 4: Methods - Step Definition (Most Important)

**Core Challenge:** What is a "step" in a clinical note?

**Math/Code PRMs:**

- Clear steps: one equation or line of code
- Sequential reasoning

**Clinical Notes:**

- Semi-structured text
- Multiple problems addressed simultaneously
- No obvious "steps"

**Solution: Hierarchical Step Structure**

- ➊ **Problem-level step:** Problem description (e.g., "1. Congestive heart failure")
- ➋ **Sentence-level steps:** Each sentence within problem
- ➌ **Problem completeness step:** Checks if problem fully documented
- ➍ **Note completeness step:** Checks if all problems addressed
- ➎ **End-of-note step:** Overall quality score

**Design Rationale:**

- Aligns with problem-oriented charting (standard clinical practice)

## Section 4: Methods - Step Definition Example

### **Original Clinical Note:** *Assessment and Plan:*

#### *1. Congestive heart failure exacerbation*

*Assessment: Patient presents with dyspnea and peripheral edema. Physical exam shows bilateral lower extremity edema. Echocardiogram reveals reduced ejection fraction at 35%.*

*Plan: Increase furosemide to 40mg twice daily. Restrict sodium intake to  $\leq 2$ g/day. Follow up in 1 week to reassess fluid status.*

#### *2. Hypertension*

*Assessment: Blood pressure well controlled on current regimen.*

*Plan: Continue lisinopril 20mg daily.*

## Section 4: Methods - Step Definition Example

### Transformed to Steps:

- ① Problem: "Congestive heart failure exacerbation"
- ② "Assessment: Patient presents with dyspnea and peripheral edema."
- ③ "Physical exam shows bilateral lower extremity edema."
- ④ "Echocardiogram reveals reduced ejection fraction at 35%."
- ⑤ "Plan: Increase furosemide to 40mg twice daily."
- ⑥ "Restrict sodium intake to  $\leq 2$ g/day."
- ⑦ "Follow up in 1 week to reassess fluid status."
- ⑧ Problem 1 completeness
- ⑨ Problem: "Hypertension"
- ⑩ "Assessment: Blood pressure well controlled on current regimen."
- ⑪ "Plan: Continue lisinopril 20mg daily."
- ⑫ Problem 2 completeness
- ⑬ Note completeness
- ⑭ End-of-note

# Section 4: Methods - Why This Design Matters

## Alignment with Real Clinical Workflows

### 1. Problem-Oriented Charting

- Standard medical documentation approach
- Problem list critical for:
  - Medical coding and billing
  - Insurance reimbursement
  - Clinical communication between providers

### 2. Prevents Reward Hacking

- Without completeness steps: Model might prefer shorter notes
- Example bad behavior: Omit entire problems to get higher scores
- Completeness steps enforce thoroughness

### 3. Multi-Granularity Verification

- **Sentence level:** Detect factual errors, hallucinations
- **Problem level:** Ensure complete assessment & plan per problem
- **Note level:** Verify all relevant problems addressed

### 4. Explainability

- Can identify: "Error in Step 5 of Problem 1"
- Physicians can quickly locate and fix issues

# Section 4: Methods - Error Taxonomy

## Four Error Categories (from physician review of LLM outputs)

### 1. Factual Inaccuracy

- **Definition:** Information referenced in conversation but not supported by content
- **Examples:**
  - Laterality: "left knee pain" → "right knee pain"
  - Dosage: "furosemide 40mg" → "furosemide 80mg"
  - Timeline: "follow up in 1 month" → "follow up in 6 months"
- **Impact:** Can lead to serious clinical consequences

### 2. Hallucination

- **Definition:** Completely unrelated entities never mentioned in conversation
- **Examples:**
  - Adding "history of diabetes" when never discussed
  - Fabricating test results not mentioned
  - Inventing symptoms patient didn't report
- **Key distinction:** Entirely novel information vs. misrepresentation

## Section 4: Methods - Error Taxonomy (continued)

### 3. Unhelpfulness

- **Definition:** Vague, incomplete, or confusing expressions lacking critical details
- **Examples:**
  - Imprecise: "patient has some issues" vs "patient reports chest pain"
  - Vague timing: "follow up soon" vs "follow up in 2 weeks"
  - Missing specificity: "adjust medication" vs "increase lisinopril to 20mg"
- **Impact:** Reduces clinical utility even if technically accurate

### 4. Incompleteness

- **Definition:** Missing specific steps or entire problems
- **Implementation:** Randomly remove steps or problems from samples
- **Examples:**
  - Omitting problem from problem list
  - Missing plan for documented assessment
  - No follow-up instructions
- **Rationale:** Ensures model doesn't favor brevity over completeness

**Key Point:** All four error types based on real failure modes observed in LLM-generated clinical notes.

# Section 4: Methods - Synthetic Error Generation Process

**Goal:** Generate realistic errors at scale without human annotation

## Step 1: Prompt Engineering

- Carefully designed prompts for Gemini Pro 1.5
- Separate prompt for each error type
- Instructions specify: location (step/problem level), number of errors, output format

## Step 2: Error Pool Generation

- Generate 10 unique errors per type per case
- Total: 40 errors per case ( $10 \times 4$  types)
- Output in structured JSON format

## Step 3: Manual Quality Control

- Physician co-authors inspect generated errors
- Verify errors are realistic and clinically plausible
- Ensure error severity is appropriate

## Step 4: Systematic Injection

- Randomly select steps in gold-reference notes
- Replace with errors from pool



## Section 4: Methods - Error Generation Details

### Prompt Template Example (Factual Inaccuracy):

*"You are provided with a doctor-patient conversation and its corresponding clinical note in JSON format. Your task is to introduce 10 errors into the clinical note.*

*Error type: Factual Inaccuracy - Introduce detailed factual errors related to information or topics discussed in the conversation but not supported by it. Examples include changing 'left' to 'right', altering medication names, or modifying follow-up timeframe.*

*For each change, include: error\_type, problem\_no, step\_no, detailed\_error, new\_content, original\_content"*

### Output Format (JSON): {

```
"Errors": [{  
  "Error_type": "Factual Inaccuracy",  
  "Problem_no": "1", "Step_no": "4",  
  "New_content": "Increase furosemide to 80mg twice daily",  
  "Original_content": "Increase furosemide to 40mg twice daily"  
}]
```

}

### Why This Works:

- Scalable: Generate thousands of samples quickly
- Realistic: LLM understands clinical context
- Controllable: Can adjust error distribution and severity

# Section 3: Methods — Process-supervised Data Construction

## Base data

- Dialogue-G (majority) + ACI-BENCH training subset
- “Gold-reference” A&P notes follow a physician-recommended best-practice format

## Pipeline

- 1 Transform A&P into step hierarchy (problem + sentences + completeness steps)
- 2 Use Gemini Pro 1.5 to generate pools of errors per error type (with prompt engineering + physician inspection)
- 3 Create negative samples by swapping an original step with a synthetic error
- 4 Add semantic diversity via paraphrases that preserve meaning (replace correct steps with paraphrases)

**Outcome:** PRM-Clinic dataset: gold samples (+ everywhere) mixed with negatives (localized “-” labels).

## Section 3: Methods — PRM-Clinic Dataset (Table 1)

Statistic	Value
Cases (ACI-BENCH)	67
Cases (Dialogue-G)	1,205
Total samples	9,680
Mean samples per case	7.61
<b>Mean errors per negative sample</b>	
Factual Inaccuracy	1.16
Hallucination	1.18
Unhelpfulness	1.19
Incompleteness	1.27
Mean paraphrases per sample	2.38

Notes: Dialogue-G is the majority of instances; training mixes gold and negatives.

# Section 4: Methods - Training the PRM

## Model Architecture

- **Base:** LLaMA-3.1 8B Instruct
- Uses reserved special tokens for step and score tokens
- No architectural modifications needed

**Input Format:** [Dialogue] [Problem 1] <step> [Step 1] <score> + <step> [Step 2] <score> -  
...

## Training Objective:

- Cross-entropy loss:  $L = -\sum_{i \in I} \log p_{\theta}(t_i | t_{<i})$
- $I$  = set of token positions to include
- **Best approach:** Notes-Only loss (mask dialogue tokens)

## Labels:

- **Gold-reference samples:** All steps get "+"
- **Error-containing samples:**
  - Erroneous step gets "-"
  - Other steps get "+"
  - Completeness steps get "-" if incomplete
  - End-of-note gets "-" if any error present

# Section 5: Using PRMs at Inference - The Process

## Four-Step Inference Pipeline

### Step 1: Generate Candidate Notes

- Use LLM (e.g., LLaMA-Clinic) to generate  $N$  notes from same dialogue
- Vary temperature for diversity (0.2 to 2.0)
- Typical:  $N = 2,000$  for physician reader study

### Step 2: Compute Step-Level PRM Scores

- Single forward pass: dialogue + note through PRM
- PRM score at step  $i = p_{\theta}(\text{"+"} | \text{context}_{<i})$
- Extract softmax probability of "+" token at each step position

### Step 3: Aggregate to Note-Level Score

- **PRM**: Product of all step scores
  - $\text{Score}_{\text{note}} = \prod_{i=1}^N \text{PRM}_i$
  - In practice:  $\log \text{Score} = \sum_{i=1}^N \log \text{PRM}_i$  (numerical stability)
- **ORM**: Use only end-of-note step score

### Step 4: Best-of-N Selection

- Select note with highest note-level score

## Section 5: Evaluation Tasks

Task	Metric Type	Cases	ID/OOD	Note Source
<b>A-Verify</b>	Verification	80	OOD	LLaMA-Clinic
<b>A-Prefer</b>	Preference	80	OOD	LLaMA-Clinic
<b>Dialogue-G</b>	Verification	80	ID	Gemini Pro
<b>A-Validate</b>	Verification	20	ID	Gemini Pro

### ID vs OOD Setting:

- **ID (In-Distribution)**: Notes from Gemini Pro (same model family as training data)
- **OOD (Out-of-Distribution)**: Notes from LLaMA-Clinic (LLaMA-2 13B with domain adaptation)
- OOD tests generalization to different model architectures

### Task Details:

- **Verification (A-Verify, Dialogue-G, A-Validate)**: Select gold-reference from error-containing samples
- **Preference (A-Prefer)**: Select physician-preferred note from 3 candidates
  - Most challenging task
  - Uses physician preference labels from RLHF study
  - Captures subjective quality judgments

## Section 5: Why PRMs Help - Comparison

### PRM vs ORM Aggregation

Aggregation Method	A-Prefer	A-Verify
Product (PRM)	<b>56.2%</b>	<b>98.8%</b>
Last (ORM)	51.2%	98.8%
Mean	55.0%	98.8%
Min	45.0%	97.5%
Max	42.5%	96.2%

### Why Product Works Best:

- ① **Fine-grained error detection:** Any single error significantly lowers score
- ② **Encourages consistency:** All steps must be high quality
- ③ **Better preference alignment:** Captures physician's holistic judgment

### Additional Benefits of PRMs:

- **Explainability:** Can show physicians exactly which steps scored low
- **Debugging:** Developers can identify systematic error patterns
- **Future work:** Enable MCTS, step-level RL

## Section 6: Main Results - Overall Performance

Model	A-Prefer (OOD)	A-Verify (OOD)	Dialogue-G (ID)	A-Validate (ID)
Gemini Pro 1.0	43.8%	46.2%	45.0%	45.0%
Gemini Pro 1.5	50.0%	93.8%	95.0%	90.0%
GPT-4o	41.2%	86.2%	81.2%	90.0%
o1	52.5%	73.8%	66.2%	75.0%
o3-mini	53.8%	86.2%	86.2%	90.0%
Vanilla ORM	37.5%	70.0%	76.2%	85.0%
ORM (Ours)	51.2%	<b>98.8%</b>	97.5%	100%
PRM (Ours)	<b>56.2%</b>	<b>98.8%</b>	<b>98.8%</b>	<b>100%</b>

### Key Numbers to Emphasize:

- **98.8% on A-Verify:** Near-perfect gold-reference detection (OOD)
- **56.2% on A-Prefer:** Best physician-preference alignment (OOD)
- **100% on A-Validate:** Perfect performance on ID verification

### Comparison Highlights:

- **vs Gemini Pro 1.5:** +6.2% on A-Prefer, +5% on A-Verify
- **vs o3-mini:** +2.4% on A-Prefer (with 8B vs proprietary model)
- **vs Vanilla ORM:** +18.7% on A-Prefer (massive improvement)



# Section 6: Main Results - PRM vs ORM Insights

## Same Model Checkpoint, Different Usage

### Verification Tasks (A-Verify, Dialogue-G, A-Validate):

- PRM and ORM perform **comparably**
- Both achieve near-perfect accuracy
- Detecting errors is straightforward for both

### Preference Task (A-Prefer):

- **PRM: 56.2%**
- **ORM (Ours): 51.2%**
- **Vanilla ORM: 37.5%**
- **PRM advantage: 5%** over same-checkpoint ORM

### Critical Insights:

- ① **Step-level training helps even for ORM:**
  - ORM (Ours) vs Vanilla ORM: 51.2% vs 37.5% (+13.7%)
  - Learning step-level correctness improves overall judgment
- ② **Product aggregation better captures preferences:**
  - Multiplicative scoring ensures consistency
  - Better aligns with physician holistic evaluation

## Section 7: Ablation Studies - Loss Functions

**Question:** Which tokens should be included in loss computation?

Loss Function	PRM (A-Prefer)	ORM (A-Prefer)
All tokens	46.2%	38.8%
Score-Token-Only	37.5%	27.5%
Special-Token	48.8%	42.5%
<b>Notes-Only</b>	<b>55.0%</b>	<b>48.8%</b>
+ Data Selection	<b>56.2%</b>	<b>51.2%</b>

**Findings:**

- **Score-Token-Only:** Severe degradation (37.5%)
  - Model can't learn context without seeing note text
- **Notes-Only:** Best performance (55.0%)
  - Masks dialogue tokens, focuses on clinical documentation
  - Prevents overfitting to repetitive dialogue patterns
- **All tokens:** Baseline (46.2%)
- **Special-Token:** Slight improvement (48.8%)

**Interpretation:** Model needs to learn to **generate** notes (conditioned on dialogue) while simultaneously predicting correctness

## Section 7: Ablation Studies - Data Selection

**Question:** Does quality filtering help? What about paraphrases?

Data Selection	Samples	PRM (A-Prefer)
High Quality Only	5,854	35.0%
High + Paraphrases	5,854	45.0%
High + Medium	10,094	48.8%
High + Med + Para	10,094	46.2%
<b>All Data + Para</b>	<b>10,952</b>	<b>56.2%</b>

**Findings:**

- ① **Paraphrases help:** Especially for smaller datasets (+10%)
- ② **More data > perfect quality:** Full dataset beats filtered subsets
- ③ **Best combination:** All data + paraphrases (56.2%)

**Hypothesis:** When training data is limited, model benefits from diverse examples (including lower-quality ones) to learn robust patterns

**Practical Implication:** Don't over-filter training data; diversity and quantity can outweigh perfect quality

## Section 8: Physician Reader Study - Setup

**Research Question:** Which metric better predicts downstream Best-of-N performance?

- A-Prefer (physician preference alignment)
- A-Verify (gold-reference detection)

**Methodology:**

- 1 **Select PRM checkpoints** with different A-Prefer/A-Verify scores
  - Dual High (both metrics high)
  - Dual Low (both metrics low)
  - High A-Prefer vs Low A-Prefer (matched on A-Verify)
  - High A-Verify vs Low A-Verify (matched on A-Prefer)
- 2 **Generate candidates:** 2,000 notes per case using LLaMA-Clinic
  - Vary temperature (0.2 to 2.0)
  - Total: 40 cases from ACI-BENCH test1
- 3 **Select with PRM:** Each checkpoint selects top note via Best-of-2000
- 4 **Physician review:** 9 physicians evaluate in blinded, randomized manner
  - Pairwise comparisons between checkpoint selections
  - Majority vote determines winner

## Section 8: Physician Reader Study - Results

**Win Rates** (percentage preferring first model):

Comparison	Win Rate
Dual High vs Dual Low	55.6%
High A-Prefer vs Low A-Prefer	50.0%
High A-Verify vs Low A-Verify	47.5%

**Key Findings:**

- Both metrics predict real-world performance**
  - Models strong on either metric outperform weak ones
  - Dual High significantly beats Dual Low (55.6% win rate)
- A-Prefer slightly more predictive**
  - 50.0% vs 47.5% win rates
  - Makes intuitive sense - directly measures preference
- Optimize for both metrics**
  - Verification accuracy matters for error detection
  - Preference alignment matters for subjective quality
  - Best models excel at both

**Practical Implication:** For real-world deployment, monitor both verification and preference metrics

# Section 9: Limitations

## Study Limitations

### 1. Limited Physician Pool

- Only 9 physicians in reader study
- All from internal medicine specialty
- Preferences may not generalize to other specialties

### 2. Single Specialty Focus

- "Best Practice" format designed for internal medicine
- Other specialties may have different documentation standards
- Step definitions may need adjustment for other domains

### 3. Proprietary LLM Dependency

- Uses Gemini Pro 1.5 for error generation
- Could potentially use open-source alternatives (e.g., LLaMA-3.1 405B)
- Methodology is model-agnostic

### 4. Modest Preference Performance

- 56.2% on A-Prefer is SOTA but leaves room for improvement
- Many factors influencing physician preferences still unexplored

# Section 9: Ethical Considerations & Future Work

## Ethical Considerations

- **Child safety:** Cautious about content involving minors
- **Bias amplification:** Synthetic data must not introduce/amplify biases
  - Certain error types disproportionately associated with specific populations
  - Could reinforce inequities in care delivery
- **Validation at scale:** Essential before real-world deployment
- **Reward hacking:** Need safeguards against unintended optimization

## Future Directions

- 1 **Other medical specialties**
  - Adapt step definitions and error taxonomy
  - Surgery, pediatrics, emergency medicine
- 2 **Expand error taxonomy**
  - Additional error types beyond current four
  - Specialty-specific errors
- 3 **Inference-time scaling**
  - Monte Carlo Tree Search (MCTS)
  - Beam search with PRM guidance
- 4 **Step-level reinforcement learning**
  - Use PRM scores as rewards for policy gradient training

# Section 10: Conclusions

## Main Contributions Summary

### 1. Novel Framework

- First PRM for clinical text generation
- Generalizable methodology for domains without ground-truth

### 2. Domain-Informed Design

- Hierarchical step decomposition based on clinical expertise
- Error taxonomy from real LLM failure modes

### 3. Scalable Supervision

- LLM-generated synthetic errors at scale
- Avoids expensive human annotation

### 4. State-of-the-Art Results

- 98.8% verification accuracy (OOD)
- 56.2% preference alignment (OOD)
- Outperforms proprietary reasoning models with 8B parameters

**"PRMs are not about math — they're about structure."**