DLX SIMULATOR -TUTORIAL

A. Simulating an Assembly file

1. Login to any ***i80labpcXX.ira.uka.de*** directly or using SSH or using X2Go Client. For example login as ***asip-sajjad04*** into ***i80labpc02.ira.uka.de***
2. Open shell terminal from the start menu. It should be in your default home directory. Go to the directory "***~/ASIP_SS17/Session1/ASIPMeisterProjects/brownie:$***"
3. Set the proper path and parameters in "env_settings" like dlxsim path, project path and project name.
4. Go to the application directory, for example: "***~/ASIP_SS17/Session1/ASIPMeisterProjects/brownie/Applications/Arith:$***" and type "***make clean***" clean this directory it there are previously generated files.

```
asip04@i80labpc04:~/ASIP_SS17/Session1/ASIPMeisterProjects/brownie/Applications/Arith:$make clean
/bin/rm -rf BUILD_SIM BUILD_FPGA
asip04@i80labpc04:~/ASIP_SS17/Session1/ASIPMeisterProjects/brownie/Applications/Arith:$ls
1_Arith.s  Makefile
asip04@i80labpc04:~/ASIP_SS17/Session1/ASIPMeisterProjects/brownie/Applications/Arith:$
```

5. As this application subdirectory contains .s file, you can directly simulate it using "***make dlxsim***" without compiling it. If this application has .c file, then you have to compile it using "***make sim***". For example to load "***1_Arith.s***" and using no forwarding, use the following parameters. A directory "***BUILD_SIM***" is created which contains different temporary files and a .dlxsim file to be simulated in dlxsim (in this case it is "***Arith.dlxsim***").

```
asip04@i80labpc04:~/ASIP_SS17/Session1/ASIPMeisterProjects/brownie/Applications/Arith:$make dlxsim DLXSIM_PARAM="-f1_Arith.s -da0 -pf0"
---------------------------------------------------
Transforming file "1_Arith.s" for target SIMULATION.
---------------------------------------------------
---------------------------------------------------
Assembling/Linking for target SIMULATION:
---------------------------------------------------
Creating combined files.
STACK_START:                    0xFFFFC
---------------------------------------------------
FINISHED ASSEMBLING/LINKING for target SIMULATION.
---------------------------------------------------



---------------------------------------------------
Starting dlxsim:
---------------------------------------------------
/Software/epp/dlxsim_Laboratory/dlxsim -fBUILD_SIM/Arith.dlxsim -f1_Arith.s -da0 -pf0
Biggest used address for Text Section (word aligned): 0x1c
Biggest used address for Data Section (word aligned): 0x0
(dlxsim)
```

6. Then in dlxsim you can use "go" or "step" command to simulate all instructions or each instruction step by step respectively.

```
(dlxsim) step
stopped after (single) step, pc = _main+0x04 (0x0004): addi r2,r0,0x9
(dlxsim) step
stopped after (single) step, pc = _main+0x08 (0x0008): or r3,r1,r2
(dlxsim) get r2
r2:         0x00000009
(dlxsim) go
TRAP #0 received
Altogether 41,0e0(41) cycles executed.
  0 Warnings for unresolved data dependencies printed.
  0 Warnings for successive load/store commands printed.
  0 Warnings for load/stores in the text section printed.
(dlxsim)
```

7. You can see different statistics using "***stats***" command.
8. Enter "***quit***" command to exit from dlxsim simulator.

B. Simulating a C file

9. If the application consists of C files then you can use "***make sim***", which will compile your application into assembly file and automatically starts dlxsim. The other steps remain the same. Remember, "***make sim***" only works if you have already created Compiler.

```
asip04@i80labpc04:~/ASIP_SS17/Session1/ASIPMeisterProjects/brownie/Applications/Arith:$make sim
```

10. You can have different parameter to "***make sim***" like optimization identifier and number of NOPS added for simulating your application in hardware.

```
asip04@i80labpc04:~/ASIP_SS17/Session1/ASIPMeisterProjects/brownie/Applications/Arith:$make sim GCC_PARAM=-O3
```

11. You can now start dlxsim simulation using following different commands:

```
asip04@i80labpc04:~/ASIP_SS17/Session1/ASIPMeisterProjects/brownie/Applications/Arith:$make dlxsim GCC_PARAM=-O3
```

OR

```
asip04@i80labpc04:~/ASIP_SS17/Session1/ASIPMeisterProjects/brownie/Applications/Arith:$make dlxsim DLXSIM_PARAM="-fBUILD_SIM/Arith.dlxsim -da0 –pf1"
```

12. You can save dlxsim simulation output to different file using "***–lf***", "***–uf***", or ***"–af***" for LCD, UART or audio respectively as following:

```
asip04@i80labpc04:~/ASIP_SS17/Session1/ASIPMeisterProjects/brownie/Applications/Arith:$make dlxsim DLXSIM_PARAM="-fBUILD_SIM/Arith.dlxsim -da0 –pf1 –lfoutput_dlxsim.txt"
```