

---

```

from __future__ import print_function
import numpy as np
import argparse
import torch
import torch.nn as nn
import torch.nn.functional as F
import torch.optim as optim
from torchvision import datasets, transforms
from sklearn.metrics import *
from matplotlib import pyplot as plt
%matplotlib inline

class CNN(nn.Module):
    def __init__(self):
        super(CNN, self).__init__()
        self.conv1 = nn.Conv2d(1, 20, 5, 1)
        .....self.conv2.=.nn.Conv2d(20,.20,.5,.1)

        .....self.conv3.=.nn.Conv2d(20,.50,.1,.1)
        .....self.conv4.=.nn.Conv2d(50,.50,.1,.1)
        .....self.conv5.=.nn.Conv2d(50,.50,.1,.1)
        .....self.conv6.=.nn.Conv2d(50,.50,.1,.1)
        .....self.conv7.=.nn.Conv2d(50,.50,.1,.1)

        .....self.fc1.=.nn.Linear(4*4*50,.500)
        .....self.fc2.=.nn.Linear(500,.10)

    ....def forward(self, x):
        .....x.=.F.relu(self.conv1(x))
        .....x.=.F.max_pool2d(x,.2,.2)
        .....x.=.F.relu(self.conv2(x))
        .
        .....x.=.F.relu(self.conv3(x))
        .....x.=.F.relu(self.conv4(x))
        .....x.=.F.relu(self.conv5(x))
        .....x.=.F.relu(self.conv6(x))
        .....x.=.F.relu(self.conv7(x))
        .....
        .....x.=.F.max_pool2d(x,.2,.2)

        .....x.=.x.view(-1,.4*4*50)
        .....x.=.F.relu(self.fc1(x))
        .....x.=.self.fc2(x)
        .....return F.log_softmax(x,.dim=1)

def train(model, device, train_loader, optimizer, epoch):
    losses = []
    model.train()
    for batch_idx, (data, target) in enumerate(train_loader):
        data, target = data.to(device), target.to(device)
        optimizer.zero_grad()
        output = model(data)
        loss = F.nll_loss(output, target)
        loss.backward()

```

```

        loss.backward_(),
        optimizer.step()
        losses.append(loss.item())
        if batch_idx > 0 and batch_idx % 100 == 0:
            print('Train Epoch: {} [{}/{}]\t({:.0f}%) \tLoss: {:.6f}'.format(
                epoch, batch_idx * len(data), len(train_loader.dataset),
                100. * batch_idx / len(train_loader), loss.item()))
    return losses

def test(model, device, test_loader):
    model.eval()
    test_loss = 0
    correct = 0
    with torch.no_grad():
        for data, target in test_loader:
            data, target = data.to(device), target.to(device)
            output = model(data)
            test_loss += F.nll_loss(output, target, reduction='sum').item() # sum up batch
            pred = output.argmax(dim=1, keepdim=True) # get the index of the max log-probability
            correct += pred.eq(target.view_as(pred)).sum().item()
    test_loss /= len(test_loader.dataset)
    print('\nTest set: Average loss: {:.4f}, Accuracy: {}/{} ({:.0f}%) \n'.format(
        test_loss, correct, len(test_loader.dataset),
        100. * correct / len(test_loader.dataset)))
    return (float(correct) / len(test_loader.dataset))

train_loader = torch.utils.data.DataLoader(
    datasets.MNIST(
        '../data',
        train=True,
        download=True,
        transform=transforms.Compose([
            transforms.ToTensor(),
            transforms.Normalize((0.1307,), (0.3081,))
        ])
    ),
    batch_size=64,
    shuffle=True)
test_loader = torch.utils.data.DataLoader(
    datasets.MNIST(
        '../data',
        train=False,
        transform=transforms.Compose([
            transforms.ToTensor(),
            transforms.Normalize((0.1307,), (0.3081,))
        ])
    ),
    batch_size=1000,
    shuffle=True)

model = CNN()
optimizer = optim.SGD(model.parameters(), lr=0.01, momentum=0.5)
device = torch.device("cpu") # or 'gpu'
losses = []
accuracies = []
for epoch in range(0, 10):

```


```
    losses.extend(train(model, device, train_loader, optimizer, epoch))
    accuracies.append(test(model, device, train_loader))
```



Downloading <http://yann.lecun.com/exdb/mnist/train-images-idx3-ubyte.gz>

```
def mean(li): return sum(li)/len(li)
plt.figure(figsize=(14, 4))
plt.xlabel('training batch')
plt.ylabel('loss')
plt.plot([mean(losses[i:i+10]) for i in range(len(losses))])
```


[<matplotlib.lines.Line2D at 0x7f00466b8fd0>]



Train Epoch: 0 [12800/60000 (21%)] Loss: 2.307724

```
plt.figure(figsize=(14, 4))
plt.xticks(range(len(accuracies)))
plt.xlabel('training epoch')
plt.ylabel('accuracy')
plt.plot(accuracies, marker='o')
```

[<matplotlib.lines.Line2D at 0x7f0046628ad0>]



Train Epoch: 0 [12800/60000 (21%)] Loss: 2.307724

```
def test_label_predictions(model, device, test_loader):
    model.eval()
    actuals = []
    predictions = []
    with torch.no_grad():
        for data, target in test_loader:
            data, target = data.to(device), target.to(device)
            output = model(data)
```

```

        prediction = output.argmax(dim=1, keepdim=True)
        actuals.extend(target.view_as(prediction))
        predictions.extend(prediction)
    return [i.item() for i in actuals], [i.item() for i in predictions]

```

```

actuals, predictions = test_label_predictions(model, device, test_loader)
print('Confusion matrix:')
print(confusion_matrix(actuals, predictions))
print('F1 score: %f' % f1_score(actuals, predictions, average='micro'))
print('Accuracy score: %f' % accuracy_score(actuals, predictions))

```

Confusion matrix:

```

[[ 973    0    1    0    0    0    5    1    0    0]
 [    0 1122    3    0    0    0    5    1    4    0]
 [    4    2 1016    0    0    0    6    0    4    0]
 [    1    1   10  964    0   23    0    3    8    0]
 [    1    0    5    1  962    0    5    0    0    8]
 [   10    1    0    6    0  862    8    1    1    3]
 [    8    2    0    0    1    6  941    0    0    0]
 [    2    9   24    0    1    0    0  971   12    9]
 [    4    0    6    1    2    5   13    0  941    2]
 [    9    0    0    0   15    2    1    5   13  964]]

```

F1 score: 0.971600

Accuracy score: 0.971600

Train Epoch: 5 112800/100000 (41%) Loss: 0.134133

```

def test_class_probabilities(model, device, test_loader, which_class):
    model.eval()
    actuals = []
    probabilities = []
    with torch.no_grad():
        for data, target in test_loader:
            data, target = data.to(device), target.to(device)
            output = model(data)
            prediction = output.argmax(dim=1, keepdim=True)
            actuals.extend(target.view_as(prediction) == which_class)
            probabilities.extend(np.exp(output[:, which_class]))
    return [i.item() for i in actuals], [i.item() for i in probabilities]

```


which\_class = 9

actuals, class\_probabilities = test\_class\_probabilities(model, device, test\_loader, which\_

```

fpr, tpr, _ = roc_curve(actuals, class_probabilities)
roc_auc = auc(fpr, tpr)
plt.figure()
lw = 2
plt.plot(fpr, tpr, color='darkorange',
         lw=lw, label='ROC curve (area = %0.2f)' % roc_auc)
plt.plot([0, 1], [0, 1], color='navy', lw=lw, linestyle='--')
plt.xlim([0.0, 1.0])
plt.ylim([0.0, 1.05])
plt.xlabel('False Positive Rate')
plt.ylabel('True Positive Rate')
plt.title('ROC for digit=%d class' % which_class)
plt.legend(loc="lower right")
plt.show()

```



```
print('Trainable parameters:')
for name, param in model.named_parameters():
    if param.requires_grad:
        print(name, '\t', param.numel())
```

```
Trainable parameters:
conv1.weight      500
conv1.bias        20
conv2.weight     10000
conv2.bias        20
conv3.weight     1000
conv3.bias        50
conv4.weight     2500
conv4.bias        50
conv5.weight     2500
conv5.bias        50
conv6.weight     2500
conv6.bias        50
conv7.weight     2500
conv7.bias        50
fc1.weight      400000
fc1.bias        500
fc2.weight      5000
fc2.bias        10
```

