W04 Learning Activities

- Due Mar 26 at 4:59pm
- Points 11
- Questions 9
- Available until Apr 2 at 4:59pm
- Time Limit None
- Allowed Attempts 3

Instructions

1. **Complete** the **learning activities.** **(https://byui-cse.github.io/wdd131-ww-course/week04/)**
2. **Complete** this quiz to check your understanding.
3. Conditions
   - The quiz is open note, application, and internet.
   - Your latest score will be recorded in the gradebook.

Attempt History

	Attempt	Time	Score
KEPT	Attempt 3	1 minute	10 out of 11
LATEST	Attempt 3	1 minute	10 out of 11
	Attempt 2	4 minutes	10 out of 11
	Attempt 1	19 minutes	8 out of 11

Correct answers are hidden.

Score for this attempt: 10 out of 11
Submitted Mar 20 at 4:39pm
This attempt took 1 minute.

Question 1
3 / 3 pts
I completed all the assigned learning activities.

- True
- False

Question 2
1 / 1 pts

Which of the following would change the background color of every other row in an HTML table?
Check all that apply.

- [x] tr:nth-child(odd) {background-color: skyblue}
- [ ] tr:even-rows {background-color: skyblue}
- [ ] tr:nth-child(:not(first)) {background-color: skyblue}
- [ ] tr:odd-rows {background-color: skyblue}
- [x] tr:nth-child(even) {background-color: skyblue}

Incorrect

Question 3

0 / 1 pts

In JavaScript, to set the text node of a preselected div element assigned to a variable identified as "reveal" as intended by the code, which of the following could you use?
Check all that apply.

- [ ] reveal.innerHTML = `🎉 Congratulations! You are having a <strong>${babygender}</strong>!`;
- [ ] reveal.HTMLvalue = `🎉 Congratulations! You are having a <strong>${babygender}</strong>!`;
- [ ] reveal.text = `🎉 Congratulations! You are having a <strong>${babygender}</strong>!`;
- [x] reveal.textContent = `🎉 Congratulations! You are having a <strong>${babygender}</strong>!`;

Question 4

1 / 1 pts

Rewrite the following JavaScript string build that uses concatenation (+) to use a **template literal** instead.

```
"Welcome to the " + courseName + " " + stuFirstName + "!"
```

`Welcome to the ${courseName} ${stuFirstName}!`

Question 5

1 / 1 pts

Given this function expression that computes the wind chill factor,

```
const computeWindChill = function(windSpeed, temperature) {
  // Fahrenheit Only
  return 35.74 + (0.6215 * temperature) - (35.75 * Math.pow(windSpeed, 0.16)) + (0.4275 * temperatur
e * Math.pow(windSpeed, 0.16));
};
```

Which of the following correctly **calls** the function using arguments of **speed** and **temp?**

- function computeWindChill()
- let windChill = windChill(windSpeed, temperature)
- computeWindChill(windSpeed, temperature)
- computeWindChill(speed, temp)
- function computeWindChill(speed, temp)

Question 6

1 / 1 pts

Given the following object definition:

```
let esomeprazole = {'id':'mnb78932','amount':23145,'amountType':'ct','expDate':'10/01/2021'}
```

Which of the following JavaScript statements accesses the value associated with the **amount** key for this variable and stores it in a variable named **dose?**

*The variable **dose** may or may not already exist.*

Check all that apply.

- [ ] let dose = amount
- [ ] const dose = esomeprazole[0].amount[1];
- [x] let dose = esomeprazole['amount']
- [x] let dose = esomeprazole.amount
- [ ] const dose = amount

Question 7

1 / 1 pts

Given the following array definition and subsequent code,

```
const countries = ["Canada", "Chili", "Colombia", "Croatia", "Costa Rica"];
const countriesLong = countries.filter((country) => country.length > 7);
```

What will be assigned to the array **countriesLong**?

- "Canada", "Chili", "Colombia", "Croatia", "Costa Rica"
- undefined
- null
- "Colombia", "Costa Rica"

Question 8

1 / 1 pts

Given the following segment of code, which of the following options will return a new array named **statusReport** which will contain the course **status** of any array of point total grades?
*An example array is provided as **points**.*

```
const points = [100, 88, 94, 78, 84, 69];

function convertPointsToStatus(pointTotal) {
  let status = 'Not Complete';
  if (pointTotal >= 93) {
    status = "Excellent";
  } else if (pointTotal >= 70) {
    status = "Complete";
  }
  return status;
}
```

- (selected) const statusReport = points.map(convertPointsToStatus);
- const statusReport = points.reduce(convertPointsToStatus);
- const statusReport = points.filter(convertPointsToStatus);
- const statusReport = points.convert(convertPointsToStatus);

Question 9
1 / 1 pts

In your **base.css** file you have the following CSS rule:

```
span p {font-size: 1.5rem}
```

In the **larger.css** file you have the following rule:

```
@media only screen and (min-width: 32rem) {
     span {font-size: 2rem}
}
```

What will the font size be for paragraphs in span elements when rendered on a browser?
Check all that apply.

- The font size on larger screens cannot be determined and the result will be a default font size.
- (selected) On larger screens the font size will be 1.5rem.
- On larger screens the font size will be 2rem.

Quiz Score: 10 out of 11

COPYRIGHT 2026 BYU-PATHWAY WORLDWIDE