

ECE264 Fall 2021 Exam 1

6:30-7:30 PM, September 30

Name: _____ Login: _____

Please use DARK ink. When you take this exam, you agree with the Purdue Honor Pledge: advancing a culture of academic integrity, seeing academic dishonesty and cheating as threats to Purdue's reputation.

Character table

Value	Char	Value	Char	Value	Char	Value	Char	Value	Char
48	0	65	A	78	N	97	a	110	n
49	1	66	B	79	O	98	b	111	o
50	2	67	C	80	P	99	c	112	p
51	3	68	D	81	Q	100	d	113	q
52	4	69	E	82	R	101	e	114	r
53	5	70	F	83	S	102	f	115	s
54	6	71	G	84	T	103	g	116	t
55	7	72	H	85	U	104	h	117	u
56	8	73	I	86	V	105	i	118	v
57	9	74	J	87	W	106	j	119	w
		75	K	88	X	107	k	120	x
		76	L	89	Y	108	l	121	y
		77	M	90	Z	109	m	122	z

1. Structures

Consider the following structure definitions:

```
1 typedef struct {          6 typedef struct {          11 typedef struct {
2   int p[10];              7   int r[10];              12   int x;
3   int q[10];              8   int s[10];              13   A * y;
4 } A;                      9 } B;                      14   B * z;
5                           10                               15 } C;
```

QUESTION A: Assume you have a structure variable var: C var; How would you allocate space for the y field of var? Your answer should be one line of C code.

A: _____

QUESTION B: Assume that all of the fields of var are correctly allocated and initialized. Which of these statements makes the 3rd element of the second field of the z field of var equal to 7? Your answer should be the number of the correct statement from the list below.

1. var.z.s[3] = 7; 2. var.z->s[2] = 7; 3. var->z.s[3] = 7;
4. var->z.s[2] = 7; 5. var.z.s[2] = 7; 6. var.z->s[3] = 7;

B: _____

2. Makefile

Consider the following Makefile and answer the questions A - D.

```
1 CFLAGS = -std=c99 -g -Wall -Wshadow --pedantic -Wvla -Werror
2 GCC = gcc $(CFLAGS)
3 EXEC = mkfileprog
4 TESTFLAGS = -DTEST_COMPARE
5
6 SRCS = add.c compare.c main.c
7 OBJS = $(SRCS:%.c=%.o)
8 # <--- Question A: What is the value of OBJS? --->
9
10 all: $(EXEC)
11
12 # link .o to executable
13 $(EXEC): $(OBJS)
14 # <--- Question B: Fix the following --->
15     $(GCC) $(TESTFLAGS) $(OBJS) [ ANSWER B ] $(EXEC)
16
17 # convert .c to .o
18 %.o: %.c
19     $(GCC) $(TESTFLAGS) -c $<
20
21 testall: test1 test2 test3
```

```

22
23 test1: $(EXEC)
24     ./$$(EXEC) inputs/input1 > output1
25
26 test2: $(EXEC)
27     ./$$(EXEC) inputs/input2 > output2
28
29 test3: $(EXEC)
30     ./$$(EXEC) inputs/input3 > output3
31
32 clean: # remove all machine generated files
33     rm -f $(EXEC) *.o *.out *gcda *gcno *gcov

```

QUESTION A: Write down the value of OBJS.

QUESTION B: Fix the command at line 15. Your answer should be what needs to go in [ANSWER B].

QUESTION C: Using the given Makefile, what is the Unix command to test with all test cases (input1, input2, input3)? Your answer should be a single command (plus any needed arguments) you can type at the command line.

QUESTION D: Suppose we have the following in compare.c:

```

# ifdef TEST_COMPARE                # ifdef TEST_FUNC
void func1(void) {                  void func2(void) {
    ...                             ...
}                                   }
# endif                            # endif

```

When we use the given Makefile to test the program, which function(s) is/are compiled and tested? Your answer should be the number of the correct response. 1. func1 2. func2 3. Both func1 and func2 4. None of them

A: _____ **B:** _____
C: _____ **D:** _____

3. Memory Leak

Consider the following function:

```

1 #include <stdio.h>
2 #include <stdlib.h>
3 #include <string.h>
4 #pragma pack(1) // tell compiler not to pad any space
5 // assume sizeof(char) = 1, sizeof(a pointer) = 8
6
7 int main(int argc, char ** argv)
8 {
9     if (argc < 2) {
10         printf("Not enough inputs\n");
11         return EXIT_FAILURE;
12     }
13
14     char ** arr = malloc((argc-1) * sizeof(char *));
15     int i = 0;
16     for (; i < argc-1; i++) {
17         // strlen(argv[i+1]) computes the length of the
18         // string argv[i+1], not including the
19         // terminating null character, '\0'.
20         arr[i] = malloc((strlen(argv[i+1]) + 1) * sizeof(char));
21
22         // strcpy copies the string pointed to
23         // by argv[i+1] to arr[i]
24         strcpy(arr[i], argv[i+1]);
25         printf("%s\n", arr[i]);
26     }
27
28     for (i = 0; i < argc-1; i++) {
29         free(arr[i]); // release memory
30     }
31     // <--- Question A: Fix the following code to release memory --->
32     free( [ ANSWER A ] );
33
34     return EXIT_SUCCESS;
35 }

```

Suppose the executable program is named memleakprog. We run the program with `./memleakprog ece 264 midterm1`. Answer the questions A - C. Hint: The output of the program will be `ece, 264, midterm1` (one per line).

QUESTION A: Fix the code at line 32 to properly release memory. Your answer should be the expression that is the argument to free.

QUESTION B: If we do not release memory at line 32, how many bytes of memory will be leaked?

QUESTION C: If we do not release memory at line 29, but we do release the memory at line 32, how many bytes of memory will be leaked?

A: _____ **B:** _____ **C:** _____

4. Data Types

Consider the following program that reads an input file as integers or floating point numbers.

```
1 #include <stdio.h>
2 #include <stdlib.h>
3
4 int main(int argc, char ** argv)
5 {
6     if (argc != 2)
7     {
8         fprintf(stderr, "Need one input file\n");
9         return EXIT_FAILURE;
10    }
11    FILE * fptr = fopen(argv[1], "r");
12    if (fptr == NULL) // fopen fail
13    {
14        return EXIT_FAILURE;
15    }
16    int count = 0;
17    // -----
18    // treat the input as integers
19    count = 0;
20    fseek(fptr, 0, SEEK_SET); // return to the beginning of the file
21    int ival;
22    while (fscanf(fptr, "%d", &ival) == 1)
23    {
24        count++;
25    }
26    printf("The file has %d integers.\n", count); // <=== ANSWER A
27    printf("The last read int is %d.\n", ival);   // <=== ANSWER B
28    // -----
29    // treat the input as float
30    count = 0;
31    fseek(fptr, 0, SEEK_SET); // return to the beginning of the file
32    float fval;
33    while (fscanf(fptr, "%f", &fval) == 1)
34    {
35        count++;
36    }
37    printf("The file has %d floats.\n", count); // <=== ANSWER C
38    printf("The last read float is %f.\n", fval); // <=== ANSWER D
39    // -----
40    // understand the sizes of different types
41    // assume
42    // sizeof(char) is 1
43    // sizeof(int) is 4
44    // sizeof(int *) is 8
45    // sizeof(double) is 8
46    double darr[] = {2.64, 20.11, 0.9, 2.8};
47    int sizediff = (int) sizeof(darr) - (int) sizeof(darr[0]);
48    printf("%d\n", sizediff); // <=== ANSWER E
49    return EXIT_SUCCESS;
50 }
```

This is the input file: 2 64 20.11 9 17. The following table shows bytes of this input file.

Byte	0	1	2	3	4	5	6	7	8	9	10	11	12	13	14
Character	2		6	4		2	0	.	1	1		9		1	7
ASCII (decimal)	50	32	54	52	32	50	48	46	49	49	32	57	32	49	55

Suppose you run the program with the above input file. Please write down the program's output from the five print statements, for ANSWERS A-E. Your answers should be ONLY the numbers.

A: _____ **B:** _____ **C:** _____

D: _____ E: _____

5. Pointers and Arrays

Consider the following piece of C code:

```
1 #include <stdlib.h>
2 #include <stdio.h>
3
4 int main(int argc, char * argv[])
5 {
6     int * x = malloc(5 * sizeof(int));
7     int * y = malloc(5 * sizeof(int));
8     int * p = x;
9     int * q = y;
10    int ** r = &x;
11    int ** s = &y;
12
13    for (int i = 0; i < 5; i++) {
14        x[i] = i;        // x has values [0, 1, 2, 3, 4]
15        y[i] = 4 - i;    // y has values [4, 3, 2, 1, 0]
16    }
17
18    printf("(p + 1) = %d\n", *(p + 1)); // <=== ANSWER A
19
20    printf("(s + 1) = %d\n", *(s + 1)); // <=== ANSWER B
21
22    p = p + 1;
23    printf("p[1] = %d\n", p[1]); // <=== ANSWER C
24
25    *s = x;
26    printf("y[1] = %d\n", y[1]); // <=== ANSWER D
27
28    *r = (*r + 1);
29    printf("*x = %d\n", *x); // <=== ANSWER E
30
31    return EXIT_SUCCESS;
32 }
```

Each print statement prints out an integer value. The answers to the 5 questions are those integer values. (Note: this code leaks memory; you can ignore that for this problem.)

Hint: the output of the program will be: `*(p + 1) = [ANSWER A];` `*(s + 1) = [ANSWER B];` `p[1] = [ANSWER C];` `y[1] = [ANSWER D];` `*x = [ANSWER E]`

A: _____ B: _____ C: _____
D: _____ E: _____