

Remal - Database Schema

1. users

Registered customers. Phone-based OTP authentication.

Column	Type	PK	NN	Notes / Description
id	bigint unsigned	Y	Y	Auto-increment primary key
name	varchar(255)	N	Y	Full name
email	varchar(255)	N	N	Optional, unique
password	varchar(255)	N	N	Nullable (OTP-first flow)
phone	varchar(20)	N	Y	Unique - main identifier
nationality	varchar(100)	N	N	
passport_number	varchar(50)	N	N	
birth_date	date	N	N	
gender	enum	N	N	male female
otp	varchar(10)	N	N	One-time password (transient)
otp_expires_at	timestamp	N	N	
phone_verified_at	timestamp	N	N	Nullable - set on first OTP verify
remember_token	varchar(100)	N	N	
created_at	timestamp	N	N	
updated_at	timestamp	N	N	

2. activities

Individual tourism activities shown on the home screen.

Column	Type	PK	NN	Notes / Description
id	bigint unsigned	Y	Y	
title	varchar(255)	N	Y	
description	text	N	N	
location	varchar(255)	N	N	
price	decimal(10,2)	N	Y	
image	varchar(255)	N	N	Relative storage path
is_active	boolean	N	Y	Default true
sort_order	int	N	Y	Default 0
created_at	timestamp	N	N	
updated_at	timestamp	N	N	

3. packages

Tourism packages (multi-city trips).

Column	Type	PK	NN	Notes / Description
id	bigint unsigned	Y	Y	
title	varchar(255)	N	Y	
location	varchar(255)	N	N	Display location label

Remal - Database Schema

trip_type	enum	N	Y	local international
price	decimal(10,2)	N	Y	
image	varchar(255)	N	N	Relative storage path
nights_count	int	N	N	Total nights
is_active	boolean	N	Y	Default true
sort_order	int	N	Y	Default 0
created_at	timestamp	N	N	
updated_at	timestamp	N	N	

4. package_cities

Cities within a package (ordered itinerary stops).

Column	Type	PK	NN	Notes / Description
id	bigint unsigned	Y	Y	
package_id	bigint unsigned	N	Y	FK -> packages.id
city	varchar(255)	N	Y	
nights	int	N	Y	Nights spent in this city
sort_order	int	N	Y	Default 0
created_at	timestamp	N	N	
updated_at	timestamp	N	N	

Foreign Keys:

package_id -> packages.id (CASCADE DELETE)

5. package_activities

Activity labels attached to a package (display tags).

Column	Type	PK	NN	Notes / Description
id	bigint unsigned	Y	Y	
package_id	bigint unsigned	N	Y	FK -> packages.id
activity_name	varchar(255)	N	Y	
created_at	timestamp	N	N	
updated_at	timestamp	N	N	

Foreign Keys:

package_id -> packages.id (CASCADE DELETE)

6. offers

Promotional offers displayed in the Offers tab.

Column	Type	PK	NN	Notes / Description
id	bigint unsigned	Y	Y	
title	varchar(255)	N	Y	
description	text	N	N	

Remal - Database Schema

image	varchar(255)	N	N	Relative storage path
original_price	decimal(10,2)	N	Y	
discounted_price	decimal(10,2)	N	Y	
discount_percentage	int	N	N	Computed or stored %
expires_at	timestamp	N	N	NULL = no expiry
is_active	boolean	N	Y	Default true
created_at	timestamp	N	N	
updated_at	timestamp	N	N	

7. bookings

Master booking record for any service type.

Column	Type	PK	NN	Notes / Description
id	bigint unsigned	Y	Y	
user_id	bigint unsigned	N	Y	FK -> users.id
type	enum	N	Y	flight hotel package activity
status	enum	N	Y	pending booked cancelled
price	decimal(10,2)	N	Y	
is_current	boolean	N	Y	true = upcoming, false = history
created_at	timestamp	N	N	
updated_at	timestamp	N	N	

Foreign Keys:

user_id -> users.id (CASCADE DELETE)

8. flight_bookings

Flight-specific details linked to a booking.

Column	Type	PK	NN	Notes / Description
id	bigint unsigned	Y	Y	
booking_id	bigint unsigned	N	Y	FK -> bookings.id (1-to-1)
airline	varchar(255)	N	Y	
from_airport	varchar(10)	N	Y	IATA code
to_airport	varchar(10)	N	Y	IATA code
departure_time	varchar(10)	N	N	e.g. 09:30
arrival_time	varchar(10)	N	N	
departure_date	date	N	Y	
duration	varchar(20)	N	N	e.g. 2h 30m
stops	int	N	Y	Default 0 = direct flight
created_at	timestamp	N	N	
updated_at	timestamp	N	N	

Foreign Keys:

booking_id -> bookings.id (CASCADE DELETE)

Remal - Database Schema

9. passengers

Passengers associated with a booking (flight / package).

Column	Type	PK	NN	Notes / Description
id	bigint unsigned	Y	Y	
booking_id	bigint unsigned	N	Y	FK -> bookings.id
full_name	varchar(255)	N	Y	
nationality	varchar(100)	N	N	
passport_number	varchar(50)	N	N	
birth_date	date	N	N	
gender	enum	N	N	male female
created_at	timestamp	N	N	
updated_at	timestamp	N	N	

Foreign Keys:

booking_id -> bookings.id (CASCADE DELETE)

10. support_tickets

Customer support messages; admin can reply from Filament panel.

Column	Type	PK	NN	Notes / Description
id	bigint unsigned	Y	Y	
user_id	bigint unsigned	N	Y	FK -> users.id
subject	varchar(255)	N	Y	
message	text	N	Y	
admin_reply	text	N	N	NULL until replied
status	enum	N	Y	open in_progress closed
created_at	timestamp	N	N	
updated_at	timestamp	N	N	

Foreign Keys:

user_id -> users.id (CASCADE DELETE)

Entity Relationship Summary

Parent Table	Cardinality	Child Table	FK Column
users	1 --- N	bookings	user_id
users	1 --- N	support_tickets	user_id
bookings	1 --- N	passengers	booking_id
bookings	1 --- 1	flight_bookings	booking_id
packages	1 --- N	package_cities	package_id
packages	1 --- N	package_activities	package_id

Notes:

- All primary keys are unsigned bigint with auto-increment.
- All foreign keys use CASCADE on delete.
- Timestamps (created_at / updated_at) managed by Laravel Eloquent.
- Images stored via Laravel Storage (local disk), served through /storage symlink.
- OTP column in users is transient - cleared after successful verification.
- booking.type enum allows future extension (e.g. "car_rental").
- packages.nights_count can be derived from sum(package_cities.nights) but stored for performance.