


## R32 Monobloc Heat Pump

# QBKFXFC-030SRII 30 kW



| Key data         |                                |
|------------------|--------------------------------|
| Rated capacity   | 30 kW                          |
| Rated COP / EER  | 4.22~5.22                      |
| Power supply     | 380V-415V/3N~ / 50/60Hz V / Hz |
| Refrigerant      | 5 kg                           |
| Max. input power | 13.5 kW                        |
| Max. current     | 25 A                           |
| Sound power      | 50 dB(A)                       |
| Outlet temp.     | 25.18 kW                       |

### Performance

| Operating condition | Capacity (kW) | Input (kW) | COP / EER |
|---------------------|---------------|------------|-----------|
| A7W30-35            | 11.72~32.94   | 2.25~7.81  | 4.22~5.22 |
| A7W47-55            | 12.29~32.42   | 3.83~11.50 | 2.82~3.21 |
| A-7W35              | 8.00~25.72    | 2.34~8.93  | 2.88~3.42 |
| A-7W55              | 8.76~25.85    | 3.58~12.55 | 2.06~2.45 |
| A-15W35             | 6.70~20.44    | 2.38~8.81  | 2.32~2.82 |
| A-15W55             | 7.59~20.00    | 3.61~11.24 | 1.78~2.10 |
| A-20W35             | 6.09~16.47    | 2.49~7.84  | 2.10~2.45 |
| A-20W55             | 7.04~16.23    | 3.71~9.60  | 1.69~1.90 |
| A35W7               | 9.19~24.93    | 2.64~8.84  | 2.82~3.48 |
| A20W15-55           | 10.87~35.00   | 2.06~8.47  | 4.13~5.27 |
| A7W15-55            | 11.56~32.00   | 2.47~8.84  | 3.62~4.68 |

### Space Heating (According to EN14825:2022 ) Average Climate Water Outlet 35°C

|                                  |             |
|----------------------------------|-------------|
| Rated heat output                | 25.18 kW    |
| Seasonal Space Heating Energy    | 1.8 *       |
| SCOP                             | 4.58 *      |
| ERP Level ((EU) No 811/2013 )    | A+++ *      |
| Sound pressure level at 1 meter  | 50 dB(A)    |
| Sound pressure level at 3 meters | 40.46 dB(A) |
| Sound pressure level at 5 meters | 36.02 dB(A) |
| Sound power level                | 64 dB       |

### Space Heating (According to EN14825:2022 ) Average Climate Water Outlet 55°C

|                                  |             |
|----------------------------------|-------------|
| Rated heat output                | 25.35 kW    |
| Seasonal Space Heating Energy    | 1.36 *      |
| SCOP                             | 3.48 *      |
| ERP Level ((EU) No 811/2013 )    | A++ *       |
| Sound pressure level at 1 meter  | 50 dB(A)    |
| Sound pressure level at 3 meters | 40.46 dB(A) |
| Sound pressure level at 5 meters | 36.02 dB(A) |

|                                      |                                |
|--------------------------------------|--------------------------------|
| Sound power level                    | 65 dB                          |
| <b>Power Supply</b>                  |                                |
| Power Supply                         | 380V-415V/3N~ / 50/60Hz V / Hz |
| <b>Max. power input</b>              |                                |
| Max. power input                     | 13.5 kW                        |
| <b>Max. current</b>                  |                                |
| Max. current                         | 25 A                           |
| <b>Refrigerant □ R32 □</b>           |                                |
| Refrigerant □ R32 □                  | 5 kg                           |
| <b>Water Flow Rate</b>               |                                |
| Water Flow Rate                      | 5.16 m³/h                      |
| <b>Water Pressure Drop</b>           |                                |
| Water Pressure Drop                  | 35 kPa                         |
| <b>Diameter of pipe</b>              |                                |
| Diameter of pipe                     | DN32 mm                        |
| <b>Product Dimensions (L×W×H)</b>    |                                |
| Product Dimensions (L×W×H)           | 1100×510×1590 mm               |
| <b>Packing size(W×D×H)(carton)</b>   |                                |
| Packing size(W×D×H)(carton)          | 1220×560×1710 mm               |
| <b>Packing size(W×D×H)(Polywood)</b> |                                |
| Packing size(W×D×H)(Polywood)        | 1240×580×1720 mm               |
| <b>N.W</b>                           |                                |
| N.W                                  | 200 kg                         |