

R290 Residential Monobloc Heat Pump

QBKFXFC-024SBII 24 kW

Performance			
Operating condition	Capacity (kW)	Input (kW)	COP / EER
A7W30-35	6.98~24.00	1.34~5.87	4.09~5.22
A7W47-55	6.21~22.03	1.86~7.54	2.92~3.33
A-7W35	4.47~20.68	1.30~7.01	2.95~3.45
A-7W55	4.14~16.54	1.71~7.91	2.09~2.42
A-15W35	3.60~14.20	1.26~5.97	2.38~2.85
A-15W55	3.43~13.76	1.66~7.82	1.76~2.07
A-20W35	3.01~12.22	1.23~5.74	2.13~2.45
A-20W55	2.95~11.73	1.56~7.24	1.62~1.89
A35W7	5.84~15.38	1.68~5.57	2.76~3.47
A20W15-55	8.38~26.4	1.60~6.33	4.17~5.25
A7W15-55	6.4~22.47	1.37~6.17	3.64~4.66

Space Heating (According to EN14825:2022) Average Climate Water Outlet 35°C	
Rated heat output	15.07 kW
Seasonal Space Heating Energy	1.83 *
SCOP	4.66 *
ERP Level ((EU) No 811/2013)	A+++ *
Sound pressure level at 1 meter	47 dB(A)
Sound pressure level at 3 meters	37.46 dB(A)
Sound pressure level at 5 meters	33.02 dB(A)
Sound power level	62 dB

Space Heating (According to EN14825:2022) Average Climate Water Outlet 55°C	
Rated heat output	14.1 kW
Seasonal Space Heating Energy	1.35 *
SCOP	3.46 *
ERP Level ((EU) No 811/2013)	A++ *
Sound pressure level at 1 meter	48 dB(A)
Sound pressure level at 3 meters	38.46 dB(A)
Sound pressure level at 5 meters	34.02 dB(A)
Sound power level	63 dB

Max. power input	
Max. power input	10.54 kW

Max. current	
Max. current	17 A

Refrigerant R290	
Refrigerant R290	2 kg

Water Flow Rate	
Water Flow Rate	3.44 m³/h

Water Pressure Drop		
Water Pressure Drop		30 kPa
Diameter of pipe		
Diameter of pipe		DN25 mm
Product Dimensions (L×W×H)		
Product Dimensions (L×W×H)		1100×510×1590 mm
Packing size(W*D*H)(carton)		
Packing size(W*D*H)(carton)		1220×560×1710 mm
Packing size(W*D*H)(Polywood)		
Packing size(W*D*H)(Polywood)		1240×580×1720 mm
N.W		
N.W		180 kg