

R290 Residential Monobloc Heat Pump

QBKFXFC-030SBII 30 kW

Performance			
Operating condition	Capacity (kW)	Input (kW)	COP / EER
A7W30-35	8.59~29.95	1.61~7.64	3.92~5.32
A7W47-55	7.64~28.42	2.38~10.08	2.82~3.21
A-7W35	5.51~21.76	1.61~7.56	2.88~3.42
A-7W55	5.10~20.36	2.08~9.88	2.06~2.45
A-15W35	4.43~17.48	1.57~7.53	2.32~2.82
A-15W55	4.22~16.94	2.01~9.52	1.78~2.10
A-20W35	3.70~15.04	1.51~7.16	2.10~2.45
A-20W55	3.63~14.44	1.91~8.54	1.69~1.90
A35W7	7.19~18.93	2.08~6.76	2.80~3.45
A20W15-55	10.31~32.95	1.98~7.98	4.13~5.2
A7W15-55	7.87~28.99	1.69~8.03	3.61~4.66

Space Heating (According to EN14825:2022) Average Climate Water Outlet 35°C	
Rated heat output	19.78 kW
Seasonal Space Heating Energy	1.84 *
SCOP	4.68 *
ERP Level ((EU) No 811/2013)	A+++ *
Sound pressure level at 1 meter	49 dB(A)
Sound pressure level at 3 meters	39.46 dB(A)
Sound pressure level at 5 meters	35.02 dB(A)
Sound power level	64 dB

Space Heating (According to EN14825:2022) Average Climate Water Outlet 55°C	
Rated heat output	17.35 kW
Seasonal Space Heating Energy	1.36 *
SCOP	3.48 *
ERP Level ((EU) No 811/2013)	A++ *
Sound pressure level at 1 meter	50 dB(A)
Sound pressure level at 3 meters	40.46 dB(A)
Sound pressure level at 5 meters	36.02 dB(A)
Sound power level	65 dB

Max. power input	
Max. power input	13 kW

Max. current	
Max. current	22 A

Refrigerant R290	
Refrigerant R290	2.3 kg

Water Flow Rate	
Water Flow Rate	5.16 m³/h

Water Pressure Drop		
Water Pressure Drop		35 kPa
Diameter of pipe		
Diameter of pipe		DN32 mm
Product Dimensions (L×W×H)		
Product Dimensions (L×W×H)		1100×510×1590 mm
Packing size(W*D*H)(carton)		
Packing size(W*D*H)(carton)		1220×560×1710 mm
Packing size(W*D*H)(Polywood)		
Packing size(W*D*H)(Polywood)		1240×580×1720 mm
N.W		
N.W		200 kg