

R32 Monobloc Heat Pump

QBKFXFC-016SRI 16 kW

Performance

Operating condition	Capacity (kW)	Input (kW)	COP / EER
A7W30-35	7.57~20.51	1.46~5.00	4.10~5.18
A7W47-55	7.94~20.47	2.41~7.06	2.90~3.30
A-7W35	5.17~16.62	1.51~5.69	2.92~3.43
A-7W55	5.66~15.00	2.39~7.21	2.08~2.37
A-15W35	4.33~12.86	1.51~5.38	2.39~2.86
A-15W55	4.90~12.51	2.41~7.15	1.75~2.03
A-20W35	3.94~10.58	1.60~4.92	2.15~2.46
A-20W55	4.55~10.36	2.43~6.17	1.68~1.87
A35W7	4.94~15.01	1.42~5.89	2.55~3.49
A20W15-55	5.50~20.02	1.07~4.77	4.20~5.15
A7W15-55	7.50~20.00	1.58~5.48	3.65~4.76

Space Heating (According to EN14825:2022) Average Climate Water Outlet 35°C

Rated heat output	15.75 kW
Seasonal Space Heating Energy	1.79 *
SCOP	4.55 *
ERP Level ((EU) No 811/2013)	A+++ *
Sound pressure level at 1 meter	47 dB(A)
Sound pressure level at 3 meters	37.46 dB(A)
Sound pressure level at 5 meters	33.02 dB(A)
Sound power level	61 dB

Space Heating (According to EN14825:2022) Average Climate Water Outlet 55°C

Rated heat output	15.93 kW
Seasonal Space Heating Energy	1.37 *
SCOP	3.51 *
ERP Level ((EU) No 811/2013)	A++ *
Sound pressure level at 1 meter	48 dB(A)
Sound pressure level at 3 meters	38.46 dB(A)
Sound pressure level at 5 meters	34.02 dB(A)
Sound power level	62 dB

Power Supply

Power Supply	380V-415V/3N~ / 50/60Hz V / Hz
--------------	--------------------------------

Max. power input

Max. power input	7.5 kW
------------------	--------

Max. current

Max. current	32 A
--------------	------

Refrigerant R32

Refrigerant R32	2.8 kg
-----------------	--------

Water Flow Rate		
Water Flow Rate		2.75 m³/h
Water Pressure Drop		
Water Pressure Drop		30 kPa
Diameter of pipe		
Diameter of pipe		DN25 mm
Product Dimensions (L×W×H)		
Product Dimensions (L×W×H)		1080×510×1360 mm
Packing size(W*D*H)(carton)		
Packing size(W*D*H)(carton)		1200×560×1480 mm
Packing size(W*D*H)(Polywood)		
Packing size(W*D*H)(Polywood)		1220×580×1500 mm
N.W		
N.W		150 kg