

R32 Monobloc Heat Pump

QBKFXFC-030SRII 30 kW

Performance			
Operating condition	Capacity (kW)	Input (kW)	COP / EER
A7W30-35	11.72~32.94	2.25~7.81	4.22~5.22
A7W47-55	12.29~32.42	3.83~11.50	2.82~3.21
A-7W35	8.00~25.72	2.34~8.93	2.88~3.42
A-7W55	8.76~25.85	3.58~12.55	2.06~2.45
A-15W35	6.70~20.44	2.38~8.81	2.32~2.82
A-15W55	7.59~20.00	3.61~11.24	1.78~2.10
A-20W35	6.09~16.47	2.49~7.84	2.10~2.45
A-20W55	7.04~16.23	3.71~9.60	1.69~1.90
A35W7	9.19~24.93	2.64~8.84	2.82~3.48
A20W15-55	10.87~35.00	2.06~8.47	4.13~5.27
A7W15-55	11.56~32.00	2.47~8.84	3.62~4.68

Space Heating (According toEN14825:2022) Average Climate WaterOutlet 35°C	
Rated heat output	25.18 kW
Seasonal Space Heating Energy	1.8 *
SCOP	4.58 *
ERP Level ((EU) No 811/2013)	A+++ *
Sound pressure level at 1 meter	50 dB□A)
Sound pressure level at 3 meters	40.46 dB□A)
Sound pressure level at 5 meters	36.02 dB□A)
Sound power level	64 dB

Space Heating (According toEN14825:2022) Average Climate WaterOutlet 55°C	
Rated heat output	25.35 kW
Seasonal Space Heating Energy	1.36 *
SCOP	3.48 *
ERP Level ((EU) No 811/2013)	A++ *
Sound pressure level at 1 meter	50 dB□A)
Sound pressure level at 3 meters	40.46 dB□A)
Sound pressure level at 5 meters	36.02 dB□A)
Sound power level	65 dB

Power Supply	
Power Supply	380V-415V/3N~ / 50/60Hz V / Hz

Max. power input	
Max. power input	13.5 kW

Max. current	
Max. current	25 A

Refrigerant□R32□	
Refrigerant□R32□	5 kg

Water Flow Rate	
Water Flow Rate	5.16 m³/h
Water Pressure Drop	
Water Pressure Drop	35 kPa
Diameter of pipe	
Diameter of pipe	DN32 mm
Product Dimensions (L×W×H)	
Product Dimensions (L×W×H)	1100×510×1590 mm
Packing size(W*D*H)(carton)	
Packing size(W*D*H)(carton)	1220×560×1710 mm
Packing size(W*D*H)(Polywood)	
Packing size(W*D*H)(Polywood)	1240×580×1720 mm
N.W	
N.W	200 kg