

R32 Commercial Heat Pump

QBKFXFC-045URII 45 kW

Performance			
Operating condition	Capacity (kW)	Input (kW)	COP / EER
A7W30-35	14.42~46.69	2.77~11.31	4.13~5.21
A7W47-55	15.13~48.52	4.49~16.62	2.92~3.37
A-7W35	9.84~31.66	2.84~10.70	2.96~3.46
A-7W55	10.79~34.28	4.53~16.64	2.06~2.38
A-15W35	8.24~26.39	2.92~10.90	2.42~2.82
A-15W55	9.34~27.53	4.51~15.91	1.73~2.07
A-20W35	7.50~23.96	3.09~11.36	2.11~2.43
A-20W55	8.67~24.36	4.74~14.76	1.65~1.83
A35W7	11.0~30.0	3.19~10.53	2.85~3.45
A20W15-55	15.0~50.0	3.03~11.49	4.35~4.95
A7W15-55	13.0~48.0	2.81~13.64	3.52~4.62

Space Heating (According to EN14825:2022) Average Climate Water Outlet 35°C	
Rated heat output	30.23 kW
Seasonal Space Heating Energy	1.75 *
SCOP	4.44 *
ERP Level ((EU) No 811/2013)	A+++ *
Sound pressure level at 1 meter	53 dB(A)
Sound pressure level at 3 meters	43.46 dB(A)
Sound pressure level at 5 meters	39.02 dB(A)
Sound power level	67 dB

Space Heating (According to EN14825:2022) Average Climate Water Outlet 55°C	
Rated heat output	29.34 kW
Seasonal Space Heating Energy	1.34 *
SCOP	3.42 *
ERP Level ((EU) No 811/2013)	A++ *
Sound pressure level at 1 meter	54 dB(A)
Sound pressure level at 3 meters	44.46 dB(A)
Sound pressure level at 5 meters	40.02 dB(A)
Sound power level	68 dB

Power Supply	
Power Supply	380V-415V/3N~ / 50/60Hz V / Hz

Max. power input	
Max. power input	23 kW

Max. current	
Max. current	35 A

Refrigerant R32	
Refrigerant R32	6.5 kg

Water Flow Rate		
Water Flow Rate		7.74 m³/h
Water Pressure Drop		
Water Pressure Drop		40 kPa
Diameter of pipe		
Diameter of pipe		DN40 mm
Operating temp. range		
Operating temp. range		-35~45 °C
Outlet temp. range		
Outlet temp. range		5~60 °C
Product Dimensions (L×W×H)		
Product Dimensions (L×W×H)		905×905×1535 mm
Packing size(W*D*H)(Polywood)		
Packing size(W*D*H)(Polywood)		1000×1000×1680 mm
N.W		
N.W		265 kg