

R32 Commercial Heat Pump

QBKFXFC-070URII 70 kW

Performance			
Operating condition	Capacity (kW)	Input (kW)	COP / EER
A7W30-35	22.50~73.90	4.39~18.38	4.02~5.12
A7W47-55	22.89~74.42	7.04~26.58	2.80~3.25
A-7W35	16.00~50.12	4.71~17.59	2.85~3.40
A-7W55	16.76~51.85	6.93~25.93	2.00~2.42
A-15W35	13.50~40.23	4.70~17.19	2.34~2.87
A-15W55	14.59~40.00	6.88~23.39	1.71~2.12
A-20W35	12.00~32.21	4.90~15.71	2.05~2.45
A-20W55	13.04~33.23	6.79~20.26	1.64~1.92
A35W7	20.0~55.0	5.78~20.00	2.75~3.46
A20W15-55	25.0~80.0	5.08~19.51	4.10~4.92
A7W15-55	22.16~64.00	4.95~18.71	3.42~4.48

Space Heating (According to EN14825:2022) Average Climate Water Outlet 35°C	
Rated heat output	51.23 kW
Seasonal Space Heating Energy	1.75 *
SCOP	4.45 *
ERP Level ((EU) No 811/2013)	A+++ *
Sound pressure level at 1 meter	55 dB(A)
Sound pressure level at 3 meters	45.46 dB(A)
Sound pressure level at 5 meters	41.02 dB(A)
Sound power level	69 dB

Space Heating (According to EN14825:2022) Average Climate Water Outlet 55°C	
Rated heat output	7.16 kW
Seasonal Space Heating Energy	1.32 *
SCOP	3.38 *
ERP Level ((EU) No 811/2013)	A++ *
Sound pressure level at 1 meter	56 dB(A)
Sound pressure level at 3 meters	46.46 dB(A)
Sound pressure level at 5 meters	42.02 dB(A)
Sound power level	70 dB

Power Supply	
Power Supply	380V-415V/3N~ / 50/60Hz V / Hz

Max. power input	
Max. power input	35.82 kW

Max. current	
Max. current	55 A

Refrigerant R32	
Refrigerant R32	5.0×2 kg

Water Flow Rate		
Water Flow Rate		12.04 m³/h
Water Pressure Drop		
Water Pressure Drop		30 kPa
Diameter of pipe		
Diameter of pipe		DN65 mm
Operating temp. range		
Operating temp. range		-35~45 °C
Outlet temp. range		
Outlet temp. range		5~60 °C
Product Dimensions (L×W×H)		
Product Dimensions (L×W×H)		2000×900×1950 mm
Packing size(W*D*H)(Polywood)		
Packing size(W*D*H)(Polywood)		2000×900×1950 mm
N.W		
N.W		600 kg