

R32 Commercial Heat Pump

QBKFXFC-100URII 100 kW

Performance			
Operating condition	Capacity (kW)	Input (kW)	COP / EER
A7W30-35	29.42~100.69	5.87~25.62	3.93~5.01
A7W47-55	30.23~101.44	9.24~37.29	2.72~3.27
A-7W35	19.54~62.62	5.65~21.16	2.96~3.46
A-7W55	20.92~64.28	8.90~31.98	2.01~2.35
A-15W35	16.54~52.19	5.82~22.50	2.32~2.84
A-15W55	17.34~55.53	8.50~32.47	1.71~2.04
A-20W35	14.50~47.96	5.97~22.73	2.11~2.43
A-20W55	15.67~48.36	8.47~29.85	1.62~1.85
A35W7	22.0~62.0	6.43~22.71	2.73~3.42
A20W15-55	32.0~95.0	6.50~22.89	4.15~4.92
A7W15-55	27.0~90.0	5.93~26.32	3.42~4.55

Space Heating (According toEN14825:2022) Average Climate WaterOutlet 35°C	
Rated heat output	61.07 kW
Seasonal Space Heating Energy	1.73 *
SCOP	4.41 *
ERP Level ((EU) No 811/2013)	A+++ *
Sound pressure level at 1 meter	57 dB□A)
Sound pressure level at 3 meters	47.46 dB□A)
Sound pressure level at 5 meters	43.02 dB□A)
Sound power level	71 dB

Space Heating (According toEN14825:2022) Average Climate WaterOutlet 55°C	
Rated heat output	9.11 kW
Seasonal Space Heating Energy	1.31 *
SCOP	3.36 *
ERP Level ((EU) No 811/2013)	A++ *
Sound pressure level at 1 meter	58 dB□A)
Sound pressure level at 3 meters	48.46 dB□A)
Sound pressure level at 5 meters	44.02 dB□A)
Sound power level	72 dB

Power Supply	
Power Supply	380V-415V/3N~ / 50/60Hz V / Hz

Max. power input	
Max. power input	52.1 kW

Max. current	
Max. current	80 A

Refrigerant□R32□	
Refrigerant□R32□	6.0×2 kg

Water Flow Rate		
Water Flow Rate		17.2 m³/h
Water Pressure Drop		
Water Pressure Drop		45 kPa
Diameter of pipe		
Diameter of pipe		DN65 mm
Operating temp. range		
Operating temp. range		-35~45 °C
Outlet temp. range		
Outlet temp. range		5~60 °C
Product Dimensions (L×W×H)		
Product Dimensions (L×W×H)		2000×900×1950 mm
Packing size(W*D*H)(Polywood)		
Packing size(W*D*H)(Polywood)		2000×900×1950 mm
N.W		
N.W		800 kg