

## R32 Commercial Heat Pump

# QBKFXFC-150URII 150 kW

| Performance         |               |             |           |
|---------------------|---------------|-------------|-----------|
| Operating condition | Capacity (kW) | Input (kW)  | COP / EER |
| A7W30-35            | 46.87~150.34  | 9.05~36.67  | 4.10~5.18 |
| A7W47-55            | 49.17~156.23  | 14.90~53.87 | 2.90~3.30 |
| A-7W35              | 31.98~101.95  | 9.32~34.91  | 2.92~3.43 |
| A-7W55              | 35.07~110.38  | 14.80~53.07 | 2.08~2.37 |
| A-15W35             | 26.78~84.98   | 9.36~35.56  | 2.39~2.86 |
| A-15W55             | 30.36~88.65   | 14.96~50.66 | 1.75~2.03 |
| A-20W35             | 24.38~77.15   | 9.91~35.88  | 2.15~2.46 |
| A-20W55             | 28.18~78.44   | 15.07~46.69 | 1.68~1.87 |
| A35W7               | 35.75~96.60   | 10.24~37.88 | 2.55~3.49 |
| A20W15-55           | 48.75~161.00  | 9.47~38.33  | 4.20~5.15 |
| A7W15-55            | 42.25~154.56  | 8.88~42.35  | 3.65~4.76 |

  

| Space Heating (According toEN14825:2022 ) Average Climate WaterOutlet 35°C |             |
|----------------------------------------------------------------------------|-------------|
| Rated heat output                                                          | 15.75 kW    |
| Seasonal Space Heating Energy                                              | 1.79 *      |
| SCOP                                                                       | 4.55 *      |
| ERP Level ((EU) No 811/2013 )                                              | A+++ *      |
| Sound pressure level at 1 meter                                            | 58 dB□A)    |
| Sound pressure level at 3 meters                                           | 48.46 dB□A) |
| Sound pressure level at 5 meters                                           | 44.02 dB□A) |
| Sound power level                                                          | 72 dB       |

  

| Space Heating (According toEN14825:2022 ) Average Climate WaterOutlet 55°C |             |
|----------------------------------------------------------------------------|-------------|
| Rated heat output                                                          | 15.93 kW    |
| Seasonal Space Heating Energy                                              | 1.37 *      |
| SCOP                                                                       | 3.51 *      |
| ERP Level ((EU) No 811/2013 )                                              | A++ *       |
| Sound pressure level at 1 meter                                            | 59 dB□A)    |
| Sound pressure level at 3 meters                                           | 49.46 dB□A) |
| Sound pressure level at 5 meters                                           | 45.02 dB□A) |
| Sound power level                                                          | 73 dB       |

  

| Power Supply |                                |
|--------------|--------------------------------|
| Power Supply | 380V-415V/3N~ / 50/60Hz V / Hz |

  

| Max. power input |          |
|------------------|----------|
| Max. power input | 71.64 kW |

  

| Max. current |       |
|--------------|-------|
| Max. current | 110 A |

  

| Refrigerant□R32□ |          |
|------------------|----------|
| Refrigerant□R32□ | 7.5×2 kg |

|                                      |  |                   |
|--------------------------------------|--|-------------------|
| <b>Water Flow Rate</b>               |  |                   |
| Water Flow Rate                      |  | 25.8 m³/h         |
| <b>Water Pressure Drop</b>           |  |                   |
| Water Pressure Drop                  |  | 45 kPa            |
| <b>Diameter of pipe</b>              |  |                   |
| Diameter of pipe                     |  | DN80 mm           |
| <b>Operating temp. range</b>         |  |                   |
| Operating temp. range                |  | -35~45 °C         |
| <b>Outlet temp. range</b>            |  |                   |
| Outlet temp. range                   |  | 5~60 °C           |
| <b>Product Dimensions (L×W×H)</b>    |  |                   |
| Product Dimensions (L×W×H)           |  | 2250×1350×2400 mm |
| <b>Packing size(W*D*H)(Polywood)</b> |  |                   |
| Packing size(W*D*H)(Polywood)        |  | 2250×1350×2400 mm |
| <b>N.W</b>                           |  |                   |
| N.W                                  |  | 1200 kg           |