

R32 Commercial Heat Pump

QBKFXFC-200URII 200 kW

Performance			
Operating condition	Capacity (kW)	Input (kW)	COP / EER
A7W30-35	61.88~199.53	12.11~51.29	3.89~5.11
A7W47-55	62.95~200.93	18.96~73.60	2.73~3.32
A-7W35	44.00~135.32	13.13~47.48	2.85~3.35
A-7W55	46.09~140.00	19.87~69.65	2.01~2.32
A-15W35	37.13~108.62	13.12~46.82	2.32~2.83
A-15W55	40.12~108.00	19.96~62.79	1.72~2.01
A-20W35	33.00~86.97	13.64~41.02	2.12~2.42
A-20W55	35.86~89.72	19.70~55.73	1.61~1.82
A35W7	55.00~148.50	16.08~55.83	2.66~3.42
A20W15-55	68.75~216.00	13.35~53.07	4.07~5.15
A7W15-55	60.94~172.80	13.36~48.68	3.55~4.56

Space Heating (According toEN14825:2022) Average Climate WaterOutlet 35°C	
Rated heat output	22.07 kW
Seasonal Space Heating Energy	1.77 *
SCOP	4.51 *
ERP Level ((EU) No 811/2013)	A+++ *
Sound pressure level at 1 meter	61 dB□A)
Sound pressure level at 3 meters	51.46 dB□A)
Sound pressure level at 5 meters	47.02 dB□A)
Sound power level	75 dB

Space Heating (According toEN14825:2022) Average Climate WaterOutlet 55°C	
Rated heat output	21.1 kW
Seasonal Space Heating Energy	1.35 *
SCOP	3.46 *
ERP Level ((EU) No 811/2013)	A++ *
Sound pressure level at 1 meter	61 dB□A)
Sound pressure level at 3 meters	51.46 dB□A)
Sound pressure level at 5 meters	47.02 dB□A)
Sound power level	75 dB

Power Supply	
Power Supply	380V-415V/3N~ / 50/60Hz V / Hz

Max. power input	
Max. power input	97.68 kW

Max. current	
Max. current	150 A

Refrigerant□R32□	
Refrigerant□R32□	7.5×4 kg

Water Flow Rate		
Water Flow Rate		34.4 m³/h
Water Pressure Drop		
Water Pressure Drop		45 kPa
Diameter of pipe		
Diameter of pipe		DN80 mm
Operating temp. range		
Operating temp. range		-35~45 °C
Outlet temp. range		
Outlet temp. range		5~60 °C
Product Dimensions (L×W×H)		
Product Dimensions (L×W×H)		2200×1400×2400 mm
Packing size(W*D*H)(Polywood)		
Packing size(W*D*H)(Polywood)		2200×1400×2400 mm
N.W		
N.W		1250 kg