

Two-Stage High-Temperature Heat Pump

KFXF-060UMAI/FD 66 kW

Performance			
Operating condition	Capacity (kW)	Input (kW)	COP / EER
Low temperature rated heatinga	52	24.2	2.15
Normal temperature rated heatingb	66	27.5	2.4
Power Supply			
Power Supply		380V /3N~ /50Hz Power Supply	
Operating temp. range			
Operating temp. range		-35~40 °C	
Heating capacity/COP			
A-7W70		55/2.25 kW/-	
A-20W70		37/1.85 kW/-	
Max. operating current			
Max. operating current		70 A	
Max. input power			
Max. input power		39 kW	
Max. water outlet temperature			
Max. water outlet temperature		85 °C	
Compressor			
Form		Scroll	
Number		4 PCS	
Refrigerant			
Refrigerant		R410A+R134A	
Air Discharge Direction			
Air Discharge Direction		Top Discharge	
Number of fans			
Number of fans		2	
Hot water side flow			
Hot water side flow		11.3 m3/h	
Hot water side water inlet size			
Hot water side water inlet size		2×DN50 internal thread mm	
Hot water side pressure loss			
Hot water side pressure loss		≤40 kPa	

Buffer water side flow		
Buffer water side flow		7.2 m ³ /h
Buffer water side water inlet size		
Buffer water side water inlet size		2×DN40 internal thread mm
Buffer water side pressure loss		
Buffer water side pressure loss		≤40 kPa
Sound pressure level at 1 meter		
Sound pressure level at 1 meter		≤68 dB(A)
Product Dimensions (L×W×H)		
Product Dimensions (L×W×H)		1550×1160×1750 mm
N.W.		
N.W.		700 kg