

Two-Stage High-Temperature Heat Pump

KFXF-110UMAI/FD 110 kW

Performance			
Operating condition	Capacity (kW)	Input (kW)	COP / EER
Low temperature rated heatinga	85	39.5	2.15
Normal temperature rated heatingb	110	45.8	2.4
Power Supply			
Power Supply		380V /3N~ /50Hz Power Supply	
Operating temp. range			
Operating temp. range		-35~40 °C	
Heating capacity/COP			
A-7W70		90/2.25 kW/-	
A-20W70		60/1.85 kW/-	
Max. operating current			
Max. operating current		130 A	
Max. input power			
Max. input power		72 kW	
Max. water outlet temperature			
Max. water outlet temperature		85 °C	
Compressor			
Form		Scroll	
Number		4 PCS	
Refrigerant			
Refrigerant		R410A+R134A	
Air Discharge Direction			
Air Discharge Direction		Top Discharge	
Number of fans			
Number of fans		2	
Hot water side flow			
Hot water side flow		18.9 m3/h	
Hot water side water inlet size			
Hot water side water inlet size		2 x DN65 Flange mm	
Hot water side pressure loss			
Hot water side pressure loss		<=60 kPa	

Buffer water side flow		
Buffer water side flow		12 m ³ /h
Buffer water side water inlet size		
Buffer water side water inlet size		2×DN50 Flange mm
Buffer water side pressure loss		
Buffer water side pressure loss		≤60 kPa
Sound pressure level at 1 meter		
Sound pressure level at 1 meter		≤69 dB(A)
Product Dimensions (L×W×H)		
Product Dimensions (L×W×H)		2100×1500×2180 mm
N.W.		
N.W.	N.W.	1100 kg