

Two-Stage High-Temperature Heat Pump

KFXF-060UMAI/FD 66 kW



Key data

Rated capacity	66 kW
Rated COP / EER	2.15
Power supply	380V /3N~ /50Hz Power Supply
Refrigerant	R410A+R134A
Max. input power	39 kW
Max. current	70 A
Sound power	<=68 dB(A)
Outlet temp.	85 °C

Performance

Operating condition	Capacity (kW)	Input (kW)	COP / EER
Low temperature rated heatinga	52	24.2	2.15
Normal temperature rated heatingb	66	27.5	2.4

Power Supply

Power Supply	380V /3N~ /50Hz Power Supply
--------------	------------------------------

Operating temp. range

Operating temp. range	-35~40 °C
-----------------------	-----------

Heating capacity/COP

A-7W70	55/2.25 kW/-
A-20W70	37/1.85 kW/-

Max. operating current

Max. operating current	70 A
------------------------	------

Max. input power

Max. input power	39 kW
------------------	-------

Max. water outlet temperature

Max. water outlet temperature	85 °C
-------------------------------	-------

Compressor

Form	Scroll
Number	4 PCS

Refrigerant

Refrigerant	R410A+R134A
-------------	-------------

Air Discharge Direction	
Air Discharge Direction	Top Discharge
Number of fans	
Number of fans	2
Hot water side flow	
Hot water side flow	11.3 m ³ /h
Hot water side water inlet size	
Hot water side water inlet size	2×DN50 internal thread mm
Hot water side pressure loss	
Hot water side pressure loss	≤40 kPa
Buffer water side flow	
Buffer water side flow	7.2 m ³ /h
Buffer water side water inlet size	
Buffer water side water inlet size	2×DN40 internal thread mm
Buffer water side pressure loss	
Buffer water side pressure loss	≤40 kPa
Sound pressure level at 1 meter	
Sound pressure level at 1 meter	≤68 dB(A)
Product Dimensions (L×W×H)	
Product Dimensions (L×W×H)	1550×1160×1750 mm
N.W.	
N.W.	700 kg