

Two-Stage High-Temperature Heat Pump

KFXF-110UMAI/FD 110 kW



Key data

Rated capacity	110 kW
Rated COP / EER	2.15
Power supply	380V /3N~ /50Hz Power Supply
Refrigerant	R410A+R134A
Max. input power	72 kW
Max. current	130 A
Sound power	<=69 dB(A)
Outlet temp.	85 °C

Performance

Operating condition	Capacity (kW)	Input (kW)	COP / EER
Low temperature rated heatinga	85	39.5	2.15
Normal temperature rated heatingb	110	45.8	2.4

Power Supply

Power Supply	380V /3N~ /50Hz Power Supply
--------------	------------------------------

Operating temp. range

Operating temp. range	-35~40 °C
-----------------------	-----------

Heating capacity/COP

A-7W70	90/2.25 kW/-
A-20W70	60/1.85 kW/-

Max. operating current

Max. operating current	130 A
------------------------	-------

Max. input power

Max. input power	72 kW
------------------	-------

Max. water outlet temperature

Max. water outlet temperature	85 °C
-------------------------------	-------

Compressor

Form	Scroll
Number	4 PCS

Refrigerant

Refrigerant	R410A+R134A
-------------	-------------

Air Discharge Direction	
Air Discharge Direction	Top Discharge
Number of fans	
Number of fans	2
Hot water side flow	
Hot water side flow	18.9 m ³ /h
Hot water side water inlet size	
Hot water side water inlet size	2 x DN65 Flange mm
Hot water side pressure loss	
Hot water side pressure loss	≤60 kPa
Buffer water side flow	
Buffer water side flow	12 m ³ /h
Buffer water side water inlet size	
Buffer water side water inlet size	2×DN50 Flange mm
Buffer water side pressure loss	
Buffer water side pressure loss	≤60 kPa
Sound pressure level at 1 meter	
Sound pressure level at 1 meter	≤69 dB(A)
Product Dimensions (L×W×H)	
Product Dimensions (L×W×H)	2100×1500×2180 mm
N.W.	
N.W.	1100 kg