


R32 Monobloc Heat Pump

QBKFXFC-024SRII 24 kW



Key data	
Rated capacity	24 kW
Rated COP / EER	4.09~5.22
Power supply	380V~415V/3N~ / 50/60Hz V / Hz
Refrigerant	3.2 kg
Max. input power	11.54 kW
Max. current	20 A
Sound power	48 dB(A)
Outlet temp.	22.07 kW

Performance

Operating condition	Capacity (kW)	Input (kW)	COP / EER
A7W30-35	9.91~26.55	1.90~6.49	4.09~5.22
A7W47-55	10.40~26.36	3.12~9.03	2.92~3.33
A-7W35	6.77~21.76	1.96~7.38	2.95~3.45
A-7W55	7.41~20.57	3.06~9.84	2.09~2.42
A-15W35	5.67~16.15	1.99~6.79	2.38~2.85
A-15W55	6.42~16.30	3.10~9.26	1.76~2.07
A-20W35	5.15~13.47	2.10~6.32	2.13~2.45
A-20W55	5.96~13.81	3.15~8.52	1.62~1.89
A35W7	8.84~20.00	2.58~7.35	2.72~3.42
A20W15-55	9.40~26.00	1.79~6.24	4.17~5.25
A7W15-55	10.00~25.00	2.13~6.87	3.64~4.69

Space Heating (According to EN14825:2022) Average Climate Water Outlet 35°C

Rated heat output	22.07 kW
Seasonal Space Heating Energy	1.81 *
SCOP	4.6 *
ERP Level ((EU) No 811/2013)	A+++ *
Sound pressure level at 1 meter	48 dB(A)
Sound pressure level at 3 meters	38.46 dB(A)
Sound pressure level at 5 meters	34.02 dB(A)
Sound power level	62 dB

Space Heating (According to EN14825:2022) Average Climate Water Outlet 55°C

Rated heat output	21.1 kW
Seasonal Space Heating Energy	1.35 *
SCOP	3.46 *
ERP Level ((EU) No 811/2013)	A++ *
Sound pressure level at 1 meter	48 dB(A)
Sound pressure level at 3 meters	38.46 dB(A)
Sound pressure level at 5 meters	34.02 dB(A)

Sound power level	63 dB
Power Supply	
Power Supply	380V-415V/3N~ / 50/60Hz V / Hz
Max. power input	
Max. power input	11.54 kW
Max. current	
Max. current	20 A
Refrigerant□R32□	
Refrigerant□R32□	3.2 kg
Water Flow Rate	
Water Flow Rate	4.13 m³/h
Water Pressure Drop	
Water Pressure Drop	30 kPa
Diameter of pipe	
Diameter of pipe	DN32 mm
Product Dimensions (L×W×H)	
Product Dimensions (L×W×H)	1100×510×1590 mm
Packing size(W×D×H)(carton)	
Packing size(W×D×H)(carton)	1220×560×1710 mm
Packing size(W×D×H)(Polywood)	
Packing size(W×D×H)(Polywood)	1240×580×1720 mm
N.W	
N.W	180 kg