

R290 Residential Monobloc Heat Pump

QBKFXFC-030SBII 30 kW



Key data	
Rated capacity	30 kW
Rated COP / EER	3.92~5.32
Refrigerant	2.3 kg
Max. input power	13 kW
Max. current	22 A
Sound power	49 dB(A)
Outlet temp.	19.78 kW
Dimensions	1100×510×1590 mm

Performance

Operating condition	Capacity (kW)	Input (kW)	COP / EER
A7W30-35	8.59~29.95	1.61~7.64	3.92~5.32
A7W47-55	7.64~28.42	2.38~10.08	2.82~3.21
A-7W35	5.51~21.76	1.61~7.56	2.88~3.42
A-7W55	5.10~20.36	2.08~9.88	2.06~2.45
A-15W35	4.43~17.48	1.57~7.53	2.32~2.82
A-15W55	4.22~16.94	2.01~9.52	1.78~2.10
A-20W35	3.70~15.04	1.51~7.16	2.10~2.45
A-20W55	3.63~14.44	1.91~8.54	1.69~1.90
A35W7	7.19~18.93	2.08~6.76	2.80~3.45
A20W15-55	10.31~32.95	1.98~7.98	4.13~5.2
A7W15-55	7.87~28.99	1.69~8.03	3.61~4.66

Space Heating (According to EN14825:2022) Average Climate Water Outlet 35°C

Rated heat output	19.78 kW
Seasonal Space Heating Energy	1.84 *
SCOP	4.68 *
ERP Level ((EU) No 811/2013)	A+++ *
Sound pressure level at 1 meter	49 dB(A)
Sound pressure level at 3 meters	39.46 dB(A)
Sound pressure level at 5 meters	35.02 dB(A)
Sound power level	64 dB

Space Heating (According to EN14825:2022) Average Climate Water Outlet 55°C

Rated heat output	17.35 kW
Seasonal Space Heating Energy	1.36 *
SCOP	3.48 *
ERP Level ((EU) No 811/2013)	A++ *
Sound pressure level at 1 meter	50 dB(A)
Sound pressure level at 3 meters	40.46 dB(A)
Sound pressure level at 5 meters	36.02 dB(A)

Sound power level		65 dB
Max. power input		
Max. power input		13 kW
Max. current		
Max. current		22 A
Refrigerant □ R290 □		
Refrigerant □ R290 □		2.3 kg
Water Flow Rate		
Water Flow Rate		5.16 m³/h
Water Pressure Drop		
Water Pressure Drop		35 kPa
Diameter of pipe		
Diameter of pipe		DN32 mm
Product Dimensions (L×W×H)		
Product Dimensions (L×W×H)		1100×510×1590 mm
Packing size(W*D*H)(carton)		
Packing size(W*D*H)(carton)		1220×560×1710 mm
Packing size(W*D*H)(Polywood)		
Packing size(W*D*H)(Polywood)		1240×580×1720 mm
N.W		
N.W		200 kg