

R32 Commercial Heat Pump

QBKFXFC-150URII 150 kW



Key data

Rated capacity	150 kW
Rated COP / EER	4.10~5.18
Power supply	380V~415V/3N~ / 50/60Hz V / Hz
Refrigerant	7.5×2 kg
Max. input power	71.64 kW
Max. current	110 A
Sound power	58 dB(A)
Outlet temp.	15.75 kW

Performance

Operating condition	Capacity (kW)	Input (kW)	COP / EER
A7W30-35	46.87~150.34	9.05~36.67	4.10~5.18
A7W47-55	49.17~156.23	14.90~53.87	2.90~3.30
A-7W35	31.98~101.95	9.32~34.91	2.92~3.43
A-7W55	35.07~110.38	14.80~53.07	2.08~2.37
A-15W35	26.78~84.98	9.36~35.56	2.39~2.86
A-15W55	30.36~88.65	14.96~50.66	1.75~2.03
A-20W35	24.38~77.15	9.91~35.88	2.15~2.46
A-20W55	28.18~78.44	15.07~46.69	1.68~1.87
A35W7	35.75~96.60	10.24~37.88	2.55~3.49
A20W15-55	48.75~161.00	9.47~38.33	4.20~5.15
A7W15-55	42.25~154.56	8.88~42.35	3.65~4.76

Space Heating (According to EN14825:2022) Average Climate Water Outlet 35°C

Rated heat output	15.75 kW
Seasonal Space Heating Energy	1.79 *
SCOP	4.55 *
ERP Level ((EU) No 811/2013)	A+++ *
Sound pressure level at 1 meter	58 dB(A)
Sound pressure level at 3 meters	48.46 dB(A)
Sound pressure level at 5 meters	44.02 dB(A)
Sound power level	72 dB

Space Heating (According to EN14825:2022) Average Climate Water Outlet 55°C

Rated heat output	15.93 kW
Seasonal Space Heating Energy	1.37 *
SCOP	3.51 *
ERP Level ((EU) No 811/2013)	A++ *
Sound pressure level at 1 meter	59 dB(A)
Sound pressure level at 3 meters	49.46 dB(A)
Sound pressure level at 5 meters	45.02 dB(A)

Sound power level	73 dB
Power Supply	
Power Supply	380V-415V/3N~ / 50/60Hz V / Hz
Max. power input	
Max. power input	71.64 kW
Max. current	
Max. current	110 A
Refrigerant □ R32 □	
Refrigerant □ R32 □	7.5×2 kg
Water Flow Rate	
Water Flow Rate	25.8 m³/h
Water Pressure Drop	
Water Pressure Drop	45 kPa
Diameter of pipe	
Diameter of pipe	DN80 mm
Operating temp. range	
Operating temp. range	-35~45 °C
Outlet temp. range	
Outlet temp. range	5~60 °C
Product Dimensions (L×W×H)	
Product Dimensions (L×W×H)	2250×1350×2400 mm
Packing size(W×D×H)(Polywood)	
Packing size(W×D×H)(Polywood)	2250×1350×2400 mm
N.W	
N.W	1200 kg