Compact Alternate Marking

Tal Mizrahi Huawei Network.IO Innovation Lab

Carmi Arad

Giuseppe Fioccola Huawei Technologies

Mauro Cociglio Telecom Italia

Mach Chen Huawei Technologies Lianshu Zheng Huawei Technologies

Greg Mirsky ZTE Corporation


draft-mizrahi-ippm-compact-alternate-marking-03 IETF 103, Bangkok, November 2018

Alternate Marking - Background


Monitor data traffic from MP 1 to MP 2

- Loss
- Delay
- Delay variation MP 1 MP 2 MP = Measurement Point

Alternate Marking (RFC 8321)




Double Marking



Scope of the Current Draft

- New alternate marking methods with low overhead.
 - Single bit per packet.
 - Zero bits per packet.
- Summary of alternate marking methods.



Summary and Tradeoff of Marking Methods

·	bits	+ of # of ts coun ters	Method		+ Resilience to Reordering +		++ Resilience to Packet drops ++	
	 				LM	l DM	LM	DM
Single marking	 1 	2 2 	Step 	Step 	+	 	+	
Single marking - mean delay	1 1	2 	'	Mean 	+ 	+	+ 	- -
Double marking	2	2	 Step	 Pulse	+	+	' +	=
Single marking multiplexed	1 1	2 	Step 	Pulse 	+ +	+ +	 + 	=
Pulse marking	1	1	Pulse	Pulse	 	+ +	 -	=
Zero marking hashed	•	(2)	Hashed pulse (step)	pulse		+ + + + 	 - 	+ +
Single marking hashed +	+ 1 	+ 2 +		Hashed pulse 	+	+	+	++ + +

- + Accurate measurement.
- = Invalidate only if a measured packet
 is lost (detectable)
- No measurement in case of disturbance (detectable).
- -- False measurement in case of disturbance (not detectable).

Related Drafts

- draft-ietf-mpls-rfc6374-sfl-02
- draft-ietf-bier-pmmm-oam-04
- draft-fmm-nvo3-pm-alt-mark-03
- draft-mirsky-sfc-pmamm-02
- draft-fioccola-ippm-multipoint-alt-mark-04
- fioccola-v6ops-ipv6-alt-mark
- fear-ippm-mpdm-02
- draft-ietf-quic-spin-exp-01
- draft-trammell-quic-spin-03

Most of these drafts may benefit from the methods and analysis of the current draft.

Next Steps

• Comments will be welcome!