




ANDROID STATIC ANALYSIS REPORT



 testingapp (1.0.2)

File Name:

app-arm64-v8a-release.apk

Package Name:

com.enoconan.testingappv2

Scan Date:

Oct. 26, 2025, 7:38 a.m.

App Security Score:

64/100 (LOW RISK)

Grade:



 HIGH	 MEDIUM	 INFO	 SECURE	 HOTSPOT
0	16	3	4	2

FILE INFORMATION

File Name: app-arm64-v8a-release.apk

Size: 65.52MB

MD5: a90a5f59c2f8916a633a2e0a44238b4e

SHA1: 60eb62bf527549d6c221d80a3a3d99e4bc163a0e

SHA256: adad66f44fc41d12ebb70f34db050efde99d7a6d70429981008aeab9cd97f88c

APP INFORMATION

App Name: testingapp

Package Name: com.enoconan.testingappv2

Main Activity: com.enoconan.testingappv2.MainActivity

Target SDK: 36

Min SDK: 29

Max SDK:

Android Version Name: 1.0.2

Android Version Code: 4001

APP COMPONENTS

Activities: 39

Services: 10

Receivers: 6

Providers: 3

Exported Activities: 4

Exported Services: 1

Exported Receivers: 3
Exported Providers: 0

CERTIFICATE INFORMATION

Binary is signed
v1 signature: False
v2 signature: True
v3 signature: False
v4 signature: False
X.509 Subject: C=JP, CN=Kota
Signature Algorithm: rsassa_pkcs1v15
Valid From: 2025-01-31 10:47:53+00:00
Valid To: 2052-06-18 10:47:53+00:00
Issuer: C=JP, CN=Kota
Serial Number: 0xb202639cc17edfdf
Hash Algorithm: sha384
md5: bd6e9df50161da7c4153f7834d6f7850
sha1: 96d7375b723d441ab6f1cb4b2d22dbd5fdc9cbd6
sha256: 43f2cf97ef1e303d86354469f8cfbdf9ed152c3ebd45f334fae058e09b76ffd1
sha512: 099e87bdbb1a7b41605a5a35ed69eeea3e91876ab7a3375bcd1cab0dca4de9e8d24e0198377d6270c9a92b5a2c4fa3f3532112ae4910c07030e8c380610aa203
PublicKey Algorithm: rsa
Bit Size: 2048
Fingerprint: 098587b2d841fad7d5cda571d5bcd6cebdef271f46b192113970a6685f456d69
Found 1 unique certificates

APPLICATION PERMISSIONS

PERMISSION	STATUS	INFO	DESCRIPTION
android.permission.INTERNET	normal	full Internet access	Allows an application to create network sockets.
android.permission.USE_BIOMETRIC	normal	allows use of device-supported biometric modalities.	Allows an app to use device supported biometric modalities.

PERMISSION	STATUS	INFO	DESCRIPTION
android.permission.ACCESS_FINE_LOCATION	dangerous	fine (GPS) location	Access fine location sources, such as the Global Positioning System on the phone, where available. Malicious applications can use this to determine where you are and may consume additional battery power.
android.permission.ACCESS_COARSE_LOCATION	dangerous	coarse (network-based) location	Access coarse location sources, such as the mobile network database, to determine an approximate phone location, where available. Malicious applications can use this to determine approximately where you are.
android.permission.POST_NOTIFICATIONS	dangerous	allows an app to post notifications.	Allows an app to post notifications
android.permission.RECEIVE_BOOT_COMPLETED	normal	automatically start at boot	Allows an application to start itself as soon as the system has finished booting. This can make it take longer to start the phone and allow the application to slow down the overall phone by always running.
android.permission.VIBRATE	normal	control vibrator	Allows the application to control the vibrator.
android.permission.ACCESS_NETWORK_STATE	normal	view network status	Allows an application to view the status of all networks.
android.permission.USE_FINGERPRINT	normal	allow use of fingerprint	This constant was deprecated in API level 28. Applications should request USE_BIOMETRIC instead.
android.permission.WAKE_LOCK	normal	prevent phone from sleeping	Allows an application to prevent the phone from going to sleep.
com.google.android.c2dm.permission.RECEIVE	normal	recieve push notifications	Allows an application to receive push notifications from cloud.
com.enoconan.testingappv2.DYNAMIC_RECEIVER_NOT_EXPORTED_PERMISSION	unknown	Unknown permission	Unknown permission from android reference

FILE	DETAILS	
classes.dex	FINDINGS	DETAILS
	yara_issue	yara issue - dex file recognized by apkid but not yara module
	Anti-VM Code	Build.FINGERPRINT check Build.MANUFACTURER check Build.TAGS check
	Compiler	unknown (please file detection issue!)
classes2.dex	FINDINGS	DETAILS
	yara_issue	yara issue - dex file recognized by apkid but not yara module
	Anti-VM Code	Build.FINGERPRINT check Build.MODEL check Build.MANUFACTURER check Build.PRODUCT check
	Anti Debug Code	Debug.isDebuggerConnected() check
	Compiler	unknown (please file detection issue!)

FILE	DETAILS	
classes3.dex	FINDINGS	DETAILS
	yara_issue	yara issue - dex file recognized by apkid but not yara module
	Compiler	unknown (please file detection issue!)

BROWSABLE ACTIVITIES

ACTIVITY	INTENT
com.enoconan.testingappv2.MainActivity	Schemes: https://, testingapp://, Hosts: testing-app-4bc40.web.app, Path Prefixes: /register,
com.stripe.android.financialconnections.FinancialConnectionsSheetRedirectActivity	Schemes: stripe-auth://, stripe://, Hosts: link-accounts, link-native-accounts, native-redirect, auth-redirect, Paths: /com.enoconan.testingappv2/success, /com.enoconan.testingappv2/cancel, Path Prefixes: /com.enoconan.testingappv2/authentication_return, /com.enoconan.testingappv2,
com.stripe.android.link.LinkRedirectHandlerActivity	Schemes: link-popup://, Hosts: complete, Paths: /com.enoconan.testingappv2,
com.stripe.android.payments.StripeBrowserProxyReturnActivity	Schemes: stripesdk://, Hosts: payment_return_url, Paths: /com.enoconan.testingappv2,
com.stripe.android.financialconnections.lite.FinancialConnectionsSheetLiteRedirectActivity	Schemes: stripe://, Hosts: financial-connections-lite, Path Prefixes: /com.enoconan.testingappv2/auth_redirect,

NETWORK SECURITY

HIGH: 0 | WARNING: 0 | INFO: 0 | SECURE: 1

NO	SCOPE	SEVERITY	DESCRIPTION
1	*	secure	Base config is configured to disallow clear text traffic to all domains.

CERTIFICATE ANALYSIS

HIGH: 0 | WARNING: 0 | INFO: 1

TITLE	SEVERITY	DESCRIPTION
Signed Application	info	Application is signed with a code signing certificate

MANIFEST ANALYSIS

HIGH: 0 | WARNING: 8 | INFO: 0 | SUPPRESSED: 0

NO	ISSUE	SEVERITY	DESCRIPTION
1	App has a Network Security Configuration [android:networkSecurityConfig=@xml/network_security_config]	info	The Network Security Configuration feature lets apps customize their network security settings in a safe, declarative configuration file without modifying app code. These settings can be configured for specific domains and for a specific app.
2	Activity (com.stripe.android.financialconnections.FinancialConnectionsSheetRedirectActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.

NO	ISSUE	SEVERITY	DESCRIPTION
3	Activity (com.stripe.android.link.LinkRedirectHandlerActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
4	Activity (com.stripe.android.payments.StripeBrowserProxyReturnActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
5	Activity (com.stripe.android.financialconnections.lite.FinancialConnectionsSheetLiteRedirectActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
6	Broadcast Receiver (io.flutter.plugins.firebase.messaging.FlutterFirebaseMessagingReceiver) is Protected by a permission, but the protection level of the permission should be checked. Permission: com.google.android.c2dm.permission.SEND [android:exported=true]	warning	A Broadcast Receiver is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. It is protected by a permission which is not defined in the analysed application. As a result, the protection level of the permission should be checked where it is defined. If it is set to normal or dangerous, a malicious application can request and obtain the permission and interact with the component. If it is set to signature, only applications signed with the same certificate can obtain the permission.
7	Service (com.google.android.gms.auth.api.signin.RevocationBoundService) is Protected by a permission, but the protection level of the permission should be checked. Permission: com.google.android.gms.auth.api.signin.permission.REVOCATION_NOTIFICATION [android:exported=true]	warning	A Service is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. It is protected by a permission which is not defined in the analysed application. As a result, the protection level of the permission should be checked where it is defined. If it is set to normal or dangerous, a malicious application can request and obtain the permission and interact with the component. If it is set to signature, only applications signed with the same certificate can obtain the permission.

NO	ISSUE	SEVERITY	DESCRIPTION
8	Broadcast Receiver (com.google.firebase.iid.FirebaseInstanceIdReceiver) is Protected by a permission, but the protection level of the permission should be checked. Permission: com.google.android.c2dm.permission.SEND [android:exported=true]	warning	A Broadcast Receiver is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. It is protected by a permission which is not defined in the analysed application. As a result, the protection level of the permission should be checked where it is defined. If it is set to normal or dangerous, a malicious application can request and obtain the permission and interact with the component. If it is set to signature, only applications signed with the same certificate can obtain the permission.
9	Broadcast Receiver (androidx.profileinstaller.ProfileInstallReceiver) is Protected by a permission, but the protection level of the permission should be checked. Permission: android.permission.DUMP [android:exported=true]	warning	A Broadcast Receiver is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. It is protected by a permission which is not defined in the analysed application. As a result, the protection level of the permission should be checked where it is defined. If it is set to normal or dangerous, a malicious application can request and obtain the permission and interact with the component. If it is set to signature, only applications signed with the same certificate can obtain the permission.

</> CODE ANALYSIS

HIGH: 0 | WARNING: 7 | INFO: 3 | SECURE: 1 | SUPPRESSED: 0

NO	ISSUE	SEVERITY	STANDARDS	FILES
				A1/d.java A1/i.java A3/d.java Ab/A1.java Ac/C1476a.java Ac/e.java B2/b.java B4/a.java C2/c.java C3/h.java C4/a.java C6/e.java

NO	ISSUE	SEVERITY	STANDARDS	D3/d.java D3/e.java D4/f.java D4/m.java D4/n.java Dc/C1685i.java Dc/C1689k.java Dc/W0.java E2/C1746a.java E2/n.java Fc/i.java G1/d.java G4/h.java Gc/C1875a.java Gc/F.java Gc/J.java H3/a.java H4/b.java H6/c.java Hc/i.java J0/N.java J1/AbstractC2134b.java J1/C2149q.java J1/K.java J1/T.java J1/f0.java K1/j.java K4/r.java M1/c.java N1/i.java N2/C2461e.java N5/d.java O1/p.java O1/x.java P/V.java P7/C2556l.java P7/M.java P7/Y.java P7/d0.java P7/I0.java Pb/c.java Q5/g.java Q7/d.java Q8/f.java R6/h.java R7/c.java

NO	ISSUE	SEVERITY	STANDARDS	FILES
				S2/a.java S6/a.java S6/e.java S6/l.java S7/g.java S7/i.java T3/a.java T6/a.java T6/c.java T7/k.java V2/f.java V2/m.java W1/b.java W6/B.java W6/C2952g.java W6/D.java W6/F.java W6/k.java W6/x.java X1/a.java Y0/j.java Y1/b.java Y1/k.java Y6/c.java Y6/f.java Yb/B.java Yb/D.java Yb/i.java Z/C3041b.java Z0/a.java a2/C3152c.java a3/C3161a.java a5/w.java a6/O.java b2/C3343a.java b4/k.java b6/f.java c5/e.java com/baseflow/geolocator/GeolocatorLocationService.java com/bumptechnology/glides/b.java com/bumptechnology/glides/load/data/b.java com/bumptechnology/glides/load/data/j.java com/bumptechnology/glides/load/data/l.java com/dexterous/flutterlocalnotifications/ActionBroadcastReceiver.java

NO	ISSUE	SEVERITY	STANDARDS	FILES
1	The App logs information. Sensitive information should never be logged.	info	CWE: CWE-532: Insertion of Sensitive Information into Log File OWASP MASVS: MSTG-STORAGE-3	com/dexterous/flutterlocalnotifications/FlutterLocalNotificationsPlugin.java com/dexterous/flutterlocalnotifications/ScheduledNotificationReceiver.java com/stripe/android/stripe3ds2/transaction/o.java com/stripe/hcaptcha/webview/HcaptchaWebView.java d3/C3739c.java d3/k.java d3/n.java d5/F.java e4/C3875a.java e5/C3881e.java f3/j.java fc/C4024b.java g2/C4033c.java g3/C4035b.java g5/C4047a.java g6/C4058f.java g6/n.java g8/InterfaceC4068d.java h5/C4145a.java i3/C4228a.java i6/C4285c.java io/flutter/plugins/firebase/messaging/FlutterFirebaseMessagingBackgroundService.java io/flutter/plugins/firebase/messaging/FlutterFirebaseMessagingReceiver.java io/flutter/plugins/firebase/messaging/a.java j/AbstractC4330e.java j/LayoutInflaterFactory2C4332g.java j/m.java j/s.java j3/d.java j3/e.java j5/C4393b.java j5/P.java k5/f.java l1/d.java l3/C4529c.java l3/C4531e.java m0/C4566c.java m0/g.java m3/h.java m3/i.java

NO	ISSUE	SEVERITY	STANDARDS	FILES
				m3/k.java m3/l.java m3/z.java n3/i.java n3/j.java o/g.java o1/C4728f.java o3/C4747e.java o3/C4751i.java p/MenuItemC4819c.java p1/C4848o.java p3/ExecutorServiceC4854a.java q/B.java q/C4945v.java q/C4948y.java q/J.java q/M.java q/P.java q/Q.java q/c0.java q1/C4975a.java q3/C4983c.java q3/C4984d.java q3/C4986f.java q3/s.java q3/t.java q4/g.java q5/C5004h.java r1/j.java r2/C5046a.java r8/C5078i.java s1/C5184a.java s3/AbstractC5189a.java t2/c.java t3/B.java t3/c.java t3/d.java t3/k.java t3/m.java t3/n.java t3/r.java t3/z.java t6/C5318b.java u4/AbstractC5380A.java u4/AbstractC5389b.java u4/C5383D.java

NO	ISSUE	SEVERITY	STANDARDS	FILES
				u4/C5384E.java u4/C5390c.java u4/C5398k.java u4/C5412y.java u4/ServiceConnectionC5411x.java u7/C5416a.java v/b.java v4/C5500d.java v4/h.java v4/i.java v4/l.java v4/s.java v4/w.java v6/C5503b.java v7/C5506a.java v7/C5507b.java w1/C5592d.java w1/j.java w1/l.java w1/o.java w1/w.java w6/C5627c.java x3/C5720a.java x3/C5723d.java x3/C5729j.java x4/C5738l.java x4/C5742M.java x4/C5760e.java x4/RunnableC5741L.java x4/f0.java x4/k0.java y4/AbstractC5892c.java y4/AbstractDialogInterfaceOnClickListenerC5887G.java y4/BinderC5890a.java y4/C5884D.java y4/Y.java y4/c0.java y4/d0.java y4/e0.java y4/g0.java y4/m0.java y4/o0.java z1/C5952c.java z1/C5953d.java z1/h.java

NO	ISSUE	SEVERITY	STANDARDS	FILES
				z3/C5964e.java z3/C5965f.java z3/C5975p.java z3/C5977r.java z3/C5978s.java z3/FragmentC5974o.java z6/AbstractServiceC5991g.java z6/C5987c.java z6/C5988d.java z6/C5996l.java z6/C5998n.java z6/E.java z6/G.java z6/I.java z6/L.java z6/S.java z6/U.java z6/V.java z6/W.java z6/Z.java z6/a0.java z6/e0.java z6/h0.java
				B8/C1514b.java B8/h.java Jb/B.java K4/C2328k.java K9/b.java S8/p.java T/C2672b0.java T8/n.java Ta/U.java U7/p.java V6/b.java X0/C2963i.java X0/U.java Y8/l.java Z/C3040a1.java Z/C3085u0.java Z8/l.java ab/InterfaceC3213c.java ba/C3393G.java ba/C3399b.java

NO	ISSUE	SEVERITY	STANDARDS	FILES
2	Files may contain hardcoded sensitive information like usernames, passwords, keys etc.	warning	CWE: CWE-312: Cleartext Storage of Sensitive Information OWASP Top 10: M9: Reverse Engineering OWASP MASVS: MSTG-STORAGE-14	ba/C3414q.java ba/C3415s.java ba/InterfaceC3390D.java ba/X.java ba/r.java bb/C3423a.java bb/C3426d.java bb/j.java com/dexterous/flutterlocalnotifications/FlutterLocalNotificationsPlugin.java com/dexterous/flutterlocalnotifications/models/NotificationDetails.java com/stripe/android/auth/PaymentBrowserAuthContract.java com/stripe/android/customersheet/d.java com/stripe/android/financialconnections/model/FinancialConnectionsSession.java com/stripe/android/googlepaylauncher/GooglePayLauncherContract.java com/stripe/android/googlepaylauncher/GooglePaymentMethodLauncherContract.java com/stripe/android/link/j.java com/stripe/android/model/Source.java com/stripe/android/model/StripeIntent.java com/stripe/android/model/b.java com/stripe/android/model/c.java com/stripe/android/model/d.java com/stripe/android/model/j.java com/stripe/android/model/n.java com/stripe/android/model/p.java com/stripe/android/model/u.java com/stripe/android/model/x.java com/stripe/android/payments/bankaccount/navigation/CollectBankAccountContract.java com/stripe/android/payments/bankaccount/ui/a.java com/stripe/android/payments/core/authentication/treeds2/Stripe3ds2TransactionContract.java com/stripe/android/payments/paymentlauncher/PaymentLauncherContract.java com/stripe/android/paymentsheet/PaymentSheetContract.java com/stripe/android/paymentsheet/AddressElement/AddressElementActivityContract.java com/stripe/android/paymentsheet/AddressElement/d.java

NO	ISSUE	SEVERITY	STANDARDS	FILES
				com/stripe/android/paymentsheet/n.java com/stripe/android/paymentsheet/paymentdatacollection/polling/PollingContract.java com/stripe/android/paymentsheet/paymentdatacollection/polling/b.java com/stripe/android/stripe3ds2/transaction/n.java gb/InterfaceC4081e.java ha/C4162h.java k3/g.java l9/C4552d.java m3/d.java m3/p.java m3/x.java o8/C4791m.java oa/C4809e.java oa/InterfaceC4810f.java rb/C5107a.java rb/c.java s9/C5243e.java u8/C5419a.java u8/C5422d.java ua/C5442c.java ua/C5443d.java k2/C4473a.java
3	App can write to App Directory. Sensitive Information should be encrypted.	info	CWE: CWE-276: Incorrect Default Permissions OWASP MASVS: MSTG-STORAGE-14	
4	This App copies data to clipboard. Sensitive data should not be copied to clipboard as other applications can access it.	info	OWASP MASVS: MSTG-STORAGE-10	K0/C2267d.java io/flutter/plugin/editing/b.java io/flutter/plugin/platform/d.java
5	App uses SQLite Database and execute raw SQL query. Untrusted user input in raw SQL queries can cause SQL Injection. Also sensitive information should be encrypted and written to the database.	warning	CWE: CWE-89: Improper Neutralization of Special Elements used in an SQL Command ('SQL Injection') OWASP Top 10: M7: Client Code Quality	Yb/i.java i4/M.java i4/V.java
6	IP Address disclosure	warning	CWE: CWE-200: Information Exposure OWASP MASVS: MSTG-CODE-2	C7/a.java

NO	ISSUE	SEVERITY	STANDARDS	FILES
7	The App uses an insecure Random Number Generator.	warning	CWE: CWE-330: Use of Insufficiently Random Values OWASP Top 10: M5: Insufficient Cryptography OWASP MASVS: MSTG-CRYPTO-6	N6/d.java R6/s.java ed/AbstractC3976a.java ed/C3977b.java fd/C4025a.java
8	This App may have root detection capabilities.	secure	OWASP MASVS: MSTG-RESILIENCE-1	a6/C3182j.java
9	App can read/write to External Storage. Any App can read data written to External Storage.	warning	CWE: CWE-276: Incorrect Default Permissions OWASP Top 10: M2: Insecure Data Storage OWASP MASVS: MSTG-STORAGE-2	Fc/a.java Fc/i.java
10	SHA-1 is a weak hash known to have hash collisions.	warning	CWE: CWE-327: Use of a Broken or Risky Cryptographic Algorithm OWASP Top 10: M5: Insufficient Cryptography OWASP MASVS: MSTG-CRYPTO-4	v6/C5503b.java z6/E.java
11	App creates temp file. Sensitive information should never be written into a temp file.	warning	CWE: CWE-276: Incorrect Default Permissions OWASP Top 10: M2: Insecure Data Storage OWASP MASVS: MSTG-STORAGE-2	v6/C5504c.java

SHARED LIBRARY BINARY ANALYSIS

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
----	---------------	----	-----	-----------------	-------	-------	---------	---------	---------------------

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
1	arm64-v8a/libflutter.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Not Applicable info RELRO checks are not applicable for Flutter/Dart binaries	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['_vsnprintf_chk', '__read_chk', '__memcpy_chk', '__strcpy_chk', '__strlen_chk', '__memmove_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
2	arm64-v8a/libapp.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Not Applicable info RELRO checks are not applicable for Flutter/Dart binaries	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False info The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
3	arm64-v8a/libdatastore_shared_counter.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
4	arm64-v8a/libandroidx.graphics.path.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
5	arm64-v8a/libflutter.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Not Applicable info RELRO checks are not applicable for Flutter/Dart binaries	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['_vsnprintf_chk', '__read_chk', '__memcpy_chk', '__strcpy_chk', '__strlen_chk', '__memmove_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
6	arm64-v8a/libapp.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Not Applicable info RELRO checks are not applicable for Flutter/Dart binaries	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False info The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
7	arm64-v8a/libdatastore_shared_counter.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
8	arm64-v8a/libandroidx.graphics.path.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NIAP ANALYSIS v1.3

NO	IDENTIFIER	REQUIREMENT	FEATURE	DESCRIPTION
----	------------	-------------	---------	-------------

BEHAVIOUR ANALYSIS

RULE ID	BEHAVIOUR	LABEL	FILES
00063	Implicit intent(view a web page, make a phone call, etc.)	control	Ab/C1420h.java D8/a.java E2/C1746a.java E2/n.java Hc/h.java K0/F.java Sb/p.java Vb/S0.java b3/C3345a.java com/dexterous/flutterlocalnotifications/FlutterLocalNotificationsPlugin.java com/stripe/android/financialconnections/FinancialConnectionsSheetActivity.java com/stripe/android/financialconnections/FinancialConnectionsSheetRedirectActivity.java com/stripe/android/financialconnections/e.java com/stripe/android/financialconnections/lite/FinancialConnectionsSheetLiteActivity.java com/stripe/android/financialconnections/ui/FinancialConnectionsSheetNativeActivity.java com/stripe/android/link/LinkForegroundActivity.java com/stripe/android/payments/a.java com/stripe/android/view/j.java h3/C4137a.java v/b.java v4/e.java z6/C5987c.java
00013	Read file and put it into a stream	file	A1/k.java S6/p.java V3/i.java com/bumptech/glide/load/a.java com/dexterous/flutterlocalnotifications/FlutterLocalNotificationsPlugin.java i2/n.java i3/C4228a.java q3/C4986f.java r2/C5046a.java u7/C5416a.java v6/C5504c.java w1/C5592d.java

RULE ID	BEHAVIOUR	LABEL	FILES
00036	Get resource file from res/raw directory	reflection	b3/C3345a.java com/dexterous/flutterlocalnotifications/FlutterLocalNotificationsPlugin.java com/stripe/android/financialconnections/lite/a.java h3/C4137a.java q/P.java v4/e.java z6/C5987c.java
00109	Connect to a URL and get the response code	network command	Ca/k.java Y3/d.java com/bumptech/glide/load/data/j.java com/stripe/android/stripe3ds2/transaction/r.java q4/f.java w6/C5627c.java
00022	Open a file from given absolute path of the file	file	Fc/i.java U3/d.java i2/o.java i2/p.java i2/v.java kc/C4517f.java
00012	Read data and put it into a buffer stream	file	r2/C5046a.java
00175	Get notification manager and cancel notifications	notification	w1/o.java
00053	Monitor data identified by a given content URI changes(SMS, MMS, etc.)	sms	b3/C3345a.java
00173	Get bounds in screen of an AccessibilityNodeInfo and perform action	accessibility service	K1/j.java io/flutter/view/AccessibilityViewEmbedder.java
00125	Check if the given file path exist	file	kc/C4517f.java

RULE ID	BEHAVIOUR	LABEL	FILES
00051	Implicit intent(view a web page, make a phone call, etc.) via setData	control	D8/a.java E2/C1746a.java Hc/h.java Sb/p.java com/stripe/android/financialconnections/FinancialConnectionsSheetRedirectActivity.java com/stripe/android/link/LinkForegroundActivity.java com/stripe/android/payments/a.java h3/C4137a.java v4/e.java z6/C5987c.java
00079	Hide the current app's icon	evasion	j/AbstractC4330e.java
00096	Connect to a URL and set request method	command network	Y3/d.java com/stripe/android/stripe3ds2/transaction/r.java o8/InterfaceC4793o.java w6/C5627c.java
00147	Get the time of current location	collection location	j/s.java
00075	Get location of the device	collection location	j/s.java
00115	Get last known location of the device	collection location	j/s.java
00014	Read file into a stream and put it into a JSON object	file	S6/p.java v6/C5504c.java
00161	Perform accessibility service action on accessibility node info	accessibility service	io/flutter/view/AccessibilityViewEmbedder.java io/flutter/view/c.java
00089	Connect to a URL and receive input stream from the server	command network	Y3/d.java com/bumptech/glide/load/data/j.java com/stripe/android/stripe3ds2/transaction/r.java w6/C5627c.java

RULE ID	BEHAVIOUR	LABEL	FILES
00030	Connect to the remote server through the given URL	network	com/bumptechnology/load/data/j.java com/stripe/android/stripe3ds2/transaction/r.java
00077	Read sensitive data(SMS, CALLLOG, etc)	collection sms calllog calendar	l3/C4529c.java
00091	Retrieve data from broadcast	collection	com/stripe/android/link/LinkForegroundActivity.java
00191	Get messages in the SMS inbox	sms	q/P.java

FIREBASE DATABASES ANALYSIS

TITLE	SEVERITY	DESCRIPTION
Firebase Remote Config disabled	secure	Firebase Remote Config is disabled for https://firebaseremoteconfig.googleapis.com/v1/projects/219871201593/namespaces/firebase:fetch?key=AlzaSyAPk0X5DeMHab4ZJ4SluCd7Mv50EsU-gXM. This is indicated by the response: {'state': 'NO_TEMPLATE'}

ABUSED PERMISSIONS

TYPE	MATCHES	PERMISSIONS
Malware Permissions	7/25	android.permission.INTERNET, android.permission.ACCESS_FINE_LOCATION, android.permission.ACCESS_COARSE_LOCATION, android.permission.RECEIVE_BOOT_COMPLETED, android.permission.VIBRATE, android.permission.ACCESS_NETWORK_STATE, android.permission.WAKE_LOCK
Other Common Permissions	1/44	com.google.android.c2dm.permission.RECEIVE

Malware Permissions:

Top permissions that are widely abused by known malware.

Other Common Permissions:

Permissions that are commonly abused by known malware.

! OFAC SANCTIONED COUNTRIES

This app may communicate with the following OFAC sanctioned list of countries.

DOMAIN	COUNTRY/REGION
--------	----------------

🔍 DOMAIN MALWARE CHECK

DOMAIN	STATUS	GEOLOCATION
docs.stripe.com	ok	IP: 54.64.207.232 Country: Japan Region: Tokyo City: Tokyo Latitude: 35.689507 Longitude: 139.691696 View: Google Map
firebase.google.com	ok	IP: 142.251.42.206 Country: United States of America Region: California City: Mountain View Latitude: 37.405991 Longitude: -122.078514 View: Google Map

DOMAIN	STATUS	GEOLOCATION
api.stripe.com	ok	IP: 52.196.53.105 Country: Japan Region: Tokyo City: Tokyo Latitude: 35.689507 Longitude: 139.691696 View: Google Map
twitter.com	ok	IP: 172.66.0.227 Country: United States of America Region: California City: San Francisco Latitude: 37.775700 Longitude: -122.395203 View: Google Map
accounts.google.com	ok	IP: 173.194.174.84 Country: United States of America Region: California City: Mountain View Latitude: 37.405991 Longitude: -122.078514 View: Google Map
m.stripe.com	ok	IP: 52.34.24.17 Country: United States of America Region: Oregon City: Portland Latitude: 45.523449 Longitude: -122.676208 View: Google Map

DOMAIN	STATUS	GEOLOCATION
errors.stripe.com	ok	IP: 198.202.176.161 Country: United States of America Region: New York City: New York City Latitude: 40.797550 Longitude: -73.946190 View: Google Map
issuetracker.google.com	ok	IP: 142.250.196.110 Country: United States of America Region: California City: Mountain View Latitude: 37.405991 Longitude: -122.078514 View: Google Map
r.stripe.com	ok	IP: 54.187.119.242 Country: United States of America Region: Oregon City: Portland Latitude: 45.523449 Longitude: -122.676208 View: Google Map
static.afterpay.com	ok	IP: 104.19.176.211 Country: United States of America Region: California City: San Francisco Latitude: 37.775700 Longitude: -122.395203 View: Google Map

DOMAIN	STATUS	GEOLOCATION
merchant-ui-api.stripe.com	ok	IP: 13.113.237.213 Country: Japan Region: Tokyo City: Tokyo Latitude: 35.689507 Longitude: 139.691696 View: Google Map
link.co	ok	IP: 3.173.219.109 Country: United States of America Region: Washington City: Seattle Latitude: 47.627499 Longitude: -122.346199 View: Google Map
github.com	ok	IP: 20.27.177.113 Country: United States of America Region: Washington City: Redmond Latitude: 47.682899 Longitude: -122.120903 View: Google Map
support.google.com	ok	IP: 142.250.196.110 Country: United States of America Region: California City: Mountain View Latitude: 37.405991 Longitude: -122.078514 View: Google Map
schemas.android.com	ok	No Geolocation information available.

DOMAIN	STATUS	GEOLOCATION
developer.android.com	ok	IP: 142.251.42.174 Country: United States of America Region: California City: Mountain View Latitude: 37.405991 Longitude: -122.078514 View: Google Map
q.stripe.com	ok	IP: 54.187.159.182 Country: United States of America Region: Oregon City: Portland Latitude: 45.523449 Longitude: -122.676208 View: Google Map
ns.adobe.com	ok	No Geolocation information available.
youtrack.jetbrains.com	ok	IP: 63.35.30.167 Country: Ireland Region: Dublin City: Dublin Latitude: 53.343990 Longitude: -6.267190 View: Google Map
plus.google.com	ok	IP: 172.217.175.238 Country: Japan Region: Tokyo City: Tokyo Latitude: 35.689507 Longitude: 139.691696 View: Google Map

DOMAIN	STATUS	GEOLOCATION
dartbug.com	ok	IP: 216.239.34.21 Country: United States of America Region: California City: Mountain View Latitude: 37.405991 Longitude: -122.078514 View: Google Map
support.link.co	ok	IP: 18.64.122.21 Country: United States of America Region: Washington City: Seattle Latitude: 47.627499 Longitude: -122.346199 View: Google Map
support.stripe.com	ok	IP: 198.202.176.111 Country: United States of America Region: New York City: New York City Latitude: 40.797550 Longitude: -73.946190 View: Google Map
www.w3.org	ok	IP: 104.18.23.19 Country: United States of America Region: California City: San Francisco Latitude: 37.775700 Longitude: -122.395203 View: Google Map

DOMAIN	STATUS	GEOLOCATION
stripe.com	ok	IP: 54.64.207.232 Country: Japan Region: Tokyo City: Tokyo Latitude: 35.689507 Longitude: 139.691696 View: Google Map
goo.gle	ok	IP: 67.199.248.13 Country: United States of America Region: New York City: New York City Latitude: 40.739288 Longitude: -73.984955 View: Google Map
hooks.stripe.com	ok	IP: 13.113.237.213 Country: Japan Region: Tokyo City: Tokyo Latitude: 35.689507 Longitude: 139.691696 View: Google Map
checkout.link.com	ok	IP: 199.232.148.176 Country: United States of America Region: California City: San Francisco Latitude: 37.775700 Longitude: -122.395203 View: Google Map

DOMAIN	STATUS	GEOLOCATION
developers.google.com	ok	IP: 172.217.175.46 Country: Japan Region: Tokyo City: Tokyo Latitude: 35.689507 Longitude: 139.691696 View: Google Map
console.firebase.google.com	ok	IP: 142.251.42.174 Country: United States of America Region: California City: Mountain View Latitude: 37.405991 Longitude: -122.078514 View: Google Map
docs.flutter.dev	ok	IP: 199.36.158.100 Country: United States of America Region: California City: Mountain View Latitude: 37.405991 Longitude: -122.078514 View: Google Map
link.com	ok	IP: 3.115.61.96 Country: Japan Region: Tokyo City: Tokyo Latitude: 35.689507 Longitude: 139.691696 View: Google Map

DOMAIN	STATUS	GEOLOCATION
www.unicode.org	ok	IP: 64.182.27.164 Country: United States of America Region: Texas City: Dallas Latitude: 32.814899 Longitude: -96.879204 View: Google Map

EMAILS

EMAIL	FILE
support@stripe.com	i8/C4288a.java
support@stripe.com	o8/C4791m.java
e.android.stripe3ds2@21.19	ob/b.java
support@stripe.com	j8/C4437l.java
u0013android@android.com u0013android@android.com0	v4/r.java
email@email.com	S9/C2663a.java
support@stripe.com	Android String Resource
appro@openssl.org	lib/arm64-v8a/libflutter.so
appro@openssl.org	apktool_out/lib/arm64-v8a/libflutter.so

HARDCODED SECRETS

POSSIBLE SECRETS

"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Parol"

"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "□□"

"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL" : "■■■■■■■■■■"

"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL" : "□□□□"

"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL" : "Passnøkkel"

"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL" : "ກະແຈຜ່າງ"

"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Palavra-passe"

"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Passwort"

"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Senha"

"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL" : "■■■■■■■■■■"

"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Fjalëkalimi"

"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL" : "■■■■■■■■■■"

"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Contrasenya"

"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Geslo"

"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Heslo"

"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Wachtwoord"

POSSIBLE SECRETS
"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL" : "Sarbide-gakoa"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "■■■■■■■■■"
"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL" : "■ □ ■■■■ □ ■ □ ■■■"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Lozinka"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Parool"
"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL" : "■■■■■"
"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL" : "□□□□"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Zaporka"
"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL" : "Aðgangskyll"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Password"
"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL" : "Pääsuvõti"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "■■■■■■■"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Jelszó"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Pasahitza"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Şifre"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Adgangskode"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "■■■■■■■■■■■■■■■"

POSSIBLE SECRETS
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Парола"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Iphasiwedi"
"stripe_failure_reason_authentication" : "□□□□□□□□□□□□□□□□□□□□"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "□□□□"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "■ ■ ■ ■ ■ ■ ■ ■"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "პაროლი"
"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL" : "■ ■ ■ ■ ■ ■"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "■ ■ ■ ■ ■ ■ ■ ■ ■ ■"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "■ ■ ■ ■ ■ ■ ■ ■"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Сырсөз"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Password"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Hasło"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Aðgangsorð"
"stripe_failure_reason_authentication" : "□□□□□□□□□□□□□□□□□□□□"
"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL" : "□□□"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "■ ■ ■ ■ ■ ■ ■ ■ ■ ■ ■ ■ ■ ■"
"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL" : "Toegangssleutel"

POSSIBLE SECRETS
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "סיסמה"
"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL" : "■■■■■■■■■"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "■■■■■■■■■■■"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "■■■■■■■■■■■"
"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL" : "Azonosítókulcs"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Salasana"
"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL" : "■■■■■■■■■■■"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "■■■■■■■□■□"
"google_api_key" : "AlzaSyAPk0X5DeMHab4ZJ4SluCd7Mv50EsU-gXM"
"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL" : "■■■■■■■"
"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL" : "Klucz"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "□□"
"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL" : "گذرکلید"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Passord"
"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL" : "Passkey"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "■■■■■■■■■■■"
"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL" : "□□□□"

POSSIBLE SECRETS
"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL" : "Wagwoordsleutel"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "■■■■■■■■■■"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Գաղտնաբառ"
"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL" : "Nyckel"
"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL" : "Passkey"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "گذرواژه"
"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL" : "■■■■■"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Parolă"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Nenosiri"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Parole"
"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL" : "■■■■■.■■"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "■■■■■■■■"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Slaptažodis"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Wagwoord"
"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL" : "■■■■■"
"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL" : "Avainkoodi"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Contrasinal"

POSSIBLE SECRETS

```
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "ລະຫັດຜ່ານ"
```

```
"android.credentials.TYPE_PASSWORD_CREDENTIAL": "Лозинка"
```

```
"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL": "██████"
```

```
"android.credentials.TYPE_PASSWORD_CREDENTIAL": "■■■■■■■■"
```

```
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Contraseña"
```

[illegible]

```
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Пароль"
```

```
"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL" : "Adgangsnøgle"
```

```
"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL": "000"
```

```
"google_crash_reporting_api_key": "AlzaSyAPk0X5DeMHab4ZJ4SluCd7Mv50EsU-gXM"
```

```
"android.credentials.TYPE_PASSWORD_CREDENTIAL": "000000"
```

```
"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL": "████████"
```

```
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Lösenord"
```

```
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Sandi"
```

115792089237316195423570985008687907852837564279074904382605163141518161494337

36134250956749795798585127919587881956611106672985015071877198253568414405109

8325710961489029985546751289520108179287853048861315594709205902480503199884419224438643760392947333078086511627871

POSSIBLE SECRETS
3757180025770020463545507224491183603594455134769762486694567779615544477440556316691234405012945539562144444537289428522585666729196580810124344277578376784
VGhpcyBpcyB0aGUgcHJlZml4IGZvciBCaWdJbnRlZ2Vy
32670510020758816978083085130507043184471273380659243275938904335757337482424
115792089210356248762697446949407573530086143415290314195533631308867097853951
115792089210356248762697446949407573530086143415290314195533631308867097853948
1093849038073734274511112390766805569936207598951683748994586394495953116150735016013708737573759623248592132296706313309438452531591012912142327488478985984
26247035095799689268623156744566981891852923491109213387815615900925518854738050089022388053975719786650872476732087
39402006196394479212279040100143613805079739270465446667948293404245721771496870329047266088258938001861606973112316
55066263022277343669578718895168534326250603453777594175500187360389116729240
115792089237316195423570985008687907853269984665640564039457584007908834671663
48439561293906451759052585252797914202762949526041747995844080717082404635286
39402006196394479212279040100143613805079739270465446667948293404245721771496870329047266088258938001861606973112319
41058363725152142129326129780047268409114441015993725554835256314039467401291
dcb428fea25c40e7b99f81ae5981ee6a
6864797660130609714981900799081393217269435300143305409394463459185543183397656052122559640661454554977296311391480858037121987999716643812574028291115057148
6864797660130609714981900799081393217269435300143305409394463459185543183397656052122559640661454554977296311391480858037121987999716643812574028291115057151

POSSIBLE SECRETS
27580193559959705877849011840389048093056905856361568521428707301988689241309860865136260764883745107765439761230575
39402006196394479212279040100143613805079739270465446667946905279627659399113263569398956308152294913554433653942643
115792089210356248762697446949407573529996955224135760342422259061068512044369
6864797660130609714981900799081393217269435300143305409394463459185543183397655394245057746333217197532963996371363321113864768612440380340372808892707005449
deca87e736574c5c83c07314051fd93a
2661740802050217063228768716723360960729859168756973147706671368418802944996427808491545080627771902352094241225065558662157113545570916814161637315895999846

SCAN LOGS

Timestamp	Event	Error
2025-10-26 07:38:29	Generating Hashes	OK
2025-10-26 07:38:29	Extracting APK	OK
2025-10-26 07:38:29	Unzipping	OK
2025-10-26 07:38:29	Parsing APK with androguard	OK
2025-10-26 07:38:29	Extracting APK features using aapt/aapt2	OK

2025-10-26 07:38:29	Getting Hardcoded Certificates/Keystores	OK
2025-10-26 07:38:32	Parsing AndroidManifest.xml	OK
2025-10-26 07:38:32	Extracting Manifest Data	OK
2025-10-26 07:38:32	Manifest Analysis Started	OK
2025-10-26 07:38:32	Reading Network Security config from network_security_config.xml	OK
2025-10-26 07:38:32	Parsing Network Security config	OK
2025-10-26 07:38:32	Performing Static Analysis on: testingapp (com.enoconan.testingappv2)	OK
2025-10-26 07:38:33	Fetching Details from Play Store: com.enoconan.testingappv2	OK
2025-10-26 07:38:33	Checking for Malware Permissions	OK
2025-10-26 07:38:33	Fetching icon path	OK
2025-10-26 07:38:33	Library Binary Analysis Started	OK

2025-10-26 07:38:33	Analyzing lib/arm64-v8a/libflutter.so	OK
2025-10-26 07:38:33	Analyzing lib/arm64-v8a/libapp.so	OK
2025-10-26 07:38:33	Analyzing lib/arm64-v8a/libdatastore_shared_counter.so	OK
2025-10-26 07:38:33	Analyzing lib/arm64-v8a/libandroidx.graphics.path.so	OK
2025-10-26 07:38:33	Analyzing apktool_out/lib/arm64-v8a/libflutter.so	OK
2025-10-26 07:38:33	Analyzing apktool_out/lib/arm64-v8a/libapp.so	OK
2025-10-26 07:38:33	Analyzing apktool_out/lib/arm64-v8a/libdatastore_shared_counter.so	OK
2025-10-26 07:38:33	Analyzing apktool_out/lib/arm64-v8a/libandroidx.graphics.path.so	OK
2025-10-26 07:38:33	Reading Code Signing Certificate	OK
2025-10-26 07:38:34	Running APKiD 3.0.0	OK
2025-10-26 07:38:36	Detecting Trackers	OK
2025-10-26 07:38:38	Decompiling APK to Java with JADX	OK

2025-10-26 07:38:54	Converting DEX to Smali	OK
2025-10-26 07:38:54	Code Analysis Started on - java_source	OK
2025-10-26 07:38:57	Android SBOM Analysis Completed	OK
2025-10-26 07:39:04	Android SAST Completed	OK
2025-10-26 07:39:04	Android API Analysis Started	OK
2025-10-26 07:39:09	Android API Analysis Completed	OK
2025-10-26 07:39:09	Android Permission Mapping Started	OK
2025-10-26 07:39:14	Android Permission Mapping Completed	OK
2025-10-26 07:39:14	Android Behaviour Analysis Started	OK
2025-10-26 07:39:21	Android Behaviour Analysis Completed	OK
2025-10-26 07:39:21	Extracting Emails and URLs from Source Code	OK
2025-10-26 07:39:24	Email and URL Extraction Completed	OK

2025-10-26 07:39:24	Extracting String data from APK	OK
2025-10-26 07:39:24	Extracting String data from SO	OK
2025-10-26 07:39:24	Extracting String data from Code	OK
2025-10-26 07:39:24	Extracting String values and entropies from Code	OK
2025-10-26 07:39:26	Performing Malware check on extracted domains	OK
2025-10-26 07:39:30	Saving to Database	OK

Report Generated by - MobSF v4.4.3

Mobile Security Framework (MobSF) is an automated, all-in-one mobile application (Android/iOS/Windows) pen-testing, malware analysis and security assessment framework capable of performing static and dynamic analysis.

© 2025 Mobile Security Framework - MobSF | [Ajin Abraham](#) | [OpenSecurity](#).