




ANDROID STATIC ANALYSIS REPORT



 testingapp (1.0.2)

File Name:

app-arm64-v8a-release.apk

Package Name:

com.enoconan.testingappv2


Scan Date:

Oct. 26, 2025, 6:36 a.m.

App Security Score:

55/100 (MEDIUM RISK)

Grade:



 HIGH	 MEDIUM	 INFO	 SECURE	 HOTSPOT
2	17	3	3	2

FILE INFORMATION

File Name: app-arm64-v8a-release.apk
Size: 56.23MB
MD5: 9e41074ece341dcf0ef85b7b89792b16
SHA1: c4a99e7ed7ecc58049f03d26a37673feffbac306b
SHA256: 2509eae31ca6d532dfbcfd57061e38b44af057057f95f8faeb8c5122affba34f

APP INFORMATION

App Name: testingapp
Package Name: com.enoconan.testingappv2
Main Activity: com.enoconan.testingappv2.MainActivity
Target SDK: 36
Min SDK: 24
Max SDK:
Android Version Name: 1.0.2
Android Version Code: 4001

APP COMPONENTS

Activities: 39
Services: 10
Receivers: 6
Providers: 3
Exported Activities: 4
Exported Services: 1

Exported Receivers: 3
Exported Providers: 0

CERTIFICATE INFORMATION

Binary is signed
v1 signature: False
v2 signature: True
v3 signature: False
v4 signature: False
X.509 Subject: C=JP, CN=Kota
Signature Algorithm: rsassa_pkcs1v15
Valid From: 2025-01-31 10:47:53+00:00
Valid To: 2052-06-18 10:47:53+00:00
Issuer: C=JP, CN=Kota
Serial Number: 0xb202639cc17edfdf
Hash Algorithm: sha384
md5: bd6e9df50161da7c4153f7834d6f7850
sha1: 96d7375b723d441ab6f1cb4b2d22dbd5fdc9cbd6
sha256: 43f2cf97ef1e303d86354469f8cfbdf9ed152c3ebd45f334fae058e09b76ffd1
sha512: 099e87bdbb1a7b41605a5a35ed69eeea3e91876ab7a3375bcd1cab0dca4de9e8d24e0198377d6270c9a92b5a2c4fa3f3532112ae4910c07030e8c380610aa203
PublicKey Algorithm: rsa
Bit Size: 2048
Fingerprint: 098587b2d841fad7d5cda571d5bcd6cebdef271f46b192113970a6685f456d69
Found 1 unique certificates

APPLICATION PERMISSIONS

PERMISSION	STATUS	INFO	DESCRIPTION
android.permission.INTERNET	normal	full Internet access	Allows an application to create network sockets.
android.permission.WRITE_SETTINGS	dangerous	modify global system settings	Allows an application to modify the system's settings data. Malicious applications can corrupt your system's configuration.

PERMISSION	STATUS	INFO	DESCRIPTION
android.permission.USE_BIOMETRIC	normal	allows use of device-supported biometric modalities.	Allows an app to use device supported biometric modalities.
android.permission.ACCESS_FINE_LOCATION	dangerous	fine (GPS) location	Access fine location sources, such as the Global Positioning System on the phone, where available. Malicious applications can use this to determine where you are and may consume additional battery power.
android.permission.ACCESS_COARSE_LOCATION	dangerous	coarse (network-based) location	Access coarse location sources, such as the mobile network database, to determine an approximate phone location, where available. Malicious applications can use this to determine approximately where you are.
android.permission.POST_NOTIFICATIONS	dangerous	allows an app to post notifications.	Allows an app to post notifications
android.permission.RECEIVE_BOOT_COMPLETED	normal	automatically start at boot	Allows an application to start itself as soon as the system has finished booting. This can make it take longer to start the phone and allow the application to slow down the overall phone by always running.
android.permission.VIBRATE	normal	control vibrator	Allows the application to control the vibrator.
android.permission.ACCESS_NETWORK_STATE	normal	view network status	Allows an application to view the status of all networks.
android.permission.USE_FINGERPRINT	normal	allow use of fingerprint	This constant was deprecated in API level 28. Applications should request USE_BIOMETRIC instead.
android.permission.WAKE_LOCK	normal	prevent phone from sleeping	Allows an application to prevent the phone from going to sleep.

PERMISSION	STATUS	INFO	DESCRIPTION
com.google.android.c2dm.permission.RECEIVE	normal	recieve push notifications	Allows an application to receive push notifications from cloud.
com.enoconan.testingappv2.DYNAMIC_RECEIVER_NOT_EXPORTED_PERMISSION	unknown	Unknown permission	Unknown permission from android reference

 APKID ANALYSIS

FILE	DETAILS	
classes.dex	FINDINGS	DETAILS
	Anti-VM Code	Build.FINGERPRINT check Build.MANUFACTURER check
	Compiler	r8
classes2.dex	FINDINGS	DETAILS
	Compiler	r8

FILE	DETAILS	
classes3.dex	FINDINGS	DETAILS
	Anti-VM Code	Build.FINGERPRINT check Build.MODEL check Build.MANUFACTURER check Build.PRODUCT check Build.TAGS check
	Anti Debug Code	Debug.isDebuggerConnected() check
	Compiler	r8
classes4.dex	FINDINGS	DETAILS
	Compiler	r8

BROWSABLE ACTIVITIES

ACTIVITY	INTENT
com.enoconan.testingappv2.MainActivity	Schemes: http://, https://, Hosts: local.com, testing-app-4bc40.web.app, Path Prefixes: /register,

ACTIVITY	INTENT
com.stripe.android.financialconnections.FinancialConnectionsSheetRedirectActivity	Schemes: stripe-auth://, stripe://, Hosts: link-accounts, link-native-accounts, native-redirect, auth-redirect, Paths: /com.enoconan.testingappv2/success, /com.enoconan.testingappv2/cancel, Path Prefixes: /com.enoconan.testingappv2/authentication_return, /com.enoconan.testingappv2,
com.stripe.android.link.LinkRedirectHandlerActivity	Schemes: link-popup://, Hosts: complete, Paths: /com.enoconan.testingappv2,
com.stripe.android.payments.StripeBrowserProxyReturnActivity	Schemes: stripesdk://, Hosts: payment_return_url, Paths: /com.enoconan.testingappv2,
com.stripe.android.financialconnections.lite.FinancialConnectionsSheetLiteRedirectActivity	Schemes: stripe://, Hosts: financial-connections-lite, Path Prefixes: /com.enoconan.testingappv2/auth_redirect,

 NETWORK SECURITY

NO	SCOPE	SEVERITY	DESCRIPTION
----	-------	----------	-------------

 CERTIFICATE ANALYSIS

HIGH: 0 | WARNING: 0 | INFO: 1

TITLE	SEVERITY	DESCRIPTION
Signed Application	info	Application is signed with a code signing certificate

Q MANIFEST ANALYSIS

HIGH: 2 | WARNING: 9 | INFO: 0 | SUPPRESSED: 0

NO	ISSUE	SEVERITY	DESCRIPTION
1	App can be installed on a vulnerable unpatched Android version Android 7.0, [minSdk=24]	high	This application can be installed on an older version of android that has multiple unfixed vulnerabilities. These devices won't receive reasonable security updates from Google. Support an Android version => 10, API 29 to receive reasonable security updates.
2	Application Data can be Backed up [android:allowBackup] flag is missing.	warning	The flag [android:allowBackup] should be set to false. By default it is set to true and allows anyone to backup your application data via adb. It allows users who have enabled USB debugging to copy application data off of the device.
3	App Link assetlinks.json file not found [android:name=com.enoconan.testingappv2.MainActivity] [android:host=http://local.com]	high	App Link asset verification URL (http://local.com/.well-known/assetlinks.json) not found or configured incorrectly. (Status Code: 301). App Links allow users to redirect from a web URL/email to the mobile app. If this file is missing or incorrectly configured for the App Link host/domain, a malicious app can hijack such URLs. This may lead to phishing attacks, leak sensitive data in the URI, such as PII, OAuth tokens, magic link/password reset tokens and more. You must verify the App Link domain by hosting the assetlinks.json file and enabling verification via [android:autoVerify="true"] in the Activity intent-filter.
4	Activity (com.stripe.android.financialconnections.FinancialConnectionsSheetRedirectActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
5	Activity (com.stripe.android.link.LinkRedirectHandlerActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.

NO	ISSUE	SEVERITY	DESCRIPTION
6	Activity (com.stripe.android.payments.StripeBrowserProxyReturnActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
7	Activity (com.stripe.android.financialconnections.lite.FinancialConnectionsSheetLiteRedirectActivity) is not Protected. [android:exported=true]	warning	An Activity is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device.
8	Broadcast Receiver (io.flutter.plugins.firebase.messaging.FlutterFirebaseMessagingReceiver) is Protected by a permission, but the protection level of the permission should be checked. Permission: com.google.android.c2dm.permission.SEND [android:exported=true]	warning	A Broadcast Receiver is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. It is protected by a permission which is not defined in the analysed application. As a result, the protection level of the permission should be checked where it is defined. If it is set to normal or dangerous, a malicious application can request and obtain the permission and interact with the component. If it is set to signature, only applications signed with the same certificate can obtain the permission.
9	Service (com.google.android.gms.auth.api.signin.RevocationBoundService) is Protected by a permission, but the protection level of the permission should be checked. Permission: com.google.android.gms.auth.api.signin.permission.REVOCATION_NOTIFICATION [android:exported=true]	warning	A Service is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. It is protected by a permission which is not defined in the analysed application. As a result, the protection level of the permission should be checked where it is defined. If it is set to normal or dangerous, a malicious application can request and obtain the permission and interact with the component. If it is set to signature, only applications signed with the same certificate can obtain the permission.
10	Broadcast Receiver (com.google.firebase.iid.FirebaseInstanceIdReceiver) is Protected by a permission, but the protection level of the permission should be checked. Permission: com.google.android.c2dm.permission.SEND [android:exported=true]	warning	A Broadcast Receiver is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. It is protected by a permission which is not defined in the analysed application. As a result, the protection level of the permission should be checked where it is defined. If it is set to normal or dangerous, a malicious application can request and obtain the permission and interact with the component. If it is set to signature, only applications signed with the same certificate can obtain the permission.

NO	ISSUE	SEVERITY	DESCRIPTION
11	Broadcast Receiver (androidx.profileinstaller.ProfileInstallReceiver) is Protected by a permission, but the protection level of the permission should be checked. Permission: android.permission.DUMP [android:exported=true]	warning	A Broadcast Receiver is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. It is protected by a permission which is not defined in the analysed application. As a result, the protection level of the permission should be checked where it is defined. If it is set to normal or dangerous, a malicious application can request and obtain the permission and interact with the component. If it is set to signature, only applications signed with the same certificate can obtain the permission.

</> CODE ANALYSIS

HIGH: 0 | WARNING: 7 | INFO: 3 | SECURE: 1 | SUPPRESSED: 0

NO	ISSUE	SEVERITY	STANDARDS	FILES
				A1/c.java A1/d.java A1/h.java A3/e.java A3/f.java A3/o.java A3/p.java A3/r.java A3/s.java A6/AbstractServiceC1393h.java A6/C1389d.java A6/C1390e.java A6/C1398m.java A6/C1401p.java A6/G.java A6/I.java A6/K.java A6/N.java A6/U.java A6/W.java A6/X.java A6/Y.java A6/h0 iava

NO	ISSUE	SEVERITY	STANDARDS	FILES
				A6/c0.java A6/g0.java A6/j0.java B1/d.java B1/i.java B1/j.java B1/k.java B1/m.java B1/o.java B3/d.java Bb/A1.java Bc/C1530a.java Bc/e.java C2/b.java C4/a.java D2/c.java D3/h.java D4/a.java D6/e.java E3/d.java E3/j.java E4/f.java E4/n.java E4/o.java Ec/C1710i.java Ec/C1714k.java Ec/W0.java F2/C1767a.java F2/n.java G1/g.java G1/k.java Gc/i.java H1/d.java H4/h.java Hc/C1899a.java Hc/F.java Hc/J.java I3/a.java I4/d.java I6/c.java Ic/i.java K0/N.java K1/AbstractC2155b.java K1/C2170q.java K1/K.java

NO	ISSUE	SEVERITY	STANDARDS	FILES
				K1/N.java K1/T.java K1/f0.java L1/q.java L4/r.java N1/e.java N2/a.java O1/i.java O2/C.java O2/C2482e.java O5/d.java P/V.java P1/p.java P1/x.java P5/b.java Q7/C2577l.java Q7/M.java Q7/Y.java Q7/d0.java Q7/l0.java Qb/c.java R5/g.java R7/d.java R8/f.java S6/h.java S7/c.java T2/a.java T2/e.java T6/e.java T6/l.java T7/g.java T7/i.java U3/a.java U6/a.java U6/c.java U7/k.java W2/f.java W2/o.java X1/b.java X6/B.java X6/C2973g.java X6/D.java X6/F.java X6/k.java X6/x.java Y1/a.java

NO	ISSUE	SEVERITY	STANDARDS	FILES
1	The App logs information. Sensitive information should never be logged.	info	CWE: CWE-532: Insertion of Sensitive Information into Log File OWASP MASVS: MSTG-STORAGE-3	Z/C3014b.java Z1/a.java Z1/b.java Z1/k.java Z6/c.java Z6/f.java Zb/B.java Zb/D.java Zb/i.java a1/C3133a.java b2/C3332c.java b3/C3341a.java b5/w.java b6/O.java c2/C3442a.java c4/k.java c6/f.java com/baseflow/geolocator/GeolocatorLocationService.java com/bumptech/glide/b.java com/bumptech/glide/load/data/b.java com/bumptech/glide/load/data/j.java com/bumptech/glide/load/data/l.java com/dexterous/flutterlocalnotifications/ActionBroadcastReceiver.java com/dexterous/flutterlocalnotifications/FlutterLocalNotificationsPlugin.java com/dexterous/flutterlocalnotifications/ScheduledNotificationReceiver.java com/stripe/android/stripe3ds2/transaction/o.java com/stripe/hcaptcha/webview/HcaptchaWebView.java d5/e.java e3/C3878c.java e3/k.java e3/n.java e5/F.java f4/C3996a.java f5/C4004e.java g3/l.java gc/C4139b.java h2/C4154c.java h3/C4156b.java h5/C4168a.java h6/C4179f.java h6/n.iava

NO	ISSUE	SEVERITY	STANDARDS	FILES
				h8/InterfaceC4189d.java 5/c4274a.java io/flutter/plugins/firebase/messaging/FlutterFirebaseMessagingBackgroundService.java io/flutter/plugins/firebase/messaging/FlutterFirebaseMessagingReceiver.java io/flutter/plugins/firebase/messaging/a.java j/AbstractC4324e.java j/LayoutInflaterFactory2C4326g.java j/o.java j/s.java j/v.java j3/C4378a.java j6/C4435c.java k3/d.java k3/e.java k5/C4507b.java k5/P.java l5/f.java m0/f.java m0/j.java m1/d.java m3/C4655c.java m3/C4657e.java n3/h.java n3/i.java n3/k.java n3/q.java n3/z.java o/g.java o3/i.java o3/j.java p/MenuItemC4845c.java p1/C4866f.java p3/C4885e.java p3/C4889i.java q/B.java q/C4976v.java q/C4979y.java q/N.java q/P.java q/Q.java q/U.java q/V.java q/h0.java

NO	ISSUE	SEVERITY	STANDARDS	FILES
				q10.java q10.o.java q1/C5005o.java q3/ExecutorServiceC5011a.java r1/C5100a.java r3/C5108c.java r3/C5109d.java r3/C5111f.java r3/s.java r3/t.java r4/g.java r5/C5129h.java s1/j.java s2/C5235a.java s8/C5267i.java t1/C5343a.java t3/AbstractC5349b.java u2/c.java u3/C5458c.java u3/C5459d.java u3/E.java u3/G.java u3/k.java u3/r.java u3/s.java u3/w.java u6/C5467b.java v/b.java v4/AbstractC5530A.java v4/AbstractC5539b.java v4/C5533D.java v4/C5534E.java v4/C5540c.java v4/C5548k.java v4/C5562y.java v4/ServiceConnectionC5561x.java v7/C5566a.java w4/C5643d.java w4/h.java w4/i.java w4/l.java w4/s.java w4/w.java w6/C5646b.java w7/C5649a.java w7/C5650b.java

NO	ISSUE	SEVERITY	STANDARDS	x1/C5732d.java FILES x1/C5734f.java x1/l.java
				x1/n.java x1/r.java x1/z.java x6/C5767c.java y3/C5905a.java y3/C5908d.java y3/C5914j.java y4/C5923l.java y4/C5927M.java y4/C5945e.java y4/RunnableC5926L.java y4/f0.java y4/k0.java z4/AbstractC6036c.java z4/AbstractDialogInterfaceOnClickListenerC6031G.java z4/BinderC6034a.java z4/C6028D.java z4/Y.java z4/c0.java z4/d0.java z4/e0.java z4/g0.java z4/m0.java z4/o0.java
				C8/C1560b.java C8/h.java Kb/B.java L4/C2349k.java L9/b.java T/C2638b0.java T8/p.java U8/n.java Ua/U.java V7/p.java W6/b.java Y0/C2984i.java Y0/V.java Z/C3013a1.java Z/C3058u0.java Z8/l.java

NO	ISSUE	SEVERITY	STANDARDS	FILES
2	Files may contain hardcoded sensitive information like usernames, passwords, keys etc.	warning	CWE: CWE-312: Cleartext Storage of Sensitive Information OWASP Top 10: M9: Reverse Engineering OWASP MASVS: MSTG-STORAGE-14	a9/C3172l.java ca/C3492G.java ca/C3498b.java ca/C3513q.java ca/C3514s.java ca/InterfaceC3489D.java ca/X.java ca/r.java cb/C3522a.java cb/C3525d.java cb/j.java com/dexterous/flutterlocalnotifications/FlutterLocalNotificationsPlugin.java com/dexterous/flutterlocalnotifications/models/NotificationDetails.java com/stripe/android/auth/PaymentBrowserAuthContract.java com/stripe/android/customersheet/d.java com/stripe/android/financialconnections/model/FinancialConnectionsSession.java com/stripe/android/googlepaylauncher/GooglePayLauncherContract.java com/stripe/android/googlepaylauncher/GooglePaymentMethodLauncherContract.java com/stripe/android/link/j.java com/stripe/android/model/Source.java com/stripe/android/model/StripeIntent.java com/stripe/android/model/b.java com/stripe/android/model/c.java com/stripe/android/model/d.java com/stripe/android/model/j.java com/stripe/android/model/n.java com/stripe/android/model/p.java com/stripe/android/model/u.java com/stripe/android/model/x.java com/stripe/android/payments/bankaccount/navigation/CollectBankAccountContract.java com/stripe/android/payments/bankaccount/ui/a.java com/stripe/android/payments/core/authentication/treeds2/Stripe3ds2TransactionContract.java com/stripe/android/payments/paymentlauncher/PaymentLauncherContract.java com/stripe/android/paymentsheet/PaymentSheetContract.java

NO	ISSUE	SEVERITY	STANDARDS	FILES
				com/stripe/android/paymentsheet/addressesElement/ AddressesElementActivityContract.java com/stripe/android/paymentsheet/addressesElement/ d.java com/stripe/android/paymentsheet/n.java com/stripe/android/paymentsheet/paymentdatacollection/polling/PollingContract.java com/stripe/android/paymentsheet/paymentdatacollection/polling/b.java com/stripe/android/stripe3ds2/transaction/n.java hb/InterfaceC4202e.java ia/C4291h.java l3/g.java m9/C4678d.java n3/d.java n3/p.java n3/x.java p8/C4929m.java pa/C4947e.java pa/InterfaceC4948f.java sb/C5296a.java sb/c.java t9/C5403e.java v8/C5569a.java v8/C5572d.java va/C5592c.java va/C5593d.java
3	SHA-1 is a weak hash known to have hash collisions.	warning	CWE: CWE-327: Use of a Broken or Risky Cryptographic Algorithm OWASP Top 10: M5: Insufficient Cryptography OWASP MASVS: MSTG-CRYPTO-4	A6/G.java w6/C5646b.java
4	This App copies data to clipboard. Sensitive data should not be copied to clipboard as other applications can access it.	info	OWASP MASVS: MSTG-STORAGE-10	io/flutter/plugin/editing/c.java io/flutter/plugin/platform/C4308f.java
5	The App uses an insecure Random Number Generator.	warning	CWE: CWE-330: Use of Insufficiently Random Values OWASP Top 10: M5: Insufficient Cryptography OWASP MASVS: MSTG-CRYPTO-6	O6/d.java S6/s.java fd/AbstractC4100a.java fd/C4101b.java gd/C4140a.java

NO	ISSUE	SEVERITY	STANDARDS	FILES
6	App creates temp file. Sensitive information should never be written into a temp file.	warning	CWE: CWE-276: Incorrect Default Permissions OWASP Top 10: M2: Insecure Data Storage OWASP MASVS: MSTG-STORAGE-2	w6/C5647c.java
7	App uses SQLite Database and execute raw SQL query. Untrusted user input in raw SQL queries can cause SQL Injection. Also sensitive information should be encrypted and written to the database.	warning	CWE: CWE-89: Improper Neutralization of Special Elements used in an SQL Command ('SQL Injection') OWASP Top 10: M7: Client Code Quality	Zb/i.java j4/M.java j4/V.java
8	App can read/write to External Storage. Any App can read data written to External Storage.	warning	CWE: CWE-276: Incorrect Default Permissions OWASP Top 10: M2: Insecure Data Storage OWASP MASVS: MSTG-STORAGE-2	Gc/a.java Gc/i.java
9	App can write to App Directory. Sensitive Information should be encrypted.	info	CWE: CWE-276: Incorrect Default Permissions OWASP MASVS: MSTG-STORAGE-14	l2/C4600a.java
10	IP Address disclosure	warning	CWE: CWE-200: Information Exposure OWASP MASVS: MSTG-CODE-2	D7/a.java
11	This App may have root detection capabilities.	secure	OWASP MASVS: MSTG-RESILIENCE-1	b6/C3362j.java

SHARED LIBRARY BINARY ANALYSIS

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
----	---------------	----	-----	--------------	-------	-------	---------	---------	------------------

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
1	arm64-v8a/libflutter.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Not Applicable info RELRO checks are not applicable for Flutter/Dart binaries	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['_vsnprintf_chk', '__read_chk', '__memcpy_chk', '__strcpy_chk', '__strlen_chk', '__memmove_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
2	arm64-v8a/libapp.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Not Applicable info RELRO checks are not applicable for Flutter/Dart binaries	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False info The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
3	arm64-v8a/libdatastore_shared_counter.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
4	arm64-v8a/libandroidx.graphics.path.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
5	arm64-v8a/libflutter.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Not Applicable info RELRO checks are not applicable for Flutter/Dart binaries	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['_vsnprintf_chk', '_read_chk', '_memcpy_chk', '_strcpy_chk', '_strlen_chk', '_memmove_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
6	arm64-v8a/libapp.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Not Applicable info RELRO checks are not applicable for Flutter/Dart binaries	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False info The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
7	arm64-v8a/libdatastore_shared_counter.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
8	arm64-v8a/libandroidx.graphics.path.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NIAP ANALYSIS v1.3

NO	IDENTIFIER	REQUIREMENT	FEATURE	DESCRIPTION
----	------------	-------------	---------	-------------

BEHAVIOUR ANALYSIS

RULE ID	BEHAVIOUR	LABEL	FILES
00013	Read file and put it into a stream	file	B1/i.java B1/o.java T6/p.java W3/i.java com/bumptech/glide/load/a.java com/dexterous/flutterlocalnotifications/FlutterLocalNotificationsPlugin.java j2/n.java j3/C4378a.java r3/C5111f.java s2/C5235a.java v7/C5566a.java w6/C5647c.java x1/C5734f.java
00096	Connect to a URL and set request method	command network	Z3/d.java com/stripe/android/stripe3ds2/transaction/r.java p8/InterfaceC4931o.java x6/C5767c.java
00089	Connect to a URL and receive input stream from the server	command network	Z3/d.java com/bumptech/glide/load/data/j.java com/stripe/android/stripe3ds2/transaction/r.java x6/C5767c.java
00030	Connect to the remote server through the given URL	network	com/bumptech/glide/load/data/j.java com/stripe/android/stripe3ds2/transaction/r.java
00109	Connect to a URL and get the response code	network command	Da/k.java Z3/d.java com/bumptech/glide/load/data/j.java com/stripe/android/stripe3ds2/transaction/r.java r4/f.java x6/C5767c.java

RULE ID	BEHAVIOUR	LABEL	FILES
00063	Implicit intent(view a web page, make a phone call, etc.)	control	A6/C1389d.java Bb/C1474h.java E8/a.java F2/C1767a.java F2/n.java Ic/h.java L0/G.java Tb/p.java Wb/S0.java c3/C3444a.java com/dexterous/flutterlocalnotifications/FlutterLocalNotificationsPlugin.java com/stripe/android/financialconnections/FinancialConnectionsSheetActivity.java com/stripe/android/financialconnections/FinancialConnectionsSheetRedirectActivity.java com/stripe/android/financialconnections/e.java com/stripe/android/financialconnections/lite/FinancialConnectionsSheetLiteActivity.java com/stripe/android/financialconnections/ui/FinancialConnectionsSheetNativeActivity.java com/stripe/android/link/LinkForegroundActivity.java com/stripe/android/payments/a.java com/stripe/android/view/j.java i3/C4263a.java v/b.java w4/e.java
00051	Implicit intent(view a web page, make a phone call, etc.) via setData	control	A6/C1389d.java E8/a.java F2/C1767a.java Ic/h.java Tb/p.java com/stripe/android/financialconnections/FinancialConnectionsSheetRedirectActivity.java com/stripe/android/link/LinkForegroundActivity.java com/stripe/android/payments/a.java i3/C4263a.java w4/e.java
00091	Retrieve data from broadcast	collection	com/stripe/android/link/LinkForegroundActivity.java
00147	Get the time of current location	collection location	j/v.java

RULE ID	BEHAVIOUR	LABEL	FILES
00075	Get location of the device	collection location	j/v.java
00115	Get last known location of the device	collection location	j/v.java
00053	Monitor data identified by a given content URI changes(SMS, MMS, etc.)	sms	c3/C3444a.java
00036	Get resource file from res/raw directory	reflection	A6/C1389d.java c3/C3444a.java com/dexterous/flutterlocalnotifications/FlutterLocalNotificationsPlugin.java com/stripe/android/financialconnections/lite/a.java i3/C4263a.java q/U.java w4/e.java
00014	Read file into a stream and put it into a JSON object	file	T6/p.java w6/C5647c.java
00173	Get bounds in screen of an AccessibilityNodeInfo and perform action	accessibility service	L1/q.java io/flutter/view/AccessibilityViewEmbedder.java
00209	Get pixels from the latest rendered image	collection	hc/C4213i.java
00210	Copy pixels from the latest rendered image into a Bitmap	collection	hc/C4213i.java
00012	Read data and put it into a buffer stream	file	s2/C5235a.java
00077	Read sensitive data(SMS, CALLLOG, etc)	collection sms calllog calendar	m3/C4655c.java

RULE ID	BEHAVIOUR	LABEL	FILES
00022	Open a file from given absolute path of the file	file	Gc/i.java V3/d.java j2/o.java j2/p.java j2/v.java lc/C4644f.java
00191	Get messages in the SMS inbox	sms	q/U.java
00161	Perform accessibility service action on accessibility node info	accessibility service	io/flutter/view/AccessibilityViewEmbedder.java io/flutter/view/c.java
00175	Get notification manager and cancel notifications	notification	x1/r.java
00125	Check if the given file path exist	file	lc/C4644f.java
00079	Hide the current app's icon	evasion	j/AbstractC4324e.java

FIREBASE DATABASES ANALYSIS

TITLE	SEVERITY	DESCRIPTION
Firebase Remote Config disabled	secure	Firebase Remote Config is disabled for https://firebase-remoteconfig.googleapis.com/v1/projects/219871201593/namespaces/firebase:fetch?key=AlzaSyAPk0X5DeMHab4ZJ4SluCd7Mv50EsU-gXM . This is indicated by the response: {'state': 'NO_TEMPLATE'}

ABUSED PERMISSIONS

TYPE	MATCHES	PERMISSIONS
Malware Permissions	8/25	android.permission.INTERNET, android.permission.WRITE_SETTINGS, android.permission.ACCESS_FINE_LOCATION, android.permission.ACCESS_COARSE_LOCATION, android.permission.RECEIVE_BOOT_COMPLETED, android.permission.VIBRATE, android.permission.ACCESS_NETWORK_STATE, android.permission.WAKE_LOCK
Other Common Permissions	1/44	com.google.android.c2dm.permission.RECEIVE

Malware Permissions:

Top permissions that are widely abused by known malware.

Other Common Permissions:

Permissions that are commonly abused by known malware.

! OFAC SANCTIONED COUNTRIES

This app may communicate with the following OFAC sanctioned list of countries.

DOMAIN	COUNTRY/REGION
--------	----------------

DOMAIN MALWARE CHECK

DOMAIN	STATUS	GEOLOCATION
dartbug.com	ok	IP: 216.239.38.21 Country: United States of America Region: California City: Mountain View Latitude: 37.405991 Longitude: -122.078514 View: Google Map

DOMAIN	STATUS	GEOLOCATION
r.stripe.com	ok	IP: 54.186.23.98 Country: United States of America Region: Oregon City: Portland Latitude: 45.523449 Longitude: -122.676208 View: Google Map
youtrack.jetbrains.com	ok	IP: 63.35.30.167 Country: Ireland Region: Dublin City: Dublin Latitude: 53.343990 Longitude: -6.267190 View: Google Map
m.stripe.com	ok	IP: 34.210.233.131 Country: United States of America Region: Oregon City: Portland Latitude: 45.523449 Longitude: -122.676208 View: Google Map
checkout.link.com	ok	IP: 199.232.148.176 Country: United States of America Region: California City: San Francisco Latitude: 37.775700 Longitude: -122.395203 View: Google Map

DOMAIN	STATUS	GEOLOCATION
support.google.com	ok	IP: 142.250.207.46 Country: United States of America Region: California City: Mountain View Latitude: 37.405991 Longitude: -122.078514 View: Google Map
schemas.android.com	ok	No Geolocation information available.
ns.adobe.com	ok	No Geolocation information available.
accounts.google.com	ok	IP: 74.125.204.84 Country: United States of America Region: California City: Mountain View Latitude: 37.405991 Longitude: -122.078514 View: Google Map
issuetracker.google.com	ok	IP: 142.250.196.110 Country: United States of America Region: California City: Mountain View Latitude: 37.405991 Longitude: -122.078514 View: Google Map
www.w3.org	ok	IP: 104.18.23.19 Country: United States of America Region: California City: San Francisco Latitude: 37.775700 Longitude: -122.395203 View: Google Map

DOMAIN	STATUS	GEOLOCATION
plus.google.com	ok	IP: 142.250.196.110 Country: United States of America Region: California City: Mountain View Latitude: 37.405991 Longitude: -122.078514 View: Google Map
merchant-ui-api.stripe.com	ok	IP: 3.114.81.222 Country: Japan Region: Tokyo City: Tokyo Latitude: 35.689507 Longitude: 139.691696 View: Google Map
link.com	ok	IP: 3.115.110.210 Country: Japan Region: Tokyo City: Tokyo Latitude: 35.689507 Longitude: 139.691696 View: Google Map
twitter.com	ok	IP: 162.159.140.229 Country: United States of America Region: California City: San Francisco Latitude: 37.775700 Longitude: -122.395203 View: Google Map

DOMAIN	STATUS	GEOLOCATION
www.unicode.org	ok	IP: 64.182.27.164 Country: United States of America Region: Texas City: Dallas Latitude: 32.814899 Longitude: -96.879204 View: Google Map
hooks.stripe.com	ok	IP: 3.114.158.108 Country: Japan Region: Tokyo City: Tokyo Latitude: 35.689507 Longitude: 139.691696 View: Google Map
errors.stripe.com	ok	IP: 198.202.176.41 Country: United States of America Region: New York City: New York City Latitude: 40.797550 Longitude: -73.946190 View: Google Map
goo.gle	ok	IP: 67.199.248.12 Country: United States of America Region: New York City: New York City Latitude: 40.739288 Longitude: -73.984955 View: Google Map

DOMAIN	STATUS	GEOLOCATION
support.stripe.com	ok	IP: 198.202.176.41 Country: United States of America Region: New York City: New York City Latitude: 40.797550 Longitude: -73.946190 View: Google Map
developers.google.com	ok	IP: 172.217.175.46 Country: Japan Region: Tokyo City: Tokyo Latitude: 35.689507 Longitude: 139.691696 View: Google Map
link.co	ok	IP: 3.173.219.28 Country: United States of America Region: Washington City: Seattle Latitude: 47.627499 Longitude: -122.346199 View: Google Map
api.stripe.com	ok	IP: 13.230.90.110 Country: Japan Region: Tokyo City: Tokyo Latitude: 35.689507 Longitude: 139.691696 View: Google Map

DOMAIN	STATUS	GEOLOCATION
docs.flutter.dev	ok	IP: 199.36.158.100 Country: United States of America Region: California City: Mountain View Latitude: 37.405991 Longitude: -122.078514 View: Google Map
q.stripe.com	ok	IP: 54.187.119.242 Country: United States of America Region: Oregon City: Portland Latitude: 45.523449 Longitude: -122.676208 View: Google Map
stripe.com	ok	IP: 3.115.61.96 Country: Japan Region: Tokyo City: Tokyo Latitude: 35.689507 Longitude: 139.691696 View: Google Map
support.link.co	ok	IP: 18.64.122.18 Country: United States of America Region: Washington City: Seattle Latitude: 47.627499 Longitude: -122.346199 View: Google Map

DOMAIN	STATUS	GEOLOCATION
github.com	ok	IP: 20.27.177.113 Country: United States of America Region: Washington City: Redmond Latitude: 47.682899 Longitude: -122.120903 View: Google Map
console.firebase.google.com	ok	IP: 142.251.42.174 Country: United States of America Region: California City: Mountain View Latitude: 37.405991 Longitude: -122.078514 View: Google Map
developer.android.com	ok	IP: 142.251.42.174 Country: United States of America Region: California City: Mountain View Latitude: 37.405991 Longitude: -122.078514 View: Google Map
static.afterpay.com	ok	IP: 104.19.176.211 Country: United States of America Region: California City: San Francisco Latitude: 37.775700 Longitude: -122.395203 View: Google Map

DOMAIN	STATUS	GEOLOCATION
firebase.google.com	ok	IP: 142.250.196.110 Country: United States of America Region: California City: Mountain View Latitude: 37.405991 Longitude: -122.078514 View: Google Map
docs.stripe.com	ok	IP: 3.115.50.247 Country: Japan Region: Tokyo City: Tokyo Latitude: 35.689507 Longitude: 139.691696 View: Google Map

EMAILS

EMAIL	FILE
support@stripe.com	p8/C4929m.java
u0013android@android.com u0013android@android.com0	w4/r.java
e.android.stripe3ds2@21.19	pb/b.java
email@email.com	T9/C2735a.java
support@stripe.com	k8/C4551l.java
support@stripe.com	j8/C4438a.java

EMAIL	FILE
support@stripe.com	Android String Resource
appro@openssl.org	lib/arm64-v8a/libflutter.so
appro@openssl.org	apktool_out/lib/arm64-v8a/libflutter.so

HARDCODED SECRETS

POSSIBLE SECRETS
"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL" : "■■■■■■■■■■■"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "■■■■■■■■■"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "■■■■■ □□"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "□□"
"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL" : "■■■■■■■■■"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Passord"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "■■■■■■■■■"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Heslo"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Parool"
"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL" : "■ □□■■■■■ □□■■■■"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Password"

POSSIBLE SECRETS
"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL" : "■■■■■"
"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL" : "Adgangsnøgle"
"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL" : "■■■■■"
"stripe_failure_reason_authentication" : "□□□□□□□□□□□□□□□□□□□□"
"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL" : "گذرکلید"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "■■■■■■■■■■■"
"stripe_failure_reason_authentication" : "□□□□□□□□□□□□□□□□□□□□"
"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL" : "Pääsuvõti"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Парола"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Salasana"
"stripe_failure_reason_authentication" : "□□□□□□□□□□□□□□□□□□□□□□□□□□□□"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Parole"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "■■■■■■■■■"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Lösenord"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Passwort"
"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL" : "Azonosítókulcs"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Contrasenya"

POSSIBLE SECRETS
"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL" : "■■■■■"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "■■■■■"
"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL" : "■■■■■■■"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Palavra-passe"
"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL" : "■■■■■"
"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL" : "■■■■■"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Aðgangsorð"
"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL" : "Sarbide-gakoa"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Лозинка"
"google_crash_reporting_api_key" : "AlzaSyAPk0X5DeMHab4ZJ45luCd7Mv50EsU-gXM"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Senha"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Iphasiwedi"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Parol"
"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL" : "□□□□"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Password"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Geslo"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "პაროლი"

POSSIBLE SECRETS
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Hasło"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Jelszó"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Lozinka"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "■■■■■■■"
"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL" : "□□□□"
"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL" : "Nyckel"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "گذرواژه"
"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL" : "Passnøkkel"
"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL" : "ກະແຈຜ່ານ"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Sandi"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "סימנים"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "■■■■■■■■■■■■■■■"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Adgangskode"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Գաղտնաբառ"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "■■■■■■■■■■■■■■■"
"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL" : "Aðgangsslykill"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Wachtwoord"

POSSIBLE SECRETS
"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL" : "Wagwoordsleutel"
"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL" : "□□"
"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL" : "■■■■■.■■"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Şifre"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Пароль"
"google_api_key" : "AlzaSyAPk0X5DeMHab4ZJ4SluCd7Mv50EsU-gXM"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Contraseña"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "□□"
"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL" : "□□□□"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Wagwoord"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "□□□□"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "■■■■■■■■■■■■"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Сырçөз"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "■■■■■■■■■■■■"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Pasahitza"
"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL" : "Avainkoodi"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "■■■■■■■■■■"

POSSIBLE SECRETS
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Contrasinal"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "■■■■■■■■■"
"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL" : "Toegangssleutel"
"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL" : "Passkey"
"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL" : "■■■■■"
"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL" : "Klucz"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "□□□□"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "■■■■■■■■■"
"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL" : "■■■■■■■■■■■"
"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL" : "■■■■■"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "ລະຫັດຜ່ານ"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Nenosiri"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Fjalëkalimi"
"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL" : "□□□"
"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL" : "■■■■■■■■■"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Zaporka"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Slaptažodis"

POSSIBLE SECRETS
"androidx.credentials.TYPE_PUBLIC_KEY_CREDENTIAL" : "Passkey"
"android.credentials.TYPE_PASSWORD_CREDENTIAL" : "Parolă"
115792089210356248762697446949407573530086143415290314195533631308867097853951
8325710961489029985546751289520108179287853048861315594709205902480503199884419224438643760392947333078086511627871
27580193559959705877849011840389048093056905856361568521428707301988689241309860865136260764883745107765439761230575
deca87e736574c5c83c07314051fd93a
39402006196394479212279040100143613805079739270465446667948293404245721771496870329047266088258938001861606973112319
dcb428fea25c40e7b99f81ae5981ee6a
115792089210356248762697446949407573529996955224135760342422259061068512044369
48439561293906451759052585252797914202762949526041747995844080717082404635286
26247035095799689268623156744566981891852923491109213387815615900925518854738050089022388053975719786650872476732087
3757180025770020463545507224491183603594455134769762486694567779615544477440556316691234405012945539562144444537289428522585666729196580810124344277578376784
32670510020758816978083085130507043184471273380659243275938904335757337482424
6864797660130609714981900799081393217269435300143305409394463459185543183397656052122559640661454554977296311391480858037121987999716643812574028291115057151
VGhpcyBpcyB0aGUgcHJlZml4IGZvciBCaWdJbnRlZ2Vy
41058363725152142129326129780047268409114441015993725554835256314039467401291

POSSIBLE SECRETS
115792089237316195423570985008687907852837564279074904382605163141518161494337
36134250956749795798585127919587881956611106672985015071877198253568414405109
115792089210356248762697446949407573530086143415290314195533631308867097853948
115792089237316195423570985008687907853269984665640564039457584007908834671663
39402006196394479212279040100143613805079739270465446667946905279627659399113263569398956308152294913554433653942643
2661740802050217063228768716723360960729859168756973147706671368418802944996427808491545080627771902352094241225065558662157113545570916814161637315895999846
1093849038073734274511112390766805569936207598951683748994586394495953116150735016013708737573759623248592132296706313309438452531591012912142327488478985984
55066263022277343669578718895168534326250603453777594175500187360389116729240
6864797660130609714981900799081393217269435300143305409394463459185543183397655394245057746333217197532963996371363321113864768612440380340372808892707005449
39402006196394479212279040100143613805079739270465446667948293404245721771496870329047266088258938001861606973112316
6864797660130609714981900799081393217269435300143305409394463459185543183397656052122559640661454554977296311391480858037121987999716643812574028291115057148

SCAN LOGS

Timestamp	Event	Error
2025-10-26 06:36:40	Generating Hashes	OK

2025-10-26 06:36:40	Extracting APK	OK
2025-10-26 06:36:40	Unzipping	OK
2025-10-26 06:36:41	Parsing APK with androguard	OK
2025-10-26 06:36:41	Extracting APK features using aapt/aapt2	OK
2025-10-26 06:36:41	Getting Hardcoded Certificates/Keystores	OK
2025-10-26 06:36:44	Parsing AndroidManifest.xml	OK
2025-10-26 06:36:44	Extracting Manifest Data	OK
2025-10-26 06:36:44	Manifest Analysis Started	OK
2025-10-26 06:36:45	Performing Static Analysis on: testingapp (com.enoconan.testingappv2)	OK
2025-10-26 06:36:46	Fetching Details from Play Store: com.enoconan.testingappv2	OK
2025-10-26 06:36:46	Checking for Malware Permissions	OK
2025-10-26 06:36:46	Fetching icon path	OK

2025-10-26 06:36:46	Library Binary Analysis Started	OK
2025-10-26 06:36:46	Analyzing lib/arm64-v8a/libflutter.so	OK
2025-10-26 06:36:46	Analyzing lib/arm64-v8a/libapp.so	OK
2025-10-26 06:36:46	Analyzing lib/arm64-v8a/libdatastore_shared_counter.so	OK
2025-10-26 06:36:46	Analyzing lib/arm64-v8a/libandroidx.graphics.path.so	OK
2025-10-26 06:36:46	Analyzing apktool_out/lib/arm64-v8a/libflutter.so	OK
2025-10-26 06:36:46	Analyzing apktool_out/lib/arm64-v8a/libapp.so	OK
2025-10-26 06:36:46	Analyzing apktool_out/lib/arm64-v8a/libdatastore_shared_counter.so	OK
2025-10-26 06:36:46	Analyzing apktool_out/lib/arm64-v8a/libandroidx.graphics.path.so	OK
2025-10-26 06:36:46	Reading Code Signing Certificate	OK
2025-10-26 06:36:47	Running APKiD 3.0.0	OK
2025-10-26 06:36:53	Detecting Trackers	OK

2025-10-26 06:36:55	Decompiling APK to Java with JADX	OK
2025-10-26 06:37:16	Converting DEX to Smali	OK
2025-10-26 06:37:16	Code Analysis Started on - java_source	OK
2025-10-26 06:37:21	Android SBOM Analysis Completed	OK
2025-10-26 06:37:28	Android SAST Completed	OK
2025-10-26 06:37:28	Android API Analysis Started	OK
2025-10-26 06:37:32	Android API Analysis Completed	OK
2025-10-26 06:37:32	Android Permission Mapping Started	OK
2025-10-26 06:37:37	Android Permission Mapping Completed	OK
2025-10-26 06:37:37	Android Behaviour Analysis Started	OK
2025-10-26 06:37:44	Android Behaviour Analysis Completed	OK
2025-10-26 06:37:44	Extracting Emails and URLs from Source Code	OK

2025-10-26 06:37:47	Email and URL Extraction Completed	OK
2025-10-26 06:37:47	Extracting String data from APK	OK
2025-10-26 06:37:48	Extracting String data from SO	OK
2025-10-26 06:37:48	Extracting String data from Code	OK
2025-10-26 06:37:48	Extracting String values and entropies from Code	OK
2025-10-26 06:37:49	Performing Malware check on extracted domains	OK
2025-10-26 06:37:55	Saving to Database	OK

Report Generated by - MobSF v4.4.3

Mobile Security Framework (MobSF) is an automated, all-in-one mobile application (Android/iOS/Windows) pen-testing, malware analysis and security assessment framework capable of performing static and dynamic analysis.

© 2025 Mobile Security Framework - MobSF | [Ajin Abraham](#) | [OpenSecurity](#).