

Gemfile Summary

Capstone: Photo Tourist Web Application



In this lecture, we will discuss...

- ✧ Gemfile sanity check before deployment

James-MacBook-Pro:capstone_demoapp jim\$

James-MacBook-Pro:capstone_demoapp jim\$ rake

1) ApiDevelopments MongoDB-backed expose MongoDB-backed API resource

Failure/Error: expect(parsed_body).to include("id"=>object.id.to_s)

```
expected {"id" => {"$oid" => "5843384f8a6818102a0a5cf0"}, "name" => "test", "created_at" => "2016-12-03T21:25:35.398Z"..._at" => "2016-12-03T21:25:35.398Z", "url" => "http://www.example.com/api/bars/5843384f8a6818102a0a5cf0"} to include {"id" => "5843384f8a6818102a0a5cf0"}
```

Diff:

@@ -1,2 +1,6 @@

```
- "id" => "5843384f8a6818102a0a5cf0",  
+ "created_at" => "2016-12-03T21:25:35.398Z",  
+ "id" => {"$oid"=>"5843384f8a6818102a0a5cf0"},  
+ "name" => "test",  
+ "updated_at" => "2016-12-03T21:25:35.398Z",  
+ "url" => "http://www.example.com/api/bars/5843384f8a6818102a0a5cf0",
```

./spec/requests/api_developments_spec.rb:42:in `block (3 levels) in <top (required)>'

Finished in 0.08581 seconds (files took 1.59 seconds to load)

4 examples, 1 failure

Failed examples:

rspec ./spec/requests/api_developments_spec.rb:35 # ApiDevelopments MongoDB-backed expose MongoDB-backed API resource

/Users/jim/.rbenv/versions/2.2.3/bin/ruby -I/Users/jim/.rbenv/versions/2.2.3/lib/ruby/gems/2.2.0/gems/rspec-core-3.5.4/lib:/Users/jim/.rbenv/versions/2.2.3/lib/ruby/gems/2.2.0/gems/rspec-support-3.5.0/lib /Users/jim/.rbenv/versions/2.2.3/lib/ruby/gems/2.2.0/gems/rspec-core-3.5.4/exe/rspec --pattern spec/**\{,\}\/*_spec.rb failed


```
1) ApiDevelopments MongoDB-backed expose MongoDB-backed API resource
Failure/Error: expect(parsed_body).to include("id"=>object.id.to_s)
```

```
expected {"id" => {"$oid" => "5843384f8a6818102a0a5cf0"}, "name" => "test", "created_at" => "2016-12-03T21:25:35.398Z"..._at" => "2016-12-03T21:25:35.398Z", "url" => "http://www.example.com/api/bars/5843384f8a6818102a0a5cf0"} to include {"id" => "5843384f8a6818102a0a5cf0"}
```

Diff:

```
@@ -1,2 +1,6 @@
```

```
- "id" => "5843384f8a6818102a0a5cf0",
+ "created_at" => "2016-12-03T21:25:35.398Z",
+ "id" => {"$oid"=>"5843384f8a6818102a0a5cf0"},
+ "name" => "test",
+ "updated_at" => "2016-12-03T21:25:35.398Z",
+ "url" => "http://www.example.com/api/bars/5843384f8a6818102a0a5cf0",
```

```
# ./spec/requests/api_developments_spec.rb:42:in `block (3 levels) in <top (required)>'
```

Finished in 0.08581 seconds (files took 1.59 seconds to load)

4 examples, 1 failure

Failed examples:

```
rspec ./spec/requests/api_developments_spec.rb:35 # ApiDevelopments MongoDB-backed expose MongoDB-backed API resource
```

```
/Users/jim/.rbenv/versions/2.2.3/bin/ruby -I/Users/jim/.rbenv/versions/2.2.3/lib/ruby/gems/2.2.0/gems/rspec-core-3.5.4/lib:/Users/jim/.rbenv/versions/2.2.3/lib/ruby/gems/2.2.0/gems/rspec-support-3.5.0/lib /Users/jim/.rbenv/versions/2.2.3/lib/ruby/gems/2.2.0/gems/rspec-core-3.5.4/exe/rspec --pattern spec/\*\*\{,\}\/*_spec.rb failed
```

```
1 require 'rails_helper'
2
3 RSpec.describe "ApiDevelopments", type: :request do
4   def parsed_body
5     JSON.parse(response.body)
6   end
7
8   describe "RDBMS-backed" do
9     before(:each) { Foo.delete_all }
10    after(:each) { Foo.delete_all }
11
12    it "create RDBMS-backed model" do
13      object=Foo.create(:name=>"test")
14      expect(Foo.find(object.id).name).to eq("test")
15    end
16
17    it "expose RDBMS-backed API resource" do
18      object=Foo.create(:name=>"test")
19      expect(foos_path).to eq("/api/foos")
20      get foo_path(object.id)
21      expect(response).to have_http_status(:ok)
22      expect(parsed_body["name"]).to eq("test")
23    end
24  end
25
26  describe "MongoDB-backed" do
27    before(:each) { Bar.delete_all }
28    after(:each) { Bar.delete_all }
29  end
end
```

```
1 require 'rails_helper'
2
3 RSpec.describe "ApiDevelopments", type: :request do
4   def parsed_body
5     JSON.parse(response.body)
6   end
7
8   describe "RDBMS-backed" do
9     before(:each) { Foo.delete_all }
10    after(:each) { Foo.delete_all }
11
12    it "create RDBMS-backed model" do
13      object=Foo.create(:name=>"test")
14      expect(Foo.find(object.id).name).to eq("test")
15    end
16
17    it "expose RDBMS-backed API resource" do
18      object=Foo.create(:name=>"test")
19      expect(foos_path).to eq("/api/foos")
20      get foo_path(object.id)
21      expect(response).to have_http_status(:ok)
22      expect(parsed_body["name"]).to eq("test")
23    end
24  end
25
26  describe "MongoDB-backed" do
27    before(:each) { Bar.delete_all }
28    after(:each) { Bar.delete_all }
29  end
end
```



```
14     expect(Foo.find(object.id).name).to eq("test")
15   end
16
17   it "expose RDBMS-backed API resource" do
18     object=Foo.create(:name=>"test")
19     expect(foos_path).to eq("/api/foos")
20     get foo_path(object.id)
21     expect(response).to have_http_status(:ok)
22     expect(parsed_body["name"]).to eq("test")
23   end
24 end
25
26 describe "MongoDB-backed" do
27   before(:each) { Bar.delete_all }
28   after(:each)  { Bar.delete_all }
29
30   it "create MongoDB-backed model" do
31     object=Bar.create(:name=>"test")
32     expect(Bar.find(object.id).name).to eq("test")
33   end
34
35   it "expose MongoDB-backed API resource" do
36     object=Bar.create(:name=>"test")
37     expect(bars_path).to eq("/api/bars")
38     get bar_path(object.id)
39     expect(response).to have_http_status(:ok)
40     expect(parsed_body["name"]).to eq("test")
41     expect(parsed_body).to include("created_at")
42     expect(parsed_body).to include("id"=>object.id.to_s)
```

```
14     expect(Foo.find(object.id).name).to eq("test")
15   end
16
17   it "expose RDBMS-backed API resource" do
18     object=Foo.create(:name=>"test")
19     expect(foos_path).to eq("/api/foos")
20     get foo_path(object.id)
21     expect(response).to have_http_status(:ok)
22     expect(parsed_body["name"]).to eq("test")
23   end
24 end
25
26 describe "MongoDB-backed" do
27   before(:each) { Bar.delete_all }
28   after(:each)  { Bar.delete_all }
29
30   it "create MongoDB-backed model" do
31     object=Bar.create(:name=>"test")
32     expect(Bar.find(object.id).name).to eq("test")
33   end
34
35   it "expose MongoDB-backed API resource" do
36     object=Bar.create(:name=>"test")
37     expect(bars_path).to eq("/api/bars")
38     get bar_path(object.id)
39     expect(response).to have_http_status(:ok)
40     expect(parsed_body["name"]).to eq("test")
41     expect(parsed_body).to include("created_at")
42   end
end
```

```
expected {"id" => {"$oid" => "584339fb8a681810a3311716"}, "name" => "test", "created_at" => "2016-12-03T21:32:43.777Z"..._at" => "2016-12-03T21:32:43.777Z", "url" => "http://www.example.com/api/bars/584339fb8a681810a3311716"} to include {"id" => "584339fb8a681810a3311716"}
```

Diff:

```
@@ -1,2 +1,6 @@
```

```
- "id" => "584339fb8a681810a3311716",  
+ "created_at" => "2016-12-03T21:32:43.777Z",  
+ "id" => {"$oid" => "584339fb8a681810a3311716"},  
+ "name" => "test",  
+ "updated_at" => "2016-12-03T21:32:43.777Z",  
+ "url" => "http://www.example.com/api/bars/584339fb8a681810a3311716",
```

```
# ./spec/requests/api_developments_spec.rb:42:in `block (3 levels) in <top (required)>'
```

Finished in 0.08501 seconds (files took 1.59 seconds to load)

4 examples, 1 failure

Failed examples:

```
rspec ./spec/requests/api_developments_spec.rb:35 # ApiDevelopments MongoDB-backed expose MongoDB-backed API resource
```

```
/Users/jim/.rbenv/versions/2.2.3/bin/ruby -I/Users/jim/.rbenv/versions/2.2.3/lib/ruby/gems/2.2.0/gems/rspec-core-3.5.4/lib:/Users/jim/.rbenv/versions/2.2.3/lib/ruby/gems/2.2.0/gems/rspec-support-3.5.0/lib /Users/jim/.rbenv/versions/2.2.3/lib/ruby/gems/2.2.0/gems/rspec-core-3.5.4/exe/rspec --pattern spec/\*\*\{,\^\*\}\/*_spec.rb failed
```

```
Jamess-MacBook-Pro:capstone_demoapp jim$ vi spec/requests/api_developments_spec.rb
```

```
Jamess-MacBook-Pro:capstone_demoapp jim$ rake
```


RDBMS-backed

```
create RDBMS-backed model
```

```
expose RDBMS-backed API resource
```

MongoDB-backed

```
create MongoDB-backed model
```

```
expose MongoDB-backed API resource (FAILED - 1)
```

Failures:

1) ApiDevelopments MongoDB-backed expose MongoDB-backed API resource

Failure/Error: `byebug`

NameError:

undefined local variable or method `byebug' for #<RSpec::ExampleGroups::ApiDevelopments::MongoDBBacked:0x007faa60bfe958>

./spec/requests/api_developments_spec.rb:42:in `block (3 levels) in <top (required)>'

Finished in 0.07328 seconds (files took 1.61 seconds to load)

4 examples, 1 failure

Failed examples:

`rspec ./spec/requests/api_developments_spec.rb:35 # ApiDevelopments MongoDB-backed expose MongoDB-backed API resource`

`/Users/jim/.rbenv/versions/2.2.3/bin/ruby -I/Users/jim/.rbenv/versions/2.2.3/lib/ruby/gems/2.2.0/gems/rspec-core-3.5.4/lib:/Users/jim/.rbenv/versions/2.2.3/lib/ruby/gems/2.2.0/gems/rspec-support-3.5.0/lib /Users/jim/.rbenv/versions/2.2.3/lib/ruby/gems/2.2.0/gems/rspec-core-3.5.4/exe/rspec --pattern spec/**\{,/*/**\}/*_spec.rb failed`

```
1
2 source 'https://rubygems.org'
3
4 gem 'rails', '4.2.6'
5 gem 'rails-api', '~>0.4', '>=0.4.0'
6 gem 'rack-cors', '~>0.4', '>=0.4.0', :require => 'rack/cors'
7
8 gem 'jbuilder', '~> 2.0', '>=2.6.0'
9
10 group :development do
11   gem 'spring', '~>2.0', '>=2.0.0'
12 end
13
14 group :development, :test do
15   gem 'webrick', '~>1.3', '>=1.3.1', :platforms=>[:mingw, :mswin, :x64_mingw, :jruby]
16   gem 'tzinfo-data', :platforms=>[:mingw, :mswin, :x64_mingw, :jruby]
17   gem 'httparty', '~>0.14', '>=0.14.0'
18
19   gem 'rspec-rails', '~> 3.5', '>=3.5.2'
20 end
21
22 gem 'puma', '~>3.6', '>=3.6.0', :platforms=>:ruby
23 gem 'pg', '~>0.19', '>=0.19.0'
24 gem 'mongoid', '~>5.1', '>=5.1.5'
```

~
~
~
~
~


```
1 #
2 source 'https://rubygems.org'
3
4 gem 'rails', '4.2.6'
5 gem 'rails-api', '~>0.4', '>=0.4.0'
6 gem 'rack-cors', '~>0.4', '>=0.4.0', :require => 'rack/cors'
7
8 gem 'jbuilder', '~> 2.0', '>=2.6.0'
9
10 group :development do
11   gem 'spring', '~>2.0', '>=2.0.0'
12 end
13
14 group :development, :test do
15   gem 'webrick', '~>1.3', '>=1.3.1', :platforms=>[:mingw, :mswin, :x64_mingw, :jruby]
16   gem 'tzinfo-data', :platforms=>[:mingw, :mswin, :x64_mingw, :jruby]
17   gem 'byebug', '~>9.0', '>=9.0.6'
18   gem 'httparty', '~>0.14', '>=0.14.0'
19
20   gem 'rspec-rails', '~> 3.5', '>=3.5.2'
21 end
22
23 gem 'puma', '~>3.6', '>=3.6.0', :platforms=>:ruby
24 gem 'pg', '~>0.19', '>=0.19.0'
25 gem 'mongoid', '~>5.1', '>=5.1.5'
```

```
~
~
~
~
```

```
expose RDBMS-backed API resource
MongoDB-backed
create MongoDB-backed model
expose MongoDB-backed API resource (FAILED - 1)
```

Failures:

- 1) ApiDevelopments MongoDB-backed expose MongoDB-backed API resource
Failure/Error: byebug

```
NameError:
  undefined local variable or method `byebug' for #<RSpec::ExampleGroups::ApiDevelopments::MongoDBBacked:0x007faa60bfe958>
# ./spec/requests/api_developments_spec.rb:42:in `block (3 levels) in <top (required)>'
```

Finished in 0.07328 seconds (files took 1.61 seconds to load)
4 examples, 1 failure

Failed examples:

```
rspec ./spec/requests/api_developments_spec.rb:35 # ApiDevelopments MongoDB-backed expose MongoDB-backed API resource
```

```
/Users/jim/.rbenv/versions/2.2.3/bin/ruby -I/Users/jim/.rbenv/versions/2.2.3/lib/ruby/gems/2.2.0/gems/rspec-core-3.5.4/lib:/Users/jim/.rbenv/versions/2.2.3/lib/ruby/gems/2.2.0/gems/rspec-support-3.5.0/lib /Users/jim/.rbenv/versions/2.2.3/lib/ruby/gems/2.2.0/gems/rspec-core-3.5.4/exe/rspec --pattern spec/\*\*\{,\^\^\*\*\}/\*_spec.rb failed
```

```
Jamess-MacBook-Pro:capstone_demoapp jim$ vi Gemfile
```

```
Jamess-MacBook-Pro:capstone_demoapp jim$ bundle
```

```
Using mongo 2.3.1
Using sprockets 3.7.0
Using httparty 0.14.0
Using rspec-core 3.5.4
Using rspec-expectations 3.5.0
Using rspec-mocks 3.5.0
Using activesupport 4.2.6
Using loofah 2.0.3
Using mail 2.6.4
Using rails-deprecated_sanitizer 1.0.3
Using globalid 0.3.7
Using activemodel 4.2.6
Using jbuilder 2.6.0
Using spring 2.0.0
Using rails-html-sanitizer 1.0.3
Using rails-dom-testing 1.0.7
Using activejob 4.2.6
Using activerecord 4.2.6
Using mongoid 5.1.5
Using actionview 4.2.6
Using actionpack 4.2.6
Using actionmailer 4.2.6
Using railties 4.2.6
Using sprockets-rails 3.2.0
Using rails-api 0.4.0
Using rspec-rails 3.5.2
Using rails 4.2.6
```

Bundle complete! 13 Gemfile dependencies, 55 gems now installed.

Use `bundle show [gemname]` to see where a bundled gem is installed.


```
Using sprockets-rails 3.2.0
Using rails-api 0.4.0
Using rspec-rails 3.5.2
Using rails 4.2.6
```

```
Bundle complete! 13 Gemfile dependencies, 55 gems now installed.
Use `bundle show [gemname]` to see where a bundled gem is installed.
```

```
James-MacBook-Pro:capstone_demoapp jim$ rake
```

```
/Users/jim/.rbenv/versions/2.2.3/bin/ruby -I/Users/jim/.rbenv/versions/2.2.3/lib/ruby/gems/2.2.0/gems/rspec-core-3.5.4/lib:/Users/jim/.rbenv/versions/2.2.3/lib/ruby/gems/2.2.0/gems/rspec-support-3.5.0/lib /Users/jim/.rbenv/versions/2.2.3/lib/ruby/gems/2.2.0/gems/rspec-core-3.5.4/exe/rspec --pattern spec/\*\*\{,\^\*\*\}\/*_spec.rb
```

```
ApiDevelopments
```

```
  RDBMS-backed
```

```
    create RDBMS-backed model
```

```
    expose RDBMS-backed API resource
```

```
  MongoDB-backed
```

```
    create MongoDB-backed model
```

```
[37, 46] in /Users/jim/proj/fullstack/capstone_demoapp/spec/requests/api_developments_spec.rb
```

```
 37:     expect(bars_path).to eq("/api/bars")
 38:     get bar_path(object.id)
 39:     expect(response).to have_http_status(:ok)
 40:     expect(parsed_body["name"]).to eq("test")
 41:     expect(parsed_body).to include("created_at")
 42:     bybug
=> 43:     expect(parsed_body).to include("id"=>object.id.to_s)
 44:   end
 45: end
 46: end
```

```
Using sprockets-rails 3.2.0
Using rails-api 0.4.0
Using rspec-rails 3.5.2
Using rails 4.2.6
```

```
Bundle complete! 13 Gemfile dependencies, 55 gems now installed.
Use `bundle show [gemname]` to see where a bundled gem is installed.
```

```
James-MacBook-Pro:capstone_demoapp jim$ rake
```

```
/Users/jim/.rbenv/versions/2.2.3/bin/ruby -I/Users/jim/.rbenv/versions/2.2.3/lib/ruby/gems/2.2.0/gems/rspec-core-3.5.4/lib:/Users/jim/.rbenv/versions/2.2.3/lib/ruby/gems/2.2.0/gems/rspec-support-3.5.0/lib /Users/jim/.rbenv/versions/2.2.3/lib/ruby/gems/2.2.0/gems/rspec-core-3.5.4/exe/rspec --pattern spec/\*\*\{,\^\*\*\}\/*_spec.rb
```

```
ApiDevelopments
```

```
RDBMS-backed
```

```
  create RDBMS-backed model
```

```
  expose RDBMS-backed API resource
```

```
MongoDB-backed
```

```
  create MongoDB-backed model
```

```
[37, 46] in /Users/jim/proj/fullstack/capstone_demoapp/spec/requests/api_developments_spec.rb
```

```
37:      expect(bars_path).to eq("/api/bars")
38:      get bar_path(object.id)
39:      expect(response).to have_http_status(:ok)
40:      expect(parsed_body["name"]).to eq("test")
41:      expect(parsed_body).to include("created_at")
42:      bybug
=> 43:      expect(parsed_body).to include("id"=>object.id.to_s)
44:    end
45:  end
46: end
```


Using rails 4.2.6

Bundle complete! 13 Gemfile dependencies, 55 gems now installed.

Use `bundle show [gemname]` to see where a bundled gem is installed.

James-MacBook-Pro:capstone_demoapp jim\$ rake

/Users/jim/.rbenv/versions/2.2.3/bin/ruby -I/Users/jim/.rbenv/versions/2.2.3/lib/ruby/gems/2.2.0/gems/rspec-core-3.5.4/lib:/Users/jim/.rbenv/versions/2.2.3/lib/ruby/gems/2.2.0/gems/rspec-support-3.5.0/lib /Users/jim/.rbenv/versions/2.2.3/lib/ruby/gems/2.2.0/gems/rspec-core-3.5.4/exe/rspec --pattern spec/**\{,***/**_spec.rb

ApiDevelopments

RDBMS-backed

create RDBMS-backed model

expose RDBMS-backed API resource

MongoDB-backed

create MongoDB-backed model

[37, 46] in /Users/jim/proj/fullstack/capstone_demoapp/spec/requests/api_developments_spec.rb

37: expect(bars_path).to eq("/api/bars")

38: get bar_path(object.id)

39: expect(response).to have_http_status(:ok)

40: expect(parsed_body["name"]).to eq("test")

41: expect(parsed_body).to include("created_at")

42: byebug

=> 43: expect(parsed_body).to include("id"=>object.id.to_s)

44: end

45: end

46: end

(byebug) parsed_body

{"id"=>{"\$oid"=>"58433a828a681811bfc9c9f"}, "name"=>"test", "created_at"=>"2016-12-03T21:34:58.983Z", "updated_at"=>"2016-12-03T21:34:58.983Z", "url"=>"http://www.example.com/api/bars/58433a828a681811bfc9c9f"}

Using rails 4.2.6

Bundle complete! 13 Gemfile dependencies, 55 gems now installed.

Use `bundle show [gemname]` to see where a bundled gem is installed.

James-MacBook-Pro:capstone_demoapp jim\$ rake

/Users/jim/.rbenv/versions/2.2.3/bin/ruby -I/Users/jim/.rbenv/versions/2.2.3/lib/ruby/gems/2.2.0/gems/rspec-core-3.5.4/lib:/Users/jim/.rbenv/versions/2.2.3/lib/ruby/gems/2.2.0/gems/rspec-support-3.5.0/lib /Users/jim/.rbenv/versions/2.2.3/lib/ruby/gems/2.2.0/gems/rspec-core-3.5.4/exe/rspec --pattern spec/**\{,*\/**\}/*_spec.rb

ApiDevelopments

RDBMS-backed

create RDBMS-backed model

expose RDBMS-backed API resource

MongoDB-backed

create MongoDB-backed model

[37, 46] in /Users/jim/proj/fullstack/capstone_demoapp/spec/requests/api_developments_spec.rb

37: expect(bars_path).to eq("/api/bars")

38: get bar_path(object.id)

39: expect(response).to have_http_status(:ok)

40: expect(parsed_body["name"]).to eq("test")

41: expect(parsed_body).to include("created_at")

42: byebug

=> 43: expect(parsed_body).to include("id"=>object.id.to_s)

44: end

45: end

46: end

(byebug) parsed_body

{"id"=>{"\$oid"=>"58433a828a6818111bfc9c9f"}, "name"=>"test", "created_at"=>"2016-12-03T21:34:58.983Z", "updated_at"=>"2016-12-03T21:34:58.983Z", "url"=>"http://www.example.com/api/bars/58433a828a6818111bfc9c9f"}


```
ersions/2.2.3/lib/ruby/gems/2.2.0/gems/rspec-core-3.5.4/exe/rspec --pattern spec/\*\*\{,\^\*\^\*\}\/*_spec.rb
```

ApiDevelopments

RDBMS-backed

create RDBMS-backed model

expose RDBMS-backed API resource

MongoDB-backed

create MongoDB-backed model

```
[37, 46] in /Users/jim/proj/fullstack/capstone_demoapp/spec/requests/api_developments_spec.rb
```

```
37: expect(bars_path).to eq("/api/bars")
38: get bar_path(object.id)
39: expect(response).to have_http_status(:ok)
40: expect(parsed_body["name"]).to eq("test")
41: expect(parsed_body).to include("created_at")
42: byebug
=> 43: expect(parsed_body).to include("id"=>object.id.to_s)
44: end
45: end
46: end
```

(byebug) parsed_body

```
{"id"=>{"$oid"=>"58433a828a681811bfc9c9f"}, "name"=>"test", "created_at"=>"2016-12-03T21:34:58.983Z", "updated_at"=>"2016-12-03T21:34:58.983Z", "url"=>"http://www.example.com/api/bars/58433a828a681811bfc9c9f"}
```

(byebug) quit

Really quit? (y/n) y

```
/Users/jim/.rbenv/versions/2.2.3/bin/ruby -I/Users/jim/.rbenv/versions/2.2.3/lib/ruby/gems/2.2.0/gems/rspec-core-3.5.4/lib:/Users/jim/.rbenv/versions/2.2.3/lib/ruby/gems/2.2.0/gems/rspec-support-3.5.0/lib /Users/jim/.rbenv/versions/2.2.3/lib/ruby/gems/2.2.0/gems/rspec-core-3.5.4/exe/rspec --pattern spec/\*\*\{,\^\*\^\*\}\/*_spec.rb failed
```

```
1 class BarsController < ApplicationController
2   before_action :set_bar, only: [:show, :update, :destroy]
3
4   def index
5     @bars = Bar.all
6     #render json: @bars
7   end
8
9   def show
10    #render json: @bar
11    b
12  end
13
14  def create
15    @bar = Bar.new(bar_params)
16
17    if @bar.save
18      #render json: @bar, status: :created, location: @bar
19      render :show, status: :created, location: @bar
20    else
21      render json: @bar.errors, status: :unprocessable_entity
22    end
23  end
24
25  def update
26    @bar = Bar.find(params[:id])
27
28    if @bar.update(bar_params)
29      head :no_content
```

```
1 class BarsController < ApplicationController
2   before_action :set_bar, only: [:show, :update, :destroy]
3
4   def index
5     @bars = Bar.all
6     #render json: @bars
7   end
8
9   def show
10    #render json: @bar
11    byebug
12  end
13
14  def create
15    @bar = Bar.new(bar_params)
16
17    if @bar.save
18      #render json: @bar, status: :created, location: @bar
19      render :show, status: :created, location: @bar
20    else
21      render json: @bar.errors, status: :unprocessable_entity
22    end
23  end
24
25  def update
26    @bar = Bar.find(params[:id])
27
28    if @bar.update(bar_params)
29      head :no_content
```



```
1 class BarsController < ApplicationController
2   before_action :set_bar, only: [:show, :update, :destroy]
3
4   def index
5     @bars = Bar.all
6     #render json: @bars
7   end
8
9   def show
10    #render json: @bar
11    byebug
12  end
13
14  def create
15    @bar = Bar.new(bar_params)
16
17    if @bar.save
18      #render json: @bar, status: :created, location: @bar
19      render :show, status: :created, location: @bar
20    else
21      render json: @bar.errors, status: :unprocessable_entity
22    end
23  end
24
25  def update
26    @bar = Bar.find(params[:id])
27
28    if @bar.update(bar_params)
29      head :no_content
```

```
1 class BarsController < ApplicationController
2   before_action :set_bar, only: [:show, :update, :destroy]
3
4   def index
5     @bars = Bar.all
6     #render json: @bars
7   end
8
9   def show
10    #render json: @bar
11    byebug
12  end
13
14  def create
15    @bar = Bar.new(bar_params)
16
17    if @bar.save
18      #render json: @bar, status: :created, location: @bar
19      render :show, status: :created, location: @bar
20    else
21      render json: @bar.errors, status: :unprocessable_entity
22    end
23  end
24
25  def update
26    @bar = Bar.find(params[:id])
27
28    if @bar.update(bar_params)
29      head :no_content
```

```
1 #json.extract! bar, :id, :name, :created_at, :updated_at
2
3 #json.id bar.id.to_s - added for error to debug
4 byebug
5 json.id bar.id
6 json.name bar.name
7 json.created_at bar.created_at
8 json.updated_at bar.updated_at
9 json.url bar_url(bar, format: :json)
```

expose RDBMS-backed API resource

MongoDB-backed

create MongoDB-backed model

[37, 46] in /Users/jim/proj/fullstack/capstone_demoapp/spec/requests/api_developments_spec.rb

```
37: expect(bars_path).to eq("/api/bars")
38: get bar_path(object.id)
39: expect(response).to have_http_status(:ok)
40: expect(parsed_body["name"]).to eq("test")
41: expect(parsed_body).to include("created_at")
42: byebug
=> 43: expect(parsed_body).to include("id"=>object.id.to_s)
44: end
45: end
46: end
```

(byebug) parsed_body

```
{"id"=>{"$oid"=>"58433a828a681811bfc9c9f"}, "name"=>"test", "created_at"=>"2016-12-03T21:34:58.983Z", "updated_at"=>"2016-12-03T21:34:58.983Z", "url"=>"http://www.example.com/api/bars/58433a828a681811bfc9c9f"}
```

(byebug) quit

Really quit? (y/n) y

```
/Users/jim/.rbenv/versions/2.2.3/bin/ruby -I/Users/jim/.rbenv/versions/2.2.3/lib/ruby/gems/2.2.0/gems/rspec-core-3.5.4/lib:/Users/jim/.rbenv/versions/2.2.3/lib/ruby/gems/2.2.0/gems/rspec-support-3.5.0/lib /Users/jim/.rbenv/versions/2.2.3/lib/ruby/gems/2.2.0/gems/rspec-core-3.5.4/exe/rspec --pattern spec/\*\*\{,/\*/\*\*\}/\*_spec.rb failed
```

Jamess-MacBook-Pro:capstone_demoapp jim\$ vi app/controllers/bars_controller.rb

Jamess-MacBook-Pro:capstone_demoapp jim\$ rake

```
/Users/jim/.rbenv/versions/2.2.3/bin/ruby -I/Users/jim/.rbenv/versions/2.2.3/lib/ruby/gems/2.2.0/gems/rspec-core-3.5.4/lib:/Users/jim/.rbenv/versions/2.2.3/lib/ruby/gems/2.2.0/gems/rspec-support-3.5.0/lib /Users/jim/.rbenv/versions/2.2.3/lib/ruby/gems/2.2.0/gems/rspec-core-3.5.4/exe/rspec --pattern spec/\*\*\{,/\*/\*\*\}/\*_spec.rb
```



```
/Users/jim/.rbenv/versions/2.2.3/bin/ruby -I/Users/jim/.rbenv/versions/2.2.3/lib/ruby/gems/2.2.0/gems/rspec-core-3.5.4/lib:/Users/jim/.rbenv/versions/2.2.3/lib/ruby/gems/2.2.0/gems/rspec-support-3.5.0/lib /Users/jim/.rbenv/versions/2.2.3/lib/ruby/gems/2.2.0/gems/rspec-core-3.5.4/exe/rspec --pattern spec/\*\*\{,\}\*\*/\*_spec.rb failed
```

```
Jamess-MacBook-Pro:capstone_demoapp jim$ vi app/controllers/bars_controller.rb
```

```
Jamess-MacBook-Pro:capstone_demoapp jim$ rake
```

```
/Users/jim/.rbenv/versions/2.2.3/bin/ruby -I/Users/jim/.rbenv/versions/2.2.3/lib/ruby/gems/2.2.0/gems/rspec-core-3.5.4/lib:/Users/jim/.rbenv/versions/2.2.3/lib/ruby/gems/2.2.0/gems/rspec-support-3.5.0/lib /Users/jim/.rbenv/versions/2.2.3/lib/ruby/gems/2.2.0/gems/rspec-core-3.5.4/exe/rspec --pattern spec/\*\*\{,\}\*\*/\*_spec.rb
```

ApiDevelopments

RDBMS-backed

create RDBMS-backed model

expose RDBMS-backed API resource

MongoDB-backed

create MongoDB-backed model

Return value is: nil

```
[7, 16] in /Users/jim/proj/fullstack/capstone_demoapp/app/controllers/bars_controller.rb
```

```
7: end
```

```
8:
```

```
9: def show
```

```
10:   #render json: @bar
```

```
11:   byebug
```

```
=> 12: end
```

```
13:
```

```
14: def create
```

```
15:   @bar = Bar.new(bar_params)
```

```
16:
```



```
Jamess-MacBook-Pro:capstone_demoapp jim$ rake
/Users/jim/.rbenv/versions/2.2.3/bin/ruby -I/Users/jim/.rbenv/versions/2.2.3/lib/ruby/gems/2.2.0/gems/rspec-core-3.5.4/lib:/Users/jim/.rbenv/versions/2.2.3/lib/ruby/gems/2.2.0/gems/rspec-support-3.5.0/lib /Users/jim/.rbenv/versions/2.2.3/lib/ruby/gems/2.2.0/gems/rspec-core-3.5.4/exe/rspec --pattern spec/\*\*\{,\}\/*\*\*/\*_spec.rb
```

ApiDevelopments

RDBMS-backed

create RDBMS-backed model

expose RDBMS-backed API resource

MongoDB-backed

create MongoDB-backed model

Return value is: nil

[7, 16] in /Users/jim/proj/fullstack/capstone_demoapp/app/controllers/bars_controller.rb

```
7:   end
8:
9:   def show
10:     #render json: @bar
11:     byebug
=> 12:   end
13:
14:   def create
15:     @bar = Bar.new(bar_params)
16:
```

(byebug) @bar

#<Bar _id: 58433ad38a6818114acde203, created_at: 2016-12-03 21:36:19 UTC, updated_at: 2016-12-03 21:36:19 UTC, name: "test">

(byebug) @bar.id

BSON::ObjectId('58433ad38a6818114acde203')

```
James-MacBook-Pro:capstone_demoapp jim$ rake
/Users/jim/.rbenv/versions/2.2.3/bin/ruby -I/Users/jim/.rbenv/versions/2.2.3/lib/ruby/gems/2.2.0/gems/rspec-core-3.5.4/lib:/Users/jim/.rbenv/versions/2.2.3/lib/ruby/gems/2.2.0/gems/rspec-support-3.5.0/lib /Users/jim/.rbenv/versions/2.2.3/lib/ruby/gems/2.2.0/gems/rspec-core-3.5.4/exe/rspec --pattern spec/\*\*\{,\}\/*\*\*/\*_spec.rb
```

ApiDevelopments

RDBMS-backed

create RDBMS-backed model

expose RDBMS-backed API resource

MongoDB-backed

create MongoDB-backed model

Return value is: nil

```
[7, 16] in /Users/jim/proj/fullstack/capstone_demoapp/app/controllers/bars_controller.rb
```

```
7:   end
8:
9:   def show
10:     #render json: @bar
11:     byebug
=> 12:   end
13:
14:   def create
15:     @bar = Bar.new(bar_params)
16:
```

(byebug) @bar

#<Bar _id: 58433ad38a6818114acde203, created_at: 2016-12-03 21:36:19 UTC, updated_at: 2016-12-03 21:36:19 UTC, name: "test">

(byebug) @bar.id

BSON::ObjectId('58433ad38a6818114acde203')

```
[7, 16] in /Users/jim/proj/fullstack/capstone_demoapp/app/controllers/bars_controller.rb
```

```
7:   end
8:
9:   def show
10:     #render json: @bar
11:     byebug
=> 12:   end
13:
14:   def create
15:     @bar = Bar.new(bar_params)
16:
```

```
(byebug) @bar
```

```
#<Bar _id: 58433ad38a6818114acde203, created_at: 2016-12-03 21:36:19 UTC, updated_at: 2016-12-03 21:36:19 UTC, name: "test">
```

```
(byebug) @bar.id
```

```
BSON::ObjectId('58433ad38a6818114acde203')
```

```
(byebug) continue
```

```
[1, 9] in /Users/jim/proj/fullstack/capstone_demoapp/app/views/bars/_bar.json.jbuilder
```

```
1: #json.extract! bar, :id, :name, :created_at, :updated_at
2:
3: #json.id bar.id.to_s - added for error to debug
4: byebug
=> 5: json.id bar.id
6: json.name bar.name
7: json.created_at bar.created_at
8: json.updated_at bar.updated_at
9: json.url bar_url(bar, format: :json)
```



```
7: end
8:
9: def show
10:   #render json: @bar
11:   byebug
=> 12: end
13:
14: def create
15:   @bar = Bar.new(bar_params)
16:
```

(byebug) @bar

#<Bar _id: 58433ad38a6818114acde203, created_at: 2016-12-03 21:36:19 UTC, updated_at: 2016-12-03 21:36:19 UTC, name: "test">

(byebug) @bar.id

BSON::ObjectId('58433ad38a6818114acde203')

(byebug) continue

[1, 9] in /Users/jim/proj/fullstack/capstone_demoapp/app/views/bars/_bar.json.jbuilder

```
1: #json.extract! bar, :id, :name, :created_at, :updated_at
2:
3: #json.id bar.id.to_s - added for error to debug
4: byebug
=> 5: json.id bar.id
6: json.name bar.name
7: json.created_at bar.created_at
8: json.updated_at bar.updated_at
9: json.url bar_url(bar, format: :json)
```

(byebug) bar.id

BSON::ObjectId('58433ad38a6818114acde203')

```
ame: "test">
```

```
(byebug) @bar.id
```

```
BSON::ObjectId('58433ad38a6818114acde203')
```

```
(byebug) continue
```

```
[1, 9] in /Users/jim/proj/fullstack/capstone_demoapp/app/views/bars/_bar.json.jbuilder
```

```
1: #json.extract! bar, :id, :name, :created_at, :updated_at
```

```
2:
```

```
3: #json.id bar.id.to_s - added for error to debug
```

```
4: byebug
```

```
=> 5: json.id bar.id
```

```
6: json.name bar.name
```

```
7: json.created_at bar.created_at
```

```
8: json.updated_at bar.updated_at
```

```
9: json.url bar_url(bar, format: :json)
```

```
(byebug) bar.id
```

```
BSON::ObjectId('58433ad38a6818114acde203')
```

```
(byebug) next
```

```
[1, 9] in /Users/jim/proj/fullstack/capstone_demoapp/app/views/bars/_bar.json.jbuilder
```

```
1: #json.extract! bar, :id, :name, :created_at, :updated_at
```

```
2:
```

```
3: #json.id bar.id.to_s - added for error to debug
```

```
4: byebug
```

```
5: json.id bar.id
```

```
=> 6: json.name bar.name
```

```
7: json.created_at bar.created_at
```

```
8: json.updated_at bar.updated_at
```

```
9: json.url bar_url(bar, format: :json)
```

```
ame: "test">
```

```
(byebug) @bar.id
```

```
BSON::ObjectId('58433ad38a6818114acde203')
```

```
(byebug) continue
```

```
[1, 9] in /Users/jim/proj/fullstack/capstone_demoapp/app/views/bars/_bar.json.jbuilder
```

```
1: #json.extract! bar, :id, :name, :created_at, :updated_at
```

```
2:
```

```
3: #json.id bar.id.to_s - added for error to debug
```

```
4: byebug
```

```
=> 5: json.id bar.id
```

```
6: json.name bar.name
```

```
7: json.created_at bar.created_at
```

```
8: json.updated_at bar.updated_at
```

```
9: json.url bar_url(bar, format: :json)
```

```
(byebug) bar.id
```

```
BSON::ObjectId('58433ad38a6818114acde203')
```

```
(byebug) next
```

```
[1, 9] in /Users/jim/proj/fullstack/capstone_demoapp/app/views/bars/_bar.json.jbuilder
```

```
1: #json.extract! bar, :id, :name, :created_at, :updated_at
```

```
2:
```

```
3: #json.id bar.id.to_s - added for error to debug
```

```
4: byebug
```

```
5: json.id bar.id
```

```
=> 6: json.name bar.name
```

```
7: json.created_at bar.created_at
```

```
8: json.updated_at bar.updated_at
```

```
9: json.url bar_url(bar, format: :json)
```



```
9: json.url bar_url(bar, format: :json)
(byebug) bar.id
BSON::ObjectId('58433ad38a6818114acde203')
(byebug) next
```

```
[1, 9] in /Users/jim/proj/fullstack/capstone_demoapp/app/views/bars/_bar.json.jbuilder
 1: #json.extract! bar, :id, :name, :created_at, :updated_at
 2:
 3: #json.id bar.id.to_s - added for error to debug
 4: byebug
 5: json.id bar.id
=> 6: json.name bar.name
 7: json.created_at bar.created_at
 8: json.updated_at bar.updated_at
 9: json.url bar_url(bar, format: :json)
(byebug) json.id bar.id.to_s
"58433ad38a6818114acde203"
(byebug) list
```

```
[1, 9] in /Users/jim/proj/fullstack/capstone_demoapp/app/views/bars/_bar.json.jbuilder
 1: #json.extract! bar, :id, :name, :created_at, :updated_at
 2:
 3: #json.id bar.id.to_s - added for error to debug
 4: byebug
 5: json.id bar.id
=> 6: json.name bar.name
 7: json.created_at bar.created_at
 8: json.updated_at bar.updated_at
 9: json.url bar_url(bar, format: :json)
```

```
9: json.url bar_url(bar, format: :json)
(byebug) bar.id
BSON::ObjectId('58433ad38a6818114acde203')
(byebug) next
```

```
[1, 9] in /Users/jim/proj/fullstack/capstone_demoapp/app/views/bars/_bar.json.jbuilder
 1: #json.extract! bar, :id, :name, :created_at, :updated_at
 2:
 3: #json.id bar.id.to_s - added for error to debug
 4: byebug
 5: json.id bar.id
=> 6: json.name bar.name
 7: json.created_at bar.created_at
 8: json.updated_at bar.updated_at
 9: json.url bar_url(bar, format: :json)
(byebug) json.id bar.id.to_s
"58433ad38a6818114acde203"
(byebug) list
```

```
[1, 9] in /Users/jim/proj/fullstack/capstone_demoapp/app/views/bars/_bar.json.jbuilder
 1: #json.extract! bar, :id, :name, :created_at, :updated_at
 2:
 3: #json.id bar.id.to_s - added for error to debug
 4: byebug
 5: json.id bar.id
=> 6: json.name bar.name
 7: json.created_at bar.created_at
 8: json.updated_at bar.updated_at
 9: json.url bar_url(bar, format: :json)
```

```
8: json.updated_at bar.updated_at
9: json.url bar_url(bar, format: :json)
(byebug) json.id bar.id.to_s
"58433ad38a6818114acde203"
(byebug) list
```

```
[1, 9] in /Users/jim/proj/fullstack/capstone_demoapp/app/views/bars/_bar.json.jbuilder
1: #json.extract! bar, :id, :name, :created_at, :updated_at
2:
3: #json.id bar.id.to_s - added for error to debug
4: byebug
5: json.id bar.id
=> 6: json.name bar.name
7: json.created_at bar.created_at
8: json.updated_at bar.updated_at
9: json.url bar_url(bar, format: :json)
(byebug) continue
```

```
[37, 46] in /Users/jim/proj/fullstack/capstone_demoapp/spec/requests/api_developments_spec.rb
37: expect(bars_path).to eq("/api/bars")
38: get bar_path(object.id)
39: expect(response).to have_http_status(:ok)
40: expect(parsed_body["name"]).to eq("test")
41: expect(parsed_body).to include("created_at")
42: byebug
=> 43: expect(parsed_body).to include("id"=>object.id.to_s)
44: end
45: end
46: end
```



```
"58433ad38a6818114acde203"
```

```
(byebug) list
```

```
[1, 9] in /Users/jim/proj/fullstack/capstone_demoapp/app/views/bars/_bar.json.jbuilder
```

```
1: #json.extract! bar, :id, :name, :created_at, :updated_at
```

```
2:
```

```
3: #json.id bar.id.to_s - added for error to debug
```

```
4: byebug
```

```
5: json.id bar.id
```

```
=> 6: json.name bar.name
```

```
7: json.created_at bar.created_at
```

```
8: json.updated_at bar.updated_at
```

```
9: json.url bar_url(bar, format: :json)
```

```
(byebug) continue
```

```
[37, 46] in /Users/jim/proj/fullstack/capstone_demoapp/spec/requests/api_developments_spec.rb
```

```
37: expect(bars_path).to eq("/api/bars")
```

```
38: get bar_path(object.id)
```

```
39: expect(response).to have_http_status(:ok)
```

```
40: expect(parsed_body["name"]).to eq("test")
```

```
41: expect(parsed_body).to include("created_at")
```

```
42: byebug
```

```
=> 43: expect(parsed_body).to include("id"=>object.id.to_s)
```

```
44: end
```

```
45: end
```

```
46: end
```

```
(byebug) parsed_body
```

```
{"id"=>"58433ad38a6818114acde203", "name"=>"test", "created_at"=>"2016-12-03T21:36:19.434Z", "updated_at"=>"2016-12-03T21:36:19.434Z", "url"=>"http://www.example.com/api/bars/58433ad38a6818114acde203"}
```

```
3: #json.id bar.id.to_s - added for error to debug
4: byebug
5: json.id bar.id
=> 6: json.name bar.name
7: json.created_at bar.created_at
8: json.updated_at bar.updated_at
9: json.url bar_url(bar, format: :json)
(byebug) continue
```

```
[37, 46] in /Users/jim/proj/fullstack/capstone_demoapp/spec/requests/api_developments_spec.rb
```

```
37: expect(bars_path).to eq("/api/bars")
38: get bar_path(object.id)
39: expect(response).to have_http_status(:ok)
40: expect(parsed_body["name"]).to eq("test")
41: expect(parsed_body).to include("created_at")
42: byebug
=> 43: expect(parsed_body).to include("id"=>object.id.to_s)
44: end
45: end
46: end
```

```
(byebug) parsed_body
```

```
{"id"=>"58433ad38a6818114acde203", "name"=>"test", "created_at"=>"2016-12-03T21:36:19.434Z", "updated_at"=>"2016-12-03T21:36:19.434Z", "url"=>"http://www.example.com/api/bars/58433ad38a6818114acde203"}
```

```
(byebug) continue
```

```
  expose MongoDB-backed API resource
```

```
Finished in 1 minute 16.9 seconds (files took 1.61 seconds to load)
```

```
4 examples, 0 failures
```

```
1
2 source 'https://rubygems.org'
3
4 gem 'rails', '4.2.6'
5 gem 'rails-api', '~>0.4', '>=0.4.0'
6 gem 'rack-cors', '~>0.4', '>=0.4.0', :require => 'rack/cors'
7
8 gem 'jbuilder', '~> 2.0', '>=2.6.0'
9
10 group :development do
11   gem 'spring', '~>2.0', '>=2.0.0'
12 end
13
14 group :development, :test do
15   gem 'webrick', '~>1.3', '>=1.3.1', :platforms=>[:mingw, :mswin, :x64_mingw, :jruby]
16   gem 'tzinfo-data', :platforms=>[:mingw, :mswin, :x64_mingw, :jruby]
17   gem 'byebug', '~>9.0', '>=9.0.6'
18   gem 'httparty', '~>0.14', '>=0.14.0'
19
20   gem 'rspec-rails', '~> 3.5', '>=3.5.2'
21 end
22
23 gem 'puma', '~>3.6', '>=3.6.0', :platforms=>:ruby
24 gem 'pg', '~>0.19', '>=0.19.0'
25 gem 'mongoid', '~>5.1', '>=5.1.5'
```



```
1 #
2 source 'https://rubygems.org'
3
4 gem 'rails', '4.2.6'
5 gem 'rails-api', '~>0.4', '>=0.4.0'
6 gem 'pry-rails', '~>0.3', '>=0.3.4'
7 gem 'rack-cors', '~>0.4', '>=0.4.0', :require => 'rack/cors'
8
9 gem 'jbuilder', '~> 2.0', '>=2.6.0'
10
11 group :development do
12   gem 'spring', '~>2.0', '>=2.0.0'
13 end
14
15 group :development, :test do
16   gem 'webrick', '~>1.3', '>=1.3.1', :platforms=>[:mingw, :mswin, :x64_mingw, :jruby]
17   gem 'tzinfo-data', :platforms=>[:mingw, :mswin, :x64_mingw, :jruby]
18   gem 'byebug', '~>9.0', '>=9.0.6'
19   gem 'httparty', '~>0.14', '>=0.14.0'
20
21   gem 'rspec-rails', '~> 3.5', '>=3.5.2'
22 end
23
24 gem 'puma', '~>3.6', '>=3.6.0', :platforms=>:ruby
25 gem 'pg', '~>0.19', '>=0.19.0'
26 gem 'mongoid', '~>5.1', '>=5.1.5'
```

```
1 #
2 source 'https://rubygems.org'
3
4 gem 'rails', '4.2.6'
5 gem 'rails-api', '~>0.4', '>=0.4.0'
6 gem 'pry-rails', '~>0.3', '>=0.3.4'
7 gem 'rack-cors', '~>0.4', '>=0.4.0', :require => 'rack/cors'
8
9 gem 'jbuilder', '~> 2.0', '>=2.6.0'
10
11 group :development do
12   gem 'spring', '~>2.0', '>=2.0.0'
13 end
14
15 group :development, :test do
16   gem 'webrick', '~>1.3', '>=1.3.1', :platforms=>[:mingw, :mswin, :x64_mingw, :jruby]
17   gem 'tzinfo-data', :platforms=>[:mingw, :mswin, :x64_mingw, :jruby]
18   gem 'byebug', '~>9.0', '>=9.0.6'
19   gem 'httparty', '~>0.14', '>=0.14.0'
20
21   gem 'rspec-rails', '~> 3.5', '>=3.5.2'
22 end
23
24 gem 'puma', '~>3.6', '>=3.6.0', :platforms=>:ruby
25 gem 'pg', '~>0.19', '>=0.19.0'
26 gem 'mongoid', '~>5.1', '>=5.1.5'
```

Jamess-MacBook-Pro:capstone_demoapp jim\$ vi Gemfile

Jamess-MacBook-Pro:capstone_demoapp jim\$ bundle


```
Using httparty 0.14.0
Using pry 0.10.4
Using rspec-core 3.5.4
Using rspec-expectations 3.5.0
Using rspec-mocks 3.5.0
Using activesupport 4.2.6
Using loofah 2.0.3
Using mail 2.6.4
Using pry-rails 0.3.4
Using rails-deprecated_sanitizer 1.0.3
Using globalid 0.3.7
Using activemodel 4.2.6
Using jbuilder 2.6.0
Using spring 2.0.0
Using rails-html-sanitizer 1.0.3
Using rails-dom-testing 1.0.7
Using activejob 4.2.6
Using activerecord 4.2.6
Using mongoid 5.1.5
Using actionview 4.2.6
Using actionpack 4.2.6
Using actionmailer 4.2.6
Using railties 4.2.6
Using sprockets-rails 3.2.0
Using rails-api 0.4.0
Using rspec-rails 3.5.2
Using rails 4.2.6
```

```
Bundle complete! 14 Gemfile dependencies, 60 gems now installed.
Use `bundle show [gemname]` to see where a bundled gem is installed.
```

```
Using rspec-expectations 3.5.0
Using rspec-mocks 3.5.0
Using ActiveSupport 4.2.6
Using loofah 2.0.3
Using mail 2.6.4
Using pry-rails 0.3.4
Using rails-deprecated_sanitizer 1.0.3
Using globalid 0.3.7
Using activemodel 4.2.6
Using jbuilder 2.6.0
Using spring 2.0.0
Using rails-html-sanitizer 1.0.3
Using rails-dom-testing 1.0.7
Using activejob 4.2.6
Using activerecord 4.2.6
Using mongoid 5.1.5
Using actionview 4.2.6
Using actionpack 4.2.6
Using actionmailer 4.2.6
Using railties 4.2.6
Using sprockets-rails 3.2.0
Using rails-api 0.4.0
Using rspec-rails 3.5.2
Using rails 4.2.6
```

```
Bundle complete! 14 Gemfile dependencies, 60 gems now installed.
Use `bundle show [gemname]` to see where a bundled gem is installed.
```

```
James-MacBook-Pro:capstone_demoapp jim$ rails c
```

```
Running via Spring preloader in process 5170
```

```
Loading development environment (Rails 4.2.6)
```

```
Running via Spring preloader in process 5170
Loading development environment (Rails 4.2.6)
```

```
[1] pry(main)> Bar.count
```

```
=> 3
```

```
[2] pry(main)> show-models
```

```
Foo
```

```
id: integer
```

```
name: string
```

```
created_at: datetime
```

```
updated_at: datetime
```

```
Bar
```

```
_id: BSON::ObjectId
```

```
created_at: Time
```

```
name: String
```

```
updated_at: Time
```

```
[3] pry(main)> show-routes
```

Prefix	Verb	URI Pattern	Controller#Action
foos	GET	/api/foos(.:format)	foos#index {.:format=>:json}
	POST	/api/foos(.:format)	foos#create {.:format=>:json}
foo	GET	/api/foos/:id(.:format)	foos#show {.:format=>:json}
	PATCH	/api/foos/:id(.:format)	foos#update {.:format=>:json}
	PUT	/api/foos/:id(.:format)	foos#update {.:format=>:json}
	DELETE	/api/foos/:id(.:format)	foos#destroy {.:format=>:json}
bars	GET	/api/bars(.:format)	bars#index {.:format=>:json}
	POST	/api/bars(.:format)	bars#create {.:format=>:json}
bar	GET	/api/bars/:id(.:format)	bars#show {.:format=>:json}
	PATCH	/api/bars/:id(.:format)	bars#update {.:format=>:json}
	PUT	/api/bars/:id(.:format)	bars#update {.:format=>:json}
	DELETE	/api/bars/:id(.:format)	bars#destroy {.:format=>:json}


```
[2] pry(main)> show-models
```

Foo

```
id: integer
name: string
created_at: datetime
updated_at: datetime
```

Bar

```
_id: BSON::ObjectId
created_at: Time
name: String
updated_at: Time
```

```
[3] pry(main)> show-routes
```

Prefix	Verb	URI Pattern	Controller#Action
foos	GET	/api/foos(:format)	foos#index {:format=>:json}
	POST	/api/foos(:format)	foos#create {:format=>:json}
foo	GET	/api/foos/:id(:format)	foos#show {:format=>:json}
	PATCH	/api/foos/:id(:format)	foos#update {:format=>:json}
	PUT	/api/foos/:id(:format)	foos#update {:format=>:json}
	DELETE	/api/foos/:id(:format)	foos#destroy {:format=>:json}
bars	GET	/api/bars(:format)	bars#index {:format=>:json}
	POST	/api/bars(:format)	bars#create {:format=>:json}
bar	GET	/api/bars/:id(:format)	bars#show {:format=>:json}
	PATCH	/api/bars/:id(:format)	bars#update {:format=>:json}
	PUT	/api/bars/:id(:format)	bars#update {:format=>:json}
	DELETE	/api/bars/:id(:format)	bars#destroy {:format=>:json}

```
[4] pry(main)> .rake
```

```
/Users/jim/.rbenv/versions/2.2.3/bin/ruby -I/Users/jim/.rbenv/versions/2.2.3/lib/ruby/gems/2.2.0/gems/rspec-core-3.5.4/lib:/Users/jim/.rbenv/versions/2.2.3/lib/ruby/gems/2.2.0/gems/rspec-support-3.5.0/lib /Users/jim/.rbenv/versions/2.2.3/lib/ruby/gems/2.2.0/gems/rspec-core-3.5.4/exe/rspec --pattern spec/\*\*\{,/\*/\*\*\}/\*_spec.rb
```

```
POST /api/bars(:format) bars#create {:format=>:json}
bar GET /api/bars/:id(:format) bars#show {:format=>:json}
PATCH /api/bars/:id(:format) bars#update {:format=>:json}
PUT /api/bars/:id(:format) bars#update {:format=>:json}
DELETE /api/bars/:id(:format) bars#destroy {:format=>:json}
```

```
[4] pry(main)> .rake
```

```
/Users/jim/.rbenv/versions/2.2.3/bin/ruby -I/Users/jim/.rbenv/versions/2.2.3/lib/ruby/gems/2.2.0/gems/rspec-core-3.5.4/lib:/Users/jim/.rbenv/versions/2.2.3/lib/ruby/gems/2.2.0/gems/rspec-support-3.5.0/lib /Users/jim/.rbenv/versions/2.2.3/lib/ruby/gems/2.2.0/gems/rspec-core-3.5.4/exe/rspec --pattern spec/\*\*\{,\^\*\*\}\/*_spec.rb
```

ApiDevelopments

RDBMS-backed

create RDBMS-backed model

expose RDBMS-backed API resource

MongoDB-backed

create MongoDB-backed model

Return value is: nil

```
[7, 16] in /Users/jim/proj/fullstack/capstone_demoapp/app/controllers/bars_controller.rb
```

```
7:   end
8:
9:   def show
10:     #render json: @bar
11:     byebug
=> 12:   end
13:
14:   def create
15:     @bar = Bar.new(bar_params)
16:
```

```
bar GET    /api/bars/:id(.:format) bars#show {format=>:json}
      PATCH /api/bars/:id(.:format) bars#update {format=>:json}
      PUT   /api/bars/:id(.:format) bars#update {format=>:json}
      DELETE /api/bars/:id(.:format) bars#destroy {format=>:json}
```

```
[4] pry(main)> .rake
```

```
/Users/jim/.rbenv/versions/2.2.3/bin/ruby -I/Users/jim/.rbenv/versions/2.2.3/lib/ruby/gems/2.2.0/gems/rspec-core-3.5.4/lib:/Users/jim/.rbenv/versions/2.2.3/lib/ruby/gems/2.2.0/gems/rspec-support-3.5.0/lib /Users/jim/.rbenv/versions/2.2.3/lib/ruby/gems/2.2.0/gems/rspec-core-3.5.4/exe/rspec --pattern spec/\*\*\{,\^\*\^\*\}\/*_spec.rb
```

ApiDevelopments

RDBMS-backed

```
create RDBMS-backed model
```

```
expose RDBMS-backed API resource
```

MongoDB-backed

```
create MongoDB-backed model
```

```
Return value is: nil
```

```
[7, 16] in /Users/jim/proj/fullstack/capstone_demoapp/app/controllers/bars_controller.rb
```

```
7:   end
8:
9:   def show
10:     #render json: @bar
11:     byebug
=> 12:   end
13:
14:   def create
15:     @bar = Bar.new(bar_params)
16:
```

```
(byebug) pry-shell
```


Return value is: nil

[7, 16] in /Users/jim/proj/fullstack/capstone_demoapp/app/controllers/bars_controller.rb

```
7:   end
8:
9:   def show
10:     #render json: @bar
11:     byebug
=> 12:   end
13:
14:   def create
15:     @bar = Bar.new(bar_params)
16:
```

(byebug) pry-shell

[1] pry(#<BarsController>)> show-models

ActiveRecord::SchemaMigration

version: string

Foo

id: integer

name: string

created_at: datetime

updated_at: datetime

DEPRECATION WARNING: ActiveRecord::Fixtures is deprecated! Use ActiveRecord::FixtureSet instead. (called from show at (byebug):1)

Bar

_id: BSON::ObjectId

created_at: Time

name: String

updated_at: Time

Return value is: nil

[7, 16] in /Users/jim/proj/fullstack/capstone_demoapp/app/controllers/bars_controller.rb

```
7:   end
8:
9:   def show
10:     #render json: @bar
11:     byebug
=> 12:   end
13:
14:   def create
15:     @bar = Bar.new(bar_params)
16:
```

(byebug) pry-shell

[1] pry(#<BarsController>)> show-models

ActiveRecord::SchemaMigration

version: string

Foo

id: integer

name: string

created_at: datetime

updated_at: datetime

DEPRECATION WARNING: ActiveRecord::Fixtures is deprecated! Use ActiveRecord::FixtureSet instead. (called from show at (byebug):1)

Bar

_id: BSON::ObjectId

created_at: Time

name: String

updated_at: Time

ActiveModel::Validations#methods: errors invalid? validate validates_with

ActiveModel::Validations::HelperMethods#methods:

validates_absence_of validates_confirmation_of validates_inclusion_of validates_size_of

validates_acceptance_of validates_exclusion_of validates_numericality_of

ActiveModel::Conversion#methods: to_model to_param to_partial_path

ActiveModel::Serialization#methods: read_attribute_for_serialization

ActiveModel::Serializers::JSON#methods: from_json

ActiveModel::Serializers::Xml#methods: from_xml to_xml

Mongoid::Atomic#methods:

_updates atomic_attribute_name atomic_pulls delayed_atomic_sets

add_atomic_pull atomic_delete_modifier atomic_pushes delayed_atomic_unsets

add_atomic_unset atomic_insert_modifier atomic_sets flag_as_destroyed

atomic_array_add_to_sets atomic_path atomic_unsets flagged_destroys

atomic_array_pulls atomic_paths atomic_updates process_flagged_destroys

atomic_array_pushes atomic_position delayed_atomic_pulls

Mongoid::Changeable#methods:

changed changed_attributes children_changed? post_persist remove_change

changed? changes move_changes previous_changes setters

Mongoid::Clients::Options#methods: persistence_options with

Mongoid::Clients#methods: collection collection_name mongo_client

Mongoid::Attributes::Readonly#methods: attribute_writable?

Mongoid::Attributes::Processing#methods: process_attributes

Mongoid::Attributes#methods:

□ attributes= read_attribute_before_type_cast

□= attributes_before_type_cast remove_attribute

assign_attributes has_attribute? write_attribute

attribute_missing? has_attribute_before_type_cast? write_attributes

attribute_present? raw_attributes

attributes read_attribute


```
changed changed_attributes children_changed? post_persist remove_change
changed? changes move_changes previous_changes setters
```

```
Mongoid::Clients::Options#methods: persistence_options with
```

```
Mongoid::Clients#methods: collection collection_name mongo_client
```

```
Mongoid::Attributes::Readonly#methods: attribute_writable?
```

```
Mongoid::Attributes::Processing#methods: process_attributes
```

```
Mongoid::Attributes#methods:
```

```
□ attributes= read_attribute_before_type_cast
□= attributes_before_type_cast remove_attribute
assign_attributes has_attribute? write_attribute
attribute_missing? has_attribute_before_type_cast? write_attributes
attribute_present? raw_attributes
attributes read_attribute
```

```
Mongoid::Fields#methods:
```

```
apply_default apply_post_processed_defaults attribute_names lazy_settable?
apply_defaults apply_pre_processed_defaults database_field_name using_object_ids?
```

```
#<Module:0x007fab7389fe60>#methods:
```

```
_id created_at_was reset_created_at_to_default!
_id= created_at_will_change! reset_name!
_id? id reset_name_to_default!
_id_before_type_cast id= reset_updated_at!
_id_change name reset_updated_at_to_default!
_id_changed? name= updated_at
_id_changed_from_default? name? updated_at=
_id_was name_before_type_cast updated_at?
_id_will_change! name_change updated_at_before_type_cast
created_at name_changed? updated_at_change
created_at= name_changed_from_default? updated_at_changed?
```

```
[3] pry(#<BarsController>)> cd @bar
```

ActiveModel::Validations#methods: errors invalid? validate validates_with

ActiveModel::Validations::HelperMethods#methods:

validates_absence_of validates_confirmation_of validates_inclusion_of validates_size_of

validates_acceptance_of validates_exclusion_of validates_numericality_of

ActiveModel::Conversion#methods: to_model to_param to_partial_path

ActiveModel::Serialization#methods: read_attribute_for_serialization

ActiveModel::Serializers::JSON#methods: from_json

ActiveModel::Serializers::Xml#methods: from_xml to_xml

Mongoid::Atomic#methods:

_updates atomic_attribute_name atomic_pulls delayed_atomic_sets

add_atomic_pull atomic_delete_modifier atomic_pushes delayed_atomic_unsets

add_atomic_unset atomic_insert_modifier atomic_sets flag_as_destroyed

atomic_array_add_to_sets atomic_path atomic_unsets flagged_destroys

atomic_array_pulls atomic_paths atomic_updates process_flagged_destroys

atomic_array_pushes atomic_position delayed_atomic_pulls

Mongoid::Changeable#methods:

changed changed_attributes children_changed? post_persist remove_change

changed? changes move_changes previous_changes setters

Mongoid::Clients::Options#methods: persistence_options with

Mongoid::Clients#methods: collection collection_name mongo_client

Mongoid::Attributes::Readonly#methods: attribute_writable?

Mongoid::Attributes::Processing#methods: process_attributes

Mongoid::Attributes#methods:

□ attributes= read_attribute_before_type_cast

□= attributes_before_type_cast remove_attribute

assign_attributes has_attribute? write_attribute

attribute_missing? has_attribute_before_type_cast? write_attributes

attribute_present? raw_attributes

attributes read_attribute

Jamess-MacBook-Pro:capstone_demoapp jim\$


```
1
2 source 'https://rubygems.org'
3
4 gem 'rails', '4.2.6'
5 gem 'rails-api', '~>0.4', '>=0.4.0'
6 gem 'pry-rails', '~>0.3', '>=0.3.4'
7 gem 'rack-cors', '~>0.4', '>=0.4.0', :require => 'rack/cors'
8
9 gem 'jbuilder', '~> 2.0', '>=2.6.0'
10
11 group :development do
12   gem 'spring', '~>2.0', '>=2.0.0'
13 end
14
15 group :development, :test do
16   gem 'webrick', '~>1.3', '>=1.3.1', :platforms=>[:mingw, :mswin, :x64_mingw, :jruby]
17   gem 'tzinfo-data', :platforms=>[:mingw, :mswin, :x64_mingw, :jruby]
18   gem 'byebug', '~>9.0', '>=9.0.6'
19   gem 'httparty', '~>0.14', '>=0.14.0'
20
21   gem 'rspec-rails', '~> 3.5', '>=3.5.2'
22 end
23
24 gem 'puma', '~>3.6', '>=3.6.0', :platforms=>:ruby
25 gem 'pg', '~>0.19', '>=0.19.0'
26 gem 'mongoid', '~>5.1', '>=5.1.5'
```



```
1 #
2 source 'https://rubygems.org'
3
4 gem 'rails', '4.2.6'
5 gem 'rails-api', '~>0.4', '>=0.4.0'
6 gem 'pry-rails', '~>0.3', '>=0.3.4'
7 gem 'rack-cors', '~>0.4', '>=0.4.0', :require => 'rack/cors'
8
9 gem 'jbuilder', '~> 2.0', '>=2.6.0'
10
11 group :development do
12   gem 'spring', '~>2.0', '>=2.0.0'
13 end
14
15 group :development, :test do
16   gem 'webrick', '~>1.3', '>=1.3.1', :platforms=>[:mingw, :mswin, :x64_mingw, :jruby]
17   gem 'tzinfo-data', :platforms=>[:mingw, :mswin, :x64_mingw, :jruby]
18   gem 'byebug', '~>9.0', '>=9.0.6'
19   gem 'pry-byebug', '~>3.4', '>=3.4.0'
20   gem 'httparty', '~>0.14', '>=0.14.0'
21
22   gem 'rspec-rails', '~> 3.5', '>=3.5.2'
23 end
24
25 gem 'puma', '~>3.6', '>=3.6.0', :platforms=>:ruby
26 gem 'pg', '~>0.19', '>=0.19.0'
27 gem 'mongoid', '~>5.1', '>=5.1.5'
```

```
1 class BarsController < ApplicationController
2   before_action :set_bar, only: [:show, :update, :destroy]
3
4   def index
5     @bars = Bar.all
6     #render json: @bars
7   end
8
9   def show
10    #render json: @bar
11    byebug
12  end
13
14  def create
15    @bar = Bar.new(bar_params)
16
17    if @bar.save
18      #render json: @bar, status: :created, location: @bar
19      render :show, status: :created, location: @bar
20    else
21      render json: @bar.errors, status: :unprocessable_entity
22    end
23  end
24
25  def update
26    @bar = Bar.find(params[:id])
27
28    if @bar.update(bar_params)
29      head :no_content
```

```
1 class BarsController < ApplicationController
2   before_action :set_bar, only: [:show, :update, :destroy]
3
4   def index
5     @bars = Bar.all
6     #render json: @bars
7   end
8
9   def show
10    #render json: @bar
11    bi
12  end
13
14  def create
15    @bar = Bar.new(bar_params)
16
17    if @bar.save
18      #render json: @bar, status: :created, location: @bar
19      render :show, status: :created, location: @bar
20    else
21      render json: @bar.errors, status: :unprocessable_entity
22    end
23  end
24
25  def update
26    @bar = Bar.find(params[:id])
27
28    if @bar.update(bar_params)
29      head :no_content
```



```
1 class BarsController < ApplicationController
2   before_action :set_bar, only: [:show, :update, :destroy]
3
4   def index
5     @bars = Bar.all
6     #render json: @bars
7   end
8
9   def show
10    #render json: @bar
11    binding.pry
12  end
13
14  def create
15    @bar = Bar.new(bar_params)
16
17    if @bar.save
18      #render json: @bar, status: :created, location: @bar
19      render :show, status: :created, location: @bar
20    else
21      render json: @bar.errors, status: :unprocessable_entity
22    end
23  end
24
25  def update
26    @bar = Bar.find(params[:id])
27
28    if @bar.update(bar_params)
29      head :no_content
```

Jamess-MacBook-Pro:capstone_demoapp jim\$ vi Gemfile

Jamess-MacBook-Pro:capstone_demoapp jim\$ vi app/controllers/bars_controller.rb

Jamess-MacBook-Pro:capstone_demoapp jim\$ rake

```
Jamess-MacBook-Pro:capstone_demoapp jim$ vi Gemfile
Jamess-MacBook-Pro:capstone_demoapp jim$ vi app/controllers/bars_controller.rb
Jamess-MacBook-Pro:capstone_demoapp jim$ rake
/Users/jim/.rbenv/versions/2.2.3/bin/ruby -I/Users/jim/.rbenv/versions/2.2.3/lib/ruby/gems/2.2.0/gems/rspec-core-3.5.4/lib:/Users/jim/.rbenv/versions/2.2.3/lib/ruby/gems/2.2.0/gems/rspec-support-3.5.0/lib /Users/jim/.rbenv/versions/2.2.3/lib/ruby/gems/2.2.0/gems/rspec-core-3.5.4/exe/rspec --pattern spec/\*\*\{,\*\/*\*\}/\*_spec.rb
```

ApiDevelopments

RDBMS-backed

```
create RDBMS-backed model
expose RDBMS-backed API resource
```

MongoDB-backed

```
create MongoDB-backed model
```

From: /Users/jim/proj/fullstack/capstone_demoapp/app/controllers/bars_controller.rb @ line 12 BarsController#show:

```
9: def show
10:   #render json: @bar
11:   binding.pry
=> 12: end
```

[1] pry(#<BarsController>)> █


```
1 #
2 source 'https://rubygems.org'
3
4 gem 'rails', '4.2.6'
5 gem 'rails-api', '~>0.4', '>=0.4.0'
6 gem 'pry-rails', '~>0.3', '>=0.3.4'
7 gem 'rack-cors', '~>0.4', '>=0.4.0', :require => 'rack/cors'
8
9 gem 'jbuilder', '~> 2.0', '>=2.6.0'
10
11 group :development do
12   gem 'spring', '~>2.0', '>=2.0.0'
13 end
14
15 group :development, :test do
16   gem 'webrick', '~>1.3', '>=1.3.1', :platforms=>[:mingw, :mswin, :x64_mingw, :jruby]
17   gem 'tzinfo-data', :platforms=>[:mingw, :mswin, :x64_mingw, :jruby]
18   gem 'byebug', '~>9.0', '>=9.0.6'
19   gem 'pry-byebug', '~>3.4', '>=3.4.0'
20   gem 'httparty', '~>0.14', '>=0.14.0'
21
22   gem 'rspec-rails', '~> 3.5', '>=3.5.2'
23 end
24
25 gem 'puma', '~>3.6', '>=3.6.0', :platforms=>:ruby
26 gem 'pg', '~>0.19', '>=0.19.0'
27 gem 'mongoid', '~>5.1', '>=5.1.5'
```

```
1 #
2 source 'https://rubygems.org'
3
4 gem 'rails', '4.2.6'
5 gem 'rails-api', '~>0.4', '>=0.4.0'
6 gem 'pry-rails', '~>0.3', '>=0.3.4'
7 gem 'rack-cors', '~>0.4', '>=0.4.0', :require => 'rack/cors'
8
9 gem 'jbuilder', '~> 2.0', '>=2.6.0'
10
11 group :development do
12   gem 'spring', '~>2.0', '>=2.0.0'
13 end
14
15 group :development, :test do
16   gem 'webrick', '~>1.3', '>=1.3.1', :platforms=>[:mingw, :mswin, :x64_mingw, :jruby]
17   gem 'tzinfo-data', :platforms=>[:mingw, :mswin, :x64_mingw, :jruby]
18   gem 'byebug', '~>9.0', '>=9.0.6'
19   gem 'pry-byebug', '~>3.4', '>=3.4.0'
20   gem 'httparty', '~>0.14', '>=0.14.0'
21
22   gem 'rspec-rails', '~> 3.5', '>=3.5.2'
23 end
24
25 gem 'puma', '~>3.6', '>=3.6.0', :platforms=>:ruby
26 gem 'pg', '~>0.19', '>=0.19.0'
27 gem 'mongoid', '~>5.1', '>=5.1.5'
```

```
1
2 source 'https://rubygems.org'
3
4 gem 'rails', '4.2.6'
5 gem 'rails-api', '~>0.4', '>=0.4.0'
6 gem 'pry-rails', '~>0.3', '>=0.3.4'
7 gem 'rack-cors', '~>0.4', '>=0.4.0', :require => 'rack/cors'
8
9 gem 'jbuilder', '~> 2.0', '>=2.6.0'
10
11 group :development do
12   gem 'spring', '~>2.0', '>=2.0.0'
13 end
14
15 group :development, :test do
16   gem 'webrick', '~>1.3', '>=1.3.1', :platforms=>[:mingw, :mswin, :x64_mingw, :jruby]
17   gem 'tzinfo-data', :platforms=>[:mingw, :mswin, :x64_mingw, :jruby]
18   gem 'byebug', '~>9.0', '>=9.0.6'
19   gem 'pry-byebug', '~>3.4', '>=3.4.0'
20   gem 'httparty', '~>0.14', '>=0.14.0'
21
22   gem 'rspec-rails', '~> 3.5', '>=3.5.2'
23 end
24
25 gem 'puma', '~>3.6', '>=3.6.0', :platforms=>:ruby
26 gem 'pg', '~>0.19', '>=0.19.0'
27 gem 'mongoid', '~>5.1', '>=5.1.5'
```



```
1 #
2 source 'https://rubygems.org'
3
4 gem 'rails', '4.2.6'
5 gem 'rails-api', '~>0.4', '>=0.4.0'
6 gem 'pry-rails', '~>0.3', '>=0.3.4'
7 gem 'rack-cors', '~>0.4', '>=0.4.0', :require => 'rack/cors'
8
9 gem 'jbuilder', '~> 2.0', '>=2.6.0'
10
11 group :development do
12   gem 'spring', '~>2.0', '>=2.0.0'
13 end
14
15 group :development, :test do
16   gem 'webrick', '~>1.3', '>=1.3.1', :platforms=>[:mingw, :mswin, :x64_mingw, :jruby]
17   gem 'tzinfo-data', :platforms=>[:mingw, :mswin, :x64_mingw, :jruby]
18   gem 'byebug', '~>9.0', '>=9.0.6'
19   gem 'pry-byebug', '~>3.4', '>=3.4.0'
20   gem 'httparty', '~>0.14', '>=0.14.0'
21
22   gem 'rspec-rails', '~> 3.5', '>=3.5.2'
23 end
24
25 group :production do
26   gem 'rails_12factor', '~>0.0', '>= 0.0.3'
27 end
28
29 gem 'puma', '~>3.6', '>=3.6.0', :platforms=>:ruby
```

Jamess-MacBook-Pro:capstone_demoapp jim\$ vi Gemfile

Jamess-MacBook-Pro:capstone_demoapp jim\$ bundle

```
Using rails_12factor 0.0.3
Using rspec-core 3.5.4
Using rspec-expectations 3.5.0
Using rspec-mocks 3.5.0
Using activesupport 4.2.6
Using loofah 2.0.3
Using mail 2.6.4
Using pry-byebug 3.4.0
Using pry-rails 0.3.4
Using rails-deprecated_sanitizer 1.0.3
Using globalid 0.3.7
Using activemodel 4.2.6
Using jbuilder 2.6.0
Using spring 2.0.0
Using rails-html-sanitizer 1.0.3
Using rails-dom-testing 1.0.7
Using activejob 4.2.6
Using activerecord 4.2.6
Using mongoid 5.1.5
Using actionview 4.2.6
Using actionpack 4.2.6
Using actionmailer 4.2.6
Using railties 4.2.6
Using sprockets-rails 3.2.0
Using rails-api 0.4.0
Using rspec-rails 3.5.2
Using rails 4.2.6
```

```
Bundle complete! 16 Gemfile dependencies, 64 gems now installed.
Use `bundle show [gemname]` to see where a bundled gem is installed.
```

```
1
2 source 'https://rubygems.org'
3
4 gem 'rails', '4.2.6'
5 gem 'rails-api', '~>0.4', '>=0.4.0'
6 gem 'pry-rails', '~>0.3', '>=0.3.4'
7 gem 'rack-cors', '~>0.4', '>=0.4.0', :require => 'rack/cors'
8
9 gem 'jbuilder', '~> 2.0', '>=2.6.0'
10
11 group :development do
12   gem 'spring', '~>2.0', '>=2.0.0'
13 end
14
15 group :development, :test do
16   gem 'webrick', '~>1.3', '>=1.3.1', :platforms=>[:mingw, :mswin, :x64_mingw, :jruby]
17   gem 'tzinfo-data', :platforms=>[:mingw, :mswin, :x64_mingw, :jruby]
18   gem 'byebug', '~>9.0', '>=9.0.6'
19   gem 'pry-byebug', '~>3.4', '>=3.4.0'
20   gem 'httparty', '~>0.14', '>=0.14.0'
21
22   gem 'rspec-rails', '~> 3.5', '>=3.5.2'
23 end
24
25 group :production do
26   gem 'rails_12factor', '~>0.0', '>= 0.0.3'
27 end
28
29 gem 'puma', '~>3.6', '>=3.6.0', :platforms=>:ruby
```



```
3
4 gem 'rails', '4.2.6'
5 gem 'rails-api', '~>0.4', '>=0.4.0'
6 gem 'pry-rails', '~>0.3', '>=0.3.4'
7 gem 'rack-cors', '~>0.4', '>=0.4.0', :require => 'rack/cors'
8
9 gem 'jbuilder', '~> 2.0', '>=2.6.0'
10
11 group :development do
12   gem 'spring', '~>2.0', '>=2.0.0'
13 end
14
15 group :development, :test do
16   gem 'webrick', '~>1.3', '>=1.3.1', :platforms=>[:mingw, :mswin, :x64_mingw, :jruby]
17   gem 'tzinfo-data', :platforms=>[:mingw, :mswin, :x64_mingw, :jruby]
18   gem 'sqlite3', '~>1.3', '>=1.3.12'
19   gem 'byebug', '~>9.0', '>=9.0.6'
20   gem 'pry-byebug', '~>3.4', '>=3.4.0'
21   gem 'httparty', '~>0.14', '>=0.14.0'
22
23   gem 'rspec-rails', '~> 3.5', '>=3.5.2'
24 end
25
26 group :production do
27   gem 'rails_12factor', '~>0.0', '>= 0.0.3'
28 end
29
30 gem 'puma', '~>3.6', '>=3.6.0', :platforms=>:ruby
31 gem 'pg', '~>0.19', '>=0.19.0'
```

```
4 gem 'rails', '4.2.6'
5 gem 'rails-api', '~>0.4', '>=0.4.0'
6 gem 'pry-rails', '~>0.3', '>=0.3.4'
7 gem 'rack-cors', '~>0.4', '>=0.4.0', :require => 'rack/cors'
8
9 gem 'jbuilder', '~> 2.0', '>=2.6.0'
10
11 group :development do
12   gem 'spring', '~>2.0', '>=2.0.0'
13 end
14
15 group :development, :test do
16   gem 'webrick', '~>1.3', '>=1.3.1', :platforms=>[:mingw, :mswin, :x64_mingw, :jruby]
17   gem 'tzinfo-data', :platforms=>[:mingw, :mswin, :x64_mingw, :jruby]
18   gem 'sqlite3', '~>1.3', '>=1.3.12'
19   gem 'byebug', '~>9.0', '>=9.0.6'
20   gem 'pry-byebug', '~>3.4', '>=3.4.0'
21   gem 'httparty', '~>0.14', '>=0.14.0'
22
23   gem 'rspec-rails', '~> 3.5', '>=3.5.2'
24 end
25
26 group :production do
27   gem 'rails_12factor', '~>0.0', '>= 0.0.3'
28 end
29
30 gem 'puma', '~>3.6', '>=3.6.0', :platforms=>:ruby
31 gem 'mongoid', '~>5.1', '>=5.1.5'
```

```
4 gem 'rails', '4.2.6'
5 gem 'rails-api', '~>0.4', '>=0.4.0'
6 gem 'pry-rails', '~>0.3', '>=0.3.4'
7 gem 'rack-cors', '~>0.4', '>=0.4.0', :require => 'rack/cors'
8
9 gem 'jbuilder', '~> 2.0', '>=2.6.0'
10
11 group :development do
12   gem 'spring', '~>2.0', '>=2.0.0'
13 end
14
15 group :development, :test do
16   gem 'webrick', '~>1.3', '>=1.3.1', :platforms=>[:mingw, :mswin, :x64_mingw, :jruby]
17   gem 'tzinfo-data', :platforms=>[:mingw, :mswin, :x64_mingw, :jruby]
18   gem 'sqlite3', '~>1.3', '>=1.3.12'
19   gem 'byebug', '~>9.0', '>=9.0.6'
20   gem 'pry-byebug', '~>3.4', '>=3.4.0'
21   gem 'httparty', '~>0.14', '>=0.14.0'
22
23   gem 'rspec-rails', '~> 3.5', '>=3.5.2'
24 end
25
26 group :production do
27   gem 'rails_12factor', '~>0.0', '>= 0.0.3'
28   gem 'pg', '~>0.19', '>=0.19.0'
29 end
30
31 gem 'puma', '~>3.6', '>=3.6.0', :platforms=>:ruby
32 gem 'mongoid', '~>5.1', '>=5.1.5'
```

Jamess-MacBook-Pro:capstone_demoapp jim\$ vi Gemfile

Jamess-MacBook-Pro:capstone_demoapp jim\$ bundle

Jamess-MacBook-Pro:capstone_demoapp jim\$ vi Gemfile

Jamess-MacBook-Pro:capstone_demoapp jim\$ bundle --without product

Jamess-MacBook-Pro:capstone_demoapp jim\$ vi Gemfile

Jamess-MacBook-Pro:capstone_demoapp jim\$ bundle --without production

```
Using rspec-core 3.5.4
Using rspec-expectations 3.5.0
Using rspec-mocks 3.5.0
Using activesupport 4.2.6
Using loofah 2.0.3
Using mail 2.6.4
Using pry-bybug 3.4.0
Using pry-rails 0.3.4
Using rails-deprecated_sanitizer 1.0.3
Using globalid 0.3.7
Using activemodel 4.2.6
Using jbuilder 2.6.0
Using spring 2.0.0
Using rails-html-sanitizer 1.0.3
Using rails-dom-testing 1.0.7
Using activejob 4.2.6
Using activerecord 4.2.6
Using mongoid 5.1.5
Using actionview 4.2.6
Using actionpack 4.2.6
Using actionmailer 4.2.6
Using railties 4.2.6
Using sprockets-rails 3.2.0
Using rails-api 0.4.0
Using rspec-rails 3.5.2
Using rails 4.2.6
```

Bundle complete! 17 Gemfile dependencies, 61 gems now installed.

Gems in the group production were not installed.

Use `bundle show [gemname]` to see where a bundled gem is installed.

Summary

✧ byebug

Summary

- ✧ byebug
- ✧ pry shell

Summary

- ✧ byebug
- ✧ pry shell
- ✧ rails_12factor

Summary

- ✧ byebug
- ✧ pry shell
- ✧ rails_12factor
- ✧ sqlite in development profile

Summary

- ✧ byebug
- ✧ pry shell
- ✧ rails_12factor
- ✧ sqlite in development profile

What's Next?

- ✧ API Deployment