

Search catalog

Q

For Enterprise



◀ Back to Week 3

X Lessons

Prev Next

Lesson 1 - Asynchronous Behavior, Promises and Ajax in Angular

Lesson 2 - Introduction to Custom Directives

Lesson 3 - Directive APIs, Manipulating the DOM, and transclude

- Lecture 30, Part 1: Directive 7 min
- Lecture 30, Part 2: Directive APIs and "&"
- Practice Quiz: 2 questions
 Quiz 29
- Lecture 31, Part 1:

 Manipulating the DOM with 4 min link
- Lecture 31, Part 2:

 Manipulating the DOM 14 min with link
- Practice Quiz:

 Quiz 30

 3 questions
- Lecture 32, Part 1: Using

 Directive's transclude to 2 min

Quiz 30
3 questions

To Pass 100% or higher

Deadline June 11, 11:59 PM PDT

Start










3/3 points (100%)



Next Item



1. To inject 'MyService' into the link function, you must do something similar to this:

1/1 points

```
1 MyLinkFunction.$inject = ['MyService'];
2 * function MyLinkFunction (MyService) {
3   //...
4 }
```

True or False?



True



False

Correct

Correct. The link function is called with preset arguments, so you can't directly inject anything into the link function.



2. The link function's 'element' argument refers to what?

1/1 points The root element of the HTML document



The top level element in the directive's template

 \leftarrow Quiz 30 Practice Quiz, 3 questions

3/3 points (100%)



The link function's 'element' argument refers to what?

The root element of the HTML document

The element configured through the DDO.

The top level element in the directive's template.

Top level element of the directive

Correct



What needs to be done in order to have the 'element' argument refer to a jQuery (not jqLite) object?

Inject jQuery service into the directive

Do a DOM lookup for the jQuery object.

Include jQuery JS library in the HTML before the AngularJS library is included.

Correct

Angular already uses jQuery by default, so nothing needs to be done.