

Search catalog

Q

For Enterprise



Next

⊀ Back to Week 3

X Lessons

Prev

Lesson 1 - Asynchronous Behavior, Promises and Ajax in Angular

- Welcome to Module 3 1 min
- Recommended Books 10 min
 - Lecture 24, Part 1:
- Asynchronous Behavior 5 min with Promises and \$q
- Practice Quiz: 1 question Quiz 22
- Lecture 24, Part 2: Asynchronous Behavior 15 min with Promises and \$q
- Practice Quiz: 3 questions Quiz 23
- Lecture 25, Part 1: Ajax with \$http Service
- **Practice Quiz:** 2 questions Quiz 24
- Lecture 25, Part 2: Ajax 14 min with \$http Service
- ENTER RAFFLE (ends April 10 min 23rd, 2017)
- Practice Quiz: Quiz 25

2 questions

PRACTICE QUIZ Quiz 25

2 questions

To Pass

100% or higher

Deadline


June 11, 11:59 PM PDT

Start









Quiz 25
Practice Quiz, 2 questions

2/2 points (100%)



Congratulations! You passed!

Next Item



1. In the following code snippet, what would be the output seen in the console?

1/1 points

```
1 * $http({
2   method: 'GET',
3   url: 'http://someurl.com'
4  })
5 * .then(function(response) {
6   console.log(response)
7  });
```

- The payload data sent from the server
- The full HTTP response, broken out into separate objects to represent response headers, payload data, etc.

Correct.

The then() method requires BOTH a success and an error functions, so this will be an error.



2. In the following code snippet, what property of the 'response' object needs to be referenced in



Quiz 25
Practice Quiz, 2 questions

2/2 points (100%)

Correct	
Correct.	

The then() method requires BOTH a success and an error functions, so this will be an error.



2. In the following code snippet, what property of the 'response' object needs to be referenced in order for the payload of the response to be output to the console?

1/1 points

```
1 - $http({
2   method: 'GET',
3   url: 'http://someurl.com'
4  })
5 - .then(function(response) {
   console.log(response.???)
7  });
```

payload

data

Correct

- http
- header.data