


University of
Kent

Supervisors



Defensive programming not defensible


Trying to deal with all possible failure modes for a module is doomed to failure ...
... just think about Donald Rumsfeld's "unknown unknowns"!



Supervisor and worker

Design **workers** to do a particular job ...

... assuming that the rest of the world is behaving appropriately,
... and if not, to fail.




Supervisor and worker

Design **workers** to do a particular job ...



... assuming that the rest of the world is behaving appropriately,
... and if not, to fail.

A **supervisor** will do the job of dealing with the failure ...

... restarting and taking other appropriate actions.



Supervision hierarchies



How to build a supervisor?

The supervisors spawns and links to the worker using `spawn_link`.


The supervisor monitors process failures ...

- ... and restarts the process / all processes / some processes.

- ... until some threshold (per second) exceeded.

The supervisor can choose to die itself ...

- ... letting its supervisor handle the problem.




Link or monitor?

It is also possible to monitor processes in Erlang.

A monitor provides a **one way, asymmetrical** linkage between processes.



We link supervisor and worker so that a worker will be killed if the supervisor dies ... can you think why?



A supervision scenario

Build a frequency multi-server system, with two servers, supervised by a single supervisor.

Try out various restart strategies for the system, using the observer to check which processes have been restarted.



The logo of the University of Kent is centered on the page. It features the words "University of" in a smaller, blue, sans-serif font, positioned above the word "Kent" in a larger, bold, blue, serif font. The text is set against a light gray rectangular background.

University of
Kent