

University of
Kent

Records

Maps

Binaries



Macros


Macros expanded by the Erlang Preprocessor, EPP.

Macros can take parameters.

Macros invoked with ?

Macros often stored in `include` files
??X is the argument X as a string.

```
%% defs.hrl  
  
-define(ONE, 1).  
  
-define(TWICE(F), (fun(P) -> F(F(P))end)).  
  
-define(FMT(S, As), io:format(S, As)).  
  
-define(SHOW(X), ?FMT("~p=~p~n", [??X, X])).
```



Macros

Macros expanded by the Erlang Preprocessor, EPP.

Macros can take parameters.

Macros invoked with ?

Macros often stored in `include` files
??X is the argument X as a string.

```
%% defs.hrl  
  
-define(ONE, 1).  
  
-define(TWICE(F), (fun(P) -> F(F(P))end)).  
  
-define(FMT(S,As), io:format(S,As)).  
  
-define(SHOW(X), ?FMT("~p=~p~n", [??X,X])).
```

```
-module(foo).  
  
-include("defs.hrl").  
  
succ(X)      -> X+?ONE.  
  
add_two(X)   -> ?TWICE(succ)(X).  
  
show()       -> ?SHOW(add_two(7)).
```

Records

Records expanded by the EPP.

Record use with #

Notations for

- construction,
- selection,
- pattern matching,
- update.

```
%% recs.hrl
```

```
-record(twitter, {name,handle}).
```


Records

Records expanded by the EPP.

Record use with #

Notations for

- construction,
- selection,
- pattern matching,
- update.

```
%% recs.hrl
```

```
-record/twitter, {name,handle}).
```

```
-module(foo).
```

```
-include("recs.hrl").
```

```
r1() -> #twitter{name="simon",  
                handle="@si"}.
```

```
get_name(X) -> X#twitter.name.
```

```
update_si(#twitter{name="simon"} = X) ->  
    X#twitter{name="si"};
```

```
update_si(X) ->  
    X.
```

Maps

Standard `map:xxx` notation
plus some extra syntax.

Notations for

- construction,
- selection,
- pattern matching,
- update.

`=>` can add a field,

`:=` updates only.

```
-module(foo).  
  
map1() -> #{name => "simon",  
           handle => "@si"}.  
  
get_name("#{name := Y}") -> Y.  
  
update_si("#{name := \"simon\"} = X) ->  
    X#{name := \"si\"};  
update_si(X) ->  
    X.
```


Binaries

Notations for binary data structures, and pattern mapping over them.

Ideal for protocol analysis and implementation.

E:5 matches 5 bits,

E matches $n \times 8$ bits.

```
1> Bin = <<22,23,24>>.
<<22,23,24>>
2> <<C:4,D:4,E:5,F:4,G:7>> = Bin.
<<22,23,24>>
3> C.
1
4> D.
6
5> E.
2
6> F.
14
7> G.
24
```


Binaries

Notations for binary data structures, and pattern mapping over them.

Ideal for protocol analysis and implementation.

E:5 matches 5 bits,

E matches $n \times 8$ bits.

```
1> Bin = <<22,23,24>>.
<<22,23,24>>
2> <<C:4,D:4,E:5,F:4,G:7>> = Bin.
<<22,23,24>>
3> C.
1
4> D.
6
5> E.
2
6> F.
14
7> G.
24
```

Binaries

Notations for binary data structures, and pattern mapping over them.

Ideal for protocol analysis and implementation.

E:5 matches 5 bits,

E matches $n \times 8$ bits.

```
1> Bin = <<22,23,24>>.
<<22,23,24>>
2> <<C:4,D:4,E:5,F:4,G:7>> = Bin.
<<22,23,24>>
3> C.
1
4> D.
6
5> E.
2
6> F.
14
7> G.
24
```


The logo of the University of Kent is centered on the page. It features the words "University of" in a smaller, blue, sans-serif font, positioned above the word "Kent" in a larger, bold, blue, serif font. The text is set against a light gray rectangular background.

University of
Kent