

Rapidly Building Apps on the Cloud

 [udemy.com/building-highly-scalable-apps-on-the-cloud/learn/v4/t/lecture/2963950](https://www.udemy.com/building-highly-scalable-apps-on-the-cloud/learn/v4/t/lecture/2963950)

Exercise 7b – Creating a user-provided service

Section 7, Lecture 45

Bluemix allows you to create a service local to your organization. The service needs to be running, not necessarily on Bluemix, but must be reachable from Bluemix. The service definition serves as a link between the running service and your Bluemix application.

To create a service use the Command Line Interface:

```
cf cups testService -p "host, port, user, password"
```

You will then be prompted for the values of the parameters. The values you enter will be stored with the service definition and passed to the applications binding to your service

```
C:\Users\Avnet>cf cups testService -p "host, port, user, password"
host> myhost.ibm.com
port> 12345
user> user1
password> passw0rd
Creating user provided service testService in org Avnet Academy / space Vinay as
vinay.gupta@avnet.com...
OK
```

It is also possible to specify the values in the command rather than being prompted:

```
cf cups testService -p '{"host":"myhost.ibm.com", "port":"12345", "user":"user1",
"password":"passw0rd"}'
```

Create your own user-defined service and add parameters for the service using the `-p` option. You can provide the values on the command line or be prompted for the parameters.

You can list the services and see the service is now available using `cf s`:

```
C:\Users\Avnet>cf s
Getting services in org Avnet Academy / space Vinay as vinay.gupta@avnet.com...
OK
```

name	service	plan	bound apps	status
MQLight	mqlight	standard	MQLsnd, MQLrcv	available
testService	user-provided			

If you need to update the values for the service use `cf uups`.


You can bind the service to an application like any other Bluemix service and the application can parse `VCAP_SERVICES` to access the parameters you provided:

```

{
  "mqlight": [
    {
      "name": "MQLight",
      "label": "mqlight",
      "plan": "standard",
      "credentials": {
        "username": "gQPrEE5Cqgm",
        "connectionLookupURI": "http://mqlightprod-lookup.ng.bluemix.net/Lookup?serviceId=bf71ac60-17e2-4349-bd93-85b5705a7634",
        "password": "jbJYdr4Aw8LM",
        "version": "2"
      }
    }
  ],
  "user-provided": [
    {
      "name": "testService",
      "label": "user-provided",
      "credentials": {
        "host": "myhost.ibm.com",
        "password": "passw0rd",
        "port": "12345",
        "user": "user1"
      }
    }
  ]
}

```

User-provided services can be deleted like any other Bluemix service using the Bluemix Web UI :



or using the command line **cf ds** :

```

C:\Users\Avnet>cf ds testService
Really delete the service testService??> y
Deleting service testService in org Avnet Academy / space Vinay as vinay.gupta@avnet.com...
OK

```