Neo4j.rb Screencast Series

Episode 1 Creating a Rails App

[brian@Brians-MacBook-Air.local:o +1] ~/github/neo4j-contrib \$

[brian@Brians-MacBook-Air.local:o +1] ~/github/neo4j-contrib \$ rails

udemy

3. bash

[brian@Brians-MacBook-Air.local:o +1] ~/github/neo4j-contrib \$ rails new asset_portal -m http://neo4jrb.io/neo4j/neo4j.rb -0

udemy

illerm Shell Edit View Profiles Toolbelt Window Help

300 ...

3. ruby

test/controllers/.keep create test/mailers create test/mailers/.keep create test/models create test/models/.keep create create test/helpers test/helpers/.keep create create test/integration test/integration/.keep create test/test_helper.rb create create tmp/cache tmp/cache/assets create vendor/assets/javascripts create vendor/assets/javascripts/.keep create vendor/assets/stylesheets create vendor/assets/stylesheets/.keep create apply http://neo4jrb.io/neo4j/neo4j.rb gemfile neo4j (~> 5.0.0) insert config/application.rb bundle install run

```
Using rails 4.2.3
```

Using rdoc 4.2.0

Using sass 3.4.15

Using tilt 1.4.1

Using sass-rails 5.0.3

Using sdoc 0.4.1

Using spring 1.3.6

Using turbolinks 2.5.3

Using uglifier 2.7.1

Using web-console 2.1.3

Bundle complete! 12 Gemfile dependencies, 67 gems now installed.

Use `bundle show [gemname]` to see where a bundled gem is installed.

run bundle exec spring binstub --all

- * bin/rake: spring inserted
- * bin/rails: spring inserted

[brian@Brians-MacBook-Air.local:o +1] ~/github/neo4j-contrib

\$ cd asset_portal

[brian@Brians-MacBook-Air.local:o +1] ~/github/neo4j-contrib/asset_portal

udemy

\$

[brian@Brians-MacBook-Air.local:o +1] ~/github/neo4j-contrib/asset_portal
\$ rake neo4j:install[community-latest,development]

```
x neo4j-community-2.2.3/conf/neo4j-wrapper.conf
x neo4j-community-2.2.3/conf/logging.properties
x neo4j-community-2.2.3/conf/windows-wrapper-logging.properties
x neo4j-community-2.2.3/conf/neo4j-server.properties
x neo4j-community-2.2.3/CHANGES.txt
x neo4j-community-2.2.3/LICENSE.txt
x neo4j-community-2.2.3/bin/utils
x neo4j-community-2.2.3/bin/neo4j-import
x neo4j-community-2.2.3/bin/neo4j-installer
x neo4j-community-2.2.3/bin/neo4j-shell
x neo4j-community-2.2.3/bin/neo4j
x neo4j-community-2.2.3/system/resources/
x neo4j-community-2.2.3/system/resources/org.neo4j.server.plist
x neo4j-community-2.2.3/UPGRADE.txt
Neo4j Installed in to neo4j directory.
```

Type 'rake neo4j:start' or 'rake neo4j:start[ENVIRONMENT]' to start it Type 'neo4j:config[ENVIRONMENT,PORT]' for changing server port, (default 7474)

[brian@Brians-MacBook-Air.local:o +1] ~/github/neo4j-contrib/asset_portal \$

```
[brian@Brians-MacBook-Air.local:o +1] ~/github/neo4j-contrib/asset_portal
$ rake neo4j:config[development,7000]
Config Neo4j development for port 7000
```


brian@Brians-MacBook-Air.local:o +1] ~/github/neo4j-contrib/asset_portal
\$


\$ rake neo4j:start[development]

```
[brian@Brians-MacBook-Air.local:o +1] ~/github/neo4j-contrib/asset_portal
$ rake neo4j:config[development,7000]
Config Neo4j development for port 7000

[brian@Brians-MacBook-Air.local:o +1] ~/github/neo4j-contrib/asset_portal
```

Starting Neo4j development...
Starting Neo4j Server...WARNING: not changing user
process [17896]... waiting for server to be ready...





Sublime Text 2 File Edit Selection Find View Goto Tools Project Window Help

3 @ ♥ ···
UNREGISTERED


```
- development.rb - asset portal
FOLDERS
                     development.rb
W asset portal
                         config.eager_toau = Talse
                    TΒ
                   11
                   12
                         # Show full error reports and disable caching.
 ► config
                   13
                          config.consider_all_requests_local
                          config.action controller.perform caching = false
                   14
                   15
 ▶ public
                   16
                         # Don't care if the mailer can't send.


    best

                         config.action_mailer.raise_delivery_errors = false
                   17
 IF vendor
                   18
  .gitignore
                   19
                         # Print deprecation notices to the Rails logger.
  config.ru
                   20
                         config.active_support.deprecation = :log
  Cemfile
  Cemfile.lock
                   21
  Rakefile
                   22
                         # Debug mode disables concatenation and preprocessing of assets.
  README.rdoc
                   23
                         # This option may cause significant delays in view rendering with a large
                         # number of complex assets.
                   24
                   25
                         config.assets.debug = true
                   26
                   27
                         # Asset digests allow you to set far-future HTTP expiration dates on all assets,
                         # yet still be able to expire them through the digest params.
                   28
                          config.assets.digest = true
                   29
                   30
                   31
                         # Adds additional error checking when serving assets at runtime.
                          # Checks for improperly declared sprockets dependencies.
                   32
                   33
                          # Raises helpful error messages.
                   34
                          config.assets.raise_runtime_errors = true
                   35
                   36
                         # Raises error for missing translations
                   37
                         # config.action_view.raise_on_missing_translations = true
                   38
                   39
                          config.neo4j.session_type = :server_db
                          config.neo4j.session_path = 'http://localhost:7000'
                   40
                   41
```

```
[brian@Brians-MacBook-Air.local:o +1] ~/github/neo4j-contrib/asset_portal
$ rails g model Asset title:string created_at:datetime updated_at:datetime
     invoke
             neo4j
     create
               app/models/asset.rb
     invoke
               test_unit
     create
                 test/models/asset_test.rb
                 test/fixtures/assets.yml
     create
```

[brian@Brians-MacBook-Air.local:o +1] ~/github/neo4j-contrib/asset_portal \$







\$ rails c
Loading development environment (Rails 4.2.3)
2.2.0 :001 > Asset.create(title: 'A predictive analysis of predictive analytics')
 CYPHER 21ms CREATE CONSTRAINT ON (n:`Asset`) ASSERT n.`uuid` IS UNIQUE
 CYPHER 9ms CREATE (n:`Asset` {props}) RETURN ID(n) | {:props=>{:uuid=>"8f58f200-027d-4a93-a2ce-6e6989ce26bf", :title=>"A predictive analysis of predictive analytics", :created_at=>1435778277, :updated_at=>1435778277}}

=> #<Asset uuid: "8f58f200-027d-4a93-a2ce-6e6989ce26bf", created_at: Wed, 01 Jul 20 15 19:17:57 +0000, title: "A predictive analysis of predictive analytics", updated_a t: Wed, 01 Jul 2015 19:17:57 +0000> 2.2.0 :002 > ■

udemy

[brian@Brians-MacBook-Air.local:o +1] ~/github/neo4j-contrib/asset_portal

- \$ rails c
 Loading development environment (Rails 4.2.3)
- 2.2.0 :001 > Asset.create(title: 'A predictive analysis of predictive analytics')
- CYPHER 21ms CREATE CONSTRAINT ON (n: `Asset`) ASSERT n. `uuid` IS UNIQUE
- CYPHER 9ms CREATE (n: Asset` {props}) RETURN ID(n) | {:props=>{:uuid=>"8f58f200-027
- d-4a93-a2ce-6e6989ce26bf", :title=>"A predictive analysis of predictive analytics",
- :created_at=>1435778277, :updated_at=>1435778277}}
- => #<Asset uuid: "8f58f200-027d-4a93-a2ce-6e6989ce26bf", created_at: Wed, 01 Jul 20
- 15 19:17:57 +0000, title: "A predictive analysis of predictive analytics", updated_a
- t: Wed, 01 Jul 2015 19:17:57 +0000>
- 2.2.0 :002 > Asset.first
- CYPHER 46ms MATCH (n: `Asset`) RETURN n ORDER BY n.uuid LIMIT {limit_1} | {:limit_1=
- >1}
- => #<Asset uuid: "7e01e388-c926-42aa-ad5b-5183ec5deb81", created_at: Wed, 01 Jul 20
- 15 19:14:05 +0000, title: "Data crunching in the cloud", updated_at: Wed, 01 Jul 201
- 5 19:14:05 +0000>
- 2.2.0 :003 >

```
Rails App
```


```
brian@Brians-MacBook-Air.local o +1 ~/github/neo4j-contrib/asset_portal
$ rails g controller assets
     create app/controllers/assets_controller.rb
     invoke
            erb
     create app/views/assets
     invoke test_unit
     create test/controllers/assets_controller_test.rb
     invoke
            helper
     create
               app/helpers/assets_helper.rb
     invoke
               test_unit
     invoke
            assets
               coffee
     invoke
                 app/assets/javascripts/assets.coffee
     create
     invoke
               SCSS
                 app/assets/stylesheets/assets.scss
     create
```

[brian@Brians-MacBook-Air.local:o +1] ~/github/neo4j-contrib/asset_portal
\$ [






README. I doc



Rails App * asset_portal ► a00 Save ► bin ⇒ config Save As: Index.html.er F db ► lib Tags: ► log **▶** public II 🖽 🖽 ICI 🔡 🖰 assets Q Search **№** test I trep assets Favorites ▶ vendor layouts m Dropbox .gitignore config.ru (Cloud Drive Cemfile y^Δ_c Applications Gemfile.lock IIII Desktop Rakefile README.rdoc (9) Documents O Downloads m github Projects Coogle Drive Devices Remote Disc Cancel New Folder Save







[brian@Brians-MacBook-Air.local:o +1] ~/github/neo4j-contrib/asset_portal

- \$ rails s
- => Booting WEBrick
- => Rails 4.2.3 application starting in development on http://localhost:3000
- => Run `rails server -h` for more startup options
- => Ctrl-C to shutdown server
- [2015-07-01 14:12:11] INFO WEBrick 1.3.1
- [2015-07-01 14.12.11] TNFO ruby 2 2 0 (2014-12-25) [v86 64-darwin14]






































A predictive analysis of predictive analytics