

Streaming Computation

Section 1

In this Section, we are going to take a look at...

- Introduction
- Enumerables
- Streams
- Flow

Enumerables

In this Video, we are going to take a look at...


- Collection types and Enumerable
- Using Enumerable types interchangeably
- Transforming Enumerables

Collection Types

Data types that allow the composition of other data types.

Collection Types

Data types that allow the composition of other data types.



Collection Types

Data types that allow the composition of other data types.

```
→ ~ iex
Erlang/OTP 19 [erts-8.2] [source] [64-bit] [smp:8:8] [async-threads:10] [hipe] [
kernel-poll:false] [dtrace]

Interactive Elixir (1.4.2) - press Ctrl+C to exit (type h() ENTER for help)
iex(1)> list = [1,2,3,4]
[1, 2, 3, 4]
iex(2)> map = %{one: 1, two: 2}
%{one: 1, two: 2}
iex(3)> Enum.at(list, 0)
1
iex(4)> Enum.at(map, 0)
{:one, 1}
iex(5)> defmodule Sizeable do
...(5)> def first(enum) do
...(5)> Enum.at(enum, 0)
...(5)> end
...(5)> end
{:module, Sizeable,
 <<70, 79, 82, 49, 0, 0, 4, 212, 66, 69, 65, 77, 69, 120, 68, 99, 0, 0, 0, 149,
    131, 104, 2, 100, 0, 14, 101, 108, 105, 120, 105, 114, 95, 100, 111, 99, 115,

    95, 118, 49, 108, 0, 0, 0, 4, 104, 2, ...>>, {:first, 1}}
iex(6)> █
```


Collection Types

Data types that allow the composition of other data types.

```
Erlang/OTP 19 [erts-8.2] [source] [64-bit] [smp:8:8] [async-threads:10] [hipe] [
kernel-poll:false] [dtrace]

Interactive Elixir (1.4.2) - press Ctrl+C to exit (type h() ENTER for help)
iex(1)> list = [1,2,3,4]
[1, 2, 3, 4]
iex(2)> map = %{one: 1, two: 2}
%{one: 1, two: 2}
iex(3)> Enum.at(list, 0)
1
iex(4)> Enum.at(map, 0)
{:one, 1}
iex(5)> defmodule Sizeable do
...(5)> def first(enum) do
...(5)> Enum.at(enum, 0)
...(5)> end
...(5)> end
{:module, Sizeable,
 <<70, 79, 82, 49, 0, 0, 4, 212, 66, 69, 65, 77, 69, 120, 68, 99, 0, 0, 0, 149,
    131, 104, 2, 100, 0, 14, 101, 108, 105, 120, 105, 114, 95, 100, 111, 99, 115,

    95, 118, 49, 108, 0, 0, 0, 4, 104, 2, ...>>, {:first, 1}}
iex(6)> Sizeable.first(list)
1
iex(7)> Sizeable.first(map)
```


Enumerable

A protocol that binds Enumerable
collection types

Enumerable

A protocol that binds Enumerable collection types

- Collections have a variable number of elements
- One can verify if an element belongs to a collection
- Collections can be reduced by means of a function and an accumulator

Enumerable

Enum

- Collections have a variable number of elements
- One can verify if an element belongs to a collection
- Collections can be reduced by means of a function and an accumulator

Enumerable

Enum

List

Map

Transformations

Transforming collections by filtering, mapping, and reducing their elements.



Transformations

Transforming collections
by filtering, mapping, and
reducing their elements.

```
→ ~ iex
Erlang/OTP 19 [erts-8.2] [source] [64-bit] [smp:8:8] [async-threads:10] [hipe] [
kernel-poll:false] [dtrace]

Interactive Elixir (1.4.2) - press Ctrl+C to exit (type h() ENTER for help)
iex(1)> 1..1000
1..1000
iex(2)> 1..1000 |> Enum.filter(fn(x) -> rem(x, 2) == 0 end)
[2, 4, 6, 8, 10, 12, 14, 16, 18, 20, 22, 24, 26, 28, 30, 32, 34, 36, 38, 40, 42,
 44, 46, 48, 50, 52, 54, 56, 58, 60, 62, 64, 66, 68, 70, 72, 74, 76, 78, 80, 82,
 84, 86, 88, 90, 92, 94, 96, 98, 100, ...]
iex(3)> 1..1000 |> Enum.filter(fn(x) -> rem(x, 2) == 0 end) |> Enum.map(fn(x) ->
x * x end)
[4, 16, 36, 64, 100, 144, 196, 256, 324, 400, 484, 576, 676, 784, 900, 1024,
 1156, 1296, 1444, 1600, 1764, 1936, 2116, 2304, 2500, 2704, 2916, 3136, 3364,
 3600, 3844, 4096, 4356, 4624, 4900, 5184, 5476, 5776, 6084, 6400, 6724, 7056,
 7396, 7744, 8100, 8464, 8836, 9216, 9604, 10000, ...]
iex(4)> 1..1000 |> Enum.filter(fn(x) -> rem(x, 2) == 0 end) |> Enum.map(fn(x) ->
x * x end) |> Enum.reduce(1, fn(x, acc) -> x * a
```


Transformations

Transforming collections
by filtering, mapping, and
reducing their elements.

[illegible]

Project Euler

- Exercise 1:
 - If we list all the natural numbers below 10 that are multiples of 3 or 5, we get 3, 5, 6, and 9
 - The sum of these multiples is 23
 - Find the sum of all the multiples of 3 or 5 below 1000



<https://projecteuler.net/>

Project Euler — 1

If we list all the natural numbers below 10 that are multiples of 3 or 5, we get 3, 5, 6, and 9. The sum of these multiples is 23.

Find the sum of all the multiples of 3 or 5 below 1000.

```
➔ ~ iex
Erlang/OTP 19 [erts-8.2] [source] [64-bit] [smp:8:8] [async-threads:10] [hipe] [
kernel-poll:false] [dtrace]

Interactive Elixir (1.4.2) - press Ctrl+C to exit (type h() ENTER for help)
iex(1)> range = 1..9
1..9
iex(2)> range |> Enum.filter(fn(x) -> rem(x, 3) == 0 || rem(x, 5) == 0 end) |> E
num.reduce(0, fn(x, acc) -> x + acc end)
23
iex(3)> █
```

Project Euler — 1

If we list all the natural numbers below 10 that are multiples of 3 or 5, we get 3, 5, 6, and 9. The sum of these multiples is 23.

Find the sum of all the multiples of 3 or 5 below 1000.

```
➔ ~ iex
Erlang/OTP 19 [erts-8.2] [source] [64-bit] [smp:8:8] [async-threads:10] [hipe] [
kernel-poll:false] [dtrace]

Interactive Elixir (1.4.2) - press Ctrl+C to exit (type h() ENTER for help)
iex(1)> range = 1..9
1..9
iex(2)> range |> Enum.filter(fn(x) -> rem(x, 3) == 0 || rem(x, 5) == 0 end) |> E
num.reduce(0, fn(x, acc) -> x + acc end)
23
iex(3)> range = 1..999
1..999
iex(4)> range |> Enum.filter(fn(x) -> rem(x, 3) == 0 || rem(x, 5) == 0 end) |> E
num.reduce(0, fn(x, acc) -> x + acc end)
```