




Lo primero será importar nuestro laboratorio vulnerable (Máquina Windows 7), el cual haremos doble clic sobre el archivo .ova y se importará en virtualbox:



A continuación activamos la opción de adaptador puente en esta máquina para que sea visible para el resto de dispositivos de mi red:



Y haremos lo mismo con nuestra máquina kali atacante:



Dentro de la máquina kali, tendremos que identificar la IP de nuestro objetivo (máquina Windows 7), de tal forma que ejecutaremos el siguiente comando para encontrar hosts dentro de mi red:

```
arp-scan -I eth0 --localnet
```

```

(elrincondelhacker@elrincondelhacker)-[~]
$ sudo arp-scan -I eth0 --localnet
[sudo] contraseña para elrincondelhacker:
Interface: eth0, type: EN10MB, MAC: 08:00:27:7a:07:6a, IPv4: 192.168.228.26
WARNING: Cannot open MAC/Vendor file ieee-oui.txt: Permission denied
WARNING: Cannot open MAC/Vendor file mac-vendor.txt: Permission denied
Starting arp-scan 1.10.0 with 256 hosts (https://github.com/royhills/arp-scan)
192.168.228.73 3e:f6:5b:10:8e:73 (Unknown: locally administered)
192.168.228.141 52:27:ee:60:1d:a9 (Unknown: locally administered)
192.168.228.172 08:00:27:4d:11:1f (Unknown)

6 packets received by filter, 0 packets dropped by kernel
Ending arp-scan 1.10.0: 256 hosts scanned in 2.119 seconds (120.81 hosts/sec). 3 responded

```

Una vez encontrada la máquina víctima (me baso en la MAC para saber que es ella), lanzo mi escaneo de puertos con nmap:

```
nmap -p- -sS -sC -sV --min-rate 5000 -n -vvv -Pn 192.168.228.172
```

```

PORT      STATE SERVICE      REASON          VERSION
135/tcp   open  msrpc        syn-ack ttl 128 Microsoft Windows RPC
139/tcp   open  netbios-ssn  syn-ack ttl 128 Microsoft Windows netbios-ssn
445/tcp   open  microsoft-ds syn-ack ttl 128 Windows 7 Home Basic 7601 Service Pack 1 microsoft-ds (workstation)
49152/tcp open  msrpc        syn-ack ttl 128 Microsoft Windows RPC
49153/tcp open  msrpc        syn-ack ttl 128 Microsoft Windows RPC
49154/tcp open  msrpc        syn-ack ttl 128 Microsoft Windows RPC
49155/tcp open  msrpc        syn-ack ttl 128 Microsoft Windows RPC
49156/tcp open  msrpc        syn-ack ttl 128 Microsoft Windows RPC
49157/tcp open  msrpc        syn-ack ttl 128 Microsoft Windows RPC
MAC Address: 08:0C:29:34:15:BC (VMware)
Service Info: Host: MICROCH0FT; OS: Windows; CPE: cpe:/o:microsoft:windows

Host script results:
|_ p2p-conficker:
|   Checking for Conficker.C or higher...
|   Check 1 (port 41159/tcp): CLEAN (Couldn't connect)
|   Check 2 (port 35827/tcp): CLEAN (Couldn't connect)
|   Check 3 (port 7356/udp): CLEAN (Timeout)
|   Check 4 (port 31891/udp): CLEAN (Failed to receive data)
|   0/4 checks are positive: Host is CLEAN or ports are blocked
|_ smb2-security-mode:
|   2.1:0:
|     Message signing enabled but not required
|_ smb2-time:
|   1.0:0:

```

Una vez identificados los puestos, lanzamos otro escaneo de puertos pero para identificar vulnerabilidades, y así habremos identificado correctamente la vulnerabilidad CVE-2017-0143:

```
nmap -p445 -sS --script='vuln' -vvv -Pn 192.168.0.25
```

```
PORT    STATE SERVICE      REASON
445/tcp open  microsoft-ds syn-ack ttl 128
MAC Address: 00:0C:29:34:15:BC (VMware)
```

Host script results:

```
| smb-vuln-ms17-010:
|   VULNERABLE:
|     Remote Code Execution vulnerability in Microsoft SMBv1 servers (ms17-010)
|     State: VULNERABLE
|     IDs: CVE:CVE-2017-0143
|     Risk factor: HIGH
|       A critical remote code execution vulnerability exists in Microsoft SMBv1
|       servers (ms17-010).
```