

Exercise set 1

Advanced Course in Machine Learning

Enrico Buratto

Exercise 1

We want to evaluate the risk for the loss

$$\mathcal{L}(y, x, \alpha) = (y - \hat{y})^2 = (y - \alpha x)^2$$

Task a

The general definition of risk is the following:

$$\begin{aligned} R(\delta) &= \mathbb{E}_{p(y,x)}[\mathcal{L}(y, \delta(x))] \\ &= \int_{x,y} \mathcal{L}(y, \delta(x)) p(y, x) dx dy \end{aligned}$$

Where $\mathcal{L}(y, \delta(x))$ is the expected loss and $p(y, x)$ is the distribution that generates the data points. In this case, we know both:

$$\begin{aligned} \mathcal{L}(y, \delta(x)) &= \mathcal{L}(y, x, \alpha) = (y - \hat{y})^2 = (y - \alpha x)^2 \\ p(x, y) &= p(x)p(y|x) \end{aligned}$$

In the last equation, we know both $p(x)$ and $p(y|x)$:

- x is sampled uniformly in $[-3, 3]$, thus this is a simple continuous distribution. Therefore, its probability density function is

$$\mathbf{f}_{\mathbf{x}}(x) = \begin{cases} \frac{1}{b-a} = \frac{1}{6} & \text{for } x \in [-3, 3] \\ 0 & \text{otherwise} \end{cases}$$

- $y|x$ is sampled uniformly in $[2x - \frac{1}{2}, 2x + \frac{1}{2}]$, thus this is another simple continuous distribution. Therefore, its probability density function is

$$\mathbf{f}_{\mathbf{y}|\mathbf{x}}(y|x) = \begin{cases} \frac{1}{b-a} = 1 & \text{for } y \in [2x - \frac{1}{2}, 2x + \frac{1}{2}] \\ 0 & \text{otherwise} \end{cases}$$

Combining the two, we then the joint density function

$$\mathbf{f}_{\mathbf{x},\mathbf{y}}(x, y) = \begin{cases} 1 & \text{for } x \in [-3, 3], y \in [2x - \frac{1}{2}, 2x + \frac{1}{2}] \\ 0 & \text{otherwise} \end{cases}$$

We can then compute the risk $R(\alpha)$:

$$\begin{aligned} R(\alpha) &= \int_{x,y} \frac{1}{6} (y - \alpha x)^2 dx dy \\ &= \int_{2x-\frac{1}{2}}^{2x+\frac{1}{2}} \int_{-3}^3 \frac{1}{6} (y - \alpha x)^2 dx dy \\ &= \int_{2x-\frac{1}{2}}^{2x+\frac{1}{2}} y^2 + 3x^2 dy \\ &= 3\alpha^2 + 4x^2 + \frac{1}{12} \end{aligned}$$

The α that gives the smallest risk is, therefore $\alpha = 0$.

Task 2

Exercise 2

We start with this optimization problem

$$\begin{aligned} \min x^2 + y^2 \\ \text{s.t. } 3x - y + 2 \leq 0 \end{aligned}$$

For convenience, we will call the function to optimize $f(x, y)$ and the inequality constraint $g(x, y)$.

Task a

The Lagrangian function for this problem is the following:

$$\begin{aligned} \Lambda(x, y, \lambda) &= f(x, y) + \lambda g(x, y) \\ &= x^2 + y^2 + \lambda(3x - y + 2) \end{aligned}$$

The constraints for x, y to be optimal are:

- There is $\lambda \geq 0$ such that $\nabla f = -\lambda \nabla g$;
- Either $\lambda = 0$ or $g(x, y) = 0$.

Task b

In order to find an optimal solution, we first compute the gradient of the lagrangian function calculating the partial derivatives with respect to x, y and λ . We then have that:

$$\nabla \Lambda = \begin{pmatrix} 2x + 3\lambda \\ 2y - \lambda \\ 3x - y + 2 \end{pmatrix}$$

We then solve the linear system $\nabla \Lambda = \mathbf{0}$. With trivial math we get:

$$x = -\frac{3}{5}$$

$$y = \frac{1}{5}$$

$$\lambda = \frac{2}{5}$$

Finally, we check if the results respect the KKT conditions reported in Task a. Since $\lambda \neq 0$, in order for the solution to be optimal we must find $g(x, y) = g\left(-\frac{3}{5}, \frac{1}{5}\right) = 0$; otherwise, the solution is not optimal. Let's then check:

$$g\left(-\frac{3}{5}, \frac{1}{5}\right) = 3\frac{-3}{5} - \frac{1}{5} + 2 = 0 \leq 0$$

The constraints are respected, thus the solution is optimal.

Exercise 5

In order to apply PCA with 2 dimensions I used the code from Exercise 4. The additional code I used is the following:

```

# Data preparation
X = loadtxt('elec2022.txt', usecols=([i for i in range(1,56)]))
parties = loadtxt('elec2022.txt', usecols=(0))
# (changed the file using commas for convenience)
parties_names = pd.read_csv('parties.txt', sep=',', header=None)

# Apply PCA using TMC code
x1, x2 = pca(X)

# Prepare output
df = pd.DataFrame()
df['party'] = parties
df['party'] = df['party'].map(parties_names.set_index(0)[1])
df['x1'] = x1
df['x2'] = x2
df = df.groupby(['party']).mean().reset_index()

# Plot the results
fig, ax = plt.subplots()
ax.scatter(df['x1'], df['x2'])
for i, txt in enumerate(df['party']):
    ax.annotate(txt, (df['x1'][i], df['x2'][i]))
plt.xlabel('Component 1')
plt.ylabel('Component 2')
fig.set_dpi(100)

```

The figure I created, with the party labels on each point, follows.




Figure 1: Plot of averages of the two PCA components