

WISEASY P5

EMV Android POS



Quad Cortex-A53
at 2.0GHz



2GB LPDDR4 + 32GB eMMC



Android 11



Professional
scanning module



5.5-inch full screen
with thin bezel


























High-speed
thermal printer

- Equipped with Quad-core processor and Android 11 Operating System for better performance and lower power consumption
- 5.5-inch full screen with thin bezel
- More compact paper cabin for smaller size
- Professional thermal printer for speed up to 100mm/s
- Finely crafted curves, comfortable one-hand operation experience



Charging Cradle (Optional)

Technical Specifications

 Model Name P5	 Operating System WiseOS 3.0 Based on Android 11	 CPU Quad Cortex-A53 at 2.0GHz	 Memory 2GB LPDDR4 + 32GB eMMC	 Security Processor Max 32555
 Display 5.5 inch IPS Screen, 1280x720 HD Capacitive Multi-Point Touch Panel	 Network 2G/3G/4G	 WIFI 2.4G/5G, IEEE802.11 a/b/g/n/ac	 Bluetooth Bluetooth5.0, BLE	 GPS GPS/A-GPS, Glonass, Beidou
 Camera Front Camera: 2M FF(optional) Rear Camera: 5M AF (2D Scan Engine optional)	 Fingerprint FAP10, FBI/STQC (Optional)	 Audio Speaker: 1W Mic (optional)	 NFC 13.56MHz, ISO/IEC14443 TypeA&B, Mifare S50/S70, Felica	 Card Readers MSR: ISO7810-7813 3 tracks IC Card: ISO7816
 Card Slot 2*Micro SIM slot + 2*PSAM Slot +1*T-Flash slot, up to 128GB * Fiscal Module optional	 Button Power Button / Scan Button	 Battery Removable Lithium polymer battery, 7.4V/2620mAh	 Peripheral Ports Type C USB2.0 OTG 5*Pogo Pin	 Weight 443g
 Size (L*W*H) 209.09*78.59*19mm	 Printer 2"High Speed Thermal Printer Roll Size: 58*40mm Print Speed: 100mm/s Laboratory tested	 Adapter Input: AC 100-240V, 50/60Hz Output: 5V/2A	 Environment Storage temperature: -20°C to 60°C Operating temperature: -10°C to 55°C Humidity: ≤95%	 Accessories Optional: Charging Cradle, Multi-port Charging Cradle

Certifications

EMV CT L1/L2, EMV CTLS L1, VISA, Mastercard, AMEX, Discover, UPI, JCB, Pure, Interac, Rupay, MCCS, NSICCS, VCCS, PCI PTS 6.1, TQM, eftpos, FCC, IC, CE, CB, BIS, WPC, CEC, CA65, DOE, RoHs, WEEE, OFCA, Google GMS