YOHO model for Audio Segmentation and Sound Event Detection

Davide Capone [SM3500601] Enrico Stefanel [SM3500554]
{davide.capone, enrico.stefanel}@studenti.units.it

Data Science and Scientific Computing Master's Course
Department of Mathematics and Geosciences
University of Trieste

A.Y. 2023–2024

Contents

Audio Segmentation and Sound Event Detection

The goal of automatic sound event detection (SED) methods is to recognize what is happening in an audio signal and when it is happening[1]. In practice, the goal is to recognize at what temporal instances different sounds are active within an audio signal. An example of sound event detection is presented below.



Figure 1: Event Detection in an audio track.

[1] Annamaria Mesaros et al. "Sound Event Detection: A tutorial". In: *IEEE Signal Processing Magazine* 38 (2021), pp. 67–83. URL: https://api.semanticscholar.org/CorpusID:235795366.

Datasets

Common datasets for Audio Segmentation and Sound Event Detection problems are:

- **TUT Sound Event Detection**: primarily consists of street recordings with traffic and other activity, with audio examples of 2.56 s and a total size of approximately 1.5 h. It has six unique audio classes – Brakes Squeaking, Car, Children, Large Vehicle, People Speaking, and People Walking;
- **Urban-SED**: purely synthetic dataset, with audio example of 10 s and a total size of about 30 h. It has ten unique audio classes – Air Conditioner, Car Horn, Children Playing, Dog Bark, Drilling, Engine Idling, Gun Shot, Jackhammer, Siren, and Street Music.

The first dataset is too small to train a Neural Network model and requires use of augmentation techniques (we used **SpecAugment**[2]).

[2] Daniel S. Park et al. "SpecAugment: A Simple Data Augmentation Method for Automatic Speech Recognition". In: *Interspeech 2019*. 2019, pp. 2613–2617. DOI: 10.21437/Interspeech.2019-2680.

Metrics

A popular toolbox for Sound Event Detection models evaluation is **SED Eval**[3].

$$\text{Precision} = \frac{\text{TP}}{\text{TP} + \text{FP}} \qquad \text{Recall} = \frac{\text{TP}}{\text{TP} + \text{FN}}$$

$$\text{F}_1\text{-score} = 2 \times \frac{\text{Precision} \times \text{Recall}}{\text{Precision} + \text{Recall}}$$

where TP, FP and FN are respectively (for each audio segment):

- the ground truth and system output both indicate an event to be active;
- the ground truth indicates an event to be inactive, but the system as active;
- the ground truth indicates an event to be active, but the system as inactive.

[3] Annamaria Mesaros, Toni Heittola, and Tuomas Virtanen. "Metrics for Polyphonic Sound Event Detection". In: *Applied Sciences* 6.6 (2016). ISSN: 2076-3417. DOI: 10.3390/app6060162. URL: https://www.mdpi.com/2076-3417/6/6/162.

YOHO model

Presented in 2021, **YOHO**[4] is a novel and lightweight real-time algorithm for *audio segmentation* and *sound event detection*:

- it aims to detect acoustic classes and their temporal boundaries by treating the problem as a **regression task**;
- inspired by *YOLO* algorithm for machine vision.

[4] Satvik Venkatesh, David Moffat, and Eduardo Reck Miranda. "You Only Hear Once: A YOLO-like Algorithm for Audio Segmentation and Sound Event Detection". In: *Applied Sciences* 12.7 (Mar. 2022), p. 3293. ISSN: 2076-3417. DOI: 10.3390/app12073293. URL: http://dx.doi.org/10.3390/app12073293.

Input shape

The input of the network is a spectrogram



Figure 2: An example of mel-spectrogram.

Network Architecture

YOHO uses the MobileNet architecture as a backbone

Output shape



Figure 3: The YOHO output shape.

Loss Function

$$\mathcal{L}_c(\hat{y}, y) = \begin{cases} (\hat{y}_1 - y_1)^2 + \\ (\hat{y}_2 - y_2)^2 + (\hat{y}_3 - y_3)^2 & \text{if } y_1 = 1 \\ (\hat{y}_1 - y_1)^2, & \text{if } y_1 = 0 \end{cases}$$

where y and $\hat{y}$ are the ground-truth and predictions respectively. $y_1 = 1$ if the acoustic class is present and $y_1 = 0$ if the class is absent. y_2 and y_3, which are the start and endpoints for each acoustic class are considered only if $y = 1$. In other words, $(\hat{y}_1 - y_1)^2$ corresponds to **the classification loss** and $(\hat{y}_2 - y_2)^2 + (\hat{y}_3 - y_3)^2$ corresponds to **the regression loss**.

Other Details

...

Implementation challenges

Starting from the original paper, we implemented the system using PyTorch[5], writing the code keeping in mind that it had to be **clear** and permit **reproducible tests**.

```
$ python3 -m yoho.train --help
usage: train.py [-h] [--name NAME] [--epochs EPOCHS] [--batch-size BATCH_SIZE] [--cosine-annealing]
[--autocast] [--spec-augment]

options:
  -h, --help            show this help message and exit
  --name NAME           The name of the model
  --epochs EPOCHS       The number of epochs to train the model
  --batch-size BATCH_SIZE
                        The batch size for training the model
  --cosine-annealing    Use cosine annealing learning rate scheduler
  --autocast            Use autocast to reduce memory usage
  --spec-augment        Augment the training data using SpecAugment
```

Listing 1: Training script parameters

We used ORFEO[6] computational resources for the trainings of the models.

[5] All the code is available at `https://github.com/enstit/YOHO24`.

[6] `https://www.areasciencepark.it/piattaforme-tecnologiche/data-center-orfeo/`

Training results



Figure 4: Training and validation loss for YOHO model on UrbanSED dataset.

Conclusions



Figure 5: The roadmap of our journey.

Conclusions

But, after all...

It's all about the journey, not the destination.

Thank you for your attention.