

YOHO model for Audio Segmentation and Sound Event Detection

Davide Capone [SM3500601] Enrico Stefanel [SM3500554]
`{davide.capone, enrico.stefanel}@studenti.units.it`

Data Science and Scientific Computing Master's Course
Department of Mathematics and Geosciences
University of Trieste

A.Y. 2023–2024

Contents

Introduction

YOHO model


Implementation details

Conclusions



Audio Segmentation and Sound Event Detection

...



Datasets

Common datasets for Audio Segmentation and Sound Event Detection problems are:

- **TUT Sound Event Detection:** primarily consists of street recordings with traffic and other activity, with audio examples of 2.56 s and a total size of approximately 1.5 h. It has six unique audio classes – Brakes Squeaking, Car, Children, Large Vehicle, People Speaking, and People Walking;
- **Urban-SED:** purely synthetic dataset, with audio example of 10 s and a total size of about 30 h. It has ten unique audio classes – Air Conditioner, Car Horn, Children Playing, Dog Bark, Drilling, Engine Idling, Gun Shot, Jackhammer, Siren, and Street Music.

An example of Urban-SED label is:

`[(gun_shot, 0.3, 1.11), (car_horn, 0.31, 1.41)]`

meaning that an occurrence of gun shot is present from the 0.3 s to 1.11 s, and a car horn from 0.31 s to 1.41 s.

Metrics

A popular toolbox for Polyphonic Sound Event Detection models evaluation is **SED Eval**¹.

$$\text{Precision} = \frac{\text{TP}}{\text{TP} + \text{FP}}$$

$$\text{Recall} = \frac{\text{TP}}{\text{TP} + \text{FN}}$$

$$F_1 \text{ score} = 2 * \frac{\text{Precision} \times \text{Recall}}{\text{Precision} + \text{Recall}}$$

¹Annamaria Mesaros, Toni Heittola, and Tuomas Virtanen. “Metrics for Polyphonic Sound Event Detection”. In: *Applied Sciences* 6.6 (2016). ISSN: 2076-3417. DOI: [10.3390/app6060162](https://doi.org/10.3390/app6060162). URL: <https://www.mdpi.com/2076-3417/6/6/162>.

YOHO model

Presented in 2021²...

²Satvik Venkatesh, David Moffat, and Eduardo Reck Miranda. “You Only Hear Once: A YOLO-like Algorithm for Audio Segmentation and Sound Event Detection”. In: *Applied Sciences* 12.7 (Mar. 2022), p. 3293. ISSN: 2076-3417. DOI: 10.3390/app12073293. URL: <http://dx.doi.org/10.3390/app12073293>.

Input shape

...



Network Architecture

...



Output shape




Figure: The YOHO output shape.

Loss Function

$$\mathcal{L}_c(\hat{y}, y) = \begin{cases} (\hat{y}_1 - y_1)^2 + \\ (\hat{y}_2 - y_2)^2 + (\hat{y}_3 - y_3)^2 & \text{if } y_1 = 1 \\ (\hat{y}_1 - y_1)^2, & \text{if } y_1 = 0 \end{cases}$$

where y and \hat{y} are the ground-truth and predictions respectively. $y_1 = 1$ if the acoustic class is present and $y_1 = 0$ if the class is absent. y_2 and y_3 , which are the start and endpoints for each acoustic class are considered only if $y = 1$. In other words, $(\hat{y}_1 - y_1)^2$ corresponds to **the classification loss** and $(\hat{y}_2 - y_2)^2 + (\hat{y}_3 - y_3)^2$ corresponds to **the regression loss**.

Other Details

...



Implementation details

...



Problems

...



Conclusions




Figure: The roadmap of our journey.

Conclusions

But, after all...

It's all about the journey, not the destination.

Thank you for your attention.