RZ86B-Monitor Series

86" 4K UHD Infrared Touch Monitor — Display Only (no internal PC)

RZ86B Touch Monitor is an 86-inch 4K UHD Infrared (IR) touchscreen without an internal PC — designed to pair with an external Windows / Mac / Linux PC, OPS module or media player via HDMI, VGA + USB Touch. Industrial-grade power supply, 30,000-hour extended-life LCD, full aluminum alloy frame, IP65 front surface and Mohs class 7 explosion-proof glass. 20-point IR multi-touch with industry-leading ultra-narrow bezel — engineered for 24/7 commercial use in conference rooms, lecture halls and large-format signage.

86"	4K UHD	5000:1	IR 20-pt	IP65
Display	3840 × 2160	Contrast	Touch	Front Surface

KEY FEATURES

- 86-inch 4K UHD industrial LCD — 30,000-hour extended life
- Full aluminum alloy frame — premium chassis
- Mohs class 7 explosion-proof glass
- 24/7 commercial use — industrial-grade power supply
- No internal PC — connect external PC via HDMI/VGA + USB Touch
- Industry-leading ultra-narrow screen bezel
- Surface IP65 waterproof — front panel
- IR 20-point touch — 32767×32767 accuracy
- Mounting: Wall / Desktop stand / Embedded
- Total power consumption: < 400 W

ENT Group Co., Ltd. | 70/5 Moo 4, Metro Biztown, Chaengwattana 2, Pak Kret, Nonthaburi 11120, Thailand
Tel: 02-045-6104, 095-739-1053 | Sales@entgroup.co.th | www.entgroup.co.th | Tax ID: 0135558013167

THREE CONFIGURATIONS

RZ86B — IR Touch Monitor

Display only — no internal PC

86-inch 4K UHD IR touch panel with HDMI/VGA/AV/RF inputs. Pair with any external PC, OPS module or media player. Plug-and-play USB touch — no driver required on Windows/Linux.

- No internal PC — flexible compute pairing
- Inputs: HDMI / VGA / AV / RF
- USB Touch (HID) + PC Audio in/out
- Power consumption < 400 W

Sister variants of the RZ86B chassis

Same 86" 4K panel, frame and mounting — different compute

- RZ86B-Monitor: Display only — pair with any external PC via HDMI/VGA + USB Touch
- RZ86B-X86: Intel Core i3-4Gen / i5-10Gen / i7-11Gen (OPS) with Windows 10 / 11 / Linux
- RZ86B-ARM: Rockchip RK3568 / RK3288 / RK3588 with Android 9 / 11 / 12

Same panel, frame and mounting options. Contact ENT Group sales for variant comparison and project-based recommendations.

TARGET INSTALLATIONS

POS Counter · Self-Service Kiosk · Reception Desk · Smart Office · Retail Display · Hospital Check-in · Library Terminal · Conference Room

ENT Group Co., Ltd. | 70/5 Moo 4, Metro Biztown, Chaengwattana 2, Pak Kret, Nonthaburi 11120, Thailand
Tel: 02-045-6104, 095-739-1053 | Sales@entgroup.co.th | www.entgroup.co.th | Tax ID: 0135558013167

TECHNICAL SPECIFICATIONS

Configuration

PC System	None — display only (external PC required)
Signal Inputs	HDMI in × 1, VGA × 1, AV in × 1, RF × 1
Touch Output	USB Touch (HID — driverless on Windows/Linux/macOS)
Audio	PC Audio in × 1 / Audio out × 1
Remote Control	Included

LCD Panel

Display Size	86 inches
Resolution	3840 × 2160 (4K UHD)
Aspect Ratio	16 : 9
Active Display Area	1893.4 × 1064.9 mm
Colors	16.7 M
Brightness	350 cd/m²
Contrast Ratio	5000 : 1
Viewing Angle (H/V)	178° / 178°
Backlight Lifetime	LED 50,000 hours
Refresh Rate	4K @ 30 Hz

Touch Panel

Technology	Infrared (IR)
Response Time	< 8 ms
Touch Points	20-point standard
Touch Recognition	≤ 15 ms
Cursor Speed	120 / s
Scanning Accuracy	32767 × 32767
Working Voltage / Current	DC +5 V ± 5% / 180 mA
Surface Hardness	Mohs class 7 explosion-proof glass

ENVIRONMENT, POWER & DIMENSIONS

Environment & Power

Operating Temperature	0 °C to 50 °C
Operating Humidity	10% to 80%
Storage Temperature	-5 °C to 60 °C
Storage Humidity	10% to 85%
Power Input	110–240 V AC, 50/60 Hz
Power Output	DC 12 V / 5 A
Standby Power	≤ 0.5 W
Overall Power Consumption	< 400 W

Dimensions & Weight

Machine Dimensions (W×H×T)	1954 × 1153 × 93 mm
Package Dimensions (W×H×T)	2070 × 1290 × 215 mm
Net Weight	63 kg
Gross Weight	74 kg
Surface Protection	IP65 (front)
Mounting	Wall mount / Floor stand / Embedded

I/O Ports

- HDMI in × 1
- AV in × 1
- USB × 1 (Touch)
- Audio out × 1
- VGA × 1
- RF × 1
- PC Audio in × 1
- Power Socket × 1

RECOMMENDED APPLICATIONS

Application	Description
POS & Counter	Restaurant POS, queue terminals, ticketing and check-in counters.
Self-Service Kiosk	Hospital queue, library check-in, government counters.
Retail & Showroom	Interactive product display and order-taking terminals.
Smart Office	Meeting room booking, attendance and access-control panels.
Industrial HMI	Operator interface, workshop dashboards and control terminals.

ENT Group Co., Ltd. | 70/5 Moo 4, Metro Biztown, Chaengwattana 2, Pak Kret, Nonthaburi 11120, Thailand
Tel: 02-045-6104, 095-739-1053 | Sales@entgroup.co.th | www.entgroup.co.th | Tax ID: 0135558013167

CONNECT & ORDER

How to order — B2B Quotation Workflow. ENT Group operates as a B2B procurement platform. Add items to your cart on entgroup.co.th, our sales team will review your request and respond with a formal quotation (PDF). This is not an online checkout — pricing, lead time and delivery terms are tailored to each project.

View Product Page

Scan to view RZ86B Series — full specs & accessories
entgroup.co.th/products/displays-86/rz86b

Add LINE Official

Chat with our sales team for quotations & support
LINE ID: @entgroup

Get a Tailored Quotation

Scan either QR code to connect with ENT Group instantly. Our B2B sales team will prepare a quotation tailored to your project — including volume pricing, customization, installation and warranty terms.

Tel 02-045-6104, 095-739-1053
Email Sales@entgroup.co.th
Web www.entgroup.co.th