HR49-X86 Series

49" Full HD IR Touch All-in-One with Intel x86 (OPS) Windows / Linux



HR49-X86 integrates an industrial Intel x86 OPS module (Core™ i3-4Gen / Core™ i5-10Gen / Core™ i7-11Gen) into the same 49-inch HR49 chassis. Pre-installed Windows 10 / 11 or Linux delivers a full PC experience with 10-point IR touch, gigabit Ethernet and dual-band WiFi. Designed for boardrooms, smart classrooms and digital signage — full aluminum alloy frame, IP65 front surface and Mohs class 7 explosion-proof glass for 24/7 commercial use.

49"	Full HD	1400:1	IR 10-pt	IP65
Display	1920 × 1080	Contrast	Touch	Front Surface

KEY FEATURES

- 49-inch industrial LCD — 30,000-hour extended life
- Full aluminum alloy frame — premium chassis
- Mohs class 7 explosion-proof glass
- 24/7 commercial use — industrial-grade power supply
- Built-in Intel x86 OPS — Windows 10 / 11 / Linux pre-installed
- Industry-leading ultra-narrow screen bezel
- Surface IP65 waterproof — front panel
- IR 10-point touch — 200 Hz / 32768×32768 accuracy
- Mounting: Wall / Desktop stand / Embedded
- Total power consumption: < 130 W

ENT Group Co., Ltd. | 70/5 Moo 4, Metro Biztown, Chaengwattana 2, Pak Kret, Nonthaburi 11120, Thailand
Tel: 02-045-6104, 095-739-1053 | Sales@entgroup.co.th | www.entgroup.co.th | Tax ID: 0135558013167

THREE CONFIGURATIONS



HR49 — X86 All-in-One

Windows / Linux integrated (OPS)

49-inch Full HD IR touch with built-in Intel x86 OPS module. Choose Core i3-4Gen, Core i5-10Gen or Core i7-11Gen — pre-installed Windows 10 / 11 or Linux for instant deployment.

- Intel: i3-4Gen / i5-10Gen / i7-11Gen
- RAM 4–16 GB · Storage 128–512 GB
- Gigabit LAN + dual-band WiFi
- Power consumption < 130 W

Sister variants of the HR49 chassis

Same 49" panel, frame and mounting — different compute

- HR49-Monitor: Display only — pair with any external PC via HDMI/VGA + USB Touch
- HR49-X86: Intel Core i3-4Gen / i5-10Gen / i7-11Gen (OPS) with Windows 10 / 11 / Linux
- HR49-ARM: Rockchip RK3568 / RK3288 / RK3588 with Android 9 / 11 / 12

Same panel, frame and mounting options. Contact ENT Group sales for variant comparison and project-based recommendations.

TARGET INSTALLATIONS

POS Counter · Self-Service Kiosk · Reception Desk · Smart Office · Retail Display · Hospital Check-in · Library Terminal · Conference Room

ENT Group Co., Ltd. | 70/5 Moo 4, Metro Biztown, Chaengwattana 2, Pak Kret, Nonthaburi 11120, Thailand
Tel: 02-045-6104, 095-739-1053 | Sales@entgroup.co.th | www.entgroup.co.th | Tax ID: 0135558013167

TECHNICAL SPECIFICATIONS

Configuration

PC System	Intel® Core™ i3-4Gen / i5-10Gen / i7-11Gen (OPS)
GPU	Intel® HD Graphics 4600 / UHD Graphics 630 / Iris® Xe Graphics
Memory	Kingston DDR4 — 4 GB / 8 GB / 16 GB
Storage	Seagate — 128 GB / 256 GB / 512 GB
Audio	HD Audio: ALC269
Pre-installed OS	Windows 10 / 11 or Linux
Network	10/100/1000M RJ45 + 802.11 a/b/g/n/ac WiFi

LCD Panel

Display Size	49 inches
Resolution	1920 × 1080 (Full HD)
Aspect Ratio	16 : 9
Active Display Area	1076 × 606 mm
Colors	16.7 M
Brightness	300 cd/m²
Contrast Ratio	3000 : 1
Viewing Angle (H/V)	175° / 175°
Backlight Lifetime	LED 30,000 hours
Refresh Rate	60 Hz

Touch Panel

Technology	Infrared (IR)
Response Time	< 5 ms
Touch Points	10-point standard
Touch Recognition	> 1.5 mm
Scanning Frequency	200 Hz
Scanning Accuracy	32768 × 32768
Working Voltage / Current	DC +5 V ± 5% / 180 mA
Surface Hardness	Mohs class 7 explosion-proof glass

ENVIRONMENT, POWER & DIMENSIONS

Environment & Power

Operating Temperature	0 °C to 50 °C
Operating Humidity	0% to 90%
Storage Temperature	0 °C to 60 °C
Storage Humidity	0% to 65%
Power Input	100–240 V AC, 50/60 Hz
Standby Power	≤ 0.5 W
Overall Power Consumption	< 130 W

Dimensions & Weight

Machine Dimensions (W×H×T)	1127 × 657 × 60 mm
Package Dimensions (W×H×T)	1225 × 662 × 145 mm
Net Weight	26.2 kg
Gross Weight	33.2 kg
Surface Protection	IP65 (front)
Mounting	Wall mount / Desktop stand / Embedded

I/O Ports

- HDMI out × 1
- RJ45 LAN × 1
- MIC × 1
- DC 12 V × 1
- VGA × 1
- USB × 4
- WiFi Antenna × 1
- Optional: USB ×6 / RS232 ×2

RECOMMENDED APPLICATIONS

Application	Description
POS & Counter	Restaurant POS, queue terminals, ticketing and check-in counters.
Self-Service Kiosk	Hospital queue, library check-in, government counters.
Retail & Showroom	Interactive product display and order-taking terminals.
Smart Office	Meeting room booking, attendance and access-control panels.
Industrial HMI	Operator interface, workshop dashboards and control terminals.

ENT Group Co., Ltd. | 70/5 Moo 4, Metro Biztown, Chaengwattana 2, Pak Kret, Nonthaburi 11120, Thailand
Tel: 02-045-6104, 095-739-1053 | Sales@entgroup.co.th | www.entgroup.co.th | Tax ID: 0135558013167

CONNECT & ORDER

How to order — B2B Quotation Workflow. ENT Group operates as a B2B procurement platform. Add items to your cart on entgroup.co.th, our sales team will review your request and respond with a formal quotation (PDF). This is not an online checkout — pricing, lead time and delivery terms are tailored to each project.

View Product Page

Scan to view HR49 Series — full specs & accessories
entgroup.co.th/products/displays-49/hr49

Add LINE Official

Chat with our sales team for quotations & support
LINE ID: @entgroup

Get a Tailored Quotation

Scan either QR code to connect with ENT Group instantly. Our B2B sales team will prepare a quotation tailored to your project — including volume pricing, customization, installation and warranty terms.

Tel 02-045-6104, 095-739-1053
Email Sales@entgroup.co.th
Web www.entgroup.co.th