S

85" 4K UHD Infrared Touch All-in-One with OPS x86 Windows / Linux

RZ85B-X86 integrates an industrial OPS x86 module (Intel® Core™ i3-4th / i5-10th / i7-11th Gen) into the same 85-inch RZ85B chassis. Pre-installed Windows 10 / 11 or Linux delivers a full PC experience with 20-point IR touch, 4K UHD resolution, gigabit Ethernet and dual WiFi. Designed for boardrooms, smart classrooms, command centers and high-traffic digital signage — in a full aluminum alloy frame with IP65 front surface and Mohs class 7 explosion-proof glass.

85"	4K UHD	5000:1	IR 20-pt	IP65
Display	3840 × 2160	Contrast	Touch	Front Surface

KEY FEATURES

- 85-inch industrial LCD — 50,000-hour extended life
- Full aluminum alloy frame — premium chassis
- Mohs class 7 explosion-proof glass
- High contrast ratio 5000:1 — sharper visuals
- Built-in OPS x86 — Windows 10 / 11 / Linux pre-installed
- Industry-leading ultra-narrow screen bezel
- Surface IP65 waterproof — front panel
- Infrared 20-point touch — 200 Hz / 32767×32767 accuracy
- Mounting: Wall / Floor stand / Embedded
- Total power consumption: < 480 W

ENT Group Co., Ltd. | 70/5 Moo 4, Metro Biztown, Chaengwattana 2, Pak Kret, Nonthaburi 11120, Thailand
Tel: 02-045-6104, 095-739-1053 | Sales@entgroup.co.th | www.entgroup.co.th | Tax ID: 0135558013167

THREE CONFIGURATIONS

RZ85B — X86 All-in-One

OPS Windows / Linux integrated

85-inch IR touch with built-in OPS x86 module. Choose i3-4Gen, i5-10Gen or i7-11Gen — pre-installed Windows 10 / 11 or Linux for instant deployment in conference rooms, classrooms and signage.

- OPS x86: i3-4G / i5-10G / i7-11G
- RAM 4–16 GB · SSD 128–512 GB
- Gigabit LAN + dual-band WiFi
- Power consumption < 480 W

Sister variants of the RZ85B chassis

Same 85" panel, frame and mounting — different compute

- RZ85B-Monitor: Display only — pair with any external PC via HDMI/VGA + USB Touch
- RZ85B-X86: OPS i3-4Gen / i5-10Gen / i7-11Gen with Windows 10 / 11 / Linux
- RZ85B-ARM: Rockchip RK3568 / RK3288 / RK3588 with Android 9 / 11 / 12

Same panel, frame and mounting options. Contact ENT Group sales for variant comparison and project-based recommendations.

TARGET INSTALLATIONS

Conference & Boardroom · Smart Classroom · Information Kiosk · Digital Signage · Public Self-Service · Hospital Wayfinding · Retail Showroom · Corporate Lobby

ENT Group Co., Ltd. | 70/5 Moo 4, Metro Biztown, Chaengwattana 2, Pak Kret, Nonthaburi 11120, Thailand
Tel: 02-045-6104, 095-739-1053 | Sales@entgroup.co.th | www.entgroup.co.th | Tax ID: 0135558013167

TECHNICAL SPECIFICATIONS

Configuration

PC System	OPS x86 — Intel® i3-4Gen / i5-10Gen / i7-11Gen
Memory	4 GB / 8 GB / 16 GB DDR4 (Kingston)
Storage	128 GB / 256 GB / 512 GB SSD (Seagate)
Pre-installed OS	Windows 10 / 11 or Linux
Network	10/100/1000M RJ45 + 802.11 a/b/g/n/ac WiFi

LCD Panel

Display Size	85 inches
Resolution	3840 × 2160 (4K UHD)
Aspect Ratio	16 : 9
Active Display Area	1872 × 1053 mm
Colors	16.7 M
Brightness	350 cd/m²
Contrast Ratio	5000 : 1
Viewing Angle (H/V)	178° / 178°
Backlight Lifetime	LED 50,000 hours
Refresh Rate	4K @ 30 Hz

Touch Panel

Technology	Infrared (IR)
Response Time	< 5 ms
Touch Points	20-point standard
Touch Recognition Time	≤ 15 ms
Scanning Frequency	200 Hz
Scanning Accuracy	32767 × 32767
Working Voltage / Current	DC +5 V ± 5% / 180 mA
Surface Hardness	Mohs class 7 explosion-proof glass

ENT Group Co., Ltd. | 70/5 Moo 4, Metro Biztown, Chaengwattana 2, Pak Kret, Nonthaburi 11120, Thailand
Tel: 02-045-6104, 095-739-1053 | Sales@entgroup.co.th | www.entgroup.co.th | Tax ID: 0135558013167

ENVIRONMENT, POWER & DIMENSIONS

Environment & Power

Operating Temperature	0 °C to 50 °C
Operating Humidity	10% to 80%
Storage Temperature	–5 °C to 60 °C
Storage Humidity	10% to 85%
Power Input	110–240 V AC, 50/60 Hz
Power Output	DC 12 V / 5 A
Standby Power	≤ 0.5 W
Overall Power Consumption	< 480 W

Dimensions & Weight

Machine Dimensions (L×W×H)	1954 × 1153 × 93 mm
Package Dimensions (L×W×H)	2000 × 1290 × 215 mm
Net Weight	63.0 kg
Gross Weight	74.0 kg
Surface Protection	IP65 (front)
Mounting	Wall mount / Floor stand / Embedded

I/O Ports

- HDMI out × 1
- RJ45 LAN × 1
- WiFi antenna × 1
- Earphone × 1
- AC Power × 1
- VGA out × 1
- USB × 6
- MIC × 1
- Touch output × 1

RECOMMENDED APPLICATIONS

Application	Description
Conference & Boardroom	Wireless screen sharing, remote conferencing and whiteboarding.
Smart Classroom	Interactive lessons, e-learning and lecture capture.
Information Kiosk	Wayfinding, info-points, lobby and reception desks.
Digital Signage	Dynamic in-store signage, menu boards and exhibition display.
Public Self-Service	Government counters, hospital queue, library check-in.

CONNECT & ORDER

How to order — B2B Quotation Workflow. ENT Group operates as a B2B procurement platform. Add items to your cart on entgroup.co.th, our sales team will review your request and respond with a formal quotation (PDF). This is not an online checkout — pricing, lead time and delivery terms are tailored to each project.

View Product Page

Scan to view RZ85B Series — full specs & accessories
entgroup.co.th/products/displays-85/rz85b

Add LINE Official

Chat with our sales team for quotations & support
LINE ID: @entgroup

Get a Tailored Quotation

Scan either QR code to connect with ENT Group instantly. Our B2B sales team will prepare a quotation tailored to your project — including volume pricing, customization, installation and warranty terms.

Tel 02-045-6104, 095-739-1053
Email Sales@entgroup.co.th
Web www.entgroup.co.th

VIEWS & DIMENSIONS — Mechanical Drawing

Official mechanical drawing extracted from the TouchWo RZ85B spec sheet (panel manufacturer reference). All measurements in millimetres (mm). Front view shows active display area 1872 × 1053 mm and outer chassis 1953.6 × 1152.7 mm. Rear view shows VESA-compatible 4-point mounting pattern (800 × 400 mm centres) with 437.0 / 400.0 / 315.3 mm vertical reference lines.





Dimension	Value
Outer Chassis (W × H × D)	1954 × 1153 × 93 mm (195.4 × 115.3 × 9.3 cm)
Active Display Area (W × H)	1872 × 1053 mm (85" 4K UHD 16:9)
Glass Outer Reference (W × H)	1953.6 × 1152.7 mm
VESA Mount Pattern (rear)	4-point · 800 × 400 mm centres (576.8 mm side margin)
Vertical Mount References	437.0 / 400.0 / 315.3 mm
Net Weight / Gross Weight	63 kg / 74 kg
Package Dimensions (W × H × D)	2000 × 1290 × 215 mm (200 × 129 × 21.5 cm)
Mounting Options	Wall mount · Floor stand · Mobile cart (recommended professional installation due to 63 kg weight)