HR43 Series

43" Industrial PCAP Touch Display — IP65 + Mohs 7

Industrial-grade chassis: Aluminum + IP65 + Mohs 7 explosion-proof glass

HR43 is an industrial-grade 43-inch PCAP touch display series. The chassis combines an Aluminum Alloy body with a Sheet Metal frame and a Laser-cut Backplate. The display surface is IP65 waterproof and protected by Mohs class 7 explosion-proof glass. The same chassis is offered in three configurations: (1) **Touch Monitor** — display only with HDMI / DVI / VGA + USB Touch; (2) **Windows / Linux All-in-One** with Intel OPS (i3-4th / i5-10th / i7-11th); (3) **Android All-in-One** with Rockchip ARM (RK3568 / RK3288 / RK3588). Industrial-grade PSU supports 7×24H stable operation. Ideal for Public Self-service Kiosks, Education, Outdoor-readable Signage and Industrial HMI / Control Rooms.

43"	1920×1080	IP65	Mohs 7	7×24H
Display Size	FHD	Waterproof Surface	Explosion-proof	Stable Working

KEY FEATURES

- Unibody chassis — Aluminum Alloy + Sheet Metal frame
- IP65 waterproof surface — dust and water protected
- Industrial-grade PSU — 7×24H continuous operation
- Mounting: Wall mount / Floor stand / Mobile stand
- Laser-cut backplate — abrasion and corrosion resistant
- Mohs class 7 explosion-proof glass
- Plug-and-play with Auto-power Management
- 30,000-hour extended-life LED backlight

ENT Group Co., Ltd.
70/5 Moo 4, Metro Biztown, Chaengwattana 2, Khlong Phra Udom, Pak Kret, Nonthaburi 11120, Thailand
Tel: 02-045-6104, 095-739-1053 | Fax: 02-045-6105 | Email: Sales@entgroup.co.th | Tax ID: 0135558013167

THREE CONFIGURATIONS

HR43 — Touch Monitor

Display only (industrial chassis)

Industrial-grade PCAP touch panel only. Connect to an external PC, Mini PC or media player via HDMI / DVI / VGA + USB Touch. Aluminum chassis + IP65 + Mohs 7.

- Input: HDMI in + DVI + VGA + USB Touch
- Brightness 300 cd/m² + Anti-glare
- Power consumption < 90 W (lowest in series)
- Plug-and-play with Windows / Linux / macOS

HR43 — Windows / Linux PC

All-in-One (Intel OPS x86)

All-in-One PC with Intel OPS (Open Pluggable Specification) — selectable i3-4th Gen, i5-10th Gen or i7-11th Gen. Pre-installed Windows 10/11 or Linux. Supports POS / ERP / HMI / Signage Player software.

- Intel OPS i3-4th / i5-10th / i7-11th
- Kingston RAM 4 / 8 / 16 GB + Seagate SSD 128–512 GB
- Pre-install Windows 10 / 11 / Linux
- Gigabit RJ45 + Wi-Fi 802.11ac + ALC269 Audio

HR43 — Android PC

All-in-One (Rockchip ARM)

All-in-One PC with selectable Rockchip ARM CPU — RK3568 / RK3288 / RK3588. Pre-installed Android 9 / 11 / 12. Power consumption under 95 W — ideal for energy-efficient Self-service Kiosks and Digital Signage.

- Rockchip RK3568 / RK3288 / RK3588
- RAM 2–8 GB + eMMC 16–128 GB
- Pre-install Android 9 / 11 / 12
- Wi-Fi 802.11ac

ENT Group Co., Ltd.
70/5 Moo 4, Metro Biztown, Chaengwattana 2, Khlong Phra Udom, Pak Kret, Nonthaburi 11120, Thailand
Tel: 02-045-6104, 095-739-1053 | Fax: 02-045-6105 | Email: Sales@entgroup.co.th | Tax ID: 0135558013167

TECHNICAL SPECIFICATIONS

PC System (Windows / Linux x86 — OPS)

CPU (selectable)	Intel® OPS i3-4th Gen / i5-10th Gen / i7-11th Gen
Graphics	Intel® HD 4600 / UHD 630 / Iris® Xe Graphics
Audio	HD Audio: ALC269
Memory (RAM)	Kingston DDR — 4 GB / 8 GB / 16 GB
Storage	Seagate SSD — 128 GB / 256 GB / 512 GB
Network	10/100/1000M RJ45 + Wi-Fi 802.11 a/b/g/n/ac
Operating System	Windows 10 / 11 or Linux (pre-installed)

Android System (Rockchip ARM)

CPU (selectable)	Rockchip RK3568 / RK3288 / RK3588
Graphics	ARM G52 2EE / Mali-T864 / Mali-G610
Memory (RAM)	2 GB (4 GB opt.) / 2 GB / 4 GB (8 GB opt.)
Storage	eMMC 16 GB (32 GB opt.) / 16 GB / 64–128 GB
Network	10/100M RJ45 + Wi-Fi 802.11 a/b/g/n/ac
Operating System	Android 11 / Android 9 / Android 12

LCD Panel

Display Size	43 inches
Resolution	1920 × 1080 FHD
Aspect Ratio	16 : 9
Active Display Area	943 × 531 mm
Colors	16.7 M
Brightness	300 cd/m²
Contrast Ratio	1400 : 1
Viewing Angle (H/V)	175° / 175°
Backlight Lifetime	LED 30,000 hours
Refresh Rate	60 Hz

Touch Panel

Technology	PCAP (Projected Capacitive)
Response Time	< 5 ms
Touch Points	10-point standard
Touch Recognition	> 1.5 mm
Scanning Frequency	200 Hz
Scanning Accuracy	4096 × 4096
Working Voltage	180 mA / DC +5 V ±5%
Surface	Mohs class 7 explosion-proof glass + IP65

ENT Group Co., Ltd.
70/5 Moo 4, Metro Biztown, Chaengwattana 2, Khlong Phra Udom, Pak Kret, Nonthaburi 11120, Thailand
Tel: 02-045-6104, 095-739-1053 | Fax: 02-045-6105 | Email: Sales@entgroup.co.th | Tax ID: 0135558013167

ENVIRONMENT, POWER & DIMENSIONS

Environment & Power

Operating Temperature	0 °C to 50 °C
Operating Humidity	10% to 80%
Storage Temperature	-5 °C to 60 °C
Storage Humidity	10% to 85%
Power Input	110–240 V AC, 50/60 Hz
Power Output	DC 12 V 5 A
Standby Power	≤ 0.5 W
Overall Power	Monitor < 90 W / Android < 95 W / x86 < 120 W

Dimensions & Weight

Unit Dimensions	99.5 × 58.3 × 6 cm
Carton Dimensions	109.5 × 69 × 14.5 cm
Net Weight	21.4 kg
Gross Weight	27.5 kg
Mounting	Wall mount / Floor stand / Mobile stand

I/O Ports

- Power Button × 1
- DC 12V × 1
- HDMI out × 1
- Audio × 1
- RJ45 × 1 (Gigabit)
- TF / SD × 1
- USB × 2–4
- VGA × 1
- Wi-Fi Antenna × 1

RECOMMENDED APPLICATIONS

Public Self-service Kiosk	Heavy-duty self-service in airports, hospitals and government buildings — Aluminum + IP65 + Mohs 7 resists impacts and abrasion.
Education / Smart Classroom	Multi-touch 10-point classroom display with Anti-glare panel — comfortable for all-day collaborative learning.
Outdoor-readable Signage	Semi-outdoor digital signage at 300 nits with Anti-glare. Industrial PSU supports 24/7 unattended operation.
Industrial HMI / Control Room	Machine HMI in factories — impact and dust resistant, glove-touch capable PCAP, operates 0–50 °C.

ENT Group Co., Ltd.
70/5 Moo 4, Metro Biztown, Chaengwattana 2, Khlong Phra Udom, Pak Kret, Nonthaburi 11120, Thailand
Tel: 02-045-6104, 095-739-1053 | Fax: 02-045-6105 | Email: Sales@entgroup.co.th | Tax ID: 0135558013167

CONNECT & ORDER

How to order — B2B Quotation Workflow. ENT Group operates as a B2B procurement platform. Add items to your cart on entgroup.co.th, our sales team will review your request and respond with a formal quotation (PDF). This is not an online checkout — pricing, lead time and delivery terms are tailored to each project.

View Product Page

Scan to view HR43 Series, full specs & accessories
entgroup.co.th/products/displays-43/hr43

Add LINE Official

Chat with our sales team for quotations & support
LINE ID: @entgroup

Get a Tailored Quotation

Scan either QR code to connect with ENT Group instantly. Our B2B sales team will prepare a quotation tailored to your project — including volume pricing, customization, installation and warranty terms.

Tel 02-045-6104, 095-739-1053
Email Sales@entgroup.co.th
Web www.entgroup.co.th

ENT Group Co., Ltd.
70/5 Moo 4, Metro Biztown, Chaengwattana 2, Khlong Phra Udom, Pak Kret, Nonthaburi 11120, Thailand
Tel: 02-045-6104, 095-739-1053 | Fax: 02-045-6105 | Email: Sales@entgroup.co.th | Tax ID: 0135558013167