RZ98B-X86 Series

98" 4K UHD IR Touch All-in-One with Intel x86 (OPS) Windows / Linux

RZ98B-X86 integrates an industrial Intel x86 OPS module (Core™ i3-4Gen / Core™ i5-10Gen / Core™ i7-11Gen) into the same 98-inch RZ98B chassis. Pre-installed Windows 10 / 11 or Linux delivers a full PC experience with 20-point IR touch, gigabit Ethernet and dual-band WiFi. Designed for boardrooms, smart classrooms, command centers and large-format digital signage — full aluminum alloy frame, IP65 front surface and Mohs class 7 explosion-proof glass for 24/7 commercial use.

98"	4K UHD	5000:1	IR 20-pt	IP65
Display	3840 × 2160	Contrast	Touch	Front Surface

KEY FEATURES

- 98-inch 4K UHD industrial LCD — 30,000-hour extended life
- Full aluminum alloy frame — premium chassis
- Mohs class 7 explosion-proof glass
- 24/7 commercial use — industrial-grade power supply
- Built-in Intel x86 OPS — Windows 10 / 11 / Linux pre-installed
- Industry-leading ultra-narrow screen bezel
- Surface IP65 waterproof — front panel
- IR 20-point touch — 32767×32767 accuracy
- Mounting: Wall / Desktop stand / Embedded
- Total power consumption: ≤ 720 W

ENT Group Co., Ltd. | 70/5 Moo 4, Metro Biztown, Chaengwattana 2, Pak Kret, Nonthaburi 11120, Thailand
Tel: 02-045-6104, 095-739-1053 | Sales@entgroup.co.th | www.entgroup.co.th | Tax ID: 0135558013167

THREE CONFIGURATIONS

RZ98B — X86 All-in-One

Windows / Linux integrated (OPS)

98-inch 4K UHD IR touch with built-in Intel x86 OPS module. Choose Core i3-4Gen, Core i5-10Gen or Core i7-11Gen — pre-installed Windows 10 / 11 or Linux for instant deployment.

- Intel: i3-4Gen / i5-10Gen / i7-11Gen
- RAM 4–16 GB · Storage 128–512 GB
- Gigabit LAN + dual-band WiFi
- Power consumption ≤ 720 W

Sister variants of the RZ98B chassis

Same 98" 4K panel, frame and mounting — different compute

- RZ98B-Monitor: Display only — pair with any external PC via HDMI/VGA + USB Touch
- RZ98B-X86: Intel Core i3-4Gen / i5-10Gen / i7-11Gen (OPS) with Windows 10 / 11 / Linux
- RZ98B-ARM: Rockchip RK3568 / RK3288 / RK3588 with Android 9 / 11 / 12

Same panel, frame and mounting options. Contact ENT Group sales for variant comparison and project-based recommendations.

TARGET INSTALLATIONS

POS Counter · Self-Service Kiosk · Reception Desk · Smart Office · Retail Display · Hospital Check-in · Library Terminal · Conference Room

ENT Group Co., Ltd. | 70/5 Moo 4, Metro Biztown, Chaengwattana 2, Pak Kret, Nonthaburi 11120, Thailand
Tel: 02-045-6104, 095-739-1053 | Sales@entgroup.co.th | www.entgroup.co.th | Tax ID: 0135558013167

TECHNICAL SPECIFICATIONS

Configuration

PC System	Intel® Core™ i3-4Gen / i5-10Gen / i7-11Gen (OPS)
GPU	Intel® HD Graphics 4600 / UHD Graphics 630 / Iris® Xe Graphics
Memory	Kingston DDR4 — 4 GB / 8 GB / 16 GB
Storage	Seagate — 128 GB / 256 GB / 512 GB
Audio	HD Audio: ALC269
Pre-installed OS	Windows 10 / 11 or Linux
Network	10/100/1000M RJ45 + 802.11 a/b/g/n/ac WiFi

LCD Panel

Display Size	98 inches
Resolution	3840 × 2160 (4K UHD)
Aspect Ratio	16 : 9
Active Display Area	2157.9 × 1213.35 mm
Colors	16.7 M
Brightness	350 cd/m²
Contrast Ratio	5000 : 1
Viewing Angle (H/V)	178° / 178°
Backlight Lifetime	LED 50,000 hours
Refresh Rate	4K @ 30 Hz

Touch Panel

Technology	Infrared (IR)
Response Time	< 8 ms
Touch Points	20-point standard
Touch Recognition	≤ 15 ms
Cursor Speed	120 / s
Scanning Accuracy	32767 × 32767
Working Voltage / Current	DC +5 V ± 5% / 180 mA
Surface Hardness	Mohs class 7 explosion-proof glass

ENVIRONMENT, POWER & DIMENSIONS

Environment & Power

Operating Temperature	0 °C to 50 °C
Operating Humidity	10% to 80%
Storage Temperature	-5 °C to 60 °C
Storage Humidity	10% to 85%
Power Input	110–240 V AC, 50/60 Hz
Power Output	DC 12 V / 5 A
Standby Power	≤ 0.5 W
Overall Power Consumption	≤ 720 W

Dimensions & Weight

Machine Dimensions (W×H×T)	2216 × 1317 × 107 mm
Package Dimensions (W×H×T)	2355 × 1455 × 235 mm
Net Weight	88 kg
Gross Weight	102 kg
Surface Protection	IP65 (front)
Mounting	Wall mount / Floor stand / Embedded

I/O Ports

- HDMI out × 1
- RJ45 LAN × 1
- MIC × 1
- WiFi Antenna × 1
- VGA out × 1
- USB × 6
- Earphone × 1
- PWM Power × 1

RECOMMENDED APPLICATIONS

Application	Description
POS & Counter	Restaurant POS, queue terminals, ticketing and check-in counters.
Self-Service Kiosk	Hospital queue, library check-in, government counters.
Retail & Showroom	Interactive product display and order-taking terminals.
Smart Office	Meeting room booking, attendance and access-control panels.
Industrial HMI	Operator interface, workshop dashboards and control terminals.

ENT Group Co., Ltd. | 70/5 Moo 4, Metro Biztown, Chaengwattana 2, Pak Kret, Nonthaburi 11120, Thailand
Tel: 02-045-6104, 095-739-1053 | Sales@entgroup.co.th | www.entgroup.co.th | Tax ID: 0135558013167

CONNECT & ORDER

How to order — B2B Quotation Workflow. ENT Group operates as a B2B procurement platform. Add items to your cart on entgroup.co.th, our sales team will review your request and respond with a formal quotation (PDF). This is not an online checkout — pricing, lead time and delivery terms are tailored to each project.

View Product Page

Scan to view RZ98B Series — full specs & accessories
entgroup.co.th/products/displays-98/rz86b

Add LINE Official

Chat with our sales team for quotations & support
LINE ID: @entgroup

Get a Tailored Quotation

Scan either QR code to connect with ENT Group instantly. Our B2B sales team will prepare a quotation tailored to your project — including volume pricing, customization, installation and warranty terms.

Tel 02-045-6104, 095-739-1053
Email Sales@entgroup.co.th
Web www.entgroup.co.th