HD49-ARM Series

49" Full HD PCAP Touch All-in-One with Rockchip ARM (Android)

HD49-ARM combines the same 49-inch HD49 industrial chassis with a Rockchip ARM SoC (RK3568 / RK3288 / RK3588) running Android 9 / 11 / 12. Ideal for digital signage, kiosks and lobby displays where a lightweight, fanless and always-on Android player is preferred. 10-point PCAP touch, full aluminum frame, IP65 surface and Mohs class 7 explosion-proof glass — engineered for 24/7 commercial use.

27"	Full HD	1000:1	PCAP 10-pt	IP65
Display	1920 × 1080	Contrast	Touch	Front Surface

KEY FEATURES

- 27-inch industrial LCD — 30,000-hour extended life
- Full aluminum alloy frame — premium chassis
- Mohs class 7 explosion-proof glass
- 24/7 commercial use — industrial-grade power supply
- Built-in Rockchip ARM — Android pre-installed (RK3568 / RK3288 / RK3588)
- Industry-leading ultra-narrow screen bezel
- Surface IP65 waterproof — front panel
- PCAP 10-point touch — 200 Hz / 4096×4096 accuracy
- Mounting: Wall / Desktop stand / Embedded
- Total power consumption: < 130 W

ENT Group Co., Ltd. | 70/5 Moo 4, Metro Biztown, Chaengwattana 2, Pak Kret, Nonthaburi 11120, Thailand
Tel: 02-045-6104, 095-739-1053 | Sales@entgroup.co.th | www.entgroup.co.th | Tax ID: 0135558013167

THREE CONFIGURATIONS

HD49 — ARM All-in-One

Android Rockchip integrated

49-inch PCAP touch with fanless Rockchip ARM SoC running Android. Choose RK3568, RK3288 or RK3588 for kiosks, signage and always-on lobby displays — low power, instant boot, plug-and-play.

- Rockchip RK3568 / RK3288 / RK3588
- Android 11 / 9 / 12 pre-installed
- Gigabit LAN + dual-band WiFi
- Power consumption < 130 W

Sister variants of the HD49 chassis

Same 49" panel, frame and mounting — different compute

- HD49-Monitor: Display only — pair with any external PC via HDMI/VGA + USB Touch
- HD49-X86: Intel J6412 / i5-8Gen / i7-10Gen with Windows 10 / 11 / Linux
- HD49-ARM: Rockchip RK3568 / RK3288 / RK3588 with Android 9 / 11 / 12

Same panel, frame and mounting options. Contact ENT Group sales for variant comparison and project-based recommendations.

TARGET INSTALLATIONS

POS Counter · Self-Service Kiosk · Reception Desk · Smart Office · Retail Display · Hospital Check-in · Library Terminal · Conference Room

ENT Group Co., Ltd. | 70/5 Moo 4, Metro Biztown, Chaengwattana 2, Pak Kret, Nonthaburi 11120, Thailand
Tel: 02-045-6104, 095-739-1053 | Sales@entgroup.co.th | www.entgroup.co.th | Tax ID: 0135558013167

TECHNICAL SPECIFICATIONS

Configuration

PC System	Rockchip ARM — RK3568 / RK3288 / RK3588
GPU	ARM G52 2EE / Mali-T864 / Mali-G610
Memory	2 GB (4 GB opt.) / 2 GB (4 GB opt.) / 4 GB (8 GB opt.)
Storage	32 GB eMMC / 16 GB (32 GB opt.) / 64 GB (128 GB opt.)
Pre-installed OS	Android 11 / 9 / 12
Network	10/100M RJ45 (RK3568) · 100/1000M RJ45 (RK3288/3588) + 802.11 a/b/g/n/ac WiFi

LCD Panel

Display Size	49 inches
Resolution	1920 × 1080 (Full HD)
Aspect Ratio	16 : 9
Active Display Area	1076 × 606 mm
Colors	16.7 M
Brightness	300 cd/m²
Contrast Ratio	1200 : 1
Viewing Angle (H/V)	178° / 178°
Backlight Lifetime	LED 30,000 hours
Refresh Rate	60 Hz

Touch Panel

Technology	PCAP (Projected Capacitive)
Response Time	< 5 ms
Touch Points	10-point standard
Touch Recognition	> 1.5 mm
Scanning Frequency	200 Hz
Scanning Accuracy	4096 × 4096
Working Voltage / Current	DC +5 V ± 5% / 180 mA
Surface Hardness	Mohs class 7 explosion-proof glass

ENVIRONMENT, POWER & DIMENSIONS

Environment & Power

Operating Temperature	0 °C to 50 °C
Operating Humidity	0% to 90%
Storage Temperature	0 °C to 60 °C
Storage Humidity	0% to 65%
Power Input	100–240 V AC, 50/60 Hz
Standby Power	≤ 0.5 W
Overall Power Consumption	< 130 W

Dimensions & Weight

Machine Dimensions (W×H×T)	1127 × 657 × 57 mm
Package Dimensions (W×H×T)	1270 × 790 × 183 mm
Net Weight	24.1 kg
Gross Weight	30.6 kg
Surface Protection	IP65 (front)
Mounting	Wall mount / Desktop stand / Embedded

I/O Ports

- HDMI out × 1
- USB × 2
- Audio in × 1
- Power Socket × 1
- RJ45 LAN × 1
- TF card slot × 1
- Audio out × 1
- Optional: USB / RS232 / TTL

RECOMMENDED APPLICATIONS

Application	Description
POS & Counter	Restaurant POS, queue terminals, ticketing and check-in counters.
Self-Service Kiosk	Hospital queue, library check-in, government counters.
Retail & Showroom	Interactive product display and order-taking terminals.
Smart Office	Meeting room booking, attendance and access-control panels.
Industrial HMI	Operator interface, workshop dashboards and control terminals.

ENT Group Co., Ltd. | 70/5 Moo 4, Metro Biztown, Chaengwattana 2, Pak Kret, Nonthaburi 11120, Thailand
Tel: 02-045-6104, 095-739-1053 | Sales@entgroup.co.th | www.entgroup.co.th | Tax ID: 0135558013167

CONNECT & ORDER

How to order — B2B Quotation Workflow. ENT Group operates as a B2B procurement platform. Add items to your cart on entgroup.co.th, our sales team will review your request and respond with a formal quotation (PDF). This is not an online checkout — pricing, lead time and delivery terms are tailored to each project.

View Product Page

Scan to view HD49 Series — full specs & accessories
entgroup.co.th/products/displays-49/hd49

Add LINE Official

Chat with our sales team for quotations & support
LINE ID: @entgroup

Get a Tailored Quotation

Scan either QR code to connect with ENT Group instantly. Our B2B sales team will prepare a quotation tailored to your project — including volume pricing, customization, installation and warranty terms.

Tel 02-045-6104, 095-739-1053
Email Sales@entgroup.co.th
Web www.entgroup.co.th