RZ65B-Monitor Series

65" 4K UHD Infrared Touch Monitor — Display Only (no internal PC)

Connect to any external PC, Mini PC or media player via HDMI/DVI/VGA + USB Touch.

RZ65B Touch Monitor is a 65-inch Infrared (IR) touchscreen **without an internal PC** — designed to pair with an external Windows / Mac / Linux PC, Mini PC, OPS module or media player via HDMI, DVI or VGA + USB Touch. The IR touch frame supports any input object (finger, gloved hand, stylus or pen) and is highly durable for high-traffic public installations. Same industrial chassis as the All-in-One variants — full aluminum alloy frame, IP65 surface, Mohs class 7 explosion-proof glass — with an exceptional 5000:1 contrast ratio for sharper visuals.

65"	4K UHD	5000:1	IR 20-pt	IP65
Display Size	3840 × 2160	Contrast Ratio	Touch	Front Surface

KEY FEATURES

- 65-inch industrial LCD — 50,000-hour extended life
- Full aluminum alloy frame — premium chassis
- Mohs class 7 explosion-proof glass
- High contrast ratio 5000:1 — sharper visuals
- **No internal PC** — connect external PC via HDMI/DVI/VGA + USB
- Industry-leading ultra-narrow screen bezel
- Surface IP65 waterproof — front panel
- Infrared 20-point touch — 200 Hz / 32767×32767 accuracy
- Mounting: Wall / Floor stand / Embedded
- Lowest power: overall consumption < 125 W

ENT Group Co., Ltd.
70/5 Moo 4, Metro Biztown, Chaengwattana 2, Khlong Phra Udom, Pak Kret, Nonthaburi 11120, Thailand
Tel: 02-045-6104, 095-739-1053 | Fax: 02-045-6105 | Email: Sales@entgroup.co.th | Tax ID: 0135558013167

THREE CONFIGURATIONS

RZ65B — Touch Monitor

Display only — no internal PC

65-inch IR touch panel with HDMI/DVI/VGA inputs. Pair with any external PC, Mini PC or OPS module. Plug-and-play USB touch — no driver required on Windows/Linux.

- No internal PC — flexible compute pairing
- Inputs: HDMI in × 1, DVI × 1, VGA × 1
- USB Touch (HID) + Audio in/out
- Power consumption < 125 W

Need an All-in-One instead?

Sister variants available

The same RZ65B chassis is available with an integrated PC. See RZ65B Windows/Linux (OPS) or RZ65B Android (Rockchip ARM) datasheets.

- RZ65B-X86: OPS i3-4th / i5-10th / i7-11th
- RZ65B-ARM: Rockchip RK3568 / RK3288 / RK3588
- Same panel, frame and mounting options
- Contact sales for variant comparison

ENT Group Co., Ltd.
70/5 Moo 4, Metro Biztown, Chaengwattana 2, Khlong Phra Udom, Pak Kret, Nonthaburi 11120, Thailand
Tel: 02-045-6104, 095-739-1053 | Fax: 02-045-6105 | Email: Sales@entgroup.co.th | Tax ID: 0135558013167

TECHNICAL SPECIFICATIONS

Configuration

PC System	None — display only (external PC required)
Signal Inputs	HDMI in × 1, DVI × 1, VGA × 1
Touch Output	USB Touch (HID — driverless on Windows/Linux/macOS)
Audio	Audio in / Audio out

LCD Panel

Display Size	65 inches
Resolution	3840 × 2160 (4K UHD)
Aspect Ratio	16 : 9
Active Display Area	1428.5 × 803.5 mm
Colors	16.7 M
Brightness	350 cd/m²
Contrast Ratio	5000 : 1
Viewing Angle (H/V)	178° / 178°
Backlight Lifetime	LED 50,000 hours
Refresh Rate	4K @ 30 Hz

Touch Panel

Technology	Infrared (IR)
Response Time	< 5 ms
Touch Points	20-point standard
Touch Recognition Time	≤ 15 ms
Scanning Frequency	200 Hz
Scanning Accuracy	32767 × 32767
Working Voltage / Current	DC +5 V ± 5% / 180 mA
Surface Hardness	Mohs class 7 explosion-proof glass

ENT Group Co., Ltd.
70/5 Moo 4, Metro Biztown, Chaengwattana 2, Khlong Phra Udom, Pak Kret, Nonthaburi 11120, Thailand
Tel: 02-045-6104, 095-739-1053 | Fax: 02-045-6105 | Email: Sales@entgroup.co.th | Tax ID: 0135558013167

ENVIRONMENT, POWER & DIMENSIONS

Environment & Power

Operating Temperature	0 °C to 50 °C
Operating Humidity	10% to 80%
Storage Temperature	–5 °C to 60 °C
Storage Humidity	10% to 85%
Power Input	110–240 V AC, 50/60 Hz
Power Output	DC 12 V / 5 A
Standby Power	≤ 0.5 W
Overall Power Consumption	< 125 W

Dimensions & Weight

Machine Dimensions (L×W×H)	1485 × 888 × 83 mm
Package Dimensions (L×W×H)	1605 × 1010 × 195 mm
Net Weight	32.0 kg
Gross Weight	38.0 kg
Surface Protection	IP65 (front)
Mounting	Wall mount / Floor stand / Embedded

I/O Ports



- HDMI in × 1
- DVI × 1
- VGA × 1
- USB × 1 (Touch)
- Audio in / Audio out × 1
- DC 12 V Power Socket × 1

RECOMMENDED APPLICATIONS

Conference & Boardroom	Wireless screen sharing, remote conferencing and whiteboarding.
Smart Classroom	Interactive lessons, e-learning and lecture capture.
Information Kiosk	Wayfinding, info-points, lobby and reception desks.
Digital Signage	Dynamic in-store signage, menu boards and exhibition display.
Public Self-Service	Government counters, hospital queue, library check-in.

ENT Group Co., Ltd.
70/5 Moo 4, Metro Biztown, Chaengwattana 2, Khlong Phra Udom, Pak Kret, Nonthaburi 11120, Thailand
Tel: 02-045-6104, 095-739-1053 | Fax: 02-045-6105 | Email: Sales@entgroup.co.th | Tax ID: 0135558013167

CONNECT & ORDER

How to order — B2B Quotation Workflow. ENT Group operates as a B2B procurement platform. Add items to your cart on entgroup.co.th, our sales team will review your request and respond with a formal quotation (PDF). This is not an online checkout — pricing, lead time and delivery terms are tailored to each project.

View Product Page

Scan to view RZ65B-Monitor Series, full specs & accessories
entgroup.co.th/products/displays-65/rz65b

Add LINE Official

Chat with our sales team for quotations & support
LINE ID: @entgroup

Get a Tailored Quotation

Scan either QR code to connect with ENT Group instantly. Our B2B sales team will prepare a quotation tailored to your project — including volume pricing, customization, installation and warranty terms.

Tel 02-045-6104, 095-739-1053
Email Sales@entgroup.co.th
Web www.entgroup.co.th

ENT Group Co., Ltd.
70/5 Moo 4, Metro Biztown, Chaengwattana 2, Khlong Phra Udom, Pak Kret, Nonthaburi 11120, Thailand
Tel: 02-045-6104, 095-739-1053 | Fax: 02-045-6105 | Email: Sales@entgroup.co.th | Tax ID: 0135558013167