HR49-Monitor Series

49" Full HD Infrared Touch Monitor — Display Only (no internal PC)

HR49 Touch Monitor is a 49-inch Full HD Infrared (IR) touchscreen without an internal PC — designed to pair with an external Windows / Mac / Linux PC, OPS module or media player via HDMI, DVI, VGA + USB Touch. Industrial-grade power supply, 30,000-hour extended-life LCD, full aluminum alloy frame, IP65 front surface and Mohs class 7 explosion-proof glass. 10-point IR multi-touch with industry-leading ultra-narrow bezel — engineered for 24/7 commercial use in classrooms, meeting rooms and information kiosks.

49"	Full HD	1400:1	IR 10-pt	IP65
Display	1920 × 1080	Contrast	Touch	Front Surface

KEY FEATURES

- 49-inch industrial LCD — 30,000-hour extended life
- Full aluminum alloy frame — premium chassis
- Mohs class 7 explosion-proof glass
- 24/7 commercial use — industrial-grade power supply
- No internal PC — connect external PC via HDMI/DVI/VGA + USB Touch
- Industry-leading ultra-narrow screen bezel
- Surface IP65 waterproof — front panel
- IR 10-point touch — 200 Hz / 32768×32768 accuracy
- Mounting: Wall / Desktop stand / Embedded
- Total power consumption: < 100 W

ENT Group Co., Ltd. | 70/5 Moo 4, Metro Biztown, Chaengwattana 2, Pak Kret, Nonthaburi 11120, Thailand
Tel: 02-045-6104, 095-739-1053 | Sales@entgroup.co.th | www.entgroup.co.th | Tax ID: 0135558013167

THREE CONFIGURATIONS

HR49 — IR Touch Monitor

Display only — no internal PC

49-inch Full HD IR touch panel with HDMI/DVI/VGA inputs. Pair with any external PC, OPS module or media player. Plug-and-play USB touch — no driver required on Windows/Linux.

- No internal PC — flexible compute pairing
- Inputs: HDMI / DVI / VGA
- USB Touch (HID) + Audio in/out
- Power consumption < 100 W

Sister variants of the HR49 chassis

Same 49" panel, frame and mounting — different compute

- HR49-Monitor: Display only — pair with any external PC via HDMI/VGA + USB Touch
- HR49-X86: Intel Core i3-4Gen / i5-10Gen / i7-11Gen (OPS) with Windows 10 / 11 / Linux
- HR49-ARM: Rockchip RK3568 / RK3288 / RK3588 with Android 9 / 11 / 12

Same panel, frame and mounting options. Contact ENT Group sales for variant comparison and project-based recommendations.

TARGET INSTALLATIONS

POS Counter · Self-Service Kiosk · Reception Desk · Smart Office · Retail Display · Hospital Check-in · Library Terminal · Conference Room

ENT Group Co., Ltd. | 70/5 Moo 4, Metro Biztown, Chaengwattana 2, Pak Kret, Nonthaburi 11120, Thailand
Tel: 02-045-6104, 095-739-1053 | Sales@entgroup.co.th | www.entgroup.co.th | Tax ID: 0135558013167

TECHNICAL SPECIFICATIONS

Configuration

PC System	None — display only (external PC required)
Signal Inputs	HDMI in × 1, DVI × 1, VGA × 1
Touch Output	USB Touch (HID — driverless on Windows/Linux/macOS)
Audio	Audio in / out × 1

LCD Panel

Display Size	49 inches
Resolution	1920 × 1080 (Full HD)
Aspect Ratio	16 : 9
Active Display Area	1076 × 606 mm
Colors	16.7 M
Brightness	300 cd/m²
Contrast Ratio	1400 : 1
Viewing Angle (H/V)	175° / 175°
Backlight Lifetime	LED 30,000 hours
Refresh Rate	60 Hz

Touch Panel

Technology	Infrared (IR)
Response Time	< 5 ms
Touch Points	10-point standard
Touch Recognition	> 1.5 mm
Scanning Frequency	200 Hz
Scanning Accuracy	32768 × 32768
Working Voltage / Current	DC +5 V ± 5% / 180 mA
Surface Hardness	Mohs class 7 explosion-proof glass

ENVIRONMENT, POWER & DIMENSIONS

Environment & Power

Operating Temperature	0 °C to 50 °C
Operating Humidity	10% to 80%
Storage Temperature	-5 °C to 60 °C
Storage Humidity	10% to 85%
Power Input	110–240 V AC, 50/60 Hz
Power Output	DC 12 V / 5 A
Standby Power	≤ 0.5 W
Overall Power Consumption	< 100 W

Dimensions & Weight

Machine Dimensions (W×H×T)	1127 × 657 × 60 mm
Package Dimensions (W×H×T)	1225 × 662 × 145 mm
Net Weight	25.9 kg
Gross Weight	32.9 kg
Surface Protection	IP65 (front)
Mounting	Wall mount / Desktop stand / Embedded

I/O Ports

- HDMI in × 1
- VGA × 1
- Audio in / out × 1
- Power Socket × 1
- DVI × 1
- USB × 1 (Touch)
- DC 12 V × 1
- —

RECOMMENDED APPLICATIONS

Application	Description
POS & Counter	Restaurant POS, queue terminals, ticketing and check-in counters.
Self-Service Kiosk	Hospital queue, library check-in, government counters.
Retail & Showroom	Interactive product display and order-taking terminals.
Smart Office	Meeting room booking, attendance and access-control panels.
Industrial HMI	Operator interface, workshop dashboards and control terminals.

ENT Group Co., Ltd. | 70/5 Moo 4, Metro Biztown, Chaengwattana 2, Pak Kret, Nonthaburi 11120, Thailand
Tel: 02-045-6104, 095-739-1053 | Sales@entgroup.co.th | www.entgroup.co.th | Tax ID: 0135558013167

CONNECT & ORDER

How to order — B2B Quotation Workflow. ENT Group operates as a B2B procurement platform. Add items to your cart on entgroup.co.th, our sales team will review your request and respond with a formal quotation (PDF). This is not an online checkout — pricing, lead time and delivery terms are tailored to each project.

View Product Page

Scan to view HR49 Series — full specs & accessories
entgroup.co.th/products/displays-49/hr49

Add LINE Official

Chat with our sales team for quotations & support
LINE ID: @entgroup

Get a Tailored Quotation

Scan either QR code to connect with ENT Group instantly. Our B2B sales team will prepare a quotation tailored to your project — including volume pricing, customization, installation and warranty terms.

Tel 02-045-6104, 095-739-1053
Email Sales@entgroup.co.th
Web www.entgroup.co.th