# RZ85B-X86 Series

85" 4K UHD Infrared Touch Monitor — Display Only (no internal PC)

RZ85B-X86 integrates an industrial OPS x86 module (Intel® Core™ i3-4th / i5-10th / i7-11th Gen) into the same 85-inch RZ85B chassis. Pre-installed Windows 10 / 11 or Linux delivers a full PC experience with 20-point IR touch, 4K UHD resolution, gigabit Ethernet and dual WiFi. Designed for boardrooms, smart classrooms, command centers and high-traffic digital signage — in a full aluminum alloy frame with IP65 front surface and Mohs class 7 explosion-proof glass.

| 85" | 4K UHD | 5000:1 | IR 20-pt | IP65 |
|---|---|---|---|---|
| Display | 3840 × 2160 | Contrast | Touch | Front Surface |

## KEY FEATURES

- 85-inch industrial LCD — 50,000-hour extended life
- Full aluminum alloy frame — premium chassis
- Mohs class 7 explosion-proof glass
- High contrast ratio 5000:1 — sharper visuals
- Built-in OPS x86 — Windows 10 / 11 / Linux pre-installed
- Industry-leading ultra-narrow screen bezel
- Surface IP65 waterproof — front panel
- Infrared 20-point touch — 200 Hz / 32767×32767 accuracy
- Mounting: Wall / Floor stand / Embedded
- Total power consumption: < 480 W

ENT Group Co., Ltd. | 70/5 Moo 4, Metro Biztown, Chaengwattana 2, Pak Kret, Nonthaburi 11120, Thailand
Tel: 02-045-6104, 095-739-1053 | Sales@entgroup.co.th | www.entgroup.co.th | Tax ID: 0135558013167

## THREE CONFIGURATIONS

RZ85B — X86 All-in-One

OPS Windows / Linux integrated

85-inch IR touch with built-in OPS x86 module. Choose i3-4Gen, i5-10Gen or i7-11Gen — pre-installed Windows 10 / 11 or Linux for instant deployment in conference rooms, classrooms and signage.

- OPS x86: i3-4G / i5-10G / i7-11G
- RAM 4–16 GB · SSD 128–512 GB
- Gigabit LAN + dual-band WiFi
- Power consumption < 480 W

Sister variants of the RZ85B chassis

Same 85" panel, frame and mounting — different compute

- RZ85B-Monitor: Display only — pair with any external PC via HDMI/VGA + USB Touch
- RZ85B-X86: OPS i3-4Gen / i5-10Gen / i7-11Gen with Windows 10 / 11 / Linux
- RZ85B-ARM: Rockchip RK3568 / RK3288 / RK3588 with Android 9 / 11 / 12

Same panel, frame and mounting options. Contact ENT Group sales for variant comparison and project-based recommendations.

## TARGET INSTALLATIONS

Conference & Boardroom · Smart Classroom · Information Kiosk · Digital Signage · Public Self-Service · Hospital Wayfinding · Retail Showroom · Corporate Lobby

ENT Group Co., Ltd. | 70/5 Moo 4, Metro Biztown, Chaengwattana 2, Pak Kret, Nonthaburi 11120, Thailand
Tel: 02-045-6104, 095-739-1053 | Sales@entgroup.co.th | www.entgroup.co.th | Tax ID: 0135558013167

# TECHNICAL SPECIFICATIONS

## Configuration

| | |
|---|---|
| **PC System** | OPS x86 — Intel® i3-4Gen / i5-10Gen / i7-11Gen |
| **Memory** | 4 GB / 8 GB / 16 GB DDR4 (Kingston) |
| **Storage** | 128 GB / 256 GB / 512 GB SSD (Seagate) |
| **Pre-installed OS** | Windows 10 / 11 or Linux |
| **Network** | 10/100/1000M RJ45 + 802.11 a/b/g/n/ac WiFi |

## LCD Panel

| | |
|---|---|
| **Display Size** | 85 inches |
| **Resolution** | 3840 × 2160 (4K UHD) |
| **Aspect Ratio** | 16 : 9 |
| **Active Display Area** | 1872 × 1053 mm |
| **Colors** | 16.7 M |
| **Brightness** | 350 cd/m² |
| **Contrast Ratio** | 5000 : 1 |
| **Viewing Angle (H/V)** | 178° / 178° |
| **Backlight Lifetime** | LED 50,000 hours |
| **Refresh Rate** | 4K @ 30 Hz |

## Touch Panel

| | |
|---|---|
| **Technology** | Infrared (IR) |
| **Response Time** | < 5 ms |
| **Touch Points** | 20-point standard |
| **Touch Recognition Time** | ≤ 15 ms |
| **Scanning Frequency** | 200 Hz |
| **Scanning Accuracy** | 32767 × 32767 |
| **Working Voltage / Current** | DC +5 V ± 5% / 180 mA |
| **Surface Hardness** | Mohs class 7 explosion-proof glass |

ENT Group Co., Ltd. | 70/5 Moo 4, Metro Biztown, Chaengwattana 2, Pak Kret, Nonthaburi 11120, Thailand
Tel: 02-045-6104, 095-739-1053 | Sales@entgroup.co.th | www.entgroup.co.th | Tax ID: 0135558013167

# ENVIRONMENT, POWER & DIMENSIONS

## Environment & Power

| | |
|---|---|
| **Operating Temperature** | 0 °C to 50 °C |
| **Operating Humidity** | 10% to 80% |
| **Storage Temperature** | –5 °C to 60 °C |
| **Storage Humidity** | 10% to 85% |
| **Power Input** | 110–240 V AC, 50/60 Hz |
| **Power Output** | DC 12 V / 5 A |
| **Standby Power** | ≤ 0.5 W |
| **Overall Power Consumption** | < 480 W |

## Dimensions & Weight

| | |
|---|---|
| **Machine Dimensions (L×W×H)** | 1954 × 1153 × 93 mm |
| **Package Dimensions (L×W×H)** | 2000 × 1290 × 215 mm |
| **Net Weight** | 63.0 kg |
| **Gross Weight** | 74.0 kg |
| **Surface Protection** | IP65 (front) |
| **Mounting** | Wall mount / Floor stand / Embedded |

## I/O Ports

- HDMI out × 1
- RJ45 LAN × 1
- WiFi antenna × 1
- Earphone × 1
- AC Power × 1
- VGA out × 1
- USB × 6
- MIC × 1
- Touch output × 1

## RECOMMENDED APPLICATIONS

| Application | Description |
|---|---|
| **Conference & Boardroom** | Wireless screen sharing, remote conferencing and whiteboarding. |
| **Smart Classroom** | Interactive lessons, e-learning and lecture capture. |
| **Information Kiosk** | Wayfinding, info-points, lobby and reception desks. |
| **Digital Signage** | Dynamic in-store signage, menu boards and exhibition display. |
| **Public Self-Service** | Government counters, hospital queue, library check-in. |

## CONNECT & ORDER

How to order — B2B Quotation Workflow. ENT Group operates as a B2B procurement platform. Add items to your cart on entgroup.co.th, our sales team will review your request and respond with a formal quotation (PDF). This is not an online checkout — pricing, lead time and delivery terms are tailored to each project.

### View Product Page

Scan to view RZ85B Series — full specs & accessories
entgroup.co.th/products/displays-85/rz85b

### Add LINE Official

Chat with our sales team for quotations & support
LINE ID: @entgroup

### Get a Tailored Quotation

Scan either QR code to connect with ENT Group instantly. Our B2B sales team will prepare a quotation tailored to your project — including volume pricing, customization, installation and warranty terms.

Tel 02-045-6104, 095-739-1053
Email Sales@entgroup.co.th
Web www.entgroup.co.th

## VIEWS & DIMENSIONS — Mechanical Drawing

Official mechanical drawing extracted from the TouchWo RZ85B spec sheet (panel manufacturer reference). All measurements in millimetres (mm). Front view shows active display area 1872 × 1053 mm and outer chassis 1953.6 × 1152.7 mm. Rear view shows VESA-compatible 4-point mounting pattern (800 × 400 mm centres) with 437.0 / 400.0 / 315.3 mm vertical reference lines.





| Dimension | Value |
|---|---|
| Outer Chassis (W × H × D) | 1954 × 1153 × 93 mm (195.4 × 115.3 × 9.3 cm) |
| Active Display Area (W × H) | 1872 × 1053 mm (85" 4K UHD 16:9) |
| Glass Outer Reference (W × H) | 1953.6 × 1152.7 mm |
| VESA Mount Pattern (rear) | 4-point · 800 × 400 mm centres (576.8 mm side margin) |
| Vertical Mount References | 437.0 / 400.0 / 315.3 mm |
| Net Weight / Gross Weight | 63 kg / 74 kg |
| Package Dimensions (W × H × D) | 2000 × 1290 × 215 mm (200 × 129 × 21.5 cm) |
| Mounting Options | Wall mount · Floor stand · Mobile cart (recommended professional installation due to 63 kg weight) |